

**Exhibit 3 FCC REQUIRED INFORMATION**

The following information is presented in the content and format requested by the FCC:

**Section 2.1033 (c)(1):**

The full name and mailing address of the manufacturer of the device and the applicant for certification

Manufacturer:

Nokia Solutions and Networks US LLC  
6000 Connection Drive  
Irving, TX, 75039  
Attention: Steve Mitchell

Applicant:

Nokia Solutions and Networks US LLC  
6000 Connection Drive  
Irving, TX, 75039  
Attention: Steve Mitchell  
Phone: (972)374-3000  
email: [steve.mitchell@nokia.com](mailto:steve.mitchell@nokia.com)

**Section 2.1033(c)(2):** FCC Identifier: **VBNAEWF-01**

**Section 2.1033(c)(4):** Type or types of emission:

**97M5G7W 1 to 4 Carriers**  
**397M7G7W for 4 adjacent carriers. (New )**  
**Operation with 2 through 4 carriers is new.**

This Transceiver System supports the **3GPP 5G New Radio** and other LTE technologies. The subject of this certification request is for operation using the **3GPP 5G New Radio** modulation format in QPSK, 16QAM and 64QAM (LTE-TDD) for a single LTE carrier. The transceiver can be configured for the various transmit configurations by varying the digital information provided from the baseband channel electronics alone without physical, hardware or circuit changes to the transceiver.

**Section 2.1033(c)(5):** Frequency range, Transmit / Receive: **37-40 GHz**

**Section 2.1033(c)(6):** Range of operating power values or specific operating power levels, and description of any means provided for variation of operating power.

**Response:**

The Nokia **AirScale 39 GHz Radio Unit (AEWF) FCC ID: VBNAEWF-01** is capable of producing two 54 dBm EIRP transmit beams (horizontal and vertically polarized respectively) for a total transmit power of 57 dBm EIRP.

**There is no change to the Total Channel Power.**

RF Power control of the AEWf transceiver is accomplished via software control of the data stream and the RF power gain. The software controls the RF power gain through the RF transmit path with a Digital Step Attenuator (DSA) to maintain the correct RF power of the AEWf over frequency and temperature range. The DSA gain control has a resolution of 0.25 dB per step and an overall range of 11 dB.

Separate circuitry is provided to inhibit the carrier output if a synthesizer in the transmit path loses lock.

**This information is unchanged from the initial filing.**

**Exhibit 3 FCC REQUIRED INFORMATION *continued***

**Section 2.1033(c)(7):** Maximum power rating as defined in the applicable part (s) of the rules.

**Response:**

This product can produce two individual 54dBm EIRP beams (250W EIRP).

The sum of these two 54dBm EIRP beams results in the Maximum Total Power of 57 dBm EIRP (501W EIRP)

The maximum continuous RF output power available is the sum of the horizontal and vertical transmit beams generated by individual 16x16 antenna assemblies. There are no antenna connections. Each antenna assembly distributes 28 dBm of RF power with an overall gain of 29 dBi. This results in a radiated power of 54dBm EIRP per antenna assembly for a Total Radiated Power of 57 dBm EIRP

**This information is unchanged from the initial filing.**

**Section 2.1033 (c)(10):** A description of all circuitry and devices for determining and stabilizing frequency.

**Response:**

The Nokia **AirScale 39 GHz Radio Unit (AEWF), FCC ID: VBNAEFW-01** is a 800 MHz instantaneous bandwidth digital transceiver designed to operate in the **Part 30 Upper Microwave Flexible Use Service** spectrum. The FPGA to A/D transceiver in this product is designed to utilize 50 and 100 MHz carrier emission bandwidth **5G-NR** signals which are up-converted to the 37-40 GHz Band. The frequency stability of the **5G-NR** carrier frequency is maintained with an accuracy better than the rated  $\pm 0.05$  ppm by reference frequency locking the phase-locked-loop (PLL) circuitry to a stable internal reference oscillator. External reference timing is provided by locking to an external frequency disciplined reference signals. Separate circuitry is provided to inhibit the carrier output if a synthesizer in the transmit path loses lock

The **AirScale 39 GHz Radio Unit** is supplied its frequency discipline synchronization for reference from the baseband information source which is GPS capable.

**This information is unchanged from the initial filing.**