



Nemko Test Report: 10213234RUS1

Applicant: Nokia Siemens Networks
6000 Connection Drive
Irving, TX 75039
USA

Equipment Under Test: FXFB
(E.U.T.)

FCC ID: VBNFXFB-01

In Accordance With: **CFR 47, Part 24, Subpart E**
Broadband PCS Base Stations

Tested By: Nemko USA, Inc.
802 N. Kealy
Lewisville, TX 75057-3136

TESTED BY: 

David Light, Senior Wireless Engineer

DATE: 25-Aug-2011

APPROVED BY: 

Mike Cantwell, General Manager

DATE: 21-Sep-2011

Number of Pages: 87

Table of Contents

Section 1. Summary of Test Results	3
Section 2. General Equipment Specification	5
Section 3. RF Power Output.....	6
Section 4. Occupied Bandwidth	9
Section 5. Spurious Emissions at Antenna Terminals	26
Section 6. Field Strength of Spurious	75
Section 7. Frequency Stability.....	76
Section 8. Test Equipment List.....	78
ANNEX A - TEST DETAILS	79
ANNEX B - TEST DIAGRAMS	85

Section 1. Summary of Test Results

Manufacturer: Nokia Siemens Networks

Model No.: FXFB

Serial No.: N/A

General: **All measurements are traceable to national standards.**

These tests were conducted on a sample of the equipment for the purpose of demonstrating compliance with FCC Part 24, Subpart E.



New Submission



Production Unit



Class II Permissive Change



Pre-Production Unit

THIS TEST REPORT RELATES ONLY TO THE ITEM(S) TESTED.

THE FOLLOWING DEVIATIONS FROM, ADDITIONS TO, OR EXCLUSIONS FROM THE TEST SPECIFICATIONS HAVE BEEN MADE.

See "Summary of Test Data".



Nemko USA, Inc. authorizes the above named company to reproduce this report provided it is reproduced in its entirety, for use by the company's employees only.

This report must not be used to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the Federal Government. Nemko USA, Inc. is a NVLAP accredited laboratory.

Any use which a third party makes of this report, or any reliance on or decisions to be made based on it, are the responsibility of such third parties. Nemko USA, Inc. accepts no responsibility for damages, if any, suffered by any third party as a result of decisions made or actions based on this report. This report applies only to the items tested.

Summary Of Test Data

NAME OF TEST	PART 24 PARA. NO.	SPEC.	RESULT
RF Power Output	24.232	1640 W	Complies
Occupied Bandwidth	24.238	6.5.1	Complies
Spurious Emissions at Antenna Terminals	24.238(a)	-13 dBm	Complies
Field Strength of Spurious Emissions	24.238(a)	-13 dBm E.I.R.P.	NT ¹
Frequency Stability	24.235	+/-1%	NT ¹

Footnotes:

These tests were originally performed on FXFA and were not re-tested since the FXFA and FXFB are electrically equivalent.

Note: For the purpose of this test, the FXFB is electrically equivalent to the FXFA. As such, no additional testing was performed for the FXFB. The data presented in this section was compiled for the FXFA from previous Nemko test reports 1026738RUS1 (GSM/EDGE/WCDMA) and 10213334RUS1 (LTE).

Section 2. General Equipment Specification

Supply Voltage Input:	-48 Vdc nominal		
Frequency Band:	1930 to 1990 MHz		
Type of Modulation and Designator:	300KGXW GSM 300KG7W EDGE 5M00D7W QPSK/16QAM/WCDMA 5M00F9W / 10M0F9W / 15M0F9W / 20M0F9W LTE		
Maximum No. of Carriers:	6		
Output Impedance:	50 ohms		
RF Output (Rated):	60 W	.The RF output power must be reduced	
	+47.8 dBm	on the first and last channel of each	
		band when used for GSM, EDGE,	
		QPSK or 16QAM modulations.	
Band Selection:	Software <input checked="" type="checkbox"/>	Duplexer <input type="checkbox"/>	Fullband <input type="checkbox"/>

System Description

The FXFB is an FXFA which has been modified to include a Remote Electrical Tilt (RET) antenna controller module and an external RET connector. Therefore the FXFA and FXFB are deemed to be electrically equivalent. The FXFB is a 1900 MHz multistandard multicarrier radio module that consists of three individual transceivers designed to support GSM/EDGE, WCDMA and LTE in dedicated or concurrent mode. Each module supports up to six GSM/EDGE carriers in GSM/EDGE dedicated mode, up to four WCDMA carriers in WCDMA dedicated mode and up to four 5 MHz LTE carriers in LTE dedicated mode with one radio branch. In concurrent mode, a combination of all three radio technologies is supported with a single radio branch. Each module is capable to serve three radio branches with multiradio multicarrier radios of up to 60 Watts output power per branch.

The transmitter test setup for LTE dedicated mode provided QPSK, 16 QAM and 64 QAM modulation types for single carrier operation only.

The transmitter test setup for GSM/EDGE dedicated mode provided GMSK and 8PSK modulation types for both single and multicarrier operation. The transmitter WCDMA dedicated mode provided QPSK and 16QAM modulation types for both single and multicarrier operation.

Section 3. RF Power Output

NAME OF TEST: RF Power Output	PARA. NO.: 2.1046
TESTED BY: David Light	DATE: 21 April 2011 and 23 August 2011

Test Results: Complies.**Measurement Data:** Refer to table on next page.**Equipment Used:** 2071-2072-1082-1054-1064-1065 (April)
1767-1082-1054-1064-1065 (August)**Measurement Uncertainty:** +/- 1.7 dB**Temperature:** 22 °C**Relative Humidity:** 35 %**Note: Measurement made with power meter**

Test Data – RF Power Output (April 2011)

Modulation Type	Frequency (MHz)	Measured Output Power		Deviation from rated (dB)
		(dBm)	(W)	
GMSK	1930.2	35	3.2	2.0
GMSK	1930.4	48.6	72.4	0.8
GMSK	1960	49.1	81.3	1.3
GMSK	1989.6	48.8	75.9	1.0
GMSK	1989.8	34.7	3.0	1.7
8PSK	1930.2	33.1	2.0	0.1
8PSK	1930.4	48.9	77.6	1.1
8PSK	1960	49.2	83.2	1.4
8PSK	1989.6	48.9	77.6	1.1
8PSK	1989.8	32.7	1.9	-0.3
QPSK	1932.4	34.2	2.6	1.2
QPSK	1932.6	46.4	43.7	-1.4
QPSK	1960	49.2	83.2	1.4
QPSK	1987.4	47.1	51.3	-0.7
QPSK	1987.6	34	2.5	1.0
16QAM	1932.4	34.2	2.6	1.2
16QAM	1932.6	48.7	74.1	0.9
16QAM	1960	49.2	83.2	1.4
16QAM	1987.4	48.4	69.2	0.6
16QAM	1987.6	33.9	2.5	0.9

Note: The power needs to be lowered at the lowest and highest frequencies per above to ensure compliance at the band edges.

The FXFB is compliant at the other frequencies operating at full power.

Supply voltage was varied +/- 15%. No fluctuation in output power resulted.

EQUIPMENT: FXFB

Test Data – RF Power Output (August 2011)

Modulation Type	Channel Bandwidth (MHz)	Frequency (MHz)	Measured Output Power		Deviation from rated (dB)
			(dBm)	(W)	
QPSK	5	1932.5	48.3	67.6	0.5
QPSK	5	1960.0	47.6	57.5	-0.2
QPSK	5	1987.4	47.7	58.9	-0.1
16 QAM	5	1932.5	48.0	63.1	0.2
16 QAM	5	1960.0	47.5	56.2	-0.3
16 QAM	5	1987.4	47.8	60.0	0
64QAM	5	1932.5	47.9	61.7	0.1
64QAM	5	1960.0	47.8	60.0	0
64QAM	5	1987.4	47.7	58.9	-0.1
QPSK	10	1935.0	47.8	60.0	0
QPSK	10	1960.0	48.2	66.1	0.4
QPSK	10	1984.9	48.4	69.2	0.6
16 QAM	10	1935.0	48.0	63.1	0.2
16 QAM	10	1960.0	48.1	64.6	0.3
16 QAM	10	1984.9	48.5	70.8	0.7
64QAM	10	1935.0	48.3	67.6	0.5
64QAM	10	1960.0	48.2	66.1	0.4
64QAM	10	1984.9	48.4	69.2	0.6
QPSK	15	1937.5	48.2	66.1	0.4
QPSK	15	1960.0	48.0	63.1	0.2
QPSK	15	1982.4	48.2	66.1	0.4
16 QAM	15	1937.5	48.3	67.6	0.5
16 QAM	15	1960.0	47.9	61.7	0.1
16 QAM	15	1982.4	48.2	66.1	0.4
64QAM	15	1937.5	48.3	67.6	0.5
64QAM	15	1960.0	48.0	63.1	0.2
64QAM	15	1982.4	48.2	66.1	0.4
QPSK	20	1940.0	48.2	66.1	0.4
QPSK	20	1960.0	47.9	61.7	0.1
QPSK	20	1979.9	48.1	64.6	0.3
16 QAM	20	1940.0	48.1	64.6	0.3
16 QAM	20	1960.0	47.8	60.0	0
16 QAM	20	1979.9	48.0	63.1	0.2
64QAM	20	1940.0	48.2	66.1	0.4
64QAM	20	1960.0	47.9	61.7	0.1
64QAM	20	1979.9	48.1	64.6	0.3

Supply voltage was varied +/- 15%. No fluctuation in output power resulted.

Section 4. Occupied Bandwidth


NAME OF TEST: Occupied Bandwidth	PARA. NO.: 2.1049
TESTED BY: David Light	DATE: 21 April 2011 and 23 August 2011

Test Results: Complies.**Test Data:** See attached plot(s).**Equipment Used:** 1767-1054-1082-1065-1064 (April)
1767-1054-1082-1065-1064 (August)**Measurement Uncertainty:** +/- 1.6 dB**Temperature:** 22 °C**Relative Humidity:** 35 %


Spectrum analyzer settings:

Detector: Peak

Sweep: Auto

Test Data – Occupied Bandwidth (April 2011)**8PSK (EDGE)**


Date: 21.APR.2011 10:01:03

EQUIPMENT: FXFB**Test Data – Occupied Bandwidth (April 2011)****GMSK (GSM)**

Date: 21.APR.2011 09:43:00

EQUIPMENT: FXFB**Test Data – Occupied Bandwidth (April 2011)**


QPSK



Date: 21.APR.2011 14:26:55

EQUIPMENT: FXFB**Test Data – Occupied Bandwidth (April 2011)**

16QAM



Date: 21.APR.2011 14:31:47


EQUIPMENT: FXFB**Test Data – Occupied Bandwidth (August 2011)**

5 MHz Channel

QPSK

Center Channel

20 dB BW



Date: 23.AUG.2011 14:01:51


EQUIPMENT: FXFB**Test Data – Occupied Bandwidth (August 2011)**

5 MHz Channel

Center Channel

16 QAM

20 dB BW



Date: 23.AUG.2011 14:05:31


EQUIPMENT: FXFB**Test Data – Occupied Bandwidth (August 2011)**

5 MHz Channel

64 QAM

Center Channel

20 dB BW



Date: 23.AUG.2011 14:07:41


EQUIPMENT: FXFB**Test Data – Occupied Bandwidth (August 2011)**

10 MHz Channel

QPSK

Center Channel

20 dB BW



Date: 23.AUG.2011 14:47:28


EQUIPMENT: FXFB**Test Data – Occupied Bandwidth (August 2011)**

10 MHz Channel

Center Channel

16 QAM

20 dB BW



Date: 23.AUG.2011 14:48:28


EQUIPMENT: FXFB**Test Data – Occupied Bandwidth (August 2011)**

10 MHz Channel

64 QAM

Center Channel

20 dB BW



Date: 23.AUG.2011 14:50:48


EQUIPMENT: FXFB**Test Data – Occupied Bandwidth (August 2011)**

15 MHz Channel

QPSK

Center Channel

20 dB BW



Date: 24.AUG.2011 07:17:41


EQUIPMENT: FXFB**Test Data – Occupied Bandwidth (August 2011)**

15 MHz Channel

Center Channel

16 QAM

20 dB BW



Date: 24.AUG.2011 07:19:24

EQUIPMENT: FXFB


Test Data – Occupied Bandwidth (August 2011)

15 MHz Channel

64 QAM

Center Channel

20 dB BW



Date: 24.AUG.2011 07:20:10


EQUIPMENT: FXFB**Test Data – Occupied Bandwidth (August 2011)**

20 MHz Channel

QPSK

Center Channel

20 dB BW



Date: 24.AUG.2011 07:41:36


EQUIPMENT: FXFB**Test Data – Occupied Bandwidth (August 2011)**

20 MHz Channel

Center Channel

16 QAM

20 dB BW



Date: 24.AUG.2011 07:42:26


EQUIPMENT: FXFB**Test Data – Occupied Bandwidth (August 2011)**

20 MHz Channel

64 QAM

Center Channel

20 dB BW



Date: 24.AUG.2011 07:44:06

Section 5. Spurious Emissions at Antenna Terminals

NAME OF TEST: Spurious Emissions @ Antenna Terminals	PARA. NO.: 2.1051
--	-------------------

TESTED BY: David Light	DATE: April 2011 and 23 August 2011
------------------------	--

Test Results: Complies.

Test Data: Refer to plots below

Equipment Used: 1767-1082-1064-1065-1054-1054-1058 (April)
1767-1082-1064-1065-1054-1054-1058 (August)

Measurement Uncertainty: +/- 1.7 dB

Temperature: 22 °C

Relative Humidity: 35 %

Spectrum analyzer settings:

Detector: Peak

Sweep: Auto

Nemko USA, Inc.

EQUIPMENT: FXFB

CFR 47, PART 24, SUBPART E
BROADBAND PCS BASE STATIONS
PROJECT NO.: 10213234RUS1


EQUIPMENT: FXFB**Test Data – Spurious Emissions (April 2011)**

Low Band Edge

8PSK (EDGE)

Transmit Frequency: 1930.2 MHz

Transmit power reduced




Date: 21.APR.2011 12:43:40

EQUIPMENT: FXFB**Test Data – Spurious Emissions (April 2011)**

Low Band Edge Intermodulation

8PSK (EDGE)

Transmit power maximum



Date: 21.APR.2011 12:08:20


EQUIPMENT: FXFB**Test Data – Spurious Emissions (April 2011)**

Upper Band Edge

8PSK (EDGE)

Transmit Frequency: 1989.8 MHz

Transmit power reduced




Date: 21.APR.2011 12:37:04

Test Data – Spurious Emissions(April 2011)

Upper Band Edge Intermodulation

8PSK (EDGE)

Transmit power maximum




Date: 21.APR.2011 12:11:21

EQUIPMENT: FXFB**Test Data – Spurious Emissions(April 2011)**

8PSK (EDGE)

Spurs




Date: 21.APR.2011 10:02:11

EQUIPMENT: FXFB**Test Data – Spurious Emissions(April 2011)**

GMSK (GSM)

Lower Edge

Transmit 1930.2 MHz reduced power




Date: 21.APR.2011 12:40:16

EQUIPMENT: FXFB**Test Data – Spurious Emissions(April 2011)**

GMSK (GSM)

Lower band edge Intermodulation

Maximum power




EQUIPMENT: FXFB**Test Data – Spurious Emissions(April 2011)**

GMSK (GSM)

Upper band edge

Transmit 1989.8 MHz reduced power




Date: 21.APR.2011 12:32:52


EQUIPMENT: FXFB**Test Data – Spurious Emissions(April 2011)**

GMSK (GSM)

Upper band edge intermodulation

Transmit maximum power



EQUIPMENT: FXFB**Test Data – Spurious Emissions(April 2011)****GMSK (GSM)****Transmit spurs**


Date: 21.APR.2011 09:48:14

Test Data – Spurious Emissions(April 2011)

QPSK (WCDMA)

Lower band edge

Transmit 1932.4 MHz reduced power




Date: 26.APR.2011 09:15:41

Test Data – Spurious Emissions(April 2011)

QPSK (WCDMA)

Lower band edge intermodulation

Transmit maximum power




Date: 26.APR.2011 09:54:40

EQUIPMENT: FXFB**Test Data – Spurious Emissions(April 2011)**

QPSK (WCDMA)

Upper band edge

Transmit 1987.6 MHz reduced power




Date: 26.APR.2011 09:19:26

Test Data – Spurious Emissions (April 2011)

QPSK (WCDMA)

Upper band edge Intermodulation

Transmit maximum power




Date: 26.APR.2011 09:56:40

Test Data – Spurious Emissions (April 2011)

QPSK (WCDMA)

Transmit Spurs




Date: 21.APR.2011 14:28:12

Test Data – Spurious Emissions (April 2011)

16QAM (WCDMA)

Lower band edge

Transmit 1932.4 MHz reduced power




Date: 26.APR.2011 09:24:00

Test Data – Spurious Emissions (April 2011)

16QAM (WCDMA)

Lower band edge intermodulation

Transmit maximum power




Date: 29.APR.2011 12:48:00

EQUIPMENT: FXFB**Test Data – Spurious Emissions (April 2011)**

16QAM (WCDMA)

Upper band edge

Transmit 1987.6 MHz reduced power




Date: 26.APR.2011 09:21:10

EQUIPMENT: FXFB**Test Data – Spurious Emissions (April 2011)**

16QAM (WCDMA)

Upper band edge intermodulation

Transmit maximum power




Date: 29.APR.2011 12:55:11

EQUIPMENT: FXFB**Test Data – Spurious Emissions (April 2011)**

16QAM (WCDMA)

Transmit spurs




EQUIPMENT: FXFB**Test Data – Spurious Emissions (August 2011)**

5 MHz Channel

QPSK

Low Band Edge




Date: 23.AUG.2011 13:42:58

EQUIPMENT: FXFB**Test Data – Spurious Emissions (August 2011)**

5 MHz Channel

QPSK

Upper Band Edge




Date: 23.AUG.2011 14:12:53

EQUIPMENT: FXFB**Test Data – Spurious Emissions (August 2011)**

5 MHz Channel

16 QAM

Low Band Edge




Date: 23.AUG.2011 13:56:41

EQUIPMENT: FXFB**Test Data – Spurious Emissions (August 2011)**

5 MHz Channel

16 QAM

Upper Band Edge




Date: 23.AUG.2011 14:15:28

EQUIPMENT: FXFB**Test Data – Spurious Emissions (August 2011)**

5 MHz Channel

64 QAM

Low Band Edge




Date: 23.AUG.2011 13:59:21

EQUIPMENT: FXFB**Test Data – Spurious Emissions (August 2011)**

5 MHz Channel

64 QAM

Upper Band Edge




Date: 23.AUG.2011 14:19:12

EQUIPMENT: FXFB**Test Data – Spurious Emissions (August 2011)**

10 MHz Channel

QPSK

Low Band Edge




Date: 23.AUG.2011 14:37:57

EQUIPMENT: FXFB**Test Data – Spurious Emissions (August 2011)**

10 MHz Channel

QPSK

Upper Band Edge




Date: 23.AUG.2011 14:53:56

EQUIPMENT: FXFB**Test Data – Spurious Emissions (August 2011)**

10 MHz Channel

16 QAM

Low Band Edge




Date: 23.AUG.2011 14:42:30

EQUIPMENT: FXFB**Test Data – Spurious Emissions (August 2011)**

10 MHz Channel

16 QAM

Upper Band Edge




Date: 23.AUG.2011 14:57:05

EQUIPMENT: FXFB**Test Data – Spurious Emissions (August 2011)**

10 MHz Channel

64 QAM

Low Band Edge




Date: 23.AUG.2011 14:43:00

EQUIPMENT: FXFB**Test Data – Spurious Emissions (August 2011)**

10 MHz Channel

64 QAM

Upper Band Edge




Date: 23.AUG.2011 14:58:02

EQUIPMENT: FXFB**Test Data – Spurious Emissions (August 2011)**

15 MHz Channel

QPSK

Low Band Edge




Date: 24.AUG.2011 07:12:31

EQUIPMENT: FXFB**Test Data – Spurious Emissions (August 2011)**

15 MHz Channel

QPSK

Upper Band Edge




Date: 24.AUG.2011 07:22:56

EQUIPMENT: FXFB**Test Data – Spurious Emissions (August 2011)**

15 MHz Channel

16 QAM

Low Band Edge




Date: 24.AUG.2011 07:13:06

EQUIPMENT: FXFB**Test Data – Spurious Emissions (August 2011)**

15 MHz Channel

16 QAM

Upper Band Edge




Date: 24.AUG.2011 07:23:18

EQUIPMENT: FXFB**Test Data – Spurious Emissions (August 2011)**

15 MHz Channel

64 QAM

Low Band Edge




Date: 24.AUG.2011 07:16:31

EQUIPMENT: FXFB**Test Data – Spurious Emissions (August 2011)**

15 MHz Channel

64 QAM

Upper Band Edge




Date: 24.AUG.2011 07:26:13

EQUIPMENT: FXFB**Test Data – Spurious Emissions (August 2011)**

20 MHz Channel

QPSK

Low Band Edge




Date: 24.AUG.2011 07:34:36

EQUIPMENT: FXFB**Test Data – Spurious Emissions (August 2011)**

20 MHz Channel

QPSK

Upper Band Edge




Date: 24.AUG.2011 07:45:48

EQUIPMENT: FXFB**Test Data – Spurious Emissions (August 2011)**

20 MHz Channel

16 QAM

Low Band Edge




Date: 24.AUG.2011 07:38:20

EQUIPMENT: FXFB**Test Data – Spurious Emissions (August 2011)**

20 MHz Channel

16 QAM

Upper Band Edge




Date: 24.AUG.2011 07:47:57

EQUIPMENT: FXFB**Test Data – Spurious Emissions (August 2011)**

20 MHz Channel

64 QAM

Low Band Edge




Date: 24.AUG.2011 07:38:43

EQUIPMENT: FXFB**Test Data – Spurious Emissions (August 2011)**

20 MHz Channel

64 QAM

Upper Band Edge




Date: 24.AUG.2011 07:48:19

EQUIPMENT: FXFB**Test Data – Spurious Emissions (August 2011)**

QPSK

Spurs

	Ref Lvl	Marker 1 [T1]	RBW	1 MHz	RF Att	0 dB
	43.2 dBm	-20.42 dBm	VBW	1 MHz		
		15.51775551 GHz	SWT	200 ms	Unit	dBm




Date: 23.AUG.2011 14:03:36

Carrier notched.

EQUIPMENT: FXFB**Test Data – Spurious Emissions (August 2011)**

16 QAM

Spurs




Date: 23.AUG.2011 14:04:10

Carrier notched.

EQUIPMENT: FXFB**Test Data – Spurious Emissions (August 2011)**

64 QAM

Spurs



Date: 23.AUG.2011 14:08:36

Carrier notched.

Section 6. Field Strength of Spurious

NAME OF TEST: Field Strength of Spurious Emissions	PARA. NO.: 2.1051
TESTED BY: David Light	DATE: 21 April 2011

Test Results: Complies.**Test Data:** The spectrum was searched from 30 MHz to the tenth harmonic of the carrier. There were no emissions detected above the noise floor which was at least 20 dB below the specification limit.RBW/VBW=1 MHz
Detector = Peak
Sweep Time = Auto**Equipment Used:** 1783-1763-1025-1016-993-1767**Measurement Uncertainty:** +/- 1.7 dB**Temperature:** 23 °C**Relative Humidity:** 40 %

Section 7. Frequency Stability

NAME OF TEST: Frequency Stability	PARA. NO.: 2.1055
TESTED BY: David Light	DATE: : 25 April 2011

Test Results: Complies**Measurement Data:** Standard Test Frequency: 1960 MHz
Standard Test Voltage: -48 Vdc**Equipment Used:** 1767-1082-1064-1065**Measurement Uncertainty:** +/- 1.7 dB**Temperature:** 23 °C**Relative Humidity:** 40 %

EQUIPMENT: FXFB**Test Data – Frequency Stability**

Temp (°C)	Measured Frequency (MHz)	Rho	Test Voltage	Frequency Error (Hz)	Limit (+/-Hz)	Error (ppm)	Comment
20	1960.000161	0.9999	-48.0	161	1960.0	0.1	
20	1960.000183	0.9999	-55.2	183	1960.0	0.1	
20	1960.000160	0.9999	-40.8	160	1960.0	0.1	
50	1960.000103	0.9999	-48.0	103	1960.0	0.1	
40	1960.000121	0.9999	-48.0	121	1960.0	0.1	
30	1960.000115	0.9999	-48.0	115	1960.0	0.1	
10	1960.000105	0.9999	-48.0	105	1960.0	0.1	
0	1960.000101	0.9999	-48.0	101	1960.0	0.1	
-10	1960.000099	0.9999	-48.0	99	1960.0	0.1	
-20	1960.000112	0.9999	-48.0	112	1960.0	0.1	
-30	1960.000103	0.9999	-48.0	103	1960.0	0.1	
Notes:							

Section 8. Test Equipment List**Test Equipments List for Aprilt 2011 Testing**

Asset Tag	Description	Manufacturer	Model	Serial #	Last Cal	Next Cal
993	Antenna, Horn	A.H. Systems	SAS-200/571	162	09-Sep-2009	09-Sep-2011
1016	Preamplifier	Hewlett Packard	8449A	2749A00159	19-Jun-2010	19-Jun-2011
1025	Preamplifier, 25dB	Nemko USA, Inc.	LNA25	399	23-Feb-2011	23-Feb-2012
1054	Directional Coupler, Dual	Narda	3020A	34366	N/R	
1064	Attenuator	Narda	776B-20		N/R	
1065	Attenuator	Narda	776B-10		N/R	
1082	Cable, 2m	Astrolab	32027-2-29094-72TC		N/R	
1763	Antenna, Bilog	Schaffner	CBL 6111D	22926	11-Feb-2011	11-Feb-2012
1767	Receiver,	Rohde & Schwartz	ESIB26	837491/0002	01-Dec-2010	01-Dec-2011
1783	Cable Assy, 3m Chamber	Nemko	Chanmber		04-Oct-2010	04-Oct-2011
2071	Power Sensor	Agilent	E9304A	MY41495174	12-Oct-2010	12-Oct-2011
2072	Power Meter	Hewlett Packard	E4418B	GB39401848	23-Sep-2010	23-Sep-2011

Test Equipments List for August 2011 Testing

Asset Tag	Description	Manufacturer	Model	Serial #	Last Cal	Next Cal
1054	Directional Coupler, Dual	Narda	3020A	34366	N/R	
1064	Attenuator	Narda	776B-20		N/R	
1065	Attenuator	Narda	776B-10		N/R	
1082	Cable, 2m	Astrolab	32027-2-29094-72TC		N/R	
1763	Antenna, Bilog	Schaffner	CBL 6111D	22926	11-Feb-2011	11-Feb-2012
1767	Receiver,	Rohde & Schwartz	ESIB26	837491/0002	01-Dec-2010	01-Dec-2011

Nemko USA, Inc.

EQUIPMENT: FXFB

CFR 47, PART 24, SUBPART E
BROADBAND PCS BASE STATIONS
PROJECT NO.: 10213234RUS1

ANNEX A - TEST DETAILS

Nemko USA, Inc.

EQUIPMENT: FXFB

CFR 47, PART 24, SUBPART E
BROADBAND PCS BASE STATIONS
PROJECT NO.: 10213234RUS1

NAME OF TEST: RF Power Output

PARA. NO.: 2.1046

Minimum Standard: Para. No.24.232. Base stations with an emission bandwidth of 1 MHz or less are limited to 1640 watts equivalent isotropically radiated power (EIRP) with an antenna height up to 300 meters HAAT.

Base stations with an emission bandwidth greater than 1 MHz are limited to 1640 watts/MHz equivalent isotropically radiated power (EIRP) with an antenna height up to 300 meters HAAT.

Method Of Measurement:

Detachable Antenna:

The peak power at antenna terminals is measured using an in-line peak power meter or a spectrum analyzer.

Nemko USA, Inc.

EQUIPMENT: FXFB

CFR 47, PART 24, SUBPART E
BROADBAND PCS BASE STATIONS
PROJECT NO.: 10213234RUS1

NAME OF TEST: Occupied Bandwidth

PARA. NO.: 2.1049

Minimum Standard: Para. No. 24.238(b). The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated at least 26 dB.

NAME OF TEST: Spurious Emission at Antenna Terminals	PARA. NO.: 2.1051
---	--------------------------

Minimum Standard: Para. No.24.238(a). On any frequency outside a licensee's frequency block, the power of any emission shall be attenuated below the transmitter power by at least $43 + 10 \log (P)$ dB.

Method Of Measurement:

Spectrum analyzer settings:

CDMA Per ANSI/J-STD-014

RBW: 1 MHz (> 1 MHz from Band Edge)
RBW: 30 kHz (< 1MHz from Band Edge)
VBW: \geq RBW
Sweep: Auto
Video Avg: 6 Sweeps

GSM Per ANSI/J-STD-010

RBW: 1 MHz (> 1 MHz from Band Edge)
RBW: 3 kHz (< 1 MHz from Band Edge)
VBW: \geq RBW
Sweep: Auto
Video Avg: Disabled

NADC Per IS-136

RBW: 1 MHz (> 1 MHz from Band Edge)
RBW: 1 kHz (< 1 MHz from Band Edge)
VBW: \geq RBW
Sweep: Auto
Video Avg: Disabled

To demonstrate compliance at band edges the frequency of the input signal is set to the lowest and highest assigned channel and the center frequency of the spectrum analyzer is set to the upper and lower edges of the appropriate frequency block.

Nemko USA, Inc.

EQUIPMENT: FXFB

CFR 47, PART 24, SUBPART E
BROADBAND PCS BASE STATIONS
PROJECT NO.: 10213234RUS1

NAME OF TEST: Field Strength of Spurious Radiation PARA. NO.: 2.1053

Minimum Standard:

Para. No.24.238(a). On any frequency outside a licensee's frequency block, the power of any emission shall be attenuated below the transmitter power by at least $43 + 10 \log (P)$ dB.

NAME OF TEST: Frequency Stability**PARA. NO.: 2.1055**

Minimum Standard: Para. No. 24.235. The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block.

Method Of Measurement:Frequency Stability With Voltage Variation

The E.U.T. is placed in an environmental chamber and allowed to stabilize at +20 degrees Celsius for at least 15 minutes. With the voltage input to the E.U.T. set to 85% S.T.V., the frequency is measured in 30 second intervals for a period of 5 minutes. This procedure is repeated at 100% S.T.V. and 115% S.T.V.

Frequency Stability With Temperature Variation

The input voltage to the E.U.T. is set to S.T.V. and the temperature of the environmental chamber is varied in 10 degree steps from -30 degrees C to +50 degrees C. The E.U.T. is allowed to stabilize at each temperature and the frequency is measured in 30 second intervals for a period of 5 minutes.


Nemko USA, Inc.

EQUIPMENT: FXFB


CFR 47, PART 24, SUBPART E
BROADBAND PCS BASE STATIONS
PROJECT NO.: 10213234RUS1

ANNEX B - TEST DIAGRAMS


Para. No. 2.985 - R.F. Power Output




Para. No. 2.989 - Occupied Bandwidth



Para. No. 2.991 Spurious Emissions at Antenna Terminals



Para. No. 2.993 - Field Strength of Spurious Radiation



Para. No. 2.995 - Frequency Stability

