



# A Test Lab Techno Corp.

Changan Lab : No. 140 -1, Changan Street, Bade City, Taoyuan County, Taiwan R.O.C.  
Tel : 886-3-271-0188 / Fax : 886-3-271-0190



## MPE Report

|                       |                                                                   |
|-----------------------|-------------------------------------------------------------------|
| Test Report No.       | : 1412FS11                                                        |
| Applicant             | : Philips Lighting Electronics North America                      |
| Manufacturer          | : MiTAC International Corporation                                 |
| Product Type          | : CityTouch OLC                                                   |
| Trade Name            | : PHILIPS                                                         |
| Model Number          | : LLC7260                                                         |
| Date of Received      | : Sep. 23, 2014                                                   |
| Test Period           | : Dec. 06, 2014                                                   |
| Date of Issued        | : Dec. 25, 2014                                                   |
| Test Specification    | : 47 CFR § 2.1091<br>47 CFR §1.1310<br>ANSI / IEEE Std.C95.1-1992 |
| Location of Test Lab. | : Chang-an Lab.                                                   |

1. The test operations have to be performed with cautious behavior, the test results are as attached.
2. The test results are under chamber environment of A Test Lab Techno Corp. A Test Lab Techno Corp. does not assume responsibility for any conclusions and generalizations drawn from the test results with regard to other specimens or samples.
3. The measurement report has to be written approval of A Test Lab Techno Corp. It may only be reproduced or published in full. This report shall not be reproduced except in full, without the written approval of A Test Lab Techno Corp.
4. This document may be altered or revised by A Test Lab Techno. Corp. personnel only, and shall be noted in the revision section of the document.

Approved By : Bill Hu  
(Bill Hu)

Tested By : Sky Chou  
(Sky Chou)



# Contents

|    |                                                |   |
|----|------------------------------------------------|---|
| 1. | Description of Equipment under Test (EUT)..... | 3 |
| 2. | Human Exposure Assessment .....                | 4 |
| 3. | RF Output Power.....                           | 5 |
| 4. | Test Result.....                               | 9 |



## 1. Description of Equipment under Test (EUT)

|                                     |                                                                                                                                                                                                                             |
|-------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Applicant                           | Philips Lighting Electronics North America                                                                                                                                                                                  |
| Applicant Address                   | 10275 W. Higgins Road, Rosemont, Illinois, United States, 60018-5603                                                                                                                                                        |
| Manufacturer                        | MiTAC International Corporation                                                                                                                                                                                             |
| Manufacturer Address                | Building B, No. 209, Sec. 1 Nan Gang Road, Nan Gang District, Taipei Taiwan, Republic of China                                                                                                                              |
| Product Type                        | CityTouch OLC                                                                                                                                                                                                               |
| Trade Name                          | PHILIPS                                                                                                                                                                                                                     |
| Model Number                        | LLC7260                                                                                                                                                                                                                     |
| IMEI No.                            | 014332000001001                                                                                                                                                                                                             |
| Hardware Version                    | 9137 003 63303                                                                                                                                                                                                              |
| Software Version                    | 10880                                                                                                                                                                                                                       |
| FCC ID                              | VBO-LLC7260                                                                                                                                                                                                                 |
| Frequency Range                     | 824.2 - 848.8 MHz GPRS/EGPRS 850<br>1850.2 - 1909.8 MHz GPRS/EGPRS 1900<br>1852.4 - 1907.6 MHz WCDMA(RMC 12.2K)/HSDPA/HSUPA Band II<br>826.4 - 846.6 MHz WCDMA(RMC 12.2K)/HSDPA/HSUPA Band V<br>*GPRS/EGPRS Multi Class :12 |
| Transmit Power<br>(conducted power) | GPRS/EGPRS 850: 1.811 W / 32.58 dBm<br>GPRS/EGPRS 1900: 0.796 W / 29.01 dBm<br>WCDMA(RMC 12.2K)/HSDPA/HSUPA Band II: 0.213 W / 23.29 dBm<br>WCDMA(RMC 12.2K)/HSDPA/HSUPA Band V: 0.217 W / 23.37 dBm                        |
| Antenna Specification               | GPRS 850: -0.49 dBi<br>GPRS 1900: 0.10 dBi<br>WCDMA Band II: 0.10 dBi<br>WCDMA Band V: -0.49 dBi                                                                                                                            |
| Antenna Designation                 | PIFA Antenna                                                                                                                                                                                                                |
| RF Evaluation                       | 1.11 W/m <sup>2</sup>                                                                                                                                                                                                       |

The above equipment was tested by A Test Lab Techno Corp. For compliance with the requirements set forth in 47 CFR § 2.1091 & 47 CFR § 1.1310. The results of testing in this report apply only to the product/system, which was tested. Other similar equipment will not necessarily produce the same results due to production tolerance and measurement uncertainties



## 2. Human Exposure Assessment

Due to the design and installation of this product, it is not possible to conduct SAR evaluation. This is because client either manufactures or supplies the antenna(s) that will be used in the installation of this product. Therefore, this product will be evaluated as a mobile device per 47 CFR §1.1310 titled "Radiofrequency radiation exposure limits", generally referred to as MPE limits.

In 47 CFR § 2.1091, paragraph (b) defines a mobile device as "a transmitting device designed to be used in other than fixed locations and to generally be used in such a way that a separation distance of at least 20 cm is normally maintained between the transmitter's radiating structure(s) and the body of the user or nearby persons. " This product is intended to be installed into a vehicle such that the unit is physically secured at one location. In the installation guide supplied with the product,

Client has made the following statement: "IMPORTANT: To meet the FCC's RF Exposure Guidelines, the antenna should be installed so there is at least 20 cm of separation between the body of the user and nearby persons and the antenna". Based on the installation of the transceiver and the antenna, the transmitters radiating structure is more than 20 cm from the user. Thus, this product is a "mobile device" as defined in section § 2.1091 paragraph (b).

Exposure evaluation

$$S = \frac{PG}{4\pi R^2}$$

Where

S: power density

P: power input to the antenna

G: power gain of the antenna in the direction of interest relative to an isotropic radiator.

R: distance to the center of radiation of the antenna.

### 3. RF Output Power

| Band     | Date Rate | CH  | Frequency (MHz) | Average Conducted power (dBm) |
|----------|-----------|-----|-----------------|-------------------------------|
| GPRS850  | 4Down1Up  | 128 | 824.2           | <b>32.58</b>                  |
|          |           | 190 | 836.6           | 32.46                         |
|          |           | 251 | 848.8           | 32.51                         |
|          | 3Down2Up  | 128 | 824.2           | 32.42                         |
|          |           | 190 | 836.6           | 32.28                         |
|          |           | 251 | 848.8           | 32.33                         |
|          | 2Down3Up  | 128 | 824.2           | 31.71                         |
|          |           | 190 | 836.6           | 31.59                         |
|          |           | 251 | 848.8           | 31.63                         |
|          | 1Down4Up  | 128 | 824.2           | 30.55                         |
|          |           | 190 | 836.6           | 30.41                         |
|          |           | 251 | 848.8           | 30.47                         |
| EGPRS850 | 4Down1Up  | 128 | 824.2           | 27.11                         |
|          |           | 190 | 836.6           | 26.97                         |
|          |           | 251 | 848.8           | 27.07                         |
|          | 3Down2Up  | 128 | 824.2           | 26.95                         |
|          |           | 190 | 836.6           | 26.81                         |
|          |           | 251 | 848.8           | 26.91                         |
|          | 2Down3Up  | 128 | 824.2           | 26.21                         |
|          |           | 190 | 836.6           | 26.08                         |
|          |           | 251 | 848.8           | 26.15                         |
|          | 1Down4Up  | 128 | 824.2           | 24.97                         |
|          |           | 190 | 836.6           | 24.78                         |
|          |           | 251 | 848.8           | 24.87                         |

| Band      | Date Rate | CH  | Frequency (MHz) | Average Conducted power (dBm) |
|-----------|-----------|-----|-----------------|-------------------------------|
| GPRS1900  | 4Down1Up  | 512 | 1850.2          | <b>29.01</b>                  |
|           |           | 661 | 1909.8          | 28.75                         |
|           |           | 810 | 1909.8          | 28.79                         |
|           | 3Down2Up  | 512 | 1850.2          | 28.83                         |
|           |           | 661 | 1909.8          | 28.57                         |
|           |           | 810 | 1909.8          | 28.61                         |
|           | 2Down3Up  | 512 | 1850.2          | 28.22                         |
|           |           | 661 | 1909.8          | 28.01                         |
|           |           | 810 | 1909.8          | 28.07                         |
|           | 1Down4Up  | 512 | 1850.2          | 27.03                         |
|           |           | 661 | 1909.8          | 26.82                         |
|           |           | 810 | 1909.8          | 26.85                         |
| EGPRS1900 | 4Down1Up  | 512 | 1850.2          | 25.36                         |
|           |           | 661 | 1909.8          | 25.15                         |
|           |           | 810 | 1909.8          | 25.19                         |
|           | 3Down2Up  | 512 | 1850.2          | 25.21                         |
|           |           | 661 | 1909.8          | 25.00                         |
|           |           | 810 | 1909.8          | 25.04                         |
|           | 2Down3Up  | 512 | 1850.2          | 24.53                         |
|           |           | 661 | 1909.8          | 24.31                         |
|           |           | 810 | 1909.8          | 24.36                         |
|           | 1Down4Up  | 512 | 1850.2          | 23.47                         |
|           |           | 661 | 1909.8          | 23.29                         |
|           |           | 810 | 1909.8          | 23.38                         |

| Band             | Date Rate | CH   | Frequency (MHz) | Average Conducted power (dBm) |
|------------------|-----------|------|-----------------|-------------------------------|
| WCDMA<br>Band II | ---       | 9262 | 1852.4          | <b>23.29</b>                  |
|                  |           | 9400 | 1880.0          | 23.07                         |
|                  |           | 9538 | 1907.6          | 23.16                         |
| HSDPA<br>Band II | 1         | 9262 | 1852.4          | 22.43                         |
|                  |           | 9400 | 1880.0          | 22.22                         |
|                  |           | 9538 | 1907.6          | 22.31                         |
|                  | 2         | 9262 | 1852.4          | 22.39                         |
|                  |           | 9400 | 1880.0          | 22.19                         |
|                  |           | 9538 | 1907.6          | 22.26                         |
|                  | 3         | 9262 | 1852.4          | 21.96                         |
|                  |           | 9400 | 1880.0          | 21.73                         |
|                  |           | 9538 | 1907.6          | 21.83                         |
|                  | 4         | 9262 | 1852.4          | 21.93                         |
|                  |           | 9400 | 1880.0          | 21.71                         |
|                  |           | 9538 | 1907.6          | 21.78                         |
| HSUPA<br>Band II | 1         | 9262 | 1852.4          | 21.86                         |
|                  |           | 9400 | 1880.0          | 21.62                         |
|                  |           | 9538 | 1907.6          | 21.75                         |
|                  | 2         | 9262 | 1852.4          | 19.88                         |
|                  |           | 9400 | 1880.0          | 19.63                         |
|                  |           | 9538 | 1907.6          | 19.78                         |
|                  | 3         | 9262 | 1852.4          | 20.88                         |
|                  |           | 9400 | 1880.0          | 20.65                         |
|                  |           | 9538 | 1907.6          | 20.79                         |
|                  | 4         | 9262 | 1852.4          | 19.84                         |
|                  |           | 9400 | 1880.0          | 19.62                         |
|                  |           | 9538 | 1907.6          | 19.74                         |
|                  | 5         | 9262 | 1852.4          | 21.84                         |
|                  |           | 9400 | 1880.0          | 21.58                         |
|                  |           | 9538 | 1907.6          | 21.72                         |

| Band         | Date Rate | CH   | Frequency (MHz) | Average Conducted power (dBm) |
|--------------|-----------|------|-----------------|-------------------------------|
| WCDMA Band V | ---       | 4132 | 826.4           | <b>23.37</b>                  |
|              |           | 4183 | 836.6           | 23.20                         |
|              |           | 4233 | 846.4           | 23.27                         |
| HSDPA Band V | 1         | 4132 | 826.4           | 22.57                         |
|              |           | 4183 | 836.6           | 22.35                         |
|              |           | 4233 | 846.4           | 22.45                         |
|              | 2         | 4132 | 826.4           | 22.53                         |
|              |           | 4183 | 836.6           | 22.33                         |
|              |           | 4233 | 846.4           | 22.42                         |
|              | 3         | 4132 | 826.4           | 22.07                         |
|              |           | 4183 | 836.6           | 21.87                         |
|              |           | 4233 | 846.4           | 21.95                         |
|              | 4         | 4132 | 826.4           | 22.05                         |
|              |           | 4183 | 836.6           | 21.82                         |
|              |           | 4233 | 846.4           | 21.94                         |
| HSUPA Band V | 1         | 4132 | 826.4           | 22.03                         |
|              |           | 4183 | 836.6           | 21.85                         |
|              |           | 4233 | 846.4           | 21.88                         |
|              | 2         | 4132 | 826.4           | 20.05                         |
|              |           | 4183 | 836.6           | 19.89                         |
|              |           | 4233 | 846.4           | 19.91                         |
|              | 3         | 4132 | 826.4           | 21.05                         |
|              |           | 4183 | 836.6           | 20.85                         |
|              |           | 4233 | 846.4           | 20.91                         |
|              | 4         | 4132 | 826.4           | 20.01                         |
|              |           | 4183 | 836.6           | 19.85                         |
|              |           | 4233 | 846.4           | 19.85                         |
|              | 5         | 4132 | 826.4           | 22.01                         |
|              |           | 4183 | 836.6           | 21.82                         |
|              |           | 4233 | 846.4           | 21.83                         |

#### 4. Test Result

| Band      | Data Rate | Frequency (MHz) | Limit (mw/cm <sup>2</sup> ) | Distance [R] (cm) | Max. Tune-up Power [P] (dBm) | ANT Gain (dBi) | Numeric Gain [G] (dBi) | Duty Cycle | [P] x [G] with Duty cycle [TP] (mW) | Power Density [S] (mw/cm <sup>2</sup> ) |
|-----------|-----------|-----------------|-----------------------------|-------------------|------------------------------|----------------|------------------------|------------|-------------------------------------|-----------------------------------------|
| GPRS 850  | 4Down1Up  | 824.2           | 0.549                       | 20                | 33.00                        | -0.49          | 0.89                   | 0.125      | 221.97                              | 0.044                                   |
|           |           | 836.6           | 0.558                       | 20                | 33.00                        | -0.49          | 0.89                   | 0.125      | 221.97                              | 0.044                                   |
|           |           | 848.8           | 0.566                       | 20                | 33.00                        | -0.49          | 0.89                   | 0.125      | 221.97                              | 0.044                                   |
|           | 3Down2Up  | 824.2           | 0.549                       | 20                | 32.50                        | -0.49          | 0.89                   | 0.250      | 395.67                              | 0.079                                   |
|           |           | 836.6           | 0.558                       | 20                | 32.50                        | -0.49          | 0.89                   | 0.250      | 395.67                              | 0.079                                   |
|           |           | 848.8           | 0.566                       | 20                | 32.50                        | -0.49          | 0.89                   | 0.250      | 395.67                              | 0.079                                   |
|           | 2Down3Up  | 824.2           | 0.549                       | 20                | 32.00                        | -0.49          | 0.89                   | 0.375      | 528.96                              | 0.105                                   |
|           |           | 836.6           | 0.558                       | 20                | 32.00                        | -0.49          | 0.89                   | 0.375      | 528.96                              | 0.105                                   |
|           |           | 848.8           | 0.566                       | 20                | 32.00                        | -0.49          | 0.89                   | 0.375      | 528.96                              | 0.105                                   |
|           | 1Down4Up  | 824.2           | 0.549                       | 20                | 31.00                        | -0.49          | 0.89                   | 0.500      | 560.22                              | 0.111                                   |
|           |           | 836.6           | 0.558                       | 20                | 31.00                        | -0.49          | 0.89                   | 0.500      | 560.22                              | 0.111                                   |
|           |           | 848.8           | 0.566                       | 20                | 31.00                        | -0.49          | 0.89                   | 0.500      | 560.22                              | 0.111                                   |
| EGPRS 850 | 4Down1Up  | 824.2           | 0.549                       | 20                | 28.00                        | -0.49          | 0.89                   | 0.125      | 70.19                               | 0.014                                   |
|           |           | 836.6           | 0.558                       | 20                | 28.00                        | -0.49          | 0.89                   | 0.125      | 70.19                               | 0.014                                   |
|           |           | 848.8           | 0.566                       | 20                | 28.00                        | -0.49          | 0.89                   | 0.125      | 70.19                               | 0.014                                   |
|           | 3Down2Up  | 824.2           | 0.549                       | 20                | 27.00                        | -0.49          | 0.89                   | 0.250      | 111.51                              | 0.022                                   |
|           |           | 836.6           | 0.558                       | 20                | 27.00                        | -0.49          | 0.89                   | 0.250      | 111.51                              | 0.022                                   |
|           |           | 848.8           | 0.566                       | 20                | 27.00                        | -0.49          | 0.89                   | 0.250      | 111.51                              | 0.022                                   |
|           | 2Down3Up  | 824.2           | 0.549                       | 20                | 26.50                        | -0.49          | 0.89                   | 0.375      | 149.08                              | 0.030                                   |
|           |           | 836.6           | 0.558                       | 20                | 26.50                        | -0.49          | 0.89                   | 0.375      | 149.08                              | 0.030                                   |
|           |           | 848.8           | 0.566                       | 20                | 26.50                        | -0.49          | 0.89                   | 0.375      | 149.08                              | 0.030                                   |
|           | 1Down4Up  | 824.2           | 0.549                       | 20                | 25.50                        | -0.49          | 0.89                   | 0.500      | 157.89                              | 0.031                                   |
|           |           | 836.6           | 0.558                       | 20                | 25.50                        | -0.49          | 0.89                   | 0.500      | 157.89                              | 0.031                                   |
|           |           | 848.8           | 0.566                       | 20                | 25.50                        | -0.49          | 0.89                   | 0.500      | 157.89                              | 0.031                                   |

Note: The Power [P] is max tune-up power (upper limit).

| Band       | Data Rate | Frequency (MHz) | Limit (mw/cm <sup>2</sup> ) | Distance [R] (cm) | Max. Tune-up Power [P] (dBm) | ANT Gain (dBi) | Numeric Gain [G] (dBi) | Duty Cycle | [P] x [G] with Duty cycle [TP] (mW) | Power Density [S] (mw/cm <sup>2</sup> ) |
|------------|-----------|-----------------|-----------------------------|-------------------|------------------------------|----------------|------------------------|------------|-------------------------------------|-----------------------------------------|
| GPRS 1900  | 4Down1Up  | 1850.2          | 1.000                       | 20                | 30.00                        | 0.10           | 1.02                   | 0.125      | 127.50                              | 0.025                                   |
|            |           | 1880.0          | 1.000                       | 20                | 30.00                        | 0.10           | 1.02                   | 0.125      | 127.50                              | 0.025                                   |
|            |           | 1909.8          | 1.000                       | 20                | 30.00                        | 0.10           | 1.02                   | 0.125      | 127.50                              | 0.025                                   |
|            | 3Down2Up  | 1850.2          | 1.000                       | 20                | 29.00                        | 0.10           | 1.02                   | 0.250      | 202.55                              | 0.040                                   |
|            |           | 1880.0          | 1.000                       | 20                | 29.00                        | 0.10           | 1.02                   | 0.250      | 202.55                              | 0.040                                   |
|            |           | 1909.8          | 1.000                       | 20                | 29.00                        | 0.10           | 1.02                   | 0.250      | 202.55                              | 0.040                                   |
|            | 2Down3Up  | 1850.2          | 1.000                       | 20                | 28.50                        | 0.10           | 1.02                   | 0.375      | 270.79                              | 0.054                                   |
|            |           | 1880.0          | 1.000                       | 20                | 28.50                        | 0.10           | 1.02                   | 0.375      | 270.79                              | 0.054                                   |
|            |           | 1909.8          | 1.000                       | 20                | 28.50                        | 0.10           | 1.02                   | 0.375      | 270.79                              | 0.054                                   |
|            | 1Down4Up  | 1850.2          | 1.000                       | 20                | 27.50                        | 0.10           | 1.02                   | 0.500      | 286.79                              | 0.057                                   |
|            |           | 1880.0          | 1.000                       | 20                | 27.50                        | 0.10           | 1.02                   | 0.500      | 286.79                              | 0.057                                   |
|            |           | 1909.8          | 1.000                       | 20                | 27.50                        | 0.10           | 1.02                   | 0.500      | 286.79                              | 0.057                                   |
| EGPRS 1900 | 4Down1Up  | 1850.2          | 1.000                       | 20                | 26.00                        | 0.10           | 1.02                   | 0.125      | 50.76                               | 0.010                                   |
|            |           | 1880.0          | 1.000                       | 20                | 26.00                        | 0.10           | 1.02                   | 0.125      | 50.76                               | 0.010                                   |
|            |           | 1909.8          | 1.000                       | 20                | 26.00                        | 0.10           | 1.02                   | 0.125      | 50.76                               | 0.010                                   |
|            | 3Down2Up  | 1850.2          | 1.000                       | 20                | 25.50                        | 0.10           | 1.02                   | 0.250      | 90.48                               | 0.018                                   |
|            |           | 1880.0          | 1.000                       | 20                | 25.50                        | 0.10           | 1.02                   | 0.250      | 90.48                               | 0.018                                   |
|            |           | 1909.8          | 1.000                       | 20                | 25.50                        | 0.10           | 1.02                   | 0.250      | 90.48                               | 0.018                                   |
|            | 2Down3Up  | 1850.2          | 1.000                       | 20                | 25.00                        | 0.10           | 1.02                   | 0.375      | 120.96                              | 0.024                                   |
|            |           | 1880.0          | 1.000                       | 20                | 25.00                        | 0.10           | 1.02                   | 0.375      | 120.96                              | 0.024                                   |
|            |           | 1909.8          | 1.000                       | 20                | 25.00                        | 0.10           | 1.02                   | 0.375      | 120.96                              | 0.024                                   |
|            | 1Down4Up  | 1850.2          | 1.000                       | 20                | 24.00                        | 0.10           | 1.02                   | 0.500      | 128.11                              | 0.025                                   |
|            |           | 1880.0          | 1.000                       | 20                | 24.00                        | 0.10           | 1.02                   | 0.500      | 128.11                              | 0.025                                   |
|            |           | 1909.8          | 1.000                       | 20                | 24.00                        | 0.10           | 1.02                   | 0.500      | 128.11                              | 0.025                                   |

Note: The Power [P] is max tune-up power (upper limit).



| Band          | Sub-Test | Frequency (MHz) | Limit (mw/cm <sup>2</sup> ) | Distance [R] (cm) | Max. Tune-up Power [P] (dBm) | ANT Gain (dBi) | Numeric Gain [G] (dBi) | Duty Cycle | [P] x [G] with Duty cycle [TP] (mW) | Power Density [S] (mw/cm <sup>2</sup> ) |
|---------------|----------|-----------------|-----------------------------|-------------------|------------------------------|----------------|------------------------|------------|-------------------------------------|-----------------------------------------|
| WCDMA Band II | RMC12.2K | 1852.4          | 1.000                       | 20                | 24.00                        | 0.10           | 1.02                   | 1.000      | 256.21                              | 0.051                                   |
|               |          | 1880.0          | 1.000                       | 20                | 24.00                        | 0.10           | 1.02                   | 1.000      | 256.21                              | 0.051                                   |
|               |          | 1907.6          | 1.000                       | 20                | 24.00                        | 0.10           | 1.02                   | 1.000      | 256.21                              | 0.051                                   |
| WCDMA Band V  | RMC12.2K | 826.4           | 0.551                       | 20                | 24.00                        | 0.49           | 1.12                   | 1.000      | 281.33                              | 0.056                                   |
|               |          | 836.6           | 0.558                       | 20                | 24.00                        | 0.49           | 1.12                   | 1.000      | 281.33                              | 0.056                                   |
|               |          | 846.6           | 0.564                       | 20                | 24.00                        | 0.49           | 1.12                   | 1.000      | 281.33                              | 0.056                                   |

Note: The Power [P] is max tune-up power (upper limit).