

RALLY RACER

RC
RADIO CONTROL
CONTROL REMOTO



1:18

MITSUBISHI PAJERO EVOLUTION

BOX SIZE: 13.875" W x 7.625" D x 7.875" H
PRINTED AREA: 24.5" W x 32.5" H
WINDOW SIZE: 10.25" W x 12" H

MEGA SIZED WHEELS / RACER STYLING
GRANDES RUEDAS DE TAMAÑO / CARRERAS DE ESTILO



RC
RADIO CONTROL
CONTROL REMOTO

1:18

RALLY RACER

MITSUBISHI PAJERO EVOLUTION

RC
RADIO CONTROL
CONTROL REMOTO

MEGA SIZED WHEELS / RACER STYLING
GRANDES RUEDAS DE TAMAÑO
CARRERAS DE ESTILO

RALLY RACER



1:18



BATTERIES REQUIRED:
SE REQUIEREN PILAS:
NO INCLUIDAS

1.5V "AA" x 6
9V "DODOP" x 1



BATTERIES REQUIRED:
SE REQUIEREN PILAS:
NO INCLUIDAS

1.5V "AA" x 6
9V "DODOP" x 1

RALLY RACER

RC
RADIO CONTROL
CONTROL REMOTO



1:18

MITSUBISHI PAJERO EVOLUTION

RC
RADIO CONTROL
CONTROL REMOTO


1:18

RALLY RACER

MEGA SIZED WHEELS / RACER STYLING
GRANDES RUEDAS DE TAMAÑO / CARRERAS DE ESTILO



CAR & CONTROLLER LABELS
CYMK + Pantone 877C



WARNING:
CHOKING HAZARD - Small parts.
Not for children under 3 years.

ATENCION:
PIERDE CUIDADO - Partes pequeñas.
No recomendable para menores de 3 años.

MITSUBISHI PAJERO EVOLUTION

BATTERY INSTALLATION

NOTE:
1. Verify the battery is inserted to remove the access of the battery compartment cover.
2. Turn the battery to remove the cover.
3. Turn the battery to remove the cover.
4. Turn the battery to remove the cover.
5. Turn the battery to remove the cover.
6. Turn the battery to remove the cover.
7. Turn the battery to remove the cover.
8. Turn the battery to remove the cover.
9. Turn the battery to remove the cover.
10. Turn the battery to remove the cover.

TRANSMITTER

1. Turn the transmitter on and remove the cover of the battery compartment.
2. Turn the transmitter on and remove the cover of the battery compartment.
3. Turn the transmitter on and remove the cover of the battery compartment.
4. Turn the transmitter on and remove the cover of the battery compartment.
5. Turn the transmitter on and remove the cover of the battery compartment.
6. Turn the transmitter on and remove the cover of the battery compartment.
7. Turn the transmitter on and remove the cover of the battery compartment.
8. Turn the transmitter on and remove the cover of the battery compartment.
9. Turn the transmitter on and remove the cover of the battery compartment.
10. Turn the transmitter on and remove the cover of the battery compartment.

PRECAUCIONES DE LAS PILAS

1. Verificar que las pilas estén correctamente insertadas.
2. No tocar los terminales de las pilas.
3. No tocar los terminales de las pilas.
4. No tocar los terminales de las pilas.
5. No tocar los terminales de las pilas.
6. No tocar los terminales de las pilas.
7. No tocar los terminales de las pilas.
8. No tocar los terminales de las pilas.
9. No tocar los terminales de las pilas.
10. No tocar los terminales de las pilas.

HOW TO OPERATE

1. Turn the transmitter on and remove the cover of the battery compartment.
2. Turn the transmitter on and remove the cover of the battery compartment.
3. Turn the transmitter on and remove the cover of the battery compartment.
4. Turn the transmitter on and remove the cover of the battery compartment.
5. Turn the transmitter on and remove the cover of the battery compartment.
6. Turn the transmitter on and remove the cover of the battery compartment.
7. Turn the transmitter on and remove the cover of the battery compartment.
8. Turn the transmitter on and remove the cover of the battery compartment.
9. Turn the transmitter on and remove the cover of the battery compartment.
10. Turn the transmitter on and remove the cover of the battery compartment.

WHEEL ALIGNMENT

1. Turn the transmitter on and remove the cover of the battery compartment.
2. Turn the transmitter on and remove the cover of the battery compartment.
3. Turn the transmitter on and remove the cover of the battery compartment.
4. Turn the transmitter on and remove the cover of the battery compartment.
5. Turn the transmitter on and remove the cover of the battery compartment.
6. Turn the transmitter on and remove the cover of the battery compartment.
7. Turn the transmitter on and remove the cover of the battery compartment.
8. Turn the transmitter on and remove the cover of the battery compartment.
9. Turn the transmitter on and remove the cover of the battery compartment.
10. Turn the transmitter on and remove the cover of the battery compartment.

BATTERY CAUTION

1. Do not touch the battery terminals.
2. Do not touch the battery terminals.
3. Do not touch the battery terminals.
4. Do not touch the battery terminals.
5. Do not touch the battery terminals.
6. Do not touch the battery terminals.
7. Do not touch the battery terminals.
8. Do not touch the battery terminals.
9. Do not touch the battery terminals.
10. Do not touch the battery terminals.

TRANSMITTER TRANSMITTER

1. Turn the transmitter on and remove the cover of the battery compartment.
2. Turn the transmitter on and remove the cover of the battery compartment.
3. Turn the transmitter on and remove the cover of the battery compartment.
4. Turn the transmitter on and remove the cover of the battery compartment.
5. Turn the transmitter on and remove the cover of the battery compartment.
6. Turn the transmitter on and remove the cover of the battery compartment.
7. Turn the transmitter on and remove the cover of the battery compartment.
8. Turn the transmitter on and remove the cover of the battery compartment.
9. Turn the transmitter on and remove the cover of the battery compartment.
10. Turn the transmitter on and remove the cover of the battery compartment.

WHEEL ALIGNMENT

1. Turn the transmitter on and remove the cover of the battery compartment.
2. Turn the transmitter on and remove the cover of the battery compartment.
3. Turn the transmitter on and remove the cover of the battery compartment.
4. Turn the transmitter on and remove the cover of the battery compartment.
5. Turn the transmitter on and remove the cover of the battery compartment.
6. Turn the transmitter on and remove the cover of the battery compartment.
7. Turn the transmitter on and remove the cover of the battery compartment.
8. Turn the transmitter on and remove the cover of the battery compartment.
9. Turn the transmitter on and remove the cover of the battery compartment.
10. Turn the transmitter on and remove the cover of the battery compartment.

NOTE

1. The manufacturer is not responsible for any damage or interference caused by unauthorized modifications to the equipment.
2. The manufacturer is not responsible for any damage or interference caused by unauthorized modifications to the equipment.
3. The manufacturer is not responsible for any damage or interference caused by unauthorized modifications to the equipment.
4. The manufacturer is not responsible for any damage or interference caused by unauthorized modifications to the equipment.
5. The manufacturer is not responsible for any damage or interference caused by unauthorized modifications to the equipment.

PRECAUCIONES DE LAS PILAS


1. Verificar que las pilas estén correctamente insertadas.
2. No tocar los terminales de las pilas.
3. No tocar los terminales de las pilas.
4. No tocar los terminales de las pilas.
5. No tocar los terminales de las pilas.
6. No tocar los terminales de las pilas.
7. No tocar los terminales de las pilas.
8. No tocar los terminales de las pilas.
9. No tocar los terminales de las pilas.
10. No tocar los terminales de las pilas.

HOW TO OPERATE

1. Turn the transmitter on and remove the cover of the battery compartment.
2. Turn the transmitter on and remove the cover of the battery compartment.
3. Turn the transmitter on and remove the cover of the battery compartment.
4. Turn the transmitter on and remove the cover of the battery compartment.
5. Turn the transmitter on and remove the cover of the battery compartment.
6. Turn the transmitter on and remove the cover of the battery compartment.
7. Turn the transmitter on and remove the cover of the battery compartment.
8. Turn the transmitter on and remove the cover of the battery compartment.
9. Turn the transmitter on and remove the cover of the battery compartment.
10. Turn the transmitter on and remove the cover of the battery compartment.

WHEEL ALIGNMENT

1. Turn the transmitter on and remove the cover of the battery compartment.
2. Turn the transmitter on and remove the cover of the battery compartment.
3. Turn the transmitter on and remove the cover of the battery compartment.
4. Turn the transmitter on and remove the cover of the battery compartment.
5. Turn the transmitter on and remove the cover of the battery compartment.
6. Turn the transmitter on and remove the cover of the battery compartment.
7. Turn the transmitter on and remove the cover of the battery compartment.
8. Turn the transmitter on and remove the cover of the battery compartment.
9. Turn the transmitter on and remove the cover of the battery compartment.
10. Turn the transmitter on and remove the cover of the battery compartment.



NO. 61115
MADE IN CHINA
HECHO EN CHINA

