

Date : 2010-07-26 Page 1 of 17

No. : MH184069

**Applicant (GRI001):** Grandex International Development Limited

Unit 2401, Million Fortune Industrial Centre, 34-36 Chai

Wan Kok Street, Tsuen Wan, N.T., Hong Kong

Manufacturer: Grandex International Development Limited

Unit 2401, Million Fortune Industrial Centre, 34-36 Chai

Wan Kok Street, Tsuen Wan, N.T., Hong Kong

**Description of Sample(s):** Submitted samples(s) said to be

Product: Radio stunt

Brand Name: N/A Model Number: 96105

FCC ID: VC99610527T

**Date Sample(s) Received:** 2010-05-05

**Date Tested:** 2010-05-06, 2010-06-24

**Investigation Requested:** Perform ElectroMagnetic Interference measurement in

accordance with FCC 47CFR [Codes of Federal Regulations] Part 15: 2009 and ANSI C63.4:2003 for FCC Certification.

**Conclusion(s):** The submitted product <u>COMPLIED</u> with the requirements of

Federal Communications Commission [FCC] Rules and Regulations Part 15. The tests were performed in accordance with the standards described above and on Section 2.2 in this

Test Report.

**Remark**(s): ----

Dr. LEE Kam Chuen Authorized Signatory

ElectroMagnetic Compatibility Department

For and on behalf of

The Hong Kong Standards and Testing Centre Ltd.



Date: 2010-07-26 Page 2 of 17

No. : MH184069

### **CONTENT:**

	Cover Content	Page 1 of 17 Page 2-3 of 17
<u>1.0</u>	General Details	
1.1	Test Laboratory	Page 4 of 17
1.2	Applicant Details Applicant Manufacturer	Page 4 of 17
1.3	Equipment Under Test [EUT] Description of EUT operation	Page 5 of 17
1.4	Date of Order	Page 5 of 17
1.5	Submitted Sample(s)	Page 5 of 17
1.6	Test Duration	Page 5 of 17
1.7	Country of Origin	Page 5 of 17
<u>2.0</u>	Technical Details	
2.1	Investigations Requested	Page 6 of 17
2.2	Test Standards and Results Summary	Page 6 of 17
<u>3.0</u>	<u>Test Results</u>	
3.1	Emission	Page 7-9 of 17
3.2	Bandwidth Measurement	Page 10-11 of 17



Date: 2010-07-26 Page 3 of 17

: MH184069 No.

Appendix A

List of Measurement Equipment Page 12 of 17

Appendix B

Duty Cycle Correction During 100 msec Page 13-15 of 17

Appendix C

Page 16-17 of 17 Photographs



Date: 2010-07-26 Page 4 of 17

No.: MH184069

#### 1.0 General Details

# 1.1 Test Laboratory

The Hong Kong Standards and Testing Centre Ltd. EMC Laboratory 10 Dai Wang Street, Taipo Industrial Estate New Territories, Hong Kong

Telephone: 852 2666 1888 Fax: 852 2664 4353

# 1.2 Applicant Details

#### **Applicant**

Grandex International Development Limited Unit 2401, Million Fortune Industrial Centre, 34-36 Chai Wan Kok Street, Tsuen Wan, N.T., Hong Kong

#### Manufacturer

Grandex International Development Limited Unit 2401, Million Fortune Industrial Centre, 34-36 Chai Wan Kok Street, Tsuen Wan, N.T., Hong Kong



Date: 2010-07-26 Page 5 of 17

No. : MH184069

# 1.3 Equipment Under Test [EUT] Description of Sample(s)

Product: Radio stunt

Manufacturer: Grandex International Development Limited

Brand Name: N/A Model Number: 96105

Rating: 3Vd.c("AA" size battery x 2)

### 1.3.1 Description of EUT Operation

The Equipment Under Test (EUT) is a Grandex International Development Limited, Radio stunt. The EUT is a transmitter of radio control toy. The transmitter was operating with button, the EUT continues to transmit while one of the button is being pressed, It is pulse transmitter, Modulation by IC, and type is amplitude modulation.

#### 1.4 Date of Order

2010-05-05

#### 1.5 Submitted Sample(s):

1 Sample

#### 1.6 Test Duration

2010-05-06, 2010-06-24

# 1.7 Country of Origin

China



Date : 2010-07-26 Page 6 of 17

No. : MH184069

# 2.0 Technical Details

# 2.1 Investigations Requested

Perform ElectroMagnetic Interference measurement in accordance with FCC 47CFR [Codes of Federal Regulations] Part 15: 2009 and ANSI C63.4:2003 for FCC Certification.

# 2.2 Test Standards and Results Summary Tables

EMISSION									
	Results Summary								
Test Condition	Test Requirement	Test Method	Class /	Т	est Result				
			Severity	Pass	Failed	N/A			
Field Strength of Fundamental Emissions & Spurious Emissions	FCC 47CFR 15.227	ANSI C63.4:2003	N/A	$\boxtimes$					
Radiated Emissions	FCC 47CFR 15.209	ANSI C63.4:2003	N/A	$\boxtimes$					

Note: N/A - Not Applicable



Date: 2010-07-26 Page 7 of 17

No. : MH184069

3.0 Test Results

3.1 Emission

3.1.1 Radiated Emissions (30 – 1000MHz)


Test Requirement: FCC 47CFR 15.227
Test Method: ANSI C63.4:2003
Test Date: 2010-06-24
Mode of Operation: Tx mode

#### **Test Method:**

The sample was placed 0.8m above the ground plane of semi-anechoic chamber\*. Measurements in both horizontal and vertical polarities were performed. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, rotating turntable, varying antenna height from 1m to 4m in both horizontal and vertical polarizations. The emissions worst-case are shown in Test Results of the following pages.

\*: Semi-anechoic chamber located on the STC (Dongguan) Company Ltd. 68 Fumin Nan Road, Dalang, Dongguan, Guangdong, PRC with a metal ground plane filed with the FCC pursuant to section 2.948 of the FCC rules, with Registration Number: 629686.

### **Test Setup:**





Date : 2010-07-26 Page 8 of 17

No. : MH184069

#### Limits for Field Strength of Fundamental Emissions [FCC 47CFR 15.227]:

Frequency Range of	Field Strength of	Field Strength of
Fundamental	Fundamental Emission	Fundamental Emission
	[Peak]	[Average]
[MHz]	$[\mu V/m]$	$[\mu V/m]$
26.96-27.28	100,000	10,000

Results of Tx mode: PASS

Field Strength of Fundamental Emissions								
			Peak Value					
Frequency	Measured	Correction	Field	Field	Limit @3m	E-Field		
	Level @3m	Factor	Strength	Strength		Polarity		
MHz	dBμV	dB/m	dΒμV/m	μV/m	μV/m_			
27.145	42.0	18.6	60.6	1,071.5	100,000	Vertical		

Field Strength of Fundamental Emissions										
	A verage Value									
Frequency	Measured	Adjusted by	Correction	Field	Field	Limit @3m	E-Field			
	Level @3m	Duty Cycle	Factor	Strength	Strength		Polarity			
MHz	dΒμV	dB	dB/m	dBμV/m	μV/m	μV/m				
27.145	37.3	-4.7	18.6	55.9	623.7	10,000	Vertical			

According to FCC 47CFR15.35, the limit on the radio frequency emissions as measured using instrumentation with a peak detector function, corresponding to 20dB above the maximum permitted average limit for the frequency being investigated unless a different peak emission limit is otherwise specified in the rules.

### Remarks:

Correction Factor includes Antenna Factor and Cable Attenuation. Calculated measurement uncertainty: 30MHz to 1GHz 5.1dB



Date: 2010-07-26 Page 9 of 17

No. : MH184069

#### Limits for Radiated Emissions [FCC 47 CFR 15.209]:

Frequency Range	Quasi-Peak Limits		
[MHz]	$[\mu V/m]$		
30-88	100		
88-216	150		
216-960	200		
Above960	500		

The emission limits shown in the above table are based on measurement employing a CISPR quasi-peak detector and above 1000MHz are based on measurements employing an average detector.

Results of Tx mode: PASS

Radiated Emissions									
	Quasi-Peak								
Frequency	Measured	Correction	Field	Field	Limit @3m	E-Field			
	Level @ 3m	Factor	Strength	Strength		Polarity			
MHz	dΒμV	dB/m	dBμV/m	μV/m	μV/m				
54.29	7.1	9.3	16.4	6.6	100	Vertical			
81.40	25.0	6.9	31.9	39.4	100	Vertical			
108.60	5.8	8.5	14.3	5.2	150	Vertical			
135.70	14.0	7.6	21.6	12.0	150	Vertical			
162.87	19.6	9.8	29.4	29.5	150	Vertical			
190.00	6.2	10.2	16.4	6.6	150	Vertical			
217.20	6.6	11.1	17.7	7.7	200	Vertical			
434.30	7.3	18.5	25.8	19.5	200	Vertical			
461.50	8.3	18.7	27.0	22.4	200	Vertical			
488.60	6.7	20.7	27.4	23.4	200	Vertical			

#### Remarks:

No further spurious emissions found between lowest internal frequency and 30MHz.

Correction Factor includes Antenna Factor and Cable Attenuation.

Calculated measurement uncertainty : 30MHz to 1GHz 5.1dB



Date: 2010-07-26 Page 10 of 17

No. : MH184069

#### 3.2 20dB Bandwidth of Fundamental Emission

Test Requirement: FCC 47 CFR 15.227

Test Method: ANSI C63.4:2003 (Section 13.1.7)

Test Date: 2010-05-06 Mode of Operation: Tx mode

#### **Test Method:**

The bandwidth is measured at an amplitude level reduced from the reference level by a specified ratio. The reference level is the level of the highest amplitude signal observed from the transmitter at the fundamental frequency. Once the reference level is established, the equipment is conditioned with typical modulating signal to produce the worst-case (i.e. the widest) bandwidth.

#### **Test Setup:**

As Test Setup of clause 3.1.1 in this test report.




Date: 2010-07-26 Page 11 of 17

No. : MH184069

#### Limits for 20dB Bandwidth of Fundamental Emission:

Frequency Range	20dB Bandwidth	FCC Limits
[MHz]	[kHz]	[MHz]
27.04	50.8	within 26.96-27.28

# 20dB Bandwidth of Fundamental Emission \*RBW 10 kHz Marker 1





Date: 2010-07-26 Page 12 of 17

: MH184069 No.

# Appendix A

# **List of Measurement Equipment**

#### **Radiated Emission**

EQP NO.	DESCRIPTION	MANUFACTURER	MODEL NO.	SERIAL NO.	LAST CAL	DUE CAL
EM215	MULTIDEVICE CONTROLLER	EMCO	2090	00024676	N/A	N/A
EM216	MINI MAST SYSTEM	EMCO	2075	00026842	N/A	N/A
EM217	ELECTRIC POWERED TURNTABLE	EMCO	2088	00029144	N/A	N/A
EM218	ANECHOIC CHAMBER	ETS-Linggren	FACT-3		2008/12/01	2011/12/01
EM083	STCOATS				2008/12/08	2011/12/08
EM174	BICONILOG ANTENNA	EMCO	3142B	1671	2010/01/24	2012/01/24
EM229	EMI Test Receiver	R&S	ESIB40	100248	2009/09/27	2010/09/27
EM022	LOOP ANTENNA	EMCO	6502	1189-2424	2009/07/26	2011/07/26

#### Remarks:-

CM Corrective Maintenance

N/A Not Applicable TBD To Be Determined



Date: 2010-07-26 Page 13 of 17

No. : MH184069

#### Appendix B


#### **Duty Cycle Correction During 100msec**

Each function key sends a different series of characters, but each packet period (100msec) never exceeds a series of 20 long pulses (1.6msec) and 53short pulses (0.5msec). Assuming any combination of short and long pulses may be obtained due to encoding the worst case transmit duty cycle would be considered (20\*1.6msec+53\*0.5msec) per 100msec=-4.7dB duty cycle. Figure A through B show the characteristics of the pulse train for one of these functions.

#### Remarks:

Duty Cycle Correction = -4.7dB


The following figures [Figure A to Figure C] show the characteristics of the pulse train for one of these functions.





Date: 2010-07-26 Page 14 of 17


No. : MH184069





Date: 2010-07-26 Page 15 of 17

No. : MH184069





Date: 2010-07-26 Page 16 of 17

No. : MH184069

Appendix C

# **Photographs of EUT**






**Inner Circuit Top View** 











Date: 2010-07-26 Page 17 of 17

No. : MH184069

# Photographs of EUT





\*\*\*\*\* End of Test Report \*\*\*\*\*