



Compliance Certification Services (Kunshan) Inc.

CCSEM-TRF-001 Rev. 02 Sep 01, 2023

Report No.: KSCR240200027003

Page: 1 of 12

1 Cover Page

RF Exposure Evaluation Report

Application No.: KSCR2402000270AT
FCC ID: VDE20242021950
IC: 8036A-20242021950
Applicant: Generac Power Systems Inc.
Address of Applicant: S45 W29290 Hwy. 59 Waukesha, Wisconsin, United States 53189
Manufacturer: Wistron Technology (Malaysia) Sdn Bhd
Address of Manufacturer: No 1, Jalan Sultan Alauddin 5, Kawasan Perindustrian Fasa 4, Bandar Sultan Suleiman, 42000 Pelabuhan Klang, Selangor, Malaysia.

Equipment Under Test (EUT):
EUT Name: Generac Fuel Tracker Gen 5, LTE
Model No.: CG5RUU-M950
Standard(s) : FCC Rules 47 CFR §2.1091
KDB 447498 D04 interim General RF Exposure Guidance v01
RSS-102 Issue 5 Amendment 1 (February 2, 2021)
Date of Receipt: 2024-02-22
Date of Test: 2024-03-01 to 2024-03-04
Date of Issue: 2024-03-19

Test Result:	Pass*
---------------------	--------------

* In the configuration tested, the EUT complied with the standards specified above.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein.

Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.



Compliance Certification Services (Kunshan) Inc.

CCSEM-TRF-001 Rev. 02 Sep 01, 2023

Report No.: KSCR240200027003

Page: 2 of 12

<i>Revision Record</i>			
<i>Version</i>	<i>Description</i>	<i>Date</i>	<i>Remark</i>
00	Original	2024-03-19	/

Authorized for issue by:			
Tested By		<i>Maker Qi</i>	
		<hr/> Maker_Qi //Project Engineer	
Approved By		<i>Terry Hou</i>	
		<hr/> Terry Hou /Reviewer	



Compliance Certification Services (Kunshan) Inc.

CCSEM-TRF-001 Rev. 02 Sep 01, 2023

Report No.: KSCR240200027003

Page: 3 of 12

2 Contents

	Page
1 Cover Page	1
2 Contents	3
3 General Information.....	4
3.1 General Description of E.U.T.	4
3.2 Technical Specifications.....	4
3.3 Separation Distance	5
3.4 Test Location.....	6
3.5 Test Facility	6
4 FCC Radiofrequency radiation exposure limits	7
4.1 Blanket 1 mW Blanket Exemption.....	7
4.2 MPE-based Exemption	7
4.3 SAR-based Exemption.....	8
5 Measurement and Calculation.....	11
5.1 Maximum transmit power	11
5.2 RF Exposure Calculation	12

3 General Information

3.1 General Description of E.U.T.

Power supply:	2.2 - 4.35 V, typ. 3.3 V
---------------	--------------------------

3.2 Technical Specifications

BLE

Operation Frequency:	2402MHz to 2480MHz
Modulation Type:	GFSK
Number of Channels:	40
Channel Spacing:	2MHz
Antenna Type:	Chip Antenna
Antenna Gain:	0.5dBi(Provided by the manufacturer)

4G

LTE Operation Frequency Band:	Band 2/4/5/12/13/25/26/66
NB-IOT Operation Frequency Band:	Band 2/4/5/12/13/17/25/66
LTE Modulation Type:	QPSK,16QAM
NB-IOT Modulation Type:	BPSK,QPSK
Antenna Type:	FPC antenna
Antenna Gain:	Band 2:3.13dBi(Provided by the manufacturer) Band 4:3.13dBi(Provided by the manufacturer) Band 5:1.02dBi(Provided by the manufacturer) Band 12:1.02dBi(Provided by the manufacturer) Band 13: 1.02dBi(Provided by the manufacturer) Band 17: 1.02dBi(Provided by the manufacturer) Band 25: 3.13dBi(Provided by the manufacturer) Band 26: 1.02dBi(Provided by the manufacturer) Band 66: 3.13dBi(Provided by the manufacturer)
LTE Category:	M1
NB-IOT Category:	NB1



Compliance Certification Services (Kunshan) Inc.

CCSEM-TRF-001 Rev. 02 Sep 01, 2023

Report No.: KSCR240200027003

Page: 5 of 12

3.3 Separation Distance

Separation distance between the antenna to person (R):	>20cm
Remark: This minimum test separation distance is determined by the smallest distance from the antenna and radiating structures or outer surface of the device, according to the host form factor, exposure conditions and platform requirements, to any part of the body or extremity of a user or bystander. R has been stated in user manual.	

3.4 Test Location

All tests were performed at:

Compliance Certification Services (Kunshan) Inc.

No.10 Weiye Rd, Innovation park, Eco&Tec, Development Zone, Kunshan City, Jiangsu, China.

Tel: +86 512 5735 5888 Fax: +86 512 5737 0818

No tests were sub-contracted.

Note:

1.SGS is not responsible for wrong test results due to incorrect information (e.g. max. clock frequency, highest internal frequency, antenna gain, cable loss, etc) is provided by the applicant. (if applicable).

2.SGS is not responsible for the authenticity, integrity and the validity of the conclusion based on results of the data provided by applicant. (if applicable).

3. Sample source: sent by customer.

3.5 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **A2LA**

Compliance Certification Services (Kunshan) Inc. is accredited by the American Association for Laboratory Accreditation (A2LA). Certificate No. 2541.01.

- **FCC**

Compliance Certification Services (Kunshan) Inc. has been recognized as an accredited testing laboratory. Designation Number: CN1172.

- **ISED**

Compliance Certification Services (Kunshan) Inc. has been recognized by Innovation, Science and Economic Development Canada (ISED) as an accredited testing laboratory. Company Number: 2324E

- **VCCI**

The 3m and 10m Semi-anechoic chamber and Shielded Room of Compliance Certification Services (Kunshan) Inc. has been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: R-20134, R-11600, C-11707, T-11499, G-10216 respectively.

4 FCC Radiofrequency radiation exposure limits

Test exemptions apply for devices used in general population/uncontrolled exposure environments, according to the SAR-based, or MPE-based exemption thresholds.

4.1 Blanket 1 mW Blanket Exemption

The 1 mW Blanket Exemption of §1.1307(b)(3)(i)(A) applies for single fixed, mobile, and portable RF sources with available maximum time-averaged power of no more than 1 mW, regardless of separation distance.

The 1-mW blanket exemption applies at separation distances less than 0.5 cm, including where there is no separation. This exemption shall not be used in conjunction with other exemption criteria other than those for multiple RF sources in paragraph §1.1307(b)(3)(ii)(A).

The 1-mW exemption is independent of service type and covers the full range of 100 kHz to 100 GHz, but it shall not be used in conjunction with other exemption criteria or in devices with higher-power transmitters operating in the same time-averaging period. Exposure from such higher-power transmitters would invalidate the underlying assumption that exposure from the lower-power transmitter is the only contributor to SAR in the relevant volume of tissue.

4.2 MPE-based Exemption

General frequency and separation-distance dependent MPE-based effective radiated power (ERP) thresholds are in Table B.1 [Table 1 of §1.1307(b)(1)(i)(C)] to support an exemption from further evaluation from 300 kHz through 100 GHz.

Table B.1—Thresholds For Single RF Sources Subject to Routine Environmental Evaluation

RF Source Frequency			Minimum Distance			Threshold ERP
f_L MHz		f_H MHz	$\lambda_L / 2\pi$		$\lambda_H / 2\pi$	W
0.3	–	1.34	159 m	–	35.6 m	1,920 R ²
1.34	–	30	35.6 m	–	1.6 m	3,450 R ² /f ²
30	–	300	1.6 m	–	159 mm	3.83 R ²
300	–	1,500	159 mm	–	31.8 mm	0.0128 R ² f
1,500	–	100,000	31.8 mm	–	0.5 mm	19.2R ²
Subscripts L and H are low and high; λ is wavelength. From §1.1307(b)(3)(i)(C), modified by adding Minimum Distance columns.						

The table applies to any RF source (i.e. single fixed, mobile, and portable transmitters) and specifies power and distance criteria for each of the five frequency ranges used for the MPE limits. These criteria apply at separation distances from any part of the radiating structure of at least $\lambda/2\pi$. The thresholds are based on the general population MPE limits with a single perfect reflection, outside of the reactive near-field, and in the main beam of the radiator.

For mobile devices that are not exempt per Table B.1 [Table 1 of §1.1307(b)(1)(i)(C)] at distances from 20 cm to 40 cm and in 0.3 GHz to 6 GHz, evaluation of compliance with the exposure limits in §1.1310 is necessary if the ERP of the device is greater than ERP_{20cm} in Formula (B.1) [repeated from §2.1091(c)(1); also in §1.1307(b)(1)(i)(B)].

$$P_{th} \text{ (mW)} = ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases} \quad (\text{B.1})$$

If the ERP is not easily obtained, then the available maximum time-averaged power may be used (i.e., without consideration of ERP only if the physical dimensions of the radiating structure(s) do not exceed the electrical length of $\lambda/4$ or if the antenna gain is less than that of a half-wave dipole.

SAR-based exemptions are constant at separation distances between 20 cm and 40 cm to avoid discontinuities in the threshold when transitioning between SAR-based and MPE-based exemption criteria at 40 cm, considering the importance of reflections.

Limit calculation			
Frequency range	Frequency(MHz)	$R(\lambda/2\pi)$ (m)	Threshold ERP(W)
300~1500MHz	915	0.0522	0.032
1500~10000MHz	2462	0.0194	0.007

4.3 SAR-based Exemption

SAR-based thresholds are derived based on frequency, power, and separation distance of the RF source. The formula defines the thresholds in general for either available maximum time-averaged power or maximum time-averaged ERP, whichever is greater.

If the ERP of a device is not easily determined, such as for a portable device with a small form factor, the applicant may use the available maximum time-averaged power exclusively if the device antenna or radiating structure does not exceed an electrical length of $\lambda/4$.

As for devices with antennas of length greater than $\lambda/4$ where the gain is not well defined, but always less than that of a half-wave dipole (length $\lambda/2$), the available maximum time-averaged power generated by the device may be used in place of the maximum time-averaged ERP, where that value is not known. The separation distance is the smallest distance from any part of the antenna or radiating structure for all persons, during operation at the applicable ERP. In the case of mobile or portable devices, the separation distance is from the outer housing of the device where it is closest to the antenna.

The SAR-based exemption formula of §1.1307(b)(3)(i)(B), repeated here as Formula (B.2), applies for single fixed, mobile, and portable RF sources with available maximum time-averaged power or effective radiated power (ERP), whichever is greater, of less than or equal to the threshold P_{th} (mW).

This method shall only be used at separation distances from 0.5 cm to 40 cm and at frequencies from 0.3 GHz to 6 GHz (inclusive). P_{th} is given by Formula (B.2).

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}}(d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases} \quad (\text{B.2})$$

where

$$x = -\log_{10} \left(\frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right)$$

and f is in GHz, d is the separation distance (cm), and $ERP_{20 \text{ cm}}$ is per Formula (B.1).



Compliance Certification Services (Kunshan) Inc.

CCSEM-TRF-001 Rev. 02 Sep 01, 2023

Report No.: KSCR240200027003

Page: 9 of 12

Example values shown in Table B.2 are for illustration only.

Table B.2—Example Power Thresholds (mW)

Frequency (MHz)	Distance(mm)									
	5	10	15	20	25	30	35	40	45	50
300	39	65	88	110	129	148	166	184	201	217
450	22	44	67	89	112	135	158	180	203	226
835	9	25	44	66	90	116	145	175	207	240
1900	3	12	26	44	66	92	122	157	195	236
2450	3	10	22	38	59	83	111	143	179	219
3600	2	8	18	32	49	71	96	125	158	195
5800	1	6	14	25	40	58	80	106	136	169

For BLE

Limit calculation				
Frequency range(GHz)	Frequency(GHz)	X	Distance(cm)	Pth (mW)
1.5~6	2480	3.405	20	3060.000

For 4G

Limit calculation				
Frequency range(GHz)	Frequency(GHz)	X	Distance(cm)	Pth (mW)
1.5~6	1860	3.342	20	3060.000

4.4 IC Radiofrequency radiation exposure limits:

According to RSS-102 section 2.5.2, RF exposure evaluation is required if the separation distance between the user and/or bystander and the device' s radiating element is greater than 20 cm, except when the device operates as follows:

below 20 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 1 W (adjusted for tune-up tolerance);

- at or above 20 MHz and below 48 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than $4.49/f$ 0.5 W (adjusted for tune-up tolerance), where f is in MHz;
- at or above 48 MHz and below 300 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 0.6 W (adjusted for tune-up tolerance);
- at or above 300 MHz and below 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than $1.31 \times 10^{-2} f$ 0.6834 W (adjusted for tune-up tolerance), where f is in MHz;
- at or above 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 5 W (adjusted for tune-up tolerance).

For BLE device, the limit of worse case is 2.68 W,

For LTE B2,the limit of worse case is 2.14W,

For LTE B4,the limit of worse case is 2.12W,

For LTE B5,the limit of worse case is 1.29W,

For LTE B12,the limit of worse case is 1.15W,

For LTE B13,the limit of worse case is 1.24W,

For LTE B17,the limit of worse case is 1.16W,

For LTE B25,the limit of worse case is 2.24W,

For LTE B26,the limit of worse case is 1.29W,

For LTE B66,the limit of worse case is 2.12W

5 Measurement and Calculation

5.1 Maximum transmit power

The Power Data is based on the RF Test Report KSCR240200027001, R2107A0607-M1

BLE

Test Mode	Test Frequency (MHz)	Output Power (dBm)	Output Power (mW)
1M	2402	5.77	3.78
	2440	5.38	3.45
	2480	5.42	3.48
2M	2402	5.80	3.80
	2440	5.40	3.47
	2480	5.45	3.51

4G

Test Mode	Test Frequency (MHz)	Output Power (dBm)	Output Power (mW)
Band 2	1880	25.70	371.54
Band 4	1732.5	25.70	371.54
Band 5	836.5	25.70	371.54
Band 12	707.5	25.70	371.54
Band 13	782	25.70	371.54
Band 17	710	25.70	371.54
Band 25	1880	25.70	371.54
Band 26	829	25.70	371.54
Band 66	1745	25.70	371.54

Compliance Certification Services (Kunshan) Inc.

5.2 RF Exposure Calculation

For FCC

BLE:

The Max Conducted Peak Output Power is 3.80mW. The best case gain of the antenna is 0.5dBi.

0.5dBi logarithmic terms convert to numeric result is nearly 1.12.

According to the formula. calculate the EIRP test result:

$$\text{EIRP} = P \times G = 3.80 \text{ mW} \times 1.12 = 4.26\text{mW} < 3060\text{mW}$$

4G:

The Max Conducted Peak Output Power is 371.54mW. The best case gain of the antenna is 3.13dBi.

3.13dBi logarithmic terms convert to numeric result is nearly 2.06.

According to the formula. calculate the EIRP test result:

$$\text{EIRP} = P \times G = 371.54\text{mW} \times 2.06 = 765.37\text{mW} < 3060\text{mW}$$

The BLE and 4GHz WiFi can transmit simultaneously, but the maximum rate of MPE is $4.26/3060+765.37/3060=0.25 \leq 1$.

Remark: we used the maximum power between the conducted power and ERP/EIRP to perform RF exposure exemption evaluation.

	Evaluation method	Exempt Limit(mW)	Verdict
<input type="checkbox"/>	Blanket 1 mW Blanket Exemption	1mW	N/A
<input type="checkbox"/>	MPE-based Exemption(ERP)	7mW(ERP) (2.4GHz Band)	N/A
<input checked="" type="checkbox"/>	SAR-based Exemption(P_{th})	3060mW(ERP) (1.5GHz~6GHz)	Yes

For IC:

BLE:

$$\text{EIRP} = P \times G = 0.0038 \text{ W} \times 1.12 = 0.004\text{W} < 2.68\text{W}$$

4G:

$$\text{E.I.R.P.} = P \times G = 0.37154 \text{ W} \times 2.06 = 0.765\text{W} < 2.24\text{W}$$

The 2.4GHz BT and WWAN can transmit simultaneously, but the maximum rate of MPE is $0.004/2.68+0.765/2.24=0.343 \leq 1$. So the device is exclusion from SAR test.

So, the device is to qualify for SAR test exemption, the exemption report is in lieu of the SAR report

--End of the Report--