TEST REPORT

FROM



FOR

ST Electronics (Satcom & Sensor Systems) Pte Ltd

Microwave Sensor

Model: LB200

ΤО

47 CFR 15.249 :2007

Test Report Serial No.: SL07050101-STE-001(FCC 15C)

This report supersedes None

Remarks: Equipment complied with the specification [X] ΪÌ Equipment did not comply with the specification

This Test Report is Issued Under the Authority of:

Snell leing

Tested by: Snell Leong, Test Engineer

..... Reviewed by: Leslie Bai, Reviewer

Issue date:

13 June 2007 Manufacturer: ST Electronics (Satcom & Sensor Systems) Pte Ltd











Registration No. 783147

Registration No. 4842



RTA No. D23/16V









This test report may be reproduced in full only.



SL07050101-STE-001(FCC 15C) 13 June 2007 2 of 22

This page has been left blank intentionally.



SL07050101-STE-001(FCC 15C) 13 June 2007 3 of 22

CONTENTS

EX	ECUTIVE SUMMARY	5
1	TECHNICAL DETAILS	6
2	TESTS REQUIRED	7
3	ANTENNA REQUIREMENT	8
4	MEASUREMENTS, EXAMINATIONS AND DERIVED RESULTS	9
5	TEST INSTRUMENTATION	.14
AP	PENDIX A: EUT TEST CONDITIONS	.15
AP	PENDIX B: EXTERNAL PHOTOS	.16
AP	PENDIX C: CIRCUIT/BLOCK DIAGRAMS	.17
AP	PENDIX D: INTERNAL PHOTOS	.18
AP	PENDIX E: PRODUCT DESCRIPTION	.19
AP	PENDIX F: FCC LABEL LOCATION	.20
AP	PENDIX G: USER MANUAL	.21



SL07050101-STE-001(FCC 15C) 13 June 2007 4 of 22

This page has been left blank intentionally.



SL07050101-STE-001(FCC 15C) 13 June 2007 5 of 22

Executive Summary

The purpose of this test programme was to demonstrate compliance of the ST Electronics (Satcom & Sensor Systems) Pte Ltd , Microwave Sensor, model LB200 against the current 47 CFR 15.249 :2007. The Microwave Sensor demonstrated compliance with the 47 CFR 15.249 :2007.

ST Electronics (Satcom & Sensor Systems) Pte Ltd is the applicant and claimed manufacturer of this tested product. For the detailed description of this product, please refer to the Microwave Sensor User Manual.

The equipment under test operating frequency is 5800MHz.

The test has demonstrated that this unit complies with stipulated standards.



SL07050101-STE-001(FCC 15C) 13 June 2007 6 of 22

1 Technical Details

Purpose	Compliance testing of Microwave Sensor with 47 CFR 15.249 2007:
Applicant / Client	ST Electronics (Satcom & Sensor Systems) Pte Ltd 100, Jurong East St 21, Level 4, ST Electronics Jurong East Building Singapore, 609602
Manufacturer	ST Electronics (Satcom & Sensor Systems) Pte Ltd
Laboratory performing the tests	SIEMIC Labs 2206 Ringwood Avenue San Jose, CA 95131
Test location(s)	SIEMIC Labs 2206 Ringwood Avenue San Jose, CA 95131
Test report reference number Date EUT received Standard applied Dates of test (from – to)	SL07050101-STE-001(FCC 15C) 25 April 2007 47 CFR 15.249 :2007 25 April 2007 to 30 April 2007

No of Units: Equipment Category: Trade/Product Name: Type/Model Name/No: Technical Variants:

FCC ID No. IC ID No. 25 April 2007 25 April 2007 47 CFR 15.249 :2007 25 April 2007 to 30 April 2007 1 DXX LB200 LB200 N/A

> VECLB200 N/A



2 Tests Required

The product was tested in accordance with the following specifications. The test results recorded in this Test Report are exclusively referred to the tested sample(s).

Test Sta	ndard	Description	Pass / Fail	
47 CFR Part 15.225: 2006	RSS 210 Issue 6: 2005			
15.203		Antenna Requirement	Pass	
15.207(a)		Conducted Emissions Voltage	Pass	
15.249 (a), (d) & (e)		Fundamental & Radiated Spurious Emission Limits	Pass	
ANSI C63.4: 2003 / RSS-Gen Issue 1: 2005				

Notes: Deviations to above standards are outlined in specific test sections if applicable. Cable loss and external attenuation are compensated for in the measurement system when applicable.



3 Antenna Requirement

Requirement(s): 47 CFR §15.203

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

Antenna requirement must meet at least one of the following:

- a) Antenna must be permanently attached to the device.
- b) Antenna must use a unique type of connector to attach to the device.
- c) Device must be professionally installed. Installer shall be responsible for ensuring that the correct antenna is employed with the device.
- 1) The EUT antenna is attached permanently to the device which meets the requirement.



4 Measurements, Examinations and Derived Results

4.1 General observations

Equipment serial number(s)					
EUT:	Model number:	Serial number:			
Microwave Sensor	LB200	none			



 Title:
 FCC Part 15C Test Report for ST Electronics

 (Satcom & Sensor Systems) Pte Ltd , Model : LB200
 FCCID:

 FCCID:
 VECLB200

 To:
 47 CFR 15.249 :2007

Serial# Issue Date Page SL07050101-STE-001(FCC 15C) 13 June 2007 10 of 22

4.2 Test Results

4.2.1 Conducted Emissions Voltage

Requirement(s): 47 CFR §15.207

Procedures:

The EUT and supporting equipment were set up in accordance with the requirements of the standard on top of a 1.5m x 1m x 0.8m high, non-metallic table. The power supply for the EUT was fed through a $50\Omega/50\mu$ H EUT LISN, connected to filtered mains. The RF OUT of the EUT LISN was connected to the EMI test receiver via a low-loss coaxial cable. All other supporting equipment were powered separately from another mains.

The EUT was switched on and allowed to warm up to its normal operating condition. A scan was made on the NEUTRAL line over the required frequency range using an EMI test receiver. High peaks, relative to the limit line, were then selected. The EMI test receiver was then tuned to the selected frequencies and the necessary measurements made with a receiver bandwidth setting of 10kHz. Quasi-peak and Average measurements were made. The procedure was then repeated for the PHASE line.

Results:



Neutral Line Plot at 120Vac, 60Hz



Title:FCC Part 15C Test Report for ST Electronics(Satcom & Sensor Systems) Pte Ltd , Model : LB200FCCID:VECLB200To:47 CFR 15.249 :2007

Serial# Issue Date Page SL07050101-STE-001(FCC 15C) 13 June 2007 11 of 22



Phase Line Plot at 120Vac, 60Hz

LINE	FREQ (MHz)	Corrected Amplitude (dBµV) PK	Limit (dBµV) QP	Margin (dB) QP	Corrected Amplitude (dBµV) PK	Limit (dBµV) AVG	Margin (dB) AVG
Neutral	0.33	41.70	59.45	-17.75	35.60	49.45	-13.85
Neutral	1.49	40.10	56.00	-15.90	34.20	46.00	-11.80
Neutral	0.97	40.90	56.00	-15.10	34.80	46.00	-11.20
Phase	2.16	37.60	56.00	-18.40	33.10	46.00	-12.90
Phase	0.97	39.50	56.00	-16.50	35.50	46.00	-10.50
Phase	1.49	39.80	56.00	-16.20	36.60	46.00	-9.40

Conducted Emission Table

Note: PK = peak; QP = quasi-peak; AVG = average detector.

Tested By: Snell Leong Date Tested: 01 June 2007



4.2.2 Radiated Fundamental & Spurious Emissions

Requirement(s): 47 CFR §15.209; 47 CFR §15.249 (a) & (d)

Procedures: Radiated emissions were measured according to ANSI C63.4. The EUT was set to transmit at the highest output power. The EUT was set 3 meter away from the measuring antenna. The loop antenna was positioned 1 meter above the ground from the center of the loop. The measuring bandwidth was set to 10 kHz.

The limit is converted from microvolts/meter to decibel microvolts/meter.

Sample Calculation: Corrected Amplitude = Raw Amplitude($dB\mu V/m$) + ACF(dB) + Cable Loss(dB) – Distance Correction Factor



Frequency	Azimuth	Measure	Antenna Polarity	Antenna Height	Raw Amplitude @ 3m	ACF	CBL loss	Corrected Amplitude @ 3m	Limit @3m	Delta
(MHz)	(degrees)	(Avg/QP)	(H/V)	(m)	(dBuV/m)	(dBm)	(dBm)	(dBuV/m)	(dBuV/m)	(dBuV/m)
34.85	180	QP	V	1	16.20	17.9	0.7	34.8	40	-5.20
45.20	200	QP	V	1	20.10	8.5	0.7	29.3	40	-10.70
100.50	0	QP	V	1	12.90	11.3	0.9	25.1	43.5	-18.40
262.00	0	QP	Н	2.1	19.40	12.7	1	33.1	46	-12.90
548.00	180	QP	Н	2.1	11.20	18.3	1.8	31.3	46	-14.70
826.00	0	QP	Н	2.1	8.30	21.8	2.2	32.3	46	-13.70



Title:FCC Part 15C Test Report for ST Electronics
(Satcom & Sensor Systems) Pte Ltd , Model : LB200
FCCID:FCCID:VECLB200
47 CFR 15.249 :2007

Serial# Issue Date Page SL07050101-STE-001(FCC 15C) 13 June 2007 13 of 22

Results:

1GHz ~ 40GHz @ 1 Meter

Frequency	Azimuth	Antenna	Height	Raw Amp.	Pre	Ant.Corr.	Cable	Distance	Corrected Field	Limit	Delta	Detector	Remark
		Polarity		@ 3m	Amp.	Factor	Loss	Factor	Strength	@ 3m			
(GHz)	(Degrees)	(H/V)	(m)	(dBuV)	(dB)	(dB)	(dB)	dB	(dBuV/m)	(dBuV/m)	(dBuV/m)	(pk/avg)	
5.800	0	Н	1	83.3	32.41	34.47	3.89	10.00	79.24	114	-34.76	PK	Fund
5.800	0	Н	1	83.5	32.41	34.47	3.89	10.00	79.44	94	-14.56	AVG	Fund
5.800	90	V	1.5	74.2	32.41	34.27	3.89	10.00	69.94	114	-44.06	PK	Fund
5.800	90	V	1.5	73.2	32.41	34.27	3.89	10.00	68.94	94	-25.06	AVG	Fund
11.600	0	Н	1.4	49.4	32.50	43.17	5.98	10.00	56.05	74	-17.95	PK	2nd
11.600	0	Н	1.4	43.8	32.50	43.17	5.98	10.00	50.45	54	-3.55	AVG	2 nd
11.600	0	V	1	46.9	32.50	41.79	5.98	10.00	52.17	74	-21.83	PK	2 nd
11.600	0	V	1	36.33	32.50	41.79	5.98	10.00	41.60	54	-12.40	AVG	2 nd
17.400	90	Н	1	45.1	31.56	44.91	7.86	10.00	56.31	74	-17.69	PK	Noise Floor
17.400	312	Н	1	32.2	31.56	44.91	7.86	10.00	43.41	54	-10.59	AVG	Noise Floor
17.400	0	V	1	45.5	31.56	44.99	7.86	10.00	56.79	74	-17.21	PK	Noise Floor
17.400	0	V	1	32.6	31.56	44.99	7.86	10.00	43.89	54	-10.11	AVG	Noise Floor
5.725	0	V	1	32.6	32.42	34.44	3.87	10.00	28.49	54	-25.51	AVG	Bandedge
5.725	0	Н	1	32.5	32.42	34.44	3.87	10.00	28.39	54	-25.61	AVG	Bandedge
5.875	0	V	1	33.2	32.40	34.32	3.90	10.00	29.02	54	-24.98	AVG	Bandedge
5.875	0	Н	1	32.1	32.40	34.32	3.90	10.00	27.92	54	-26.08	AVG	Bandedge

Tested By: Snell Leong Date Tested: 01 June 2007



5 TEST INSTRUMENTATION

5.1 TEST INSTRUMENTATION

Instrument	Manufacturer	Model	CAL Due Date
Spectrum Analyzer	HP	8568B	04/26/2008
Quasi-Peak Adapter	HP	85650A	04/26/2008
RF Pre-Selector	HP	85685A	04/26/2008
Spectrum Analyzer	HP	8564E	05/01/2008
Power Meter	HP	437B	04/26/2008
Power Sensor	HP	8485A	04/26/2008
Antenna	EMCO	JB1	09/11/2007
Pre-Amplifier	HP(1G~26.5G)	8449	05/01/2008
Horn Antenna	COM Power(18G~40G)	AH-840	03/19/2010
Horn Antenna	EMCO(1G~18G)	3115	08/17/2007
DMM	Fluke	73111	05/01/2008
Variac	KRM	AEEC-2090	See Note
DMM	Fluke	5111	See Note
LISN (9k-30MHz) Chase		MN2050B	4/26/2008

Note: Functional Verification



APPENDIX A: EUT TEST CONDITIONS

The following is the description of supporting equipment and details of cables used with the EUT.

Equipment Description	Cable Description
(Including Brand Name)	
Microwave Sensor	1. AC Cord

EUT Description	:	Microwave Sensor
Model No	:	LB200
Serial No	:	none

The following is the description of how the EUT is exercised during testing.

Test	Description Of Operation
All testing	The EUT was set to enter CW mode automatically when powered.



Title:FCC Part 15C Test Report for ST Electronics(Satcom & Sensor Systems) Pte Ltd , Model : LB200FCCID:VECLB200To:47 CFR 15.249 :2007

Serial# Issue Date Page SL07050101-STE-001(FCC 15C) 13 June 2007 16 of 22

APPENDIX B: EXTERNAL PHOTOS



Title:FCC Part 15C Test Report for ST Electronics
(Satcom & Sensor Systems) Pte Ltd , Model : LB200
FCCID:FCCID:VECLB200
47 CFR 15.249 :2007

Serial# Issue Date Page SL07050101-STE-001(FCC 15C) 13 June 2007 17 of 22

APPENDIX C: CIRCUIT/BLOCK DIAGRAMS



SL07050101-STE-001(FCC 15C) 13 June 2007 18 of 22

APPENDIX D: INTERNAL PHOTOS



SL07050101-STE-001(FCC 15C) 13 June 2007 19 of 22

APPENDIX E: PRODUCT DESCRIPTION

Detail description of this product is shown in the User's Guide.



Title:FCC Part 15C Test Report for ST Electronics
(Satcom & Sensor Systems) Pte Ltd , Model : LB200FCCID:VECLB200To:47 CFR 15.249 :2007

Serial# Issue Date Page SL07050101-STE-001(FCC 15C) 13 June 2007 20 of 22

APPENDIX F: FCC LABEL LOCATION



SL07050101-STE-001(FCC 15C) 13 June 2007 21 of 22

APPENDIX G: USER MANUAL



Title:FCC Part 15C Test Report for ST Electronics(Satcom & Sensor Systems) Pte Ltd , Model : LB200FCCID:VECLB200To:47 CFR 15.249 :2007

Serial# Issue Date Page SL07050101-STE-001(FCC 15C) 13 June 2007 22 of 22

END OF REPORT