

## 7. RF Exposure Requirements

### 7.1 Test Equipment

Please refer to Section 10 this report.

### 7.2 Limit

According to FCC 15.247(e)(i) and FCC 1.1307(b)(1), Systems operating under provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the Commissions guidelines.

According to KDB 447498 D01 General RF Exposure Guidance v06, section 4.3.1

SAR Test Exclusion Thresholds for 100 MHz-6GHz and <=5mm

Frequency Range		Maximum measured transmitter power frequency(MHz)	SAR Limitation (mW)
Low Frequency(MHz)	High Frequency(MHz)		
2402	2480	2440	10

### 7.3 Test Result

Product	: LUCID AMPED BLUETOOTH HEADPHONE	Test Mode	: Bluetooth 4.0 LE
Test Item	: RF Exposure	Temperature	: 25 °C
Test Voltage	: DC 3V	Humidity	: 56%RH
Test Result	: <b>PASS</b>		

RF Exposure Requirements	Compliance with FCC Rules
<p>EIRP=P<sub>x</sub>G</p> <p>Where:                      P=Power input to antenna                      G=Power gain of the antenna relative to an isotropic radiator</p>	<p>Maximum output power at antenna input terminal:                      0.26dBm = 1.06mW (Bluetooth 4.0 LE, 2440MHz)                      Prediction distance: &lt;=5mm                      Antenna gain : -0.61dBi                      SAR Test Exclusion Threshold is 10mW</p> <p>Bluetooth 4.0 LE : 0.92mW                      The max. output power E.I.R.P &lt; 10mW                      Conclusion: No SAR is required.</p>