






# FCC Part 15C Measurement and Test Report

For

**K-Mark Industrial Limited.**

Flat A, 7/F., Mai On Ind. Bldg 17-21 Kung Yip St., Kwai Chung Hong Kong

**FCC ID: VEP-MXLA**

<b>FCC Rule(s):</b>	<u>FCC Part 15.247</u>
<b>Product Description:</b>	<u>Motorola XL Smart Safe</u>
<b>Tested Model:</b>	<u>MXLA</u>
<b>Report No.:</b>	<u>WTX20X01000568W-1</u>
<b>Sample Receipt Date:</b>	<u>Jan.02, 2020</u>
<b>Tested Date:</b>	<u>Jan.02, 2020 to Mar.10, 2020</u>
<b>Issued Date:</b>	<u>Mar.10, 2020</u>
<b>Tested By:</b>	<u>Jason Su Engineer</u> 
<b>Reviewed By:</b>	<u>Lion Cai / RF Manager</u> 
<b>Approved &amp; Authorized By:</b>	<u>Silin Chen / Manager</u> 
<b>Prepared By:</b>	<p><b>Waltek Testing Group (Shenzhen) Co., Ltd.</b> 1/F., Room 101, Building 1, Hongwei Industrial Park, Liuxian 2nd Road, Block 70 Bao'an District, Shenzhen, Guangdong, China Tel.: +86-755-33663308 Fax.: +86-755-33663309 Website: www.semtest.com.cn</p>

Note: This test report is limited to the above client company and the product model only. It may not be duplicated without prior permitted by Waltek Testing Group (Shenzhen) Co., Ltd.



**TABLE OF CONTENTS**

**1. GENERAL INFORMATION.....4**

    1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT).....4

    1.2 TEST STANDARDS.....5

    1.3 TEST METHODOLOGY .....5

    1.4 TEST FACILITY .....5

    1.5 EUT SETUP AND TEST MODE.....6

    1.6 MEASUREMENT UNCERTAINTY .....7

    1.7 TEST EQUIPMENT LIST AND DETAILS .....8

**2. SUMMARY OF TEST RESULTS .....10**

**3. RF EXPOSURE .....11**

    3.1 STANDARD APPLICABLE.....11

    3.2 TEST RESULT.....11

**4. ANTENNA REQUIREMENT .....12**

    4.1 STANDARD APPLICABLE.....12

    4.2 EVALUATION INFORMATION .....12

**5. POWER SPECTRAL DENSITY .....13**

    5.1 STANDARD APPLICABLE.....13

    5.2 TEST PROCEDURE.....13

    5.3 SUMMARY OF TEST RESULTS/PLOTS .....13

**6. DTS BANDWIDTH.....18**

    6.1 STANDARD APPLICABLE.....18

    6.2 TEST PROCEDURE.....18

    6.3 SUMMARY OF TEST RESULTS/PLOTS .....18

**7. RF OUTPUT POWER .....23**

    7.1 STANDARD APPLICABLE.....23

    7.2 TEST PROCEDURE.....23

    7.3 SUMMARY OF TEST RESULTS/PLOTS .....23

**8. FIELD STRENGTH OF SPURIOUS EMISSIONS .....29**

    8.1 STANDARD APPLICABLE.....29

    8.2 TEST PROCEDURE.....29

    8.3 CORRECTED AMPLITUDE & MARGIN CALCULATION.....30

    8.4 SUMMARY OF TEST RESULTS/PLOTS .....30

**9. OUT OF BAND EMISSIONS.....38**

    9.1 STANDARD APPLICABLE.....38

    9.2 TEST PROCEDURE.....38

    9.3 SUMMARY OF TEST RESULTS/PLOTS .....39

**10. CONDUCTED EMISSIONS .....60**

    10.1 TEST PROCEDURE.....60

    10.2 BASIC TEST SETUP BLOCK DIAGRAM.....60

    10.3 TEST RECEIVER SETUP .....60

    10.4 SUMMARY OF TEST RESULTS/PLOTS .....60



## Report version

Version No.	Date of issue	Description
Rev.00	Mar.10, 2020	Original
/	/	/



# 1. GENERAL INFORMATION

## 1.1 Product Description for Equipment Under Test (EUT)

### Client Information

Applicant: K-Mark Industrial Limited.  
 Address of applicant: Flat A, 7/F., Mai On Ind. Bldg 17-21 Kung Yip St.,  
 Kwai Chung Hong Kong

Manufacturer: ITSmart Security, LLC  
 Address of manufacturer: West Harrison, NY 10604, USA

General Description of EUT	
Product Name:	Motorola XL Smart Safe
Trade Name:	/
Model No.:	MXLA
Adding Model(s):	/
Rated Voltage:	DC 6V for battery/ DC5V for adapter
Power adapter	SAW12-050-2000UD INPUT: AC100-240, 50/60Hz, 0.3A; Output: DC5V, 2000mA
Serial Number :	MXLA-001-0-000008
Software Version:	V1.9.5
<i>Note: The test data is gathered from a production sample provided by the manufacturer.</i>	

Technical Characteristics of EUT	
Support Standards:	802.11b, 802.11g, 802.11n
Frequency Range:	2412-2462MHz for 802.11b/g/n-HT20 2422-2452MHz for 802.11n-HT40
RF Output Power:	14.98dBm (Conducted)
Type of Modulation:	DBPSK,BPSK,DQPSK,QPSK,16QAM,64QAM
Data Rate:	1-11Mbps, 6-54Mbps, up to 150Mbps
Quantity of Channels:	11 for 802.11b/g/n-HT20 7 for 802.11n-HT40
Channel Separation:	5MHz
Type of Antenna:	PCB Antenna
Antenna Gain:	3.0dBi

## 1.2 Test Standards

The tests were performed according to following standards:

**FCC Rules Part 15.247:** Frequency Hopping, Direct Spread Spectrum and Hybrid Systems that are in operation within the bands of 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz.

**558074 D01 15.247 Meas Guidance v05r02:** Guidance For Compliance Measurements On Digital Transmission System, Frequency Hopping Spread Spectrum System, And Hybrid System Devices Operating Under Section 15.247 Of The Fcc Rules.

**ANSI C63.10-2013:** American National Standard for Testing Unlicensed Wireless Devices.

**Maintenance of compliance** is the responsibility of the manufacturer. Any modification of the product, which result in lowering the emission, should be checked to ensure compliance has been maintained.

## 1.3 Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, KDB 558074 D01 15.247 Meas Guidance v05r02.

The equipment under test (EUT) was configured to measure its highest possible emission level. The test modes were adapted accordingly in reference to the Operating Instructions.

## 1.4 Test Facility

### Address of the test laboratory

Laboratory: Waltek Testing Group (Shenzhen) Co., Ltd.

Address: 1/F., Room 101, Building 1, Hongwei Industrial Park, Liuxian 2nd Road, Block 70 Bao'an District, Shenzhen, Guangdong, China

### FCC – Registration No.: 125990

Waltek Testing Group (Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files. The Designation Number is CN5010, and Test Firm Registration Number is 125990.

### Industry Canada (IC) Registration No.: 11464A

The 3m Semi-anechoic chamber of Waltek Testing Group (Shenzhen) Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 11464A.



### 1.5 EUT Setup and Test Mode

Use “ESP\_RF\_test\_tool\_v2.3” and follow the instructions given by the manufacturer, you can start to test. During testing, Channel and Power Controlling Software provided by the customer was used to control the operating channel as well as the output power level. Test use the customer default power level. All testing shall be performed under maximum output power condition, with a duty cycle equal to 100%, and to measure its highest possible emissions level, more detailed description as follows:

<b>Test Mode List</b>		
Test Mode	Description	Remark
TM1	802.11b	Low:2412MHz, Middle:2437MHz,High:2462MHz
TM2	802.11g	Low:2412MHz, Middle:2437MHz,High:2462MHz
TM3	802.11n-HT20	Low:2412MHz, Middle:2437MHz,High:2462MHz
TM4	802.11n-HT40	Low:2422MHz, Middle:2437MHz,High:2452MHz

<b>Test Conditions</b>	
Temperature:	22~25 °C
Relative Humidity:	50~56 %.
ATM Pressure:	1019 mbar

<b>EUT Cable List and Details</b>			
Cable Description	Length (m)	Shielded/Unshielded	With / Without Ferrite
DC Cable	1.45	Unshielded	Without Ferrite

<b>Accessories Cable List and Details</b>			
Cable Description	Length (m)	Shielded/Unshielded	With / Without Ferrite
/	/	/	/

<b>Auxiliary Equipment List and Details</b>			
Description	Manufacturer	Model	Serial Number
/	/	/	/



### 1.6 Measurement Uncertainty

Measurement uncertainty		
Parameter	Conditions	Uncertainty
RF Output Power	Conducted	$\pm 0.42\text{dB}$
Occupied Bandwidth	Conducted	$\pm 1.5\%$
Power Spectral Density	Conducted	$\pm 1.8\text{dB}$
Conducted Spurious Emission	Conducted	$\pm 2.17\text{dB}$
Conducted Emissions	Conducted	9-150kHz $\pm 3.74\text{dB}$
		0.15-30MHz $\pm 3.34\text{dB}$
Transmitter Spurious Emissions	Radiated	30-200MHz $\pm 4.52\text{dB}$
		0.2-1GHz $\pm 5.56\text{dB}$
		1-6GHz $\pm 3.84\text{dB}$
		6-18GHz $\pm 3.92\text{dB}$

**1.7 Test Equipment List and Details**

No.	Description	Manufacturer	Model	Serial No.	Cal Date	Due Date
SEMT-1072	Spectrum Analyzer	Agilent	E4407B	MY41440400	2019-04-30	2020-04-29
SEMT-1031	Spectrum Analyzer	Rohde & Schwarz	FSP30	836079/035	2019-04-30	2020-04-29
SEMT-1007	EMI Test Receiver	Rohde & Schwarz	ESVB	825471/005	2019-04-30	2020-04-29
SEMT-1008	Amplifier	Agilent	8447F	3113A06717	2019-04-30	2020-04-29
SEMT-1043	Amplifier	C&D	PAP-1G18	2002	2019-04-30	2020-04-29
SEMT-1011	Broadband Antenna	Schwarz beck	VULB9163	9163-333	2019-05-05	2021-05-04
SEMT-1042	Horn Antenna	ETS	3117	00086197	2019-05-05	2021-05-04
SEMT-1121	Horn Antenna	Schwarzbeck	BBHA 9170	BBHA9170582	2019-05-05	2021-05-04
SEMT-1069	Loop Antenna	Schwarz beck	FMZB 1516	9773	2019-05-05	2021-05-04
SEMT-1001	EMI Test Receiver	Rohde & Schwarz	ESPI	101611	2019-04-30	2020-04-29
SEMT-1003	L.I.S.N	Schwarz beck	NSLK8126	8126-224	2019-04-30	2020-04-29
SEMT-1002	Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100911	2019-04-30	2020-04-29
SEMT-1168	Pre-amplifier	Direction Systems Inc.	PAP-0126	14141-12838	2019-04-30	2020-04-29
SEMT-1169	Pre-amplifier	Direction Systems Inc.	PAP-2640	14145-14153	2019-04-30	2020-04-29
SEMT-1163	Spectrum Analyzer	Rohde & Schwarz	FSP40	100612	2019-04-30	2020-04-29
SEMT-1170	DRG Horn Antenna	A.H. SYSTEMS	SAS-574	571	2019-05-05	2021-05-04
SEMT-1166	Power Limiter	Agilent	N9356B	MY45450376	2019-04-30	2020-04-29
SEMT-1048	RF Limiter	ATTEN	AT-BSF-2400~2500	/	2019-04-30	2020-04-29
SEMT-1076	RF Switcher	Top Precision	RCS03-A2	/	2019-04-30	2020-04-29
SEMT-C001	Cable	Zheng DI	LL142-07-07-10M(A)	/	2019-03-18	2020-03-17
SEMT-C002	Cable	Zheng DI	ZT40-2.92J-2.92J-6M	/	2019-03-18	2020-03-17
SEMT-C003	Cable	Zheng DI	ZT40-2.92J-2.92J-2.5M	/	2019-03-18	2020-03-17
SEMT-C004	Cable	Zheng DI	2M0RFC	/	2019-03-18	2020-03-17
SEMT-C005	Cable	Zheng DI	1M0RFC	/	2019-03-18	2020-03-17
SEMT-C006	Cable	Zheng DI	1M0RFC	/	2019-03-18	2020-03-17





<b>Software List</b>			
Description	Manufacturer	Model	Version
EMI Test Software (Radiated Emission)*	Farad	EZ-EMC	RA-03A1
EMI Test Software (Conducted Emission)*	Farad	EZ-EMC	RA-03A1

\*Remark: indicates software version used in the compliance certification testing



## 2. SUMMARY OF TEST RESULTS

<b>FCC Rules</b>	<b>Description of Test Item</b>	<b>Result</b>
§2.1091	RF Exposure	Compliant
§15.203;15.247(b)(4)(i)	Antenna Requirement	Compliant
§15.205	Restricted Band of Operation	Compliant
§15.207(a)	Conducted Emission	Compliant
§15.247(e)	Power Spectral Density	Compliant
§15.247(a)(2)	DTS Bandwidth	Compliant
§15.247(b)(3)	RF Output Power	Compliant
§15.209(a)	Radiated Emission	Compliant
§15.247(d)	Band Edge (Out of Band Emissions)	Compliant

N/A: not applicable



### **3. RF Exposure**

---

#### **3.1 Standard Applicable**

According to §1.1307 and §2.1091, the fixed transmitter must comply the RF exposure requirements.

#### **3.2 Test Result**

This product complied with the requirement of the RF exposure, please see the RF Exposure Report.



## **4. Antenna Requirement**

---

### **4.1 Standard Applicable**

According to FCC Part 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

### **4.2 Evaluation Information**

This product has a PCB antenna, fulfill the requirement of this section.



## 5. Power Spectral Density

### 5.1 Standard Applicable

According to 15.247(a)(1)(iii), for digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

### 5.2 Test Procedure

According to the KDB 558074 D01 v05r02 Subclause 8.4 and ANSI C63.10-2013 Subclause 11.10.3, such specifications require that the same method as used to determine the conducted output power shall also be used to determine the power spectral density. The test method of power spectral density as below:

- a) Set instrument center frequency to DTS channel center frequency.
- b) Set span to at least 1.5 times the OBW.
- c) Set RBW to:  $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$ .
- d) Set VBW  $\geq 3 \times \text{RBW}$ .
- e) Detector = power averaging (RMS) or sample detector (when RMS not available).
- f) Ensure that the number of measurement points in the sweep  $\geq 2 \times \text{span}/\text{RBW}$ .
- g) Sweep time = auto couple.
- h) Employ trace averaging (RMS) mode over a minimum of 100 traces.
- i) Use the peak marker function to determine the maximum amplitude level.
- j) If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat (note that this may require zooming in on the emission of interest and reducing the span in order to meet the minimum measurement point requirement as the RBW is reduced).

### 5.3 Summary of Test Results/Plots

Test Mode	Test Channel MHz	Power Spectral Density dBm/3kHz	Limit dBm/3kHz
802.11b_11Mbps	2412	-19.32	8
	2437	-22.51	8
	2462	-25.85	8
802.11g_54Mbps	2412	-23.59	8
	2437	-25.47	8
	2462	-29.06	8
802.11n-HT20_MCS7	2412	-23.45	8
	2437	-25.49	8
	2462	-28.69	8
802.11n-HT40_MCS7	2422	-27.26	8
	2437	-27.92	8
	2452	-30.26	8

Please refer to the following test plots:

<p>802.11b-Low</p>	<p>Agilent R T Ref 0 dBm Atten 10 dB Mkr1 2.41134 GHz -19.32 dBm #Avg Log 10 dB/ Offst 1 dB Marker 2.411340000 GHz -19.32 dBm M1 S2 S3 FC AA Center 2.412 GHz Span 30 MHz #Res BW 3 kHz #VBW 10 kHz Sweep 5.425 s (1001 pts)</p>
<p>802.11b-Middle</p>	<p>Agilent R T Ref 0 dBm Atten 10 dB Mkr1 2.43592 GHz -22.51 dBm #Avg Log 10 dB/ Offst 1 dB Marker 2.435920000 GHz -22.51 dBm M1 S2 S3 FC AA Center 2.437 GHz Span 30 MHz #Res BW 3 kHz #VBW 10 kHz Sweep 5.425 s (1001 pts)</p>
<p>802.11b-High</p>	<p>Agilent R T Ref 0 dBm Atten 10 dB Mkr1 2.46269 GHz -25.85 dBm #Avg Log 10 dB/ Offst 1 dB Marker 2.462690000 GHz -25.85 dBm M1 S2 S3 FC AA Center 2.462 GHz Span 30 MHz #Res BW 3 kHz #VBW 10 kHz Sweep 5.425 s (1001 pts)</p>



<p>802.11g-Low</p>	
<p>802.11g-Middle</p>	
<p>802.11g-High</p>	



<p>802.11n-HT20-Low</p>	
<p>802.11n-HT20-Middle</p>	
<p>802.11n-HT20-High</p>	





<p>802.11n-HT40-Low</p>	
<p>802.11n-HT40-Middle</p>	
<p>802.11n-HT40-High</p>	



## 6. DTS Bandwidth

### 6.1 Standard Applicable

According to 15.247(a)(2), systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

### 6.2 Test Procedure

According to the KDB 558074 D01 v05r02 Subclause 8.2 and ANSI C63.10-2013 Subclause 11.8.1, the test method of DTS Bandwidth as below:

- a) Set RBW = 100 kHz.
- b) Set the video bandwidth (VBW)  $\geq 3 \times$  RBW.
- c) Detector = Peak.
- d) Trace mode = max hold.
- e) Sweep = auto couple.
- f) Allow the trace to stabilize.
- g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

### 6.3 Summary of Test Results/Plots

Test Mode	Test Channel MHz	6 dB Bandwidth MHz	Limit kHz
802.11b_11Mbps	2412	9.583	$\geq 500$
	2437	10.038	$\geq 500$
	2462	10.006	$\geq 500$
802.11g_54Mbps	2412	16.411	$\geq 500$
	2437	16.438	$\geq 500$
	2462	16.415	$\geq 500$
802.11n-HT20_MCS7	2412	17.136	$\geq 500$
	2437	17.071	$\geq 500$
	2462	17.060	$\geq 500$
802.11n-HT40_MCS7	2422	36.367	$\geq 500$
	2437	36.397	$\geq 500$
	2452	36.370	$\geq 500$

Please refer to the following test plots:



<p>802.11b-Low</p>	<p>Agilent R T</p> <p>Ch Freq 2.412 GHz Trig Free</p> <p>Occupied Bandwidth</p> <p>Ref 20 dBm Atten 30 dB</p> <p>#Peak Log 10 dB/ Offst 1 dB</p> <p>Center 2.412 GHz Span 30 MHz</p> <p>#Res BW 100 kHz #VBW 300 kHz Sweep 10 ms (1001 pts)</p> <p><b>Occupied Bandwidth</b> Occ BW % Pwr 99.00 % <b>12.8549 MHz</b> x dB -6.00 dB</p> <p>Transmit Freq Error -14.085 kHz x dB Bandwidth 9.583 MHz</p> <p>Freq/Channel</p> <p>Center Freq 2.41200000 GHz</p> <p>Start Freq 2.39700000 GHz</p> <p>Stop Freq 2.42700000 GHz</p> <p>CF Step 3.00000000 MHz Auto Man</p> <p>Freq Offset 0.00000000 Hz</p> <p>Signal Track On Off</p> <p>Scale Type Log Lin</p>
<p>802.11b-Middle</p>	<p>Agilent R T</p> <p>Ch Freq 2.437 GHz Trig Free</p> <p>Occupied Bandwidth</p> <p>Ref 20 dBm Atten 30 dB</p> <p>#Peak Log 10 dB/ Offst 1 dB</p> <p>Center 2.437 GHz Span 30 MHz</p> <p>#Res BW 100 kHz #VBW 300 kHz Sweep 10 ms (1001 pts)</p> <p><b>Occupied Bandwidth</b> Occ BW % Pwr 99.00 % <b>12.9431 MHz</b> x dB -6.00 dB</p> <p>Transmit Freq Error -37.686 kHz x dB Bandwidth 10.038 MHz</p> <p>Freq/Channel</p> <p>Center Freq 2.43700000 GHz</p> <p>Start Freq 2.42200000 GHz</p> <p>Stop Freq 2.45200000 GHz</p> <p>CF Step 3.00000000 MHz Auto Man</p> <p>Freq Offset 0.00000000 Hz</p> <p>Signal Track On Off</p> <p>Scale Type Log Lin</p>
<p>802.11b-High</p>	<p>Agilent R T</p> <p>Ch Freq 2.462 GHz Trig Free</p> <p>Occupied Bandwidth</p> <p>Ref 20 dBm Atten 30 dB</p> <p>#Peak Log 10 dB/ Offst 1 dB</p> <p>Center 2.462 GHz Span 30 MHz</p> <p>#Res BW 100 kHz #VBW 300 kHz Sweep 10 ms (1001 pts)</p> <p><b>Occupied Bandwidth</b> Occ BW % Pwr 99.00 % <b>12.8702 MHz</b> x dB -6.00 dB</p> <p>Transmit Freq Error 12.324 kHz x dB Bandwidth 10.006 MHz</p> <p>Freq/Channel</p> <p>Center Freq 2.46200000 GHz</p> <p>Start Freq 2.44700000 GHz</p> <p>Stop Freq 2.47700000 GHz</p> <p>CF Step 3.00000000 MHz Auto Man</p> <p>Freq Offset 0.00000000 Hz</p> <p>Signal Track On Off</p> <p>Scale Type Log Lin</p>



<p>802.11g-Low</p>	<p>Agilent R T</p> <p>Ch Freq 2.412 GHz Trig Free</p> <p>Occupied Bandwidth</p> <p>Ref 20 dBm Atten 30 dB</p> <p>#Peak Log 10 dB/Offset 1 dB</p> <p>Center 2.412 GHz Span 30 MHz</p> <p>#Res BW 100 kHz #VBW 300 kHz Sweep 10 ms (1001 pts)</p> <p><b>Occupied Bandwidth</b> Occ BW % Pwr 99.00 % <b>16.3795 MHz</b> x dB -6.00 dB</p> <p>Transmit Freq Error 633.114 Hz x dB Bandwidth 16.411 MHz</p>
<p>802.11g-Middle</p>	<p>Agilent R T</p> <p>Ch Freq 2.437 GHz Trig Free</p> <p>Occupied Bandwidth</p> <p>Ref 20 dBm Atten 30 dB</p> <p>#Peak Log 10 dB/Offset 1 dB</p> <p>Center 2.437 GHz Span 30 MHz</p> <p>#Res BW 100 kHz #VBW 300 kHz Sweep 10 ms (1001 pts)</p> <p><b>Occupied Bandwidth</b> Occ BW % Pwr 99.00 % <b>16.3800 MHz</b> x dB -6.00 dB</p> <p>Transmit Freq Error -16.435 kHz x dB Bandwidth 16.438 MHz</p>
<p>802.11g-High</p>	<p>Agilent R T</p> <p>Ch Freq 2.462 GHz Trig Free</p> <p>Occupied Bandwidth</p> <p>Ref 20 dBm Atten 30 dB</p> <p>#Peak Log 10 dB/Offset 1 dB</p> <p>Center 2.462 GHz Span 30 MHz</p> <p>#Res BW 100 kHz #VBW 300 kHz Sweep 10 ms (1001 pts)</p> <p><b>Occupied Bandwidth</b> Occ BW % Pwr 99.00 % <b>16.3759 MHz</b> x dB -6.00 dB</p> <p>Transmit Freq Error -4.522 kHz x dB Bandwidth 16.415 MHz</p>



<p>802.11n-HT20-Low</p>	<p>Agilent R T</p> <p>Ch Freq 2.412 GHz Trig Free</p> <p>Occupied Bandwidth</p> <p>Ref 20 dBm Atten 30 dB</p> <p>#Peak Log 10 dB/Offset 1 dB</p> <p>Center 2.412 GHz Span 30 MHz</p> <p>#Res BW 100 kHz #VBW 300 kHz Sweep 10 ms (1001 pts)</p> <p><b>Occupied Bandwidth</b> 17.3221 MHz</p> <p>Occ BW % Pwr 99.00 % x dB -6.00 dB</p> <p>Transmit Freq Error 5.235 kHz x dB Bandwidth 17.136 MHz</p> <p>Freq/Channel</p> <p>Center Freq 2.41200000 GHz</p> <p>Start Freq 2.39700000 GHz</p> <p>Stop Freq 2.42700000 GHz</p> <p>CF Step 3.00000000 MHz Auto Man</p> <p>Freq Offset 0.00000000 Hz</p> <p>Signal Track On Off</p> <p>Scale Type Log Lin</p>
<p>802.11n-HT20-Middle</p>	<p>Agilent R T</p> <p>Ch Freq 2.437 GHz Trig Free</p> <p>Occupied Bandwidth</p> <p>Ref 20 dBm Atten 30 dB</p> <p>#Peak Log 10 dB/Offset 1 dB</p> <p>Center 2.437 GHz Span 30 MHz</p> <p>#Res BW 100 kHz #VBW 300 kHz Sweep 10 ms (1001 pts)</p> <p><b>Occupied Bandwidth</b> 17.2892 MHz</p> <p>Occ BW % Pwr 99.00 % x dB -6.00 dB</p> <p>Transmit Freq Error -26.754 kHz x dB Bandwidth 17.071 MHz</p> <p>Freq/Channel</p> <p>Center Freq 2.43700000 GHz</p> <p>Start Freq 2.42200000 GHz</p> <p>Stop Freq 2.45200000 GHz</p> <p>CF Step 3.00000000 MHz Auto Man</p> <p>Freq Offset 0.00000000 Hz</p> <p>Signal Track On Off</p> <p>Scale Type Log Lin</p>
<p>802.11n-HT20-High</p>	<p>Agilent R T</p> <p>Ch Freq 2.462 GHz Trig Free</p> <p>Occupied Bandwidth</p> <p>Ref 20 dBm Atten 30 dB</p> <p>#Peak Log 10 dB/Offset 1 dB</p> <p>Center 2.462 GHz Span 30 MHz</p> <p>#Res BW 100 kHz #VBW 300 kHz Sweep 10 ms (1001 pts)</p> <p><b>Occupied Bandwidth</b> 17.3026 MHz</p> <p>Occ BW % Pwr 99.00 % x dB -6.00 dB</p> <p>Transmit Freq Error -13.519 kHz x dB Bandwidth 17.060 MHz</p> <p>Freq/Channel</p> <p>Center Freq 2.46200000 GHz</p> <p>Start Freq 2.44700000 GHz</p> <p>Stop Freq 2.47700000 GHz</p> <p>CF Step 3.00000000 MHz Auto Man</p> <p>Freq Offset 0.00000000 Hz</p> <p>Signal Track On Off</p> <p>Scale Type Log Lin</p>



<p>802.11n-HT40-Low</p>	<p>Agilent R T</p> <p>Ch Freq 2.422 GHz Trig Free</p> <p>Occupied Bandwidth</p> <p>Ref 20 dBm Atten 30 dB</p> <p>#Peak Log 10 dB/Offset 1 dB</p> <p>Center 2.422 GHz Span 60 MHz #Res BW 100 kHz #VBW 300 kHz Sweep 10 ms (1001 pts)</p> <p><b>Occupied Bandwidth</b> 36.0086 MHz</p> <p>Occ BW % Pwr 99.00 % x dB -6.00 dB</p> <p>Transmit Freq Error -41.151 kHz x dB Bandwidth 36.367 MHz</p> <p>Freq/Channel Center Freq 2.42200000 GHz Start Freq 2.39200000 GHz Stop Freq 2.45200000 GHz CF Step 6.00000000 MHz Auto Man Freq Offset 0.00000000 Hz Signal Track On Off Scale Type Log Lin</p>
<p>802.11n-HT40-Middle</p>	<p>Agilent R T</p> <p>Ch Freq 2.437 GHz Trig Free</p> <p>Occupied Bandwidth</p> <p>Ref 20 dBm Atten 30 dB</p> <p>#Peak Log 10 dB/Offset 1 dB</p> <p>Center 2.437 GHz Span 60 MHz #Res BW 100 kHz #VBW 300 kHz Sweep 10 ms (1001 pts)</p> <p><b>Occupied Bandwidth</b> 36.0544 MHz</p> <p>Occ BW % Pwr 99.00 % x dB -6.00 dB</p> <p>Transmit Freq Error -41.370 kHz x dB Bandwidth 36.397 MHz</p> <p>Freq/Channel Center Freq 2.43700000 GHz Start Freq 2.40700000 GHz Stop Freq 2.46700000 GHz CF Step 6.00000000 MHz Auto Man Freq Offset 0.00000000 Hz Signal Track On Off Scale Type Log Lin</p>
<p>802.11n-HT40-High</p>	<p>Agilent R T</p> <p>Ch Freq 2.452 GHz Trig Free</p> <p>Occupied Bandwidth</p> <p>Ref 20 dBm Atten 30 dB</p> <p>#Peak Log 10 dB/Offset 1 dB</p> <p>Center 2.452 GHz Span 60 MHz #Res BW 100 kHz #VBW 300 kHz Sweep 10 ms (1001 pts)</p> <p><b>Occupied Bandwidth</b> 36.0611 MHz</p> <p>Occ BW % Pwr 99.00 % x dB -6.00 dB</p> <p>Transmit Freq Error -30.975 kHz x dB Bandwidth 36.370 MHz</p> <p>Freq/Channel Center Freq 2.45200000 GHz Start Freq 2.42200000 GHz Stop Freq 2.48200000 GHz CF Step 6.00000000 MHz Auto Man Freq Offset 0.00000000 Hz Signal Track On Off Scale Type Log Lin</p>

## 7. RF Output Power

---

### 7.1 Standard Applicable

According to 15.247(b)(3), for systems using digital modulation in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands: 1 Watt.

### 7.2 Test Procedure

According to the KDB-558074 D01 v05r02 Subclause 8.3.2.2 and ANSI C63.10-2013 Subclause 11.9.2.2, when this option is exercised, the measured power is to be referenced to the OBW rather than the DTS bandwidth

- a) Set span to at least 1.5 times the OBW.
- b) Set RBW = 1-5% of the OBW, not to exceed 1 MHz.
- c) Set VBW  $\geq 3 \times$  RBW.
- d) Number of points in sweep  $\geq 2 \times$  span / RBW. (This gives bin-to-bin spacing  $\leq$  RBW/2, so that narrowband signals are not lost between frequency bins.)
- e) Sweep time = auto.
- f) Detector = RMS (i.e., power averaging), if available. Otherwise, use sample detector mode.
- g) If transmit duty cycle < 98 %, use a sweep trigger with the level set to enable triggering only on full power pulses. The transmitter shall operate at maximum power control level for the entire duration of every sweep. If the EUT transmits continuously (i.e., with no off intervals) or at duty cycle  $\geq 98$  %, and if each transmission is entirely at the maximum power control level, then the trigger shall be set to “free run” .
- h) Trace average at least 100 traces in power averaging (i.e., RMS) mode.
- i) Compute power by integrating the spectrum across the OBW of the signal using the instrument’s band power measurement function, with band limits set equal to the OBW band edges. If the instrument does not have a band power function, sum the spectrum levels (in power units) at intervals equal to the RBW extending across the entire OBW of the spectrum.

### 7.3 Summary of Test Results/Plots






Test Mode	Frequency MHz	Reading dBm	Output Power mW	Limit mW
802.11b_ 11Mbps	2412	14.98	31.48	1000
	2437	14.75	29.85	1000
	2462	14.96	31.33	1000
802.11g_54Mbps	2412	14.00	25.12	1000
	2437	12.73	18.75	1000
	2462	13.00	19.95	1000
802.11n HT20_MCS7	2412	13.56	22.70	1000
	2437	12.82	19.14	1000
	2462	12.84	19.23	1000
802.11n HT40_MCS7	2422	12.32	17.06	1000
	2437	12.19	16.56	1000
	2452	12.44	17.54	1000

Please refer to the following test plots:





<p>802.11b-Low 11Mbps</p>	 <p>Date: 25.FEB.2020 17:06:27</p>
<p>802.11b-Middle 11Mbps</p>	 <p>Date: 25.FEB.2020 17:07:33</p>
<p>802.11b-High 11Mbps</p>	 <p>Date: 25.FEB.2020 17:08:00</p>






<p>802.11g-Low 54Mbps</p>	<p>Ref 10 dBm Att 20 dB RBW 300 kHz VBM 1 MHz SWT 5 ms</p> <p>Offset 1 dB</p> <p>Center 2.412 GHz 3 MHz/ Span 30 MHz</p> <p><b>Tx Channel1</b> Bandwidth 20 MHz Power 14.00 dBm</p> <p>Date: 25.FEB.2020 17:08:40</p>
<p>802.11g-Middle 54Mbps</p>	<p>Ref 10 dBm Att 20 dB RBW 300 kHz VBM 1 MHz SWT 5 ms</p> <p>Offset 1 dB</p> <p>Center 2.437 GHz 3 MHz/ Span 30 MHz</p> <p><b>Tx Channel1</b> Bandwidth 20 MHz Power 12.73 dBm</p> <p>Date: 25.FEB.2020 17:10:58</p>
<p>802.11g-High 54Mbps</p>	<p>Ref 10 dBm Att 20 dB RBW 300 kHz VBM 1 MHz SWT 5 ms</p> <p>Offset 1 dB</p> <p>Center 2.462 GHz 3 MHz/ Span 30 MHz</p> <p><b>Tx Channel1</b> Bandwidth 20 MHz Power 13.00 dBm</p> <p>Date: 25.FEB.2020 17:14:36</p>



<p>802.11n-HT20-Low MCS7</p>	<p>Ref 10 dBm Att 20 dB RBW 300 kHz VBM 1 MHz SWT 5 ms</p> <p>Offset 1 dB</p> <p>Center 2.412 GHz 3 MHz/ Span 30 MHz</p> <p>Tx Channel1 Bandwidth 20 MHz Power 13.56 dBm</p> <p>Date: 25.FEB.2020 17:15:27</p>
<p>802.11n-HT20-Middle MCS7</p>	<p>Ref 10 dBm Att 20 dB RBW 300 kHz VBM 1 MHz SWT 5 ms</p> <p>Offset 1 dB</p> <p>Center 2.437 GHz 3 MHz/ Span 30 MHz</p> <p>Tx Channel1 Bandwidth 20 MHz Power 12.82 dBm</p> <p>Date: 25.FEB.2020 17:16:05</p>
<p>802.11n-HT20-High MCS7</p>	<p>Ref 10 dBm Att 20 dB RBW 300 kHz VBM 1 MHz SWT 5 ms</p> <p>Offset 1 dB</p> <p>Center 2.462 GHz 3 MHz/ Span 30 MHz</p> <p>Tx Channel1 Bandwidth 20 MHz Power 12.84 dBm</p> <p>Date: 25.FEB.2020 17:16:44</p>



<p>802.11n-HT40-Low MCS7</p>	 <p>Date: 25.FEB.2020 17:38:06</p>
<p>802.11n-HT40-Middle MCS7</p>	 <p>Date: 25.FEB.2020 17:36:51</p>
<p>802.11n-HT40-High MCS7</p>	 <p>Date: 25.FEB.2020 17:35:36</p>

## 8. Field Strength of Spurious Emissions

### 8.1 Standard Applicable


According to §15.247(d), in any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a).


The emission limit in this paragraph is based on measurement instrumentation employing an average detector. The provisions in §15.35 for limiting peak emissions apply. Spurious Radiated Emissions measurements starting below or at the lowest crystal frequency.

### 8.2 Test Procedure

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.205 15.247(a) and FCC Part 15.209 Limit.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle. The spacing between the peripherals was 10 cm.





Frequency :9kHz-30MHz  
 RBW=10KHz,  
 VBW =30KHz  
 Sweep time= Auto  
 Trace = max hold  
 Detector function = peak

Frequency :30MHz-1GHz  
 RBW=120KHz,  
 VBW=360KHz  
 Sweep time= Auto  
 Trace = max hold  
 Detector function = peak, QP

Frequency :Above 1GHz  
 RBW=1MHz,  
 VBW=3MHz(Peak), 10Hz(AV)  
 Sweep time= Auto  
 Trace = max hold  
 Detector function = peak, AV

### 8.3 Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and the Cable Factor, and subtracting the Amplifier Gain from the Amplitude reading. The basic equation is as follows:

$$\text{Corr. Ampl.} = \text{Indicated Reading} + \text{Ant. Factor} + \text{Cable Loss} - \text{Ampl. Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of -6dB $\mu$ V means the emission is 6dB $\mu$ V below the maximum limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Corr. Ampl.} - \text{FCC Part 15 Limit}$$

### 8.4 Summary of Test Results/Plots


*Note: this EUT was tested in 3 orthogonal positions and the worst case position data was reported.*

*All test modes (different data rate and different modulation) are performed, but only the worst case (802.11b\_11Mbps) is recorded in this report.*



➤ Spurious Emissions Below 1GHz


802.11b_11Mbps			
Test Channel	Low	Polarity:	Horizontal



No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ( )	Height (cm)	Remark
1	50.9420	28.55	-11.21	17.34	40.00	-22.66	91	100	QP
2	69.8450	33.91	-15.16	18.75	40.00	-21.25	189	100	QP
3	108.2667	28.97	-13.05	15.92	43.50	-27.58	131	100	QP
4	287.9904	41.00	-9.87	31.13	46.00	-14.87	124	100	QP
5	360.4476	35.61	-7.86	27.75	46.00	-18.25	207	100	QP
6	432.5457	38.91	-6.19	32.72	46.00	-13.28	317	100	QP



802.11b_11Mbps			
Test Channel	Low	Polarity:	Vertical




No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ( )	Height (cm)	Remark
1	36.8953	31.09	-13.03	18.06	40.00	-21.94	302	100	QP
2	95.7622	33.20	-14.14	19.06	43.50	-24.44	261	100	QP
3	143.8295	36.23	-15.68	20.55	43.50	-22.95	50	100	QP
4	175.6516	35.25	-14.72	20.53	43.50	-22.97	320	100	QP
5	287.9904	32.72	-9.87	22.85	46.00	-23.15	79	100	QP
6	510.0436	32.22	-6.16	26.06	46.00	-19.94	159	100	QP






802.11b_11Mbps			
Test Channel	Middle	Polarity:	Horizontal



No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ( )	Height (cm)	Remark
1	52.0251	28.19	-11.46	16.73	40.00	-23.27	289	100	QP
2	114.1138	29.34	-13.48	15.86	43.50	-27.64	91	100	QP
3	143.8295	29.97	-15.68	14.29	43.50	-29.21	147	100	QP
4	287.9904	40.72	-9.87	30.85	46.00	-15.15	118	100	QP
5	360.4477	35.82	-7.86	27.96	46.00	-18.04	357	100	QP
6	432.5457	39.23	-6.19	33.04	46.00	-12.96	119	100	QP




802.11b_11Mbps			
Test Channel	Middle	Polarity:	Vertical



No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ( )	Height (cm)	Remark
1	69.1141	35.45	-15.00	20.45	40.00	-19.55	90	100	QP
2	96.0986	34.03	-14.07	19.96	43.50	-23.54	196	100	QP
3	143.8295	36.94	-15.68	21.26	43.50	-22.24	75	100	QP
4	173.2051	35.13	-14.80	20.33	43.50	-23.17	229	100	QP
5	287.9904	33.42	-9.87	23.55	46.00	-22.45	282	100	QP
6	576.6443	31.66	-4.25	27.41	46.00	-18.59	193	100	QP




802.11b_11Mbps			
Test Channel	High	Polarity:	Horizontal



No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ( )	Height (cm)	Remark
1	112.1305	29.25	-13.26	15.99	43.50	-27.51	271	100	QP
2	287.9904	40.59	-9.87	30.72	46.00	-15.28	90	100	QP
3	360.4477	36.19	-7.86	28.33	46.00	-17.67	57	100	QP
4	432.5457	40.13	-6.19	33.94	46.00	-12.06	118	100	QP
5	576.6443	30.43	-4.25	26.18	46.00	-19.82	213	100	QP
6	818.8341	28.44	-1.76	26.68	46.00	-19.32	246	100	QP



802.11b_11Mbps			
Test Channel	High	Polarity:	Vertical



No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ( )	Height (cm)	Remark
1	81.4970	36.06	-15.50	20.56	40.00	-19.44	232	100	QP
2	143.8295	37.57	-15.68	21.89	43.50	-21.61	324	100	QP
3	172.5988	34.99	-14.81	20.18	43.50	-23.32	99	100	QP
4	287.9904	35.47	-9.87	25.60	46.00	-20.40	317	100	QP
5	432.5457	34.67	-6.19	28.48	46.00	-17.52	314	100	QP
6	576.6443	37.86	-4.25	33.61	46.00	-12.39	277	100	QP



- Spurious Emissions Above 1GHz
- Test Mode: 802.11b\_11Mbps (worst case)

Frequency (MHz)	Reading (dBuV/m)	Correct dB	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Polar H/V	Detector
Low Channel-2412MHz							
4824.000	60.98	-3.86	57.12	74	-16.88	H	PK
4824.000	42.34	-3.86	38.48	54	-15.52	H	AV
7236.000	53.28	1.1	54.38	74	-19.62	H	PK
7236.000	38.41	1.1	39.51	54	-14.49	H	AV
4824.000	59.2	-3.86	55.34	74	-18.66	V	PK
4824.000	42.48	-3.86	38.62	54	-15.38	V	AV
7236.000	54.66	1.1	55.76	74	-18.24	V	PK
7236.000	40.53	1.1	41.63	54	-12.37	V	AV
Middle Channel-2437MHz							
4874.000	61.84	-3.74	58.1	74	-15.9	H	PK
4874.000	43.02	-3.74	39.28	54	-14.72	H	AV
7311.000	53.13	1.47	54.6	74	-19.4	H	PK
7311.000	40.68	1.47	42.15	54	-11.85	H	AV
4874.000	60.3	-3.74	56.56	74	-17.44	V	PK
4874.000	41.43	-3.74	37.69	54	-16.31	V	AV
7311.000	54.26	1.47	55.73	74	-18.27	V	PK
7311.000	38.81	1.47	40.28	54	-13.72	V	AV
High Channel-2462MHz							
4924.000	58.12	-3.63	54.49	74	-19.51	H	PK
4924.000	43.67	-3.63	40.04	54	-13.96	H	AV
7386.000	54.11	1.62	55.73	74	-18.27	H	PK
7386.000	40.83	1.62	42.45	54	-11.55	H	AV
4924.000	61.12	-3.63	57.49	74	-16.51	V	PK
4924.000	43.86	-3.63	40.23	54	-13.77	V	AV
7386.000	54.03	1.62	55.65	74	-18.35	V	PK
7386.000	39.16	1.62	40.78	54	-13.22	V	AV

Note: Testing is carried out with frequency rang 9kHz to the tenth harmonics, other than listed in the table above are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

---

## 9. Out of Band Emissions

---

### 9.1 Standard Applicable

According to §15.247 (d), in any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a).

### 9.2 Test Procedure

According to the KDB 558074 D01 v05r02 Subclause 8.4 and ANSI C63.10-2013 Subclause 11.11, the emissions in nonrestricted frequency bands test method as follows:

- a) Set the center frequency and span to encompass frequency range to be measured.
- b) Set the RBW = 100 kHz.
- c) Set the VBW  $\geq [3 \times \text{RBW}]$ .
- d) Detector = peak.
- e) Sweep time = auto couple.
- f) Trace mode = max hold.
- g) Allow trace to fully stabilize.
- h) Use the peak marker function to determine the maximum amplitude level.

According to the KDB 558074 D01 v05r02 Subclause 8.5 and ANSI C63.10-2013 Subclause 11.12, the emissions in restricted frequency bands test method as follows:

#### A. Radiated emission measurements:

Set span = wide enough to capture the peak level of the emission operating on the channel closest to the bandedge, as well as any modulation products which fall outside of the authorized band of operation (2310MHz to 2420MHz for low bandedge, 2460MHz to 2500MHz for the high bandedge)

RBW = 1MHz, VBW = 1MHz for peak value measured

RBW = 1MHz, VBW = 10Hz for average value measured

Sweep = auto; Detector function = peak/average; Trace = max hold

All the trace to stabilize, set the marker on the emission at the bandedge, or on the highest modulation product outside of the band, if this level is greater than that at the bandedge. Enable the marker-delta function, then use the marker-to-peak function to move the marker to the peak of the in-band emission. Those emission must comply with the 15.209 limit for fall in the restricted bands listed in section 15.205. Note that the method of measurement KDB publication number: 913591 may be used for the radiated bandedge measurements.



**B. Antenna-port conducted measurements**

Peak emission levels are measured by setting the instrument as follows:

- a) RBW = as specified in Table 9.
- b) VBW  $\geq$  [3  $\times$  RBW].
- c) Detector = peak.
- d) Sweep time = auto.
- e) Trace mode = max hold.
- f) Allow sweeps to continue until the trace stabilizes. (Note that the required measurement time may be lengthened for low-duty-cycle applications.)

**Table 9—RBW as a function of frequency**

Frequency	RBW
9 kHz to 150 kHz	200 Hz to 300 Hz
0.15 MHz to 30 MHz	9 kHz to 10 kHz
30 MHz to 1000 MHz	100 kHz to 120 kHz
>1000 MHz	1 MHz

If the peak-detected amplitude can be shown to comply with the average limit, then it is not necessary to perform a separate average measurement.


Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) are attenuated by at least the minimum requirements specified in section 8.1. Report the three highest emissions relative to the limit.

**9.3 Summary of Test Results/Plots**



➤ Radiated test

802.11b_11Mbps			
Test Channel	Low	Polarity:	Horizontal (worst case)




No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2310.000	45.99	-9.66	36.33	54.00	-17.67	Average Detector
	2310.000	60.87	-9.66	51.21	74.00	-22.79	Peak Detector
2	2390.000	49.54	-9.50	40.04	54.00	-13.96	Average Detector
	2390.000	63.46	-9.50	53.96	74.00	-20.04	Peak Detector
3	2400.000	71.35	-9.48	61.87	Delta=36.82dBc		Average Detector
4	2410.389	108.15	-9.46	98.69			Average Detector






802.11b_11Mbps			
Test Channel	High	Polarity:	Horizontal (worst case)



No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2460.775	105.98	-9.36	96.62	/	/	Average Detector
	2461.671	115.82	-9.36	106.46	/	/	Peak Detector
2	2483.500	47.92	-9.31	38.61	54.00	-15.39	Average Detector
	2483.500	60.38	-9.31	51.07	74.00	-22.93	Peak Detector
3	2500.000	46.26	-9.28	36.98	54.00	-17.02	Average Detector
	2500.000	57.41	-9.28	48.13	74.00	-25.87	Peak Detector




802.11g_54Mbps			
Test Channel	Low	Polarity:	Horizontal (worst case)



No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2310.000	46.19	-9.66	36.53	54.00	-17.47	Average Detector
	2310.000	57.77	-9.66	48.11	74.00	-25.89	Peak Detector
2	2390.000	62.66	-9.50	53.16	54.00	-0.84	Average Detector
	2390.000	79.42	-9.50	69.92	74.00	-4.08	Peak Detector
3	2400.000	75.78	-9.48	66.30	Delta=30.9dBc		Average Detector
4	2411.122	106.66	-9.46	97.20		Average Detector	




802.11g_54Mbps			
Test Channel	High	Polarity:	Horizontal (worst case)



No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2468.798	102.80	-9.34	93.46	/	/	Average Detector
	2467.059	112.93	-9.35	103.58	/	/	Peak Detector
2	2483.500	56.05	-9.31	46.74	54.00	-7.26	Average Detector
	2483.500	71.27	-9.31	61.96	74.00	-12.04	Peak Detector
3	2500.000	46.78	-9.28	37.50	54.00	-16.50	Average Detector
	2500.000	59.89	-9.28	50.61	74.00	-23.39	Peak Detector




802.11n-HT20_MCS7			
Test Channel	Low	Polarity:	Horizontal (worst case)



No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2310.000	47.35	-9.66	37.69	54.00	-16.31	Average Detector
	2310.000	60.77	-9.66	51.11	74.00	-22.89	Peak Detector
2	2390.000	60.37	-9.50	50.87	54.00	-3.13	Average Detector
	2390.000	77.43	-9.50	67.93	74.00	-6.07	Peak Detector
3	2400.000	73.67	-9.48	64.19	Delta=30.06dBc		Average Detector
4	2406.364	103.72	-9.47	94.25			Average Detector




802.11n-HT20_MCS7			
Test Channel	High	Polarity:	Horizontal (worst case)



No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2467.119	100.44	-9.35	91.09	/	/	Average Detector
	2466.340	111.83	-9.35	102.48	/	/	Peak Detector
2	2483.500	56.82	-9.31	47.51	54.00	-6.49	Average Detector
	2483.500	74.51	-9.31	65.20	74.00	-8.80	Peak Detector
3	2500.000	46.90	-9.28	37.62	54.00	-16.38	Average Detector
	2500.000	60.31	-9.28	51.03	74.00	-22.97	Peak Detector




802.11n-HT40_MCS7			
Test Channel	Low	Polarity:	Horizontal (worst case)



No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2310.000	46.30	-9.66	36.64	54.00	-17.36	Average Detector
		60.27	-9.66	50.61	74.00	-23.39	Peak Detector
2	2390.000	59.21	-9.50	49.71	54.00	-4.29	Average Detector
		76.58	-9.50	67.08	74.00	-6.92	Peak Detector
3	2400.000	69.90	-9.48	60.42	Delta=30.16dBc		Average Detector
4	2432.619	100.00	-9.42	90.58			Average Detector



802.11n-HT40_MCS7			
Test Channel	High	Polarity:	Horizontal (worst case)





No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2440.582	98.13	-9.40	88.73	/	/	Average Detector
	2440.374	109.74	-9.41	100.33	/	/	Peak Detector
2	2483.500	61.21	-9.31	51.90	54.00	-2.10	Average Detector
	2483.500	74.53	-9.31	65.22	74.00	-8.78	Peak Detector
3	2500.000	53.02	-9.28	43.74	54.00	-10.26	Average Detector
	2500.000	68.77	-9.28	59.49	74.00	-14.51	Peak Detector



➤ Conducted test

802.11b\_11Mbps

Low









802.11b\_11Mbps



Middle





802.11b\_11Mbps



High





802.11g\_54Mbps



Low





802.11g\_54Mbps



Middle





802.11g\_54Mbps



High





802.11n-HT20\_MCS7



Low





802.11n-HT20\_MCS7



Middle





802.11n-HT20\_MCS7

High









802.11n-HT40\_MCS7



Low





802.11n-HT40\_MCS7



Middle





802.11n-HT40\_MCS7

High




## 10. Conducted Emissions

### 10.1 Test Procedure

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 Limit.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle. The spacing between the peripherals was 10 cm.

### 10.2 Basic Test Setup Block Diagram



### 10.3 Test Receiver Setup


During the conducted emission test, the test receiver was set with the following configurations:

- Start Frequency ..... 150 kHz
- Stop Frequency ..... 30 MHz
- Sweep Speed ..... Auto
- IF Bandwidth..... 10 kHz
- Quasi-Peak Adapter Bandwidth ..... 9 kHz
- Quasi-Peak Adapter Mode ..... Normal

### 10.4 Summary of Test Results/Plots




Test Mode	Communication	AC120V 60Hz	Polarity:	Neutral
-----------	---------------	-------------	-----------	---------



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.1660	23.46	9.95	33.41	55.15	-21.74	AVG
2	0.1740	44.15	9.95	54.10	64.76	-10.66	QP
3	0.2500	37.89	10.01	47.90	61.75	-13.85	QP
4	0.2620	24.31	10.02	34.33	51.36	-17.03	AVG
5	0.3740	30.98	10.02	41.00	58.41	-17.41	QP
6*	0.4180	31.79	10.01	41.80	47.49	-5.69	AVG



Test Mode	Communication	AC120V 60Hz	Polarity:	Line
-----------	---------------	-------------	-----------	------



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1*	0.1539	46.25	9.95	56.20	65.78	-9.58	QP
2	0.1620	21.51	9.95	31.46	55.36	-23.90	AVG
3	0.2420	38.60	10.00	48.60	62.02	-13.42	QP
4	0.2500	20.65	10.01	30.66	51.75	-21.09	AVG
5	0.4020	32.09	10.01	42.10	57.81	-15.71	QP
6	0.4180	26.00	10.01	36.01	47.49	-11.48	AVG

\*\*\*\*\* END OF REPORT \*\*\*\*\*