

Client:	RedOctane	Job Number:	J76177
Model:	95849.809(DJ Hero Wireless Turntable)	T-Log Number:	T76271
Contact:	Mark Johnson	Account Manager:	Sheareen Washington
Standard:	FCC 15.247, RSS-210	Class:	N/A

Maximum Permissible Exposure

Test Specific Details

Objective: The objective of this test session is to perform final qualification testing of the EUT with respect to the specification listed above.

Date of Test: 9/1/2009

Test Engineer: Mark Hill

General Test Configuration

Calculation uses the free space transmission formula:

$$S = (PG)/(4 \pi d^2)$$

Where: S is power density (W/m^2), P is output power (W), G is antenna gain relative to isotropic, d is separation distance from the transmitting antenna (m).

Summary of Results

Device exceeds SAR threshold for handheld device used within 5cm of body	No
Power Density @ 20cm (mW/cm^2)	0.0004

Modifications Made During Testing

No modifications were made to the EUT during testing

Deviations From The Standard

No deviations were made from the requirements of the standard.

SAR Threshold for handheld devices used within 5cm of body = $300 \cdot [f(\text{GHz})]^{-0.5} \text{ mW}$

Freq (GHz): 2.48

SAR Threshold (mW): 190.50

EUT Power (mW): 2.1

Result: The EUT is below the threshold for SAR for a handheld device used within 5cm of body.

Client:	RedOctane	Job Number:	J76177
Model:	95849.809(DJ Hero Wireless Turntable)	T-Log Number:	T76271
Contact:	Mark Johnson	Account Manager:	Sheareen Washington
Standard:	FCC 15.247, RSS-210	Class:	N/A

MPE Calculation

Use: General
 Antenna: Internal - 0dBi

Freq. MHz	EUT Power		Cable Loss	Ant Gain	Power at Ant	EIRP	Power Density (S) at 20 cm	MPE Limit at 20 cm
	dBm	mW*	dB	dBi	dBm	mW	mW/cm ²	mW/cm ²
2402	1.2	1.3	0	0	1.2	1.31	0.0003	1.000
2440	3.3	2.1	0	0	3.3	2.14	0.0004	1.000
2480	1.2	1.3	0	0	1.2	1.33	0.0003	1.000