

# Specification for MT – 462008/N/A Omni Directional Antenna 4.9 – 5.875 GHz, 9.5 dBi

THIS DOCUMENT AND THE INFORMATION CONTAINED IN IT ARE PROPRIETARY AND CONFIDENTIAL TO MTI. NO PERSON IS ALLOWED TO COPY REPRINT REPRODUCE OR PUBLISH ANY PART OF THIS DOCUMENT NOR DISCLOSE ITS CONTENTS TO OTHERS NOR MAKE ANY USE OF IT NOR ALLOW OR ASSIST OTHERS TO MAKE ANY USE OF IT, UNLESS BY THE PRIOR WRITTEN EXPRESS AUTHORIZATION OF MTI AND THEN ONLY TO THE EXTENT AUTHORIZED.

(C) COPYRIGHT – MTI WIRELESS EDGE LTD.

MTI WIRELESS EDGE LTD.	MT – 462008/N/A	REV-A
SCALE: NONE	DOC NO. RD42121000C	SHEET 1 OF 4

REVISION RECORD				
REV	ECO	DESCRIPTION	APVD	DATE
A	CZ44	RELAESD	Yael H.	30.3.08

SHEET	43	44	45	46	47	48	49	50	51	52	53	54	55	56
REV														
SHEET	29	30	31	32	33	34	35	36	37	38	39	40	41	42
REV														
SHEET	15	16	17	18	19	20	21	22	23	24	25	26	27	28
REV														
SHEET	1	2	3	4	5	6	7	8	9	10	11	12	13	14
REV	A	A	A	A										

<b>PRODUCT STATUS:</b>			
<input type="checkbox"/> PROPOSAL	<input type="checkbox"/> IN DEVELOPMENT	<input type="checkbox"/> PREPRODUCTION	<input checked="" type="checkbox"/> PRODUCTION

CONTRACT NO			
ACTION	NAME	SIGN	DATE
PREP	Yael HARASH	Yael	11.3.07
CHKD	DANIEL ZERAH	D.Z	27.3.08
CHKD			
CHKD			
DSGN	MICHAEL HAIKIN	M.H	19.3.08
PROJ	MOTI ROSTMI	M.R	19.3.08
MFG			
QA	MOTI MOTOVICH	MOTI	24.3.08
MARK.	DAVID SHANI	S.D	27.3.08

MTI WIRELESS EDGE LTD.	Specification for MT – 462008/N/A Omni Directional Antenna		
DOC NO. RD42121000C	4.9 – 5.875 GHz, 9.5 dBi		
SCALE: NONE	CLASSIFICATION: NONE	REV-A	SHEET 2 OF 4

## SPECIFICATION

### OMNIDIRECTIONAL ANTENNA

<b>MTI PART NUMBER</b>	<b>MT – 462008/N/A</b>
Regulatory Compliance	RoHS , CE 0682
<b><u>1. ELECTRICAL</u></b>	
Frequency Range	4.9 – 5.875 GHz
Peak Gain	9.5 dBi ± 1 dB
VSWR	2.0 :1 (max)
Azimuth Beamwidth	360°
Azimuth Ripple	± 1.0 dB (max) @ 4.9 – 5.47 GHz ± 1.5 dB (max) @ 5.47 – 5.875GHz
Polarization	Linear Vertical
E - Plane Beamwidth	7° (typ)
E - Plane Sidelobes	-10 dB (max)
Input Impedance	50 (ohms)
Power	6 W (max)
Lightning Protection	DC Grounded
<b><u>2. MECHANICAL</u></b>	
Dimensions :	Diameter 28 mm (max) Height 460 mm (max)
Weight	0.7 kg (max)
Connector	N – Type male
Radome	Plastic, UV Resistant
Outline Drawing	RD42198100C
<b><u>3. MOUNTING KIT</u></b>	
Configuration	Mounted to radio's N-female output

<b>MTI WIRELESS EDGE LTD.</b>	<b>Specification for MT – 462008/N/A Omni Directional Antenna</b>		
<b>DOC NO. RD42121000C</b>	<b>4.9 – 5.875 GHz, 9.5 dBi</b>		
<b>SCALE: NONE</b>	<b>CLASSIFICATION: NONE</b>	<b>REV-A</b>	<b>SHEET 3 OF 4</b>

<b>4. ENVIRONMENTAL</b>				
<b>TEST</b>	<b>STANDARD</b>	<b>DURATION</b>	<b>TEMPERTURE</b>	<b>NOTES</b>
Low Temperature	IEC 68-2-1	72 h	-55°C	-
High Temperature	IEC 68-2-2	72 h	+71°C	-
Temp. Cycling	IEC 68-2-14	1 h	-45°C +70°C	3 Cycles
Vibration	IEC 60721-3-4	30 min/axis	-	Random 4M5
Shock Mechanical	IEC 60721-3-4	-	-	4M5
Humidity	ETSI EN300-2-4 T4.1E	144 h	-	95%
Water Tightness	IEC 529	-	-	IP67
Solar Radiation	ASTM G53	1000 h	-	-
Flammability	UL 94	-	-	Class HB
Salt Spray	IEC 68-2-11 Ka	500 h	-	-
Ice And Snow	-	-	-	25mm Radial
Wind Speed Survival Operation	-	-	-	220 Km/h 160 Km/h

<b>MTI WIRELESS EDGE LTD.</b>		<b>Specification for MT – 462008/N/A</b>	
<b>DOC NO. RD42121000C</b>		<b>Omni Directional Antenna</b>	
		<b>4.9 – 5.875 GHz, 9.5 dBi</b>	
<b>SCALE: NONE</b>	<b>CLASSIFICATION: NONE</b>	<b>REV-A</b>	<b>SHEET 4 OF 4</b>