

Specification for MT – 464018/ND Dual Slant Pol B.S. Antenna 4.9 – 5.95 GHz, 16dBi, 90°

THIS DOCUMENT AND THE INFORMATION CONTAINED IN IT ARE PROPRIETARY AND CONFIDENTIAL TO MTI. NO PERSON IS ALLOWED TO COPY REPRINT REPRODUCE OR PUBLISH ANY PART OF THIS DOCUMENT NOR DISCLOSE ITS CONTENTS TO OTHERS NOR MAKE ANY USE OF IT NOR ALLOW OR ASSIST OTHERS TO MAKE ANY USE OF IT, UNLESS BY THE PRIOR WRITTEN EXPRESS AUTHORIZATION OF MTI AND THEN ONLY TO THE EXTENT AUTHORIZED.

(C) COPYRIGHT – MTI WIRELESS EDGE LTD.

MTI WIRELESS EDGE LTD.		MT – 464018/MD	REV-E
SCALE: NONE	DOC NO. RD42761300CRD420XXX00CRD420 XXX00C		SHEET 1 OF 5

REVISION RECORD				
REV	ECO	DESCRIPTION	APVD	DATE
01		Update Gain And Elevation Beamwidth	Yael h.	30.4.09
02		UPDATE SPEC	Yael H.	7.5.09
03		UPDATE DIM.	Yael H.	26.7.09
A	DB40	RELAISED	Yael H.	4.8.09
B	4190	Delete Passive Inter Modulation (Pim)	Yael H.	28.8.09
C	4287	UPDATE SPEC	Yael H.	14.12.09
D	4298	UPDATE F/B	Yael H.	23.12.09
E	4575	UPDATE WEIGHT	Yael H.	14.4.10

SHEET	43	44	45	46	47	48	49	50	51	52	53	54	55	56
REV														
SHEET	29	30	31	32	33	34	35	36	37	38	39	40	41	42
REV														
SHEET	15	16	17	18	19	20	21	22	23	24	25	26	27	28
REV														
SHEET	1	2	3	4	5	6	7	8	9	10	11	12	13	14
REV	E	E	E	E										

PRODUCT STATUS:			
<input type="checkbox"/> PROPOSAL	<input type="checkbox"/> IN DEVELOPMENT	<input type="checkbox"/> PREPRODUCTION	<input checked="" type="checkbox"/> PRODUCTION

CONTRACT NO			
ACTION	NAME	SIGN	DATE
PREP	Yael HARASH	Yael	22.4.09
CHKD	DANIEL ZERHA	D.Z	3.8.09
CHKD			
CHKD			
DSGN	ASAF HAVIV	A.H	26.7.09
PROJ	LARISA MEDVEDOVSKY	L.M	26.7.09
MFG			

MTI WIRELESS EDGE LTD.	Specification For MT – 464018/ND Dual Slant Pol Bs Antenna 4.9 – 5.95 GHz, 16dBi, 90°		
DOC NO. RD42761300CRD420XXX00CRD420 XXX00C			
SCALE: NONE	CLASSIFICATION: NONE	REV-E	SHEET 2 OF 5

QA	MOTI MOTOVICH	MOTI	2.8.09
MARK.	DROR REISS	D.R	2.8.09

MTI WIRELESS EDGE LTD.	Specification For MT – 464018/ND Dual Slant Pol Bs Antenna		
DOC NO. RD42761300CRD420XXX00CRD420 XXX00C	4.9 – 5.95 GHz, 16dBi, 90°		
SCALE: NONE	CLASSIFICATION: NONE	REV-E	SHEET 3 OF 5

SPECIFICATION

Flat Panel Base Station Antenna Dual-Slant Polarization

MTI PART NUMBER	MT – 464018/ND
Regulatory Compliance	RoHS , CE 0682
1. ELECTRICAL	
Frequency Range	4.9 – 5.95 GHz
Gain	16.0dBi (min) , 16.5dBi (typ)
VSWR	2 :1 (max) 1.7 : 1 (typ)
4dB Azimuth Beamwidth	90° (typ)
3dB Elevation Beamwidth	6° (typ)
Polarization	Dual Linear, ±45°
Cross Polarization	-15 dB (max)
F/B Ratio	25dB (min)
EI Upper Sidelobes Level	-11dB (typ)
EI 1st Null Fill	-10dB(typ)
Port To Port Isolation	22dB (min) , 25 dB (typ)
Input Impedance	50 Ω
Input Power	20W (max)
Lightning Protection	DC Grounded
2. MECHANICAL	
Dimensions (L x W x D)	550 x 250 x 17 mm (max)
Weight	2.5kg (max)
Connectors	2 x N-type female
Radome	Plastic
Base Plate	Aluminum with chemical conversion coating
Outline Drawing	RD42830900C
3. MOUNTING KIT	SEE RD41191800C, MT-120025

MTI WIRELESS EDGE LTD.	Specification For MT – 464018/ND Dual Slant Pol Bs Antenna		
DOC NO. RD42761300CRD420XXX00CRD420 XXX00C	4.9 – 5.95 GHz, 16dBi, 90°		
SCALE: NONE	CLASSIFICATION: NONE	REV-E	SHEET 4 OF 5

4. ENVIRONMENTAL				
TEST	STANDARD	DURATION	TEMPERTURE	NOTES
Low Temperature	IEC 68-2-1	72 h	-45°C	-
High Temperature	IEC 68-2-2	72 h	+71°C	-
Temp. Cycling	IEC 68-2-14	1 h	-45°C +70°C	3 Cycles
Vibration	IEC 60721-3-4	30 min/axis	-	Random 4M5
Shock Mechanical	IEC 60721-3-4	-	-	4M5
Humidity	ETSI EN300-2-4 T4.1E	144 h	-	95%
Water Tightness	IEC 529	-	-	IP67
Solar Radiation	ASTM G 154	1000 h	-	-
Flammability	UL 94	-	-	Class HB
Salt Spray	IEC 68-2-11 Ka	500 h	-	-
Ice And Snow	-	-	-	25mm Radial
Wind Speed				
Survival	-	-	-	220 Km/h
Operation	-	-	-	160 Km/h

MTI WIRELESS EDGE LTD.	Specification For MT – 464018/ND Dual Slant Pol Bs Antenna		
DOC NO. RD42761300CRD420XXX00CRD420 XXX00C	4.9 – 5.95 GHz, 16dBi, 90°		
SCALE: NONE	CLASSIFICATION: NONE	REV-E	SHEET 5 OF 5