

MPE REPORT

Report No.:	20230617G06649X-E-1
Product Name:	Microwave Oven
Trade Name:	Midea
Model Tested:	EMB17G4V-S
FCC ID:	VG8EMB17GYY
Applicant:	Guangdong Midea Kitchen Appliances Manufacturing Co., Ltd.
Received Date:	2023.06.19
Test Data:	2023.06.25-2023.06.26
Issued by:	CCIC Southern Testing Co., Ltd.
Lab Location:	Electronic Testing Building, No.43, Shahe Road, Xili Street, Nanshan District, Shenzhen, Guangdong, China Tel: 86 755 26627338 Fax: 86 755 26627238

This test report consists of **4** pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product endorsement by CCIC-SET. The test results in the report only apply to the tested sample. The test report shall be invalid without all the signatures of testing engineers, reviewer and approver. Any objections must be raised to CCIC-SET within 15 days since the date when the report is received. It will not be taken into consideration beyond this limit



MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Product Name:	Microwave Oven			
Model Tested	EMB17G4V-S			
Trade Name	Midea			
Applicant:	Guangdong Midea Kitchen Appliances Manufacturing Co., Ltd.			
Applicant Address:	No.6, Yong An Road, Beijiao, Shunde, Foshan, China			
Manufacturer:	nufacturer Guangdong Midea Kitchen Appliances Manufacturing Co., Lto			
Manufacturer Address:	No.6, Yong An Road, Beijiao, Shunde, Foshan, China			
Standard(s)	FCC/OST MP-5(1986), OET Bulletin 56(1999)			
Test Result:	PASS			
Tested by	Ruihong Xie			
	Ruihong Xie Test Engineer	2023.06.26		
Reviewed by:	Chris You			
	Chris You Senior Engineer	2023.06.26		
Approved by:	Yang Fan			
	Yang Fan, Manager	2023.06.26		
	rang ran, manager			



1.1 RADIATION HAZARD TEST

1.1.1 Radiation Hazard (Health) Requirement

For ISM equipment operating on higher frequencies (above 900 MHz), in particulars microwave ovens and medical diathermy equipment, radiation leakage should be measured in accordance with the current Bureau of Radiological Health standard, employing an electromagnetic radiation monitor. This test is made primarily to assure that personnel will not be exposed to radiation hazard in testing the equipment. Equipment submitted to the FCC which have radiation leakage apparently in excess of BRH limit will be reported to BRH for their evaluation. See FCC Bulletin OST 56, "Questions and Answers about Biological Effects and Potential Hazards of Radiofrequency Radiation".

1.1.2 Test Procedure

The EUT was set-up according to the FCC MP-5 and FCC Part 18 for radiation Hazard measurement. The measurement was using a microwave leakage meter to measure the radiation leakage in the asreceived condition with the oven door closed A 770mL water load in a breaker was located in the center of the oven and the microwave oven was set to maximum power. While the oven operating, the microwave meter will check the leakage and then record the maximum leakage.

1.1.3 Limit

Frequency	Electric Field	Magnetic Field	Power Density	Averaging Time
Range	Strength (E)	Strength (H)	(S)	$ E ^{2}$, $ H ^{2}$ or S
(MHz)	(V/m)	(A/m)	(mW/cm ²)	(minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	$(180/f^2)^*$	30
30-300	27.5	0.073	0.2	30
300-1500	77		f/1500	30
1500-100,000			1.0	30

Limits for General Population/Uncontrolled Exposure

f = frequency in MHz

*Plane-wave equivalent power density

NOTE 1: Occupational/controlled limits apply in situations in which persons are exposed as a consequence of their employment provided those persons are fully aware of the potential for exposure and can exercise control over their exposure. Limits for occupational/controlled exposure also apply in situations when an individual is transient through a location where occupational/controlled limits apply provided he or she is made aware of the potential for exposure.



NOTE 2: General population/uncontrolled exposures apply in situations in which the general public may be exposed, or in which persons that are exposed as a consequence of their employment may not be fully aware of the potential for exposure or cannot exercise control over their exposure.

A maximum of 1.0mW/cm^2 is allowed in according with the applicable FCC standards

1.1.4 Test results

There was no microwave leakage exceeding a power level of 0.75 mW/cm² Observed at any point 5cm or more from the external surface of the oven

End of the report