EXHIBITA-FCC ID LABEL AND LOCATION

(PL

LISTED 54NJ

E214180

FCC ID Label

Midea

MICROWAVE OVEN MODEL: TR923X7ZE-SS0D00 POWER SUPPLY:120V~ 60Hz RATED INPUT(MICROWAVE):1200W RATED OUTPUT(MICROWAVE):900W MAX. INPUT(STEAM):1500W MAX. INPUT(GRILL):1500W MAX. INPUT(AIRFRY):1500W

MAX. INPUT(BAKE):1500W MICROWAVE OUTPUT FREQUENCY:2450MHz MANUFACTURE DATE:MM.YYYY

MANUFACTURE DATE: MM, YYYY
FCC ID: V68TR923XYYW
Contain FCC ID: 2ADQOMWB-SWB01
HOUSEHOLD USE ONLY
(NOT FOR COMMERCIAL USE)
THIS DEVICE COMPLIES WITH DHHS RADIATION PERFORMANCE STANDARDS 21 CFR SUBCHAPTER J.

MADE IN CHINA Guangdong Midea Kitchen Appliances Manufacturing Co., Ltd. No.6, Yong An Road, Beijiao, Shunde, Foshan, Guangdong, P.R. China

WARNING: Cancer and Reproductive .Harm-www.p65warnings.ca.gov

CAUTION THIS DEVICE IS TO BE SERVICED ONLY BY PROPERLY QUALIFIED SERVICE PERSONNEL. CONSULT THE SERVICE MANUAL FOR PROPER SERVICE PROCEDURES TO ASSURE CONTINUED COMPLIANCE WITH THE FEDERAL PERFORMANCE STANDARD FOR MICROWAYE OVENS AND FOR PRECAUTIONS TO BE TAKEN TO AVOID POSSIBLE EXPOSURE TO EXCESSIVE MICROWAYE ENERGY.

WARNING - TO ENSURE CONTINUED PROTECTION AGAINST ELECTRICAL SHOCK HAZARD, CONNECT TO PROPERLY GROUNDED OUTLETS ONLY DISCONNECT APPLIANCE BEFORE SERVICING. REMOVAL OF OUTERCASE WITH PRODUCT ENERGIZED MAY EXPOSE SERVICEMAN TO HAZARDOUS HIGH VOLTAGE POTENTIALS.

- CERTAIN INTERNAL PARTS ARE INTENTIONALLY NOT GROUNDED AND MAY PRESENT A RISK OF ELECTRIC SHOCK ONLY DURING SERVICING SERVICE PERSONNEL -DO NOT CONTACT THE FOLLOWING PARTS WHILE THE APPLIANCE IS ENERGIZED: IF PROVIDED FAN MOTOR, TURNTABLE MOTOR, DAMPER MOTOR L.V.TRANSFORMER (TOUCH CONTROL TYPE) OR TIMER MOTOR ASSEMBLY (MECHANICAL TYPE).

- RISK OF ELECTRIC SHOCK. NON-REMOVABLE FASTENERS ARE PROVIDED BECAUSE OF INTERNAL HIGH VOLTAGES.

- NOT FOR BUILT-IN INSTALLATION.

NOT FOR BUILT-IN INSTALLATION.

CAUTION - Hot

FCC ID Label Location Information



The label shown shall be permanently affixed at a conspicuous location on the device and be readily visible to the time purchase (Labeling requirements per 2.295)