



**CONFORMANCE TEST REPORT
FOR
FCC 47 CFR, Part 15 Subpart C
and
Canada RSS-210**

Report No.: 11-02-MAS-043-05

Client: OpenPeak Inc.
Product: Cisco Cius
Model: CIUS-7-K9
FCC ID: VGBCSCOT0710
IC ID: 2461B-CSCOT0710
Manufacturer: Celestica Thailand Ltd.

Date test item received: 2010/12/23
Date test campaign completed: 2011/03/14
Date of issue: 2011/03/17




The test result only corresponds to the tested sample. It is not permitted to copy this report, in part or in full, without the permission of the test laboratory.

Total number of pages of this test report: 69 pages

Total number of pages of photos: External photos 5 pages

Internal photos 8 pages

Setup photos 4 pages

Test Engineer	Checked By	Approved By
 Ivan Tsai	 James Cheng	 Joe Hsieh

ELECTRONICS TESTING CENTER, TAIWAN
NO.8, LANE 29, WENMING RD.,
LESHAN TSUEN, GUISHAN SHIANG,
TAOYUAN COUNTY, TAIWAN 33383,
R.O.C.TAIWAN, R.O.C.

TEL: (03) 3276170~4
INT: +886-3-3276170~4
FAX: (03) 3276188
INT: +886-3-3276188



Client : OpenPeak Inc.
Address : 1750 Clint Moore Rd. Boca Raton, FL, USA 33487
Manufacturer : Celestica Thailand Ltd.
Address : 49/18 laem Chabang Industrial Estate Moo 5, Tungsukhla Sriracha, Chaburi,
Thailand 20230
EUT : Cisco Cius
Brand/Trade name : Cisco Systems, Inc.
Model No. : CIUS-7-K9
Power Source : Adapter 1: (APD / DA-20A05)
Input: 100-240Vac, 50-60Hz, 1.0A Max
Output: 5V, 4A Max
Adapter 2: (ENG / 3A-204DB05)
Input: 100-240Vac, 50-60Hz, 0.5A
Output: 5V, 4.0A
Regulations applied : FCC 47 CFR, Part 15 Subpart C
Canada RSS-210 Issue 8 / RSS-Gen Issue 3

The testing described in this report has been carried out to the best of our knowledge and ability, and our responsibility is limited to the exercise of reasonable care. This certification is not intended to believe the sellers from their legal and/or contractual obligations.

The compliance test is only certified for the test equipment and the results of the testing report relate only to the item tested. The compliance test of this report was conducted in accordance with the appropriate standards. It's not intention to assure the quality and performance of the product. This report shall not be reproduced except in full, without the approval of ETC. This report must not be used by the client to claim product endorsement by NVLAP or any agency of the U.S. Government.

Laboratory Introduction: Electronics Testing Center, Taiwan is recognized, filed and mutual recognition arrangement as following:

- ① ISO9001: TÜV Product Service
- ② ISO/IEC 17025: BSMI, CNLA, NCC, NVLAP, CCIBLAC, UL, Compliance
- ③ Filing: FCC, Industry Canada, VCCI
- ④ MRA: Australia, Hong Kong, New Zealand, Singapore, USA, Japan, Korea, China, APLAC through TAF
- ⑤ FCC Registration Number: 90588, 91094, 91095
- ⑥ Industry Canada Site Regisitration number: IC 2949A-1



NVLAP Lab Code 200133-0

Table of Contents	Page
1 GENERAL INFORMATION.....	5
1.1 Product Description	5
1.2 Characteristics of Device	5
1.3 Test Methodology	5
1.4 Modification List of EUT	5
1.5 Test Facility	5
1.6 Test Summary	5
2 PROVISIONS APPLICABLE	6
2.1 Definition	6
2.2 Requirement for Compliance	7
2.3 Restricted Bands of Operation	9
2.4 Labeling Requirement.....	9
2.5 User Information.....	10
3. SYSTEM TEST CONFIGURATION.....	11
3.1 Justification.....	11
3.2 Devices for Tested System.....	11
4 RADIATED EMISSION MEASUREMENT	13
4.1 Applicable Standard.....	13
4.2 Measurement Procedure	13
4.3 Measuring Instrument	15
4.4 Radiated Emission Data	16
4.5 Field Strength Calculation.....	20
5 CONDUCTED EMISSION MEASUREMENT	21
5.1 Standard Applicable	21
5.2 Measurement Procedure.....	21
5.3 Conducted Emission Data	22
5.4 Result Data Calculation.....	24
5.5 Conducted Measurement EquipMent	24
6 ANTENNA REQUIREMENT	25
6.1 Standard Applicable	25
6.2 Antenna Construction and Directional Gain	25
7 20dB EMISSION BANDWIDTH MEASUREMENT	26
7.1 Standard Applicable	26
7.2 Measurement Procedure.....	26

7.3 Measurement EquipMent	26
7.4 Measurement Data.....	27
8 OUTPUT POWER MEASUREMENT	34
8.1 Standard Applicable	34
8.2 Measurement Procedure	34
8.3 Measurement EquipMent	34
8.4 Measurement Data.....	35
9 OUT-OF-BAND RF CONDUCTED SPURIOUS EMISSION MEASUREMENT	47
9.1 Standard Applicable	47
9.2 Measurement Procedure	47
9.3 Measurement EquipMent	47
9.4 Measurement Data.....	48
10 NUMBER OF HOPPING CHANNELS	54
10.1 Standard Applicable	54
10.2 Measurement Procedure.....	54
10.3 Measurement EquipMent.....	54
10.4 Measurement Data	54
11 HOPPING CHANNEL CARRIER FREQUENCY SEPARATED	58
11.1 Standard Applicable	58
11.2 Measurement Procedure.....	58
11.3 Measurement EquipMent.....	58
11.4 Measurement Data	59
12 DWELL TIME	61
12.1 Standard Applicable	61
12.2 Measurement Procedure.....	61
12.3 Measurement EquipMent.....	61
12.4 Measurement Data.....	61

1 GENERAL INFORMATION

1.1 Product Description

- a) Type of EUT : Cisco Cius
- b) Trade Name : Cisco Systems, Inc.
- c) Model No. : CIUS-7-K9
- d) FCC ID : VGBCSCOT0710
- e) IC ID : 2461B-CSCOT0710

1.2 Characteristics of Device

The EUT is a Mobile Collaboration Tablet based on the Bluetooth technology. Bluetooth is a short-range radio link intended to be a cable replacement between portable or fixed electronic devices. Bluetooth operates in the unlicensed ISM Band at 2.4GHz. In this band, 79 RF channels spaced 1MHz apart are defined. The rated output power is 8.12 dBm (6.49 mW).

1.3 Test Methodology

All testing were performed according to the procedures in ANSI C63.4 (2003) an FCC CFR 47 Part 2 and Part 15.

1.4 Modifiction List of EUT

N/A

1.5 Test Facility

The semi-anechoic chamber and conducted measurement facility used to collect the radiated and conducted data are located inside the Building at No.8, Lane 29, Wen-ming Road, Lo-shan Tsun, Kweishan Hsiang, Taoyuan, Taiwan, R.O.C.

This site has been accreditation as a FCC filing site.

1.6 Test Summary

Requirement	IC Paragraph #	FCC Paragraph #	Test Pass
Radiated Emission	RSS-210_2.2	15.209	☒
Conducted Emission	RSS-Gen_7.2.4	15.207	☒
Antenna Requirement	RSS-210_A8.4(2)	15.203	☒
20dB Emission Bandwidth	RSS-210_A8.1(b)	15.247 (a)(1)	☒
Output Power	RSS-210_A8.4(2)	15.247 (b)(1)	☒
OUT-OF-BAND RF Conducted Spurious Emission	RSS-210_A8.5	15.247 (c)	☒
Number of Hopping Channels	RSS-210_A8.4(2)	15.247 (b)(1)	☒
Hopping Channel Carrier Frequency Seperated	RSS-210_A8.1(b)	15.247 (a)(1)	☒
Dwell Time	RSS-210_A8.1(d)	15.247 (a)(1)(iii)	☒

2 PROVISIONS APPLICABLE

2.1 Definition

Unintentional radiator:

A device that intentionally generates and radio frequency energy for use within the device, or that sends radio frequency signals by conduction to associated equipment via connecting wiring, but which is not intended to emit RF energy by radiation or induction.

Class A Digital Device:

A digital device which is marketed for use in commercial or business environment; exclusive of a device which is market for use by the general public, or which is intended to be used in the home.

Class B Digital Device :

A digital device which is marketed for use in a residential environment notwithstanding use in a commercial, business or industrial environment. Example of such devices that are marketed for the general public.

Note : A manufacturer may also qualify a device intended to be marketed in a commercial, business, or industrial environment as a Class B digital device, and in fact is encouraged to do so, provided the device complies with the technical specifications for a Class B Digital Device. In the event that a particular type of device has been found to repeatedly cause harmful interference to radio communications, the Commission may classify such a digital device as a Class B Digital Device, Regardless of its intended use.

Intentional radiator:

A device that intentionally generates and emits radio frequency energy by radiation or induction.

2.2 Requirement for Compliance

(1) Conducted Emission Requirement

For unintentional device, according to §15.107(a) Line Conducted Emission Limits is as following:

Frequency MHz	Quasi Peak dB μ V	Average dB μ V
0.15 - 0.5	66-56*	56-46*
0.5 - 5.0	56	46
5.0 - 30.0	60	50

*Decreases with the logarithm of the frequency.

For intentional device, according to §15.207(a) Line Conducted Emission Limits is same as above table.

(2) Radiated Emission Requirement

For unintentional device, according to §15.109(a), except for Class A digital devices, the field strength of radiated emissions from unintentional radiators at a distance of 3 meters shall not exceed the following values:

Frequency MHz	Distance Meters	Radiated dB μ V/m	Radiated μ V/m
30 - 88	3	40.0	100
88 - 216	3	43.5	150
216 - 960	3	46.0	200
above 960	3	54.0	500

For intentional device, according to §15.209(a), the general requirement of field strength of radiated emissions from intentional radiators at a distance of 3 meters shall not exceed the above table.

(3) Antenna Requirement

For intentional device, according to §15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to §15.247 (c),(i) Systems operating in the 2400-2483.5 MHz band that are used exclusively for fixed, point-to point operations may employ transmitting antennas with directional gain greater than 6 dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi. (ii) Systems operating in the 5725-5850 MHz band that are used exclusively for fixed, point-to point operations may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter conducted output power.

(4) 20dB Bandwidth Requirement

For frequency hopping systems, according to 15.247(a)(1), hopping channel carrier frequencies separated by a minimum of 25kHz or the 20dB bandwidth of hopping channel, whichever is greater.

(5) Output Power Requirement

For frequency hopping systems, according to 15.247(b)(1), operating in the 2400-2483.5MHz band employing at least 75 hopping channels. The maximum peak output power of the transmitter shall not exceed 1 Watt. If transmitting antennas of directional gain greater than 6 dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

(6) 100 kHz Bandwidth of Frequency Band Edges Requirement

According to 15.247(c), if any 100 kHz bandwidth outside these frequency bands, the radio frequency power that is produced by the modulation products of the spreading sequence, the information sequence and the carrier frequency shall be either at least 20 dB below that in any 100 kHz bandwidth within the band that contains the highest level of the desired power or shall not exceed the general levels specified in §15.209(a), whichever results in the lesser attenuation.

(7) Number of Hopping Channels

According to 15.247(b)(1), for frequency hopping systems, operating in the 2400-2483.5MHz band employing at least 75 hopping channels.

(8) Channel Carrier Frequencies Separation

According to 15.247(a)(1)(iii), the frequency hopping systems shall have hopping channel carrier frequencies separated by minimum of 25kHz or the 20dB bandwidth of hopping channel, whichever is greater.

(9) Dwell Time

According to 15.247(a)(1)(iii), frequency hopping system in the 2400-2483.5MHz band employing at least 15 non-overlapping channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 second multiplied by the number of hopping channels employed.

(10) Power Spectral Density

According to 15.247(d), for bluetooth device, the peak power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3kHz band during any time interval of continuous transmission.

2.3 Restricted Bands of Operation

Only spurious emissions are permitted in any of the frequency bands listed below :

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42-16.423	399.9-410	4.5-5.25
0.495 - 0.505 **	16.69475 - 16.69525	608-614	5.35-5.46
2.1735 - 2.1905	16.80425 - 16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475 - 156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2655-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	Above 38.6
13.36-13.41			

** : Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz

2.4 Labeling Requirement

The device shall bear the following statement in a conspicuous location on the device :

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

2.5 User Information

The users manual or instruction manual for an intentional or unintentional radiator shall caution the user that changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

For a Class B digital device or peripheral, the instructions furnished the user shall include the following or similar statement, placed in a prominent location in the text of the manual.

The Federal Communications Commission Radio Frequency Interference Statement includes the following paragraph.

This equipment has been tested and found to comply with the limits for a Class B Digital Device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation.

This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instruction may cause harmful interference to radio communication. However, there is no guarantee that interference will not occur in a particular installation.

If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio / TV technician for help.

To comply with the FCC RF exposure compliance requirement, this device and its antenna must not be co-located or operating to conjunction with any other antenna or transmitter.

3. SYSTEM TEST CONFIGURATION

3.1 Justification

For the purposes of this test report ancillary equipment is defined as equipment which is used in conjunction with the EUT to provide operational and control features to the EUT during the test. Notebook PC was used to control the RF channel under the highest, middle and lowest frequency and transmit the maximum RF power. Customer would not use it. But never the less ancillary equipment can influence the test results..


3.2 Devices for Tested System

3.2.1

Device	Manufacture	Model	Cable Description
* Cisco Cius	Celestica Thailand Ltd.	CIUS-7-K9	2.5m*1, Unshielded Power Line / Adapter
Test Jig	N/A	N/A	1.8m*1, Unshielded Power Line 1.8m*1 Unshielded Signal Line
Notebook	HP	nx6320	3.1m*1, Unshielded Power Line

Remark

1. “*” means equipment under test.



Note: A HP notebook performs the control test mode. The notebook removes away after the control command is ready.

3.2.2 Test Mode Description

3.2.2.1 Modulation Type

Test Mode	Modulation	Test Channel	Frequency (MHz)
A	GFSK	Channel Low	2402
B	$\pi/4$ -DQPSK	Channel Mid	2441
C	8-DPSK	Channel High	2480

3.2.2.2 Test Mode and Worse Case Determination

Item	Test Item	Test Mode	Test Frequency (MHz)
1	Output Power	A	2402,2441,2480
		B	2402,2441,2480
		C	2402,2441,2480
	Worse Case	Mode A (note 1)	
2.	Conducted Emission	A	2441(Worse Case)
3	Out of Band Conducted Emission	A	2402,2441,2480
4.1	Number of Channel	A	2402~2480
4.2	Channel Separation	A	2441 (note 2)
4.3	Dwell Time	A	2441 (note 2)
5.1	Radiated Emission (below 1GHz)	A	2441 (Worse Case)
5.2	Radiated Emission (above 1GHz)	A	2402,2441,2480

note:

1. The worse case is determined as the modulation with highest output power.
2. Pretest result is no difference in three test modes by channel low, middle and high. Choose one for final testing and record the result.

4 RADIATED EMISSION MEASUREMENT

4.1 Applicable Standard

For unintentional radiator, the radiated emission shall comply with §15.109(a).

For intentional radiators, according to §15.247 (a), operation under this provision is limited to frequency hopping and digitally modulated, and the out band emission shall be comply with § 15.247 (c)

4.2 Measurement Procedure

1. Setup the configuration per figure 1 and 2 for frequencies measured below and above 1 GHz respectively. Turn on EUT and make sure that it is in continuous operating function.
2. For emission frequencies measured below 1 GHz, a pre-scan is performed in a semi-anechoic chamber to determine the accurate frequencies of higher emissions and then each selected frequency is precisely measured. As the same purpose, for emission measured above 1 GHz, a pre-scan also be performed with a 1 meter measuring distance before final test.
3. For emission measured below and above 1 GHz, set the spectrum analyzer on a 120 kHz and 1 MHz resolution bandwidth respectively for each frequency measured in step 2.
4. The search antenna is to be raised and lowered over a range from 1 to 4 meters in horizontally polarized orientation. Position the highness when the highest value is indicated on spectrum analyzer, then change the orientation of EUT on test table over a range from 0° to 360° with a speed as slow as possible, and keep the azimuth that highest emission is indicated on the spectrum analyzer. Vary the antenna position again and record the highest value as a final reading. A RF test receiver is also used to confirm emissions measured.

Figure 1 : Frequencies measured below 1 GHz configuration





Figure 2 : Frequencies measured above 1 GHz configuration



4.3 Measuring Instrument

The following instrument are used for radiated emissions measurement :

Equipment	Manufacturer	Model No.	Next Cal. Due
EMI Test Receiver	R&S	ESIB7	07/19/2011
Spectrum Analyzer	Rohde & Schwarz	FSU46	11/25/2011
Horn Antenna	EMCO	3115	07/18/2011
BiLog Antenna	Schaffner	CBL 6112B	09/02/2011
Horn Antenna	EMCO	3116	07/16/2011
Preamplifier	Hewlett-Packard	8449B	10/25/2011

Measuring instrument setup in measured frequency band when specified detector function is used :

Frequency Band (MHz)	Instrument	Function	Resolution Bandwidth	Video Bandwidth
30 to 1000	RF Test Receiver	Quasi-Peak	120 kHz	300 kHz
	RF Test Receiver	Peak	120 kHz	300 kHz
Above 1000	Spectrum Analyzer	Peak	1 MHz	1 MHz
	Spectrum Analyzer	Average	1 MHz	10 Hz

4.4 Radiated Emission Data

4.4.1 RF Portion

a) Channel 0

Operation Mode : Transmitting

Fundamental Frequency : 2402 MHz

Test Date : Mar. 14, 2011 Temperature : 26

Humidity : 57%

Frequency (MHz)	Reading (dBuV)				Factor (dB) Corr.	Result @3m (dBuV/m) Peak Ave (H/V Max.)		Limit @3m (dBuV/m) Peak Ave.	
	H Peak	H Ave	V Peak	V Ave		Peak	Ave	Peak	Ave
4804.000	---	---	---	---	0.6	---	---	74.0	54.0
7206.000	---	---	---	---	2.2	---	---	74.0	54.0
9608.000	---	---	---	---	2.6	---	---	74.0	54.0

b) Channel 39

Fundamental Frequency : 2441 MHz

Frequency (MHz)	Reading (dBuV)				Factor (dB) Corr.	Result @3m (dBuV/m) Peak Ave (H/V Max.)		Limit @3m (dBuV/m) Peak Ave.	
	H Peak	H Ave	V Peak	V Ave		Peak	Ave	Peak	Ave
4882.000	---	---	---	---	0.5	---	---	74.0	54.0
7323.000	---	---	---	---	2.9	---	---	74.0	54.0
9764.000	---	---	---	---	4.2	---	---	74.0	54.0

c) Channel 78


Fundamental Frequency : 2480 MHz

Frequency (MHz)	Reading (dBuV)				Factor (dB) Corr.	Result @3m (dBuV/m) Peak Ave (H/V Max.)		Limit @3m (dBuV/m) Peak Ave.	
	H Peak	H Ave	V Peak	V Ave		Peak	Ave	Peak	Ave
4960.000	---	---	---	---	0.5	---	---	74.0	54.0
7440.000	---	---	---	---	2.9	---	---	74.0	54.0
9920.000	---	---	---	---	4.2	---	---	74.0	54.0
14880.000	---	---	---	---	3.1	---	---	74.0	54.0
17360.000	---	---	---	---	6.3	---	---	74.0	54.0

Note :

1. Item of margin shown in above table refer to average limit.
2. Remark “---” means that the emissions level is too low to be measured.
3. Item “Margin” referred to Average limit while there is only peak result.
4. The radiation emissions have been measured to beyond the tenth harmonic of the fundamental frequency and show the significant frequencies, other means the value is too low to be detected.

File: **suede** Data: **#2814** Date: **2010/12/23** Temperature: **26**
 Time: **AM 09:28:38** Humidity: **57 %**



Condition: **FCC Part15 RE-Class B_30-1000MHz** Polarization: **Vertical**
 EUT: Distance: **3m**
 Model:
 Test Mode:

No.	Frequency (MHz)	Reading (dBuV/m)	Detector	Corrected (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
1	118.0762	22.60	QP	13.99	36.59	43.50	-6.91
2	156.3525	21.07	peak	12.38	33.45	43.50	-10.05
3	236.4830	24.32	QP	13.60	37.92	46.00	-8.08
4	315.7515	17.14	peak	16.51	33.65	46.00	-12.35
5	423.5471	18.47	QP	19.43	37.90	46.00	-8.10
6	515.9720	14.38	peak	21.08	35.46	46.00	-10.54

B. above 1GHz

Frequency (MHz)	Ant Pol H / V	Reading (dBuV) Peak	Correct Factor (dB)	Duty Factor (dB)	Result @3m (dBuV/m) Peak AVG	Limit @3m (dBuV/m) Peak AVG	Margins (dB)
Radiated emission frequencies above 1 GHz to 25 GHz were too low to be measured.							

Note:

1. Place of Measurement: Measuring site of the ETC.
2. If the data table appeared symbol of "***" means the value was too low to be measured.
3. The estimated measurement uncertainty of the result measurement is
 - ±4.6dB (30MHz f<300MHz).
 - ±4.4dB (300MHz f<1000MHz).
 - ±4.1dB (1GHz f 18GHz).
 - ±4.4dB (18GHz<f 40GHz).
- 4 Remark “---” means that the emissions level is too low to be measured.

4.4.3 Radiated Measurement at Bandedge with Fundamental Frequencies

(A)

Channel 0

Operation Mode : Transmitting

Fundamental Frequency : 2402 MHz

Test Date : Mar. 14, 2011

Temperature : 26

Humidity : 57%

Frequency (MHz)	Reading (dBuV)				Factor (dB) Corr.	Result @3m (dBuV/m) Peak Ave (H/V Max.)		Limit @3m (dBuV/m) Peak Ave.	
	Peak	Ave	Peak	Ave		Peak	Ave	Peak	Ave
2390.000	27.69	15.08	29.82	15.91	29.8	58.67	45.71	74	54

Note:

The result is the highest value of radiated emission from restrict band of 2310 ~2390 MHz.

(B)

Channel 78

Operation Mode : Transmitting

Fundamental Frequency : 2480 MHz

Frequency (MHz)	Reading (dBuV)				Factor (dB) Corr.	Result @3m (dBuV/m) Peak Ave (H/V Max.)		Limit @3m (dBuV/m) Peak Ave.	
	Peak	Ave	Peak	Ave		Peak	Ave	Peak	Ave
2483.500	28.36	15.13	30.11	16.81	29.8	59.91	46.61	74	54

Note:

The result is the highest value of radiated emission from restrict band of 2483.5 ~2500 MHz.

4.5 Field Strength Calculation

The field strength is calculated by adding the Antenna Factor, High Pass Filter Loss(if used) and Cable Loss, and subtracting the Amplifier Gain (if any) from the measured reading. The basic equation calculation is as follows:

$$\text{Result} = \text{Reading} + \text{Corrected Factor}$$

where

$$\text{Corrected Factor} = \text{Antenna Factor} + \text{Cable Loss} + \text{High Pass Filter Loss} - \text{Amplifier Gain}$$


5 CONDUCTED EMISSION MEASUREMENT

5.1 Standard Applicable

For unintentional and intentional device, Line Conducted Emission Limits are in accordance to § 15.107(a) and §15.207(a) respectively. Both Limits are identical specification.

5.2 Measurement Procedure

1. Setup the configuration per figure 3.
2. A preliminary scan with a spectrum monitor is performed to identify the frequency of emission that has the highest amplitude relative to the limit by operating the EUT in selected modes of operation, typical cable positions, and with a typical system configuration.
3. Record the 6 highest emissions relative to the limit.
4. Measure each frequency obtained from step 3 by a test receiver set on quasi peak detector function, and then record the accuracy frequency and emission level. If all emissions measured in the specified band are attenuated more than 20 dB from the limit, this step would be ignored, and the peak detector function would be used.
5. Confirm the highest three emissions with variation of the EUT cable configuration and record the final data.
6. Repeat all above procedures on measuring each operation mode of EUT.



File: 1103

Data: #27

Date: 2011/1/20

Temperature: 20

Time: PM 12:53:04

Humidity: 69 %



Condition:

Phase:

L2

EUT:

Power:

No.	Frequency (MHz)	Reading (dBuV)	Detector	Corrected dB	Result (dBuV)	Limit (dBuV)	Margin (dB)
1	0.1734	59.72	peak	0.12	59.84	64.80	-4.96
2	0.1758	40.67	AVG	0.12	40.79	54.68	-13.89
3	0.2281	50.58	peak	0.11	50.69	62.52	-11.83
4	0.2984	45.66	peak	0.10	45.76	60.29	-14.53
5	3.6133	30.58	peak	0.16	30.74	56.00	-25.26
6	4.7773	38.07	peak	0.19	38.26	56.00	-17.74
7	5.0898	37.27	peak	0.20	37.47	60.00	-22.53

Note:

1. Place of measurement: EMC LAB. of the ETC.
2. “***” means the value was too low to be measured.
3. If the data table appeared symbol of “----” means the Q.P. value is under the limit of AVG. so, the AVG. value doesn't need to be measured.
4. “#” means the noise was too low, so record the peak value.
5. The estimated measurement uncertainty of the result measurement is ± 2.5 dB.

5.4 Result Data Calculation

The result data is calculated by adding the LISN Factor to the measured reading. The basic equation with a sample calculation is as follows:

$$\mathbf{RESULT = READING + LISN FACTOR (Included Cable Loss)}$$

5.5 Conducted Measurement EquipMent

The following test equipMent are used during the conducted test.

EquipMent	Manufacturer	Model No.	Next Cal. Due
RF Test Receiver	Rohde and Schwarz	ESCS30	09/06/2011
LISN	EMCO	37100/2M	03/04/2011

6 ANTENNA REQUIREMENT

6.1 Standard Applicable

For intentional device, according to §15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

And according to §15.247 (c),(i) Systems operating in the 2400-2483.5 MHz band that are used exclusively for fixed, point-to point operations may employ transmitting antennas with directional gain greater than 6 dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi. (ii) Systems operating in the 5725-5850 MHz band that are used exclusively for fixed, point-to point operations may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter conducted output power.

6.2 Antenna Construction and Directional Gain

The peak gain of antenna used is 3.5 dBi.

Antenna Type	
Model Number	N/A
Brand Name	N/A
Peak Antenna Gain	3.5 dBi

The directional gain of antenna doesn't greater than 6 dBi, the power won't be reduced.

7 20dB EMISSION BANDWIDTH MEASUREMENT

7.1 Standard Applicable

According to 15.247(a)(1), for frequency hopping systems, hopping channel carrier frequencies separated by a minimum of 25kHz or the 20dB bandwidth of hopping channel, whichever is greater.

7.2 Measurement Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. The setup of the EUT as shown in figure 4. Turn on the EUT and connect it to measurement instrument. Then set it to any convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. Measure the frequency difference of two frequencies that were attenuated 20 dB from the reference level. Record the frequency difference as the emission bandwidth.
4. Repeat above procedures until all frequencies measured were complete.

Figure 4: Emission bandwidth measurement configuration.



7.3 Measurement EquipMent

EquipMent	Manufacturer	Model No.	Next Cal. Due
Spectrum Analyzer	Agilent	E4446A	09/26/2011

7.4 Measurement Data

Test Date : Mar. 14, 2011

Temperature : 15

Humidity : 55%

Channel	Frequency (MHz)	20 dB Bandwidth (MHz)	Chart
0	2402	0.940	Page 28
39	2441	0.940	Page 29
78	2480	0.940	Page 30

99% bandwidth

Channel	Frequency (MHz)	99% Bandwidth (MHz)	Chart
0	2402	1.053	Page 31
39	2441	1.134	Page 32
78	2480	1.165	Page 33

Note: Please refer to page 28 to page 33 for chart.

File: CISCO


Data: #11

Date: 2011/3/14

Temperature: 15

Time: AM 09:04:56

Humidity: 55 %



Condition: -14.42dBm

Horizontal

EUT:

Sweep Time: 3.2ms Att.: 20dB

Model:

RBW: 30 KHz VBW: 100 KHz

Test Mode:

Note: FCC-Bluetooth Channel 00-20dB EBW

No.	Frequency(MHz)	Level(dBm)
1	2401.55000	-15.27
2	2401.99500	5.58
3	2402.49000	-14.69

No.	Frequency(MHz)	Level(dB)
1	mk3-mk1	0.94

File: CISCO


Data: #17

Date: 2011/3/14

Temperature: 15

Time: AM 09:10:44

Humidity: 55 %



Condition: -14.59dBm

Horizontal

EUT:

Sweep Time: 3.2ms Att.: 20dB

Model:

RBW: 30 KHz VBW: 100 KHz

Test Mode:

Note: FCC-Bluetooth Channel 39-20dB EBW

No.	Frequency(MHz)	Level(dBm)
1	2440.55000	-15.46
2	2440.99500	5.41
3	2441.49000	-14.68

No.	Frequency(MHz)	Level(dB)
1	mk3-mk1	0.78

File: CISCO


Data: #14

Date: 2011/3/14

Temperature: 15

Time: AM 09:07:58

Humidity: 55 %



Condition: -15.4dBm

Horizontal

EUT:

Sweep Time: 3.2ms Att.: 20dB

Model:

RBW: 30 KHz VBW: 100 KHz

Test Mode:

Note: FCC-Bluetooth Channel 78-20dB EBW

No.	Frequency(MHz)	Level(dBm)
1	2479.55000	-16.39
2	2479.99500	4.60
3	2480.49000	-15.44

No.	Frequency(MHz)	Level(dB)
1	mk3-mk1	0.94

Agilent R T

Ch Freq 2.402 GHz Trig Free

Occupied Bandwidth [] []

Ref 16.06 dBm Atten 20 dB

#Peak

Log

10

dB/

Offst

10

dB

Center 2.402 000 GHz Span 3 MHz

#Res BW 30 kHz #VBW 100 kHz #Sweep 100 ms (601 pts)

Occupied Bandwidth	Occ BW % Pwr 99.00 %
821.5358 kHz	x dB -26.00 dB
Transmit Freq Error 23.704 kHz	
x dB Bandwidth 1.053 MHz*	

Copyright 2000-2008 Agilent Technologies

Freq/Channel

Center Freq 2.40200000 GHz

Start Freq 2.40050000 GHz

Stop Freq 2.40350000 GHz

CF Step 300.000000 kHz
Auto Man

Freq Offset 0.00000000 Hz

Signal Track On Off

Agilent

R T

Ch Freq 2.441 GHz Trig Free

Occupied Bandwidth

Center 2.441000000 GHz

Ref 16.06 dBm

Atten 20 dB

#Peak

Log


10

dB/

Offst

10

dB



Center 2.441 000 GHz

Span 3 MHz

#Res BW 30 kHz

#VBW 100 kHz

#Sweep 100 ms (601 pts)

Occupied Bandwidth

856.2971 kHz

Occ BW % Pwr 99.00 %

x dB -26.00 dB

Transmit Freq Error 18.214 kHz

x dB Bandwidth 1.134 MHz*

Freq/Channel

Center Freq
2.44100000 GHz

Start Freq
2.43950000 GHz

Stop Freq
2.44250000 GHz

CF Step
300.000000 kHz
Auto Man

Freq Offset
0.00000000 Hz

Signal Track
On Off

Copyright 2000-2008 Agilent Technologies

Agilent R T

Ch Freq 2.48 GHz Trig Free		Freq/Channel
Occupied Bandwidth		Center Freq 2.48000000 GHz
		Start Freq 2.47850000 GHz
Ref 16.06 dBm Atten 20 dB		Stop Freq 2.48150000 GHz
#Peak		CF Step 300.000000 kHz Auto Man
Log		Freq Offset 0.00000000 Hz
10 dB/Offst		Signal Track On Off
10 dB		
Center 2.480 000 GHz Span 3 MHz		
#Res BW 30 kHz #VBW 100 kHz #Sweep 100 ms (601 pts)		
Occupied Bandwidth		
855.4610 kHz		Occ BW % Pwr 99.00 % x dB -26.00 dB
Transmit Freq Error 10.879 kHz		
x dB Bandwidth 1.165 MHz*		
Copyright 2000-2008 Agilent Technologies		

8 OUTPUT POWER MEASUREMENT

8.1 Standard Applicable

For frequency hopping system, according to 15.247(b), the maximum peak output power of the transmitter shall not exceed 1 Watt. If Receiving antennas of directional gain greater than 6 dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

8.2 Measurement Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. The setup of the EUT as shown in figure 4. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any measured frequency within its operating range and make sure the instrument is operated in its linear range.
3. Set RBW of spectrum analyzer to 1 MHz and VBW to 3 MHz.
4. Measure the highest amplitude appearing on spectral display and record the level to calculate result data.
5. Repeat above procedures until all frequencies measured were complete.

8.3 Measurement EquipMent

EquipMent	Manufacturer	Model No.	Next Cal. Due
Spectrum Analyzer	Agilent	E4446A	09/26/2011

8.4 Measurement Data

8.4.1 Operation Mode: GFSK

Test Date : Mar. 14, 2011

Temperature : 15

Humidity : 55%

Channel	Frequency (MHz)	Maximum Peak Output Power (dBm)	Maximum Peak Output Power (mW)	FCC Limit (mW)	Chart
0	2402	8.12	6.49	1000	Page 36
39	2441	7.96	6.25	1000	Page 37
78	2480	7.16	5.20	1000	Page 38

Note: Please refer to page 36 to page 38 for chart.

File: CISCO


Data: #2

Date: 2011/3/14

Temperature: 15

Time: AM 08:55:54

Humidity: 55 %



Condition:

Horizontal

EUT:

Sweep Time: 1ms Att.: 20dB

Model:

RBW: 2000 KHz VBW: 2000 KHz

Test Mode:

Note: FCC Bluetooth CH00 Output Power (GFSK)

No.	Frequency(MHz)	Level(dBm)
1	2401.95830	8.12

File: CISCO


Data: #5

Date: 2011/3/14

Temperature: 15

Time: AM 08:59:02

Humidity: 55 %



Condition:

Horizontal

EUT:

Sweep Time: 1ms Att.: 20dB

Model:

RBW: 2000 KHz VBW: 2000 KHz

Test Mode:

Note: FCC Bluetooth CH39 Output Power (GFSK)

No.	Frequency(MHz)	Level(dBm)
1	2440.92500	7.96

File: CISCO


Data: #8

Date: 2011/3/14

Temperature: 15

Time: AM 09:01:51

Humidity: 55 %



Condition:

Horizontal

EUT:

Sweep Time: 1ms Att.: 20dB

Model:

RBW: 2000 KHz VBW: 2000 KHz

Test Mode:

Note: FCC Bluetooth CH78 Output Power (GFSK)

No.	Frequency(MHz)	Level(dBm)
1	2479.87500	7.16

8.4.2 Operation Mode: 8DPSK

Test Date : Mar. 14, 2011

Temperature : 15

Humidity : 55%

Channel	Frequency (MHz)	Maximum Peak Output Power (dBm)	Maximum Peak Output Power (mW)	FCC Limit (mW)	Chart
0	2402	7.41	5.51	1000	Page 40
39	2441	7.41	5.51	1000	Page 41
78	2480	6.72	4.70	1000	Page 42

Note: Please refer to page 40 to page 42 for chart.

File: CISCO


Data: #4

Date: 2011/3/14

Temperature: 15

Time: AM 08:57:55

Humidity: 55 %



Condition:

Horizontal

EUT:

Sweep Time: 1ms Att.: 20dB

Model:

RBW: 2000 KHz VBW: 2000 KHz

Test Mode:

Note: FCC Bluetooth CH00 Output Power(8DPSK)

No.	Frequency(MHz)	Level(dBm)
1	2401.95830	7.41

File: CISCO


Data: #7

Date: 2011/3/14

Temperature: 15

Time: AM 09:00:54

Humidity: 55 %



Condition:

Horizontal

EUT:

Sweep Time: 1ms Att.: 20dB

Model:

RBW: 2000 KHz VBW: 2000 KHz

Test Mode:

Note: FCC Bluetooth CH39 Output Power(8DPSK)

No.	Frequency(MHz)	Level(dBm)
1	2440.96670	7.41

File: CISCO


Data: #10

Date: 2011/3/14

Temperature: 15

Time: AM 09:03:42

Humidity: 55 %



Condition:

Horizontal

EUT:

Sweep Time: 1ms Att.: 20dB

Model:

RBW: 2000 KHz VBW: 2000 KHz

Test Mode:

Note: FCC Bluetooth CH78 Output Power(8DPSK)

No.	Frequency(MHz)	Level(dBm)
1	2479.95000	6.72

8.4.3 Operation Mode: $\pi/4$ -DQPSK

Test Date : Mar. 14, 2011

Temperature : 15

Humidity : 55%

Channel	Frequency (MHz)	Maximum Peak Output Power (dBm)	Maximum Peak Output Power (mW)	FCC Limit (mW)	Chart
0	2402	6.98	4.99	1000	Page 44
39	2441	7.05	5.07	1000	Page 45
78	2480	6.42	4.39	1000	Page 46

Note: Please refer to page 44 to page 46 for chart.

File: CISCO


Data: #3

Date: 2011/3/14

Temperature: 15

Time: AM 08:57:00

Humidity: 55 %



Condition:

Horizontal

EUT:

Sweep Time: 1ms Att.: 20dB

Model:

RBW: 2000 KHz VBW: 2000 KHz

Test Mode:

Note: FCC Bluetooth CH00 Output Power (QPSK)

No.	Frequency(MHz)	Level(dBm)
1	2402.1000	6.98

File: CISCO


Data: #6

Date: 2011/3/14

Temperature: 15

Time: AM 08:59:58

Humidity: 55 %



Condition:

Horizontal

EUT:

Sweep Time: 1ms Att.: 20dB

Model:

RBW: 2000 KHz VBW: 2000 KHz

Test Mode:

Note: FCC Bluetooth CH39 Output Power (QPSK)

No.	Frequency(MHz)	Level(dBm)
1	2441.08330	7.05

File: CISCO


Data: #9

Date: 2011/3/14

Temperature: 15

Time: AM 09:02:47

Humidity: 55 %



Condition:

Horizontal

EUT:

Sweep Time: 1ms Att.: 20dB

Model:

RBW: 2000 KHz VBW: 2000 KHz

Test Mode:

Note: FCC Bluetooth CH78 Output Power (QPSK)

No.	Frequency(MHz)	Level(dBm)
1	2480.06670	6.42

9 OUT-OF-BAND RF CONDUCTED SPURIOUS EMISSION MEASUREMENT

9.1 Standard Applicable

According to 15.247(c), if any 100 kHz bandwidth outside these frequency bands, the radio frequency power that is produced by the modulation products of the spreading sequence, the information sequence and the carrier frequency shall be either at least 20 dB below that in any 100 kHz bandwidth within the band that contains the highest level of the desired power or shall not exceed the general levels specified in §15.209(a), whichever results in the lesser attenuation.

9.2 Measurement Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. The setup of the EUT as shown in figure 4. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any measured frequency within its operating range and make sure the instrument is operated in its linear range.
3. Set RBW of spectrum analyzer to 100 kHz with a convenient frequency span including 100kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

9.3 Measurement EquipMent

EquipMent	Manufacturer	Model No.	Next Cal. Due
Spectrum Analyzer	Agilent	E4446A	09/26/2011

9.4 Measurement Data

Test Date : Mar. 14, 2011


Temperature : 15

Humidity : 55%

Channel	Test Frequency Range	Note	Chart
0	2350 MHz - 2450 MHz	Lower Band Edge	Page 49
78	2433.5 MHz - 2533.5 MHz	Upper Band Edge	Page 50
0	30 MHz - 25 GHz		Page 51
39	30 MHz - 25 GHz		Page 52
78	30 MHz - 25 GHz		Page 53

Note: Please refer to page 49 to page 53 for chart.


File: CISCO Data: #13 Date: 2011/3/14 Temperature: 15
 Time: AM 09:07:03 Humidity: 55 %



Condition: -11.89dBm Horizontal
 EUT: Sweep Time: 2.32ms Att.: 20dB
 Model: RBW: 100 KHz VBW: 300 KHz
 Test Mode:
 Note: FCC-Bluetooth Channel 00-Bandedge (Fixed)

No.	Frequency(MHz)	Level(dBm)
1	2399.96000	-52.97
2	2401.84000	8.11

File: CISCO Data: #12 Date: 2011/3/14 Temperature: 15
 Time: AM 09:06:21 Humidity: 55 %



Condition: -13.86dBm Horizontal
 EUT: Sweep Time: 2386.4ms Att.: 20dB
 Model: RBW: 100 KHz VBW: 300 KHz
 Test Mode:
 Note: FCC-BT Channel 00-Conducted Spurious

No.	Frequency(MHz)	Level(dBm)
1	1736.28330	-57.46
2	2402.15000	6.14
3	24292.51670	-52.24

File: CISCO


Data: #18

Date: 2011/3/14

Temperature: 15

Time: AM 09:12:08

Humidity: 55 %



Condition: -12.17dBm

Horizontal

EUT:

Sweep Time: 2386.4ms Att.: 20dB

Model:

RBW: 100 KHz VBW: 300 KHz

Test Mode:

Note: FCC-BT Channel 39-Conducted Spurious

No.	Frequency(MHz)	Level(dBm)
1	1736.28330	-57.30
2	2443.76670	7.83
3	24334.13330	-51.63

File: CISCO


Data: #15

Date: 2011/3/14

Temperature: 15

Time: AM 09:09:22

Humidity: 55 %



Condition: -14.49dBm

Horizontal

EUT:

Sweep Time: 2386.4ms Att.: 20dB

Model:

RBW: 100 KHz VBW: 300 KHz

Test Mode:

Note: FCC-BT Channel 78-Conducted Spurious

No.	Frequency(MHz)	Level(dBm)
1	1736.28330	-56.52
2	2485.38330	5.51
3	24292.51670	-52.01

10 NUMBER of HOPPING CHANNELS

10.1 Standard Applicable

According to 15.247(b)(1), for frequency hopping systems, operating in the 2400-2483.5MHz band employing at least 75 hopping channels

10.2 Measurement Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. The setup of the EUT as shown in figure 4. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set EUT to hopping operating mode and set spectrum analyzer maximum to measure the number of hopping channels.

10.3 Measurement EquipMent

EquipMent	Manufacturer	Model No.	Next Cal. Due
Spectrum Analyzer	Agilent	E4446A	09/26/2011

10.4 Measurement Data

Test Date : Mar. 14, 2011 Temperature : 15 Humidity : 55%

Number of hopping channels = 79 channels

Note: Please refer to page 55 to page 57 for chart.

File: CISCO


Data: #26

Date: 2011/3/14

Temperature: 15

Time: AM 09:18:48

Humidity: 55 %



Condition:

Horizontal

EUT:

Sweep Time: 1ms Att.: 20dB

Model:

RBW: 300 KHz VBW: 300 KHz

Test Mode:

Note:

FCC-Bluetooth Number of Hopping Channels -Part1

File: CISCO


Data: #27

Date: 2011/3/14

Temperature: 15

Time: AM 09:20:44

Humidity: 55 %



Condition:

Horizontal

EUT:

Sweep Time: 1ms Att.: 20dB

Model:

RBW: 300 KHz VBW: 300 KHz

Test Mode:

Note:

FCC-Bluetooth Number of Hopping Channels -Part2

File: CISCO


Data: #28

Date: 2011/3/14

Temperature: 15

Time: AM 09:22:30

Humidity: 55 %



Condition:

Horizontal

EUT:

Sweep Time: 1ms Att.: 20dB

Model:

RBW: 300 KHz VBW: 300 KHz

Test Mode:

Note:

FCC-Bluetooth Number of Hopping Channels -Part3

11 HOPPING CHANNEL CARRIER FREQUENCY SEPARATED

11.1 Standard Applicable

According to 15.247(a)(1), the frequency hopping system shall have hopping channel carrier frequencies separated by minimum of 25kHz or the 20dB bandwidth of hopping channel, whichever is greater.

Alternatively, frequency hopping systems operating in the 2400 – 2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125mW.

11.2 Measurement Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. The setup of the EUT as shown in figure 4. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any measurement frequency within its operating range and make sure the instrument is operated in its linear range.
3. Set spectrum analyzer maximum hold to measure channel carrier frequency , then adjust channel carrier frequency to adjacent channel.
4. Repeat above procedure until all measured frequencies were complete.

11.3 Measurement EquipMent

EquipMent	Manufacturer	Model No.	Next Cal. Due
Spectrum Analyzer	Agilent	E4446A	09/26/2011

11.4 Measurement Data

Test Date : Mar. 14, 2011

Temperature : 15

Humidity : 55%

Channel	Frequency (MHz)	Hopping Channel Carrier Frequency Separated (MHz)	Chart
39	2441	1.045	Page 60

Note: 1. Please refer to page 60 for chart.

2. CH Low, CH Mid and CH High have the same test result. Only Mid test result showed in the test report.

File: CISCO


Data: #25

Date: 2011/3/14

Temperature: 15

Time: AM 09:16:50

Humidity: 55 %



Condition:

Horizontal

EUT:

Sweep Time: 3.2ms Att.: 20dB

Model:

RBW: 30 KHz VBW: 100 KHz

Test Mode:

Note: FCC-Bluetooth Carrier Frequency Separation

No.	Frequency(MHz)	Level(dBm)
1	2440.97500	5.25
2	2442.02000	5.50

No.	Frequency(MHz)	Level(dB)
1	mk2-mk1 1.045	0.25

12 Dwell Time

12.1 Standard Applicable

According to 15.247(a)(1)(iii), frequency hopping system in the 2400-2483.5MHz band employing at least 15 non-overlapping channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 second multiplied by the number of hopping channels employed.

12.2 Measurement Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. The setup of the EUT as shown in figure 4.

12.3 Measurement EquipMent

EquipMent	Manufacturer	Model No.	Next Cal. Due
Spectrum Analyzer	Agilent	E4446A	09/26/2011

12.4 Measurement Data

Test Date : Mar. 14, 2011 Temperature : 15 Humidity : 55%

12.4.1 DH1

Test period=0.4(second/channel)× 79 channel=31.6sec
2402MHz dwell time= 383.3 us× 340 = 130.32ms

Note: Please refer to page 62 to page 63 for chart.

File: CISCO


Data: #20

Date: 2011/3/14

Temperature: 15

Time: AM 09:13:28

Humidity: 55 %



Condition: -2.06dBm

Horizontal

EUT:

Sweep Time: 1ms Att.: 20dB

Model:

RBW: 1000 KHz VBW: 1000 KHz

Test Mode:

Note: DH1 pulse width

No.	Sweep time(ms)	Level(dBm)
1	0.1967	-28.90
2	0.4450	7.94
3	0.5800	-3.56

No.		Time(ms)	Level(dB)
1	mk3-mk1	0.3833	25.34

File: CISCO


Data: #19

Date: 2011/3/14

Temperature: 15

Time: AM 09:13:05

Humidity: 55 %



Condition:

Horizontal

EUT:

Sweep Time: 3300ms Att.: 20dB

Model:

RBW: 1000 KHz VBW: 1000 KHz

Test Mode:


Note: DH1 Hops per 3.16 seconds

12.4.2 DH3

Test period=0.4(second/channel)×79 channel=31.6sec
2441MHz dwell time= 1.645 ms×150 = 246.75 ms

Note: Please refer to page 65 to page 66 for chart.

File: CISCO Data: #22 Date: 2011/3/14 Temperature: 15
 Time: AM 09:14:31 Humidity: 55 %



Condition: -10.53dBm Horizontal
 EUT: Sweep Time: 3ms Att.: 20dB
 Model: RBW: 1000 KHz VBW: 1000 KHz
 Test Mode:
 Note: DH3 pusle width

No.	Sweep time(ms)	Level(dBm)
1	0.7900	-41.62
2	2.3950	-0.53
3	2.4350	-55.89

No.	Time(ms)	Level(dB)
1	mk3-mk1	-14.27

File: CISCO


Data: #21

Date: 2011/3/14

Temperature: 15

Time: AM 09:14:05

Humidity: 55 %



Condition:

Horizontal

EUT:

Sweep Time: 3300ms Att.: 20dB

Model:

RBW: 1000 KHz VBW: 1000 KHz

Test Mode:

Note: DH3 Hops per 3.16 seconds

12.4.3 DH5

Test period=0.4(second/channel)×79 channel=31.6sec
2480MHz dwell time= 2.9 ms×90 = 261 ms

Note: Please refer to page 68 to page 69 for chart.

File: CISCO Data: #24 Date: 2011/3/14 Temperature: 15
 Time: AM 09:15:45 Humidity: 55 %



Condition: -10.54dBm Horizontal
 EUT: Sweep Time: 5ms Att.: 20dB
 Model: RBW: 1000 KHz VBW: 1000 KHz
 Test Mode:
 Note: DH5 pulse width

No.	Sweep time(ms)	Level(dBm)
1	0.7750	-35.88
2	1.3583	-0.54
3	3.6750	-57.74

No.		Time(ms)	Level(dB)
1	mk3-mk1	2.9	-21.86

File: CISCO


Data: #23

Date: 2011/3/14

Temperature: 15

Time: AM 09:15:22

Humidity: 55 %



Condition:

Horizontal

EUT:

Sweep Time: 3300ms Att.: 20dB

Model:

RBW: 1000 KHz VBW: 1000 KHz

Test Mode:

Note:

DH5 Hops per 3.16 seconds