



Test report No. : 4789166774-US-R2-V0
Page : 1 of 11
Issued date : Apr. 8, 2020
FCC ID : VGY2765

Maximum Permissible Exposure Report

Product : DSL Router

Model Name : Vigor2765Vac

Series Model : Vigor2765ac, Vigor2766ac, Vigor2766Vac, Vigor2135ac, Vigor2135Vac, Vigor2135Fac, Vigor2135FVac, Vigor2125ac, Vigor2125Vac, Vigor2125Fac, Vigor2125FVac

FCC ID : VGY2765

Test Regulation : 47 CFR FCC Part 2.1091

Received Date : Sep. 11, 2019

Issued Date : Apr. 8, 2020

Applicant : DrayTek Corp.
No.26 Fu Shing Rd., HuKou County, Hsin-Chu Industrial Park,
Hsin-Chu, Taiwan 303 R.O.C

Issued By : Underwriters Laboratories Taiwan Co., Ltd.
Building B and Building E, No. 372-7, Sec. 4, Zhongxing Rd.,
Zhudong Township, Hsinchu County, Taiwan



The results reported herein have been performed in accordance with the laboratory's terms of accreditation. This report shall not be reproduced except in full without the written approval of the Laboratory. The results in this report are responsible of the test sample(s) provided by the client only and are not to be used to indicate applicability to other similar products.

Underwriters Laboratories Taiwan Co., Ltd.

Building B and Building E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan
Telephone : +886-2-7737-3000
Facsimile (FAX) : +886-3-583-7948

Doc No: 17-EM-F0864 / 3.0



REVISION HISTORY

Original Test Report No.: 4789166774-US-R2-V0

Rev.	Test report No.	Date	Page revised	Contents
Original	4789166774-US-R2-V0	Mar. 30, 2020	-	Initial issue
-	4789166774-US-R2-V0	Apr. 8, 2020	P.1, P.4, P.8, P.9	Delete the blank space between Vigor and number for all models



Table Of Contents

1. Attestation of Test Results.....	4
2. Test Methodology and Reference Procedures	5
3. Facilities and Accreditation	5
4. Equipment Under Test	6
4.1. Description of EUT.....	6
4.2. Description Of Available Antennas	9
5. Requirement	10
6. Radio Frequency Radiation Exposure Evaluation	11

Underwriters Laboratories Taiwan Co., Ltd.

Building B and Building E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan
Telephone :+886-2-7737-3000
Facsimile (FAX) :+886-3-583-7948



1. Attestation of Test Results

APPLICANT: DrayTek Corp.
 No.26 Fu Shing Rd., HuKou County, Hsin-Chu Industrial Park, Hsin-Chu, Taiwan 303 R.O.C

MANUFACTURER DrayTek Corp.
 No.26 Fu Shing Rd., HuKou County, Hsin-Chu Industrial Park, Hsin-Chu, Taiwan 303 R.O.C

EUT DESCRIPTION: DSL Router

BRAND: DrayTek

MODEL: Vigor2765Vac

SERIES MODEL: Vigor2765ac, Vigor2766ac, Vigor2766Vac, Vigor2135ac, Vigor2135Vac, Vigor2135Fac, Vigor2135FVac, Vigor2125ac, Vigor2125Vac, Vigor2125Fac, Vigor2125FVac

SAMPLE STAGE: Engineering sample

APPLICABLE STANDARDS	
STANDARD	Test Results
47 CFR FCC PART 2.1091	PASS

Underwriters Laboratories Taiwan Co., Ltd. tested the above equipment in accordance with the requirements set forth in the above standards. All indications of Pass/Fail in this report are opinions expressed by Underwriters Laboratories Taiwan Co., Ltd. based on interpretations and/or observations of test results. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

Note: The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. This document may not be altered or revised in any way unless done so by Underwriters Laboratories Taiwan Co., Ltd. and all revisions are duly noted in the revisions section. Any alteration of this document not carried out by Underwriters Laboratories Taiwan Co., Ltd. will constitute fraud and shall nullify the document. This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, any agency of the Federal Government, or any agency of any government.

Prepared By:

Cindy Hsin
 Project Handler

Date : Apr. 8, 2020

Approved and Authorized By:

Howard Kao Date : Apr. 8, 2020
 Project Engineer

Underwriters Laboratories Taiwan Co., Ltd.

Building B and Building E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan
 Telephone :+886-2-7737-3000
 Facsimile (FAX) :+886-3-583-7948



2. Test Methodology and Reference Procedures

The tests documented in this report were performed in accordance with KDB 447498 D01 General RF Exposure Guidance v06.

3. Facilities and Accreditation

Test Location	Underwriters Laboratories Taiwan Co., Ltd.
Address	Building B and Building E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan
Accreditation Certificate	Underwriters Laboratories Taiwan Co., Ltd. is accredited by TAF, Laboratory Code 3398. The full scope of accreditation can be viewed at http://accreditation.taftw.org.tw/taf/public/basic/viewApplyItems.action?unitNo=3398

Underwriters Laboratories Taiwan Co., Ltd.

Building B and Building E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan
Telephone :+886-2-7737-3000
Facsimile (FAX) :+886-3-583-7948



4. Equipment Under Test

4.1. Description of EUT

Product Name	DSL Router	
Brand Name	DrayTek	
Model Name	Vigor2765Vac	
Series Model	Vigor2765ac, Vigor2766ac, Vigor2766Vac, Vigor2135ac, Vigor2135Vac, Vigor2135Fac, Vigor2135FVac, Vigor2125ac, Vigor2125Vac, Vigor2125Fac, Vigor2125FVac	
S/N	191001DAA185F58	
Operating Frequency	WLAN	2.4GHz: 2412MHz ~ 2462MHz 5GHz: 5180MHz ~ 5240MHz 5745MHz ~ 5825MHz
Modulation	WLAN	CCK, DQPSK, DBPSK for DSSS 64QAM, 16QAM, QPSK, BPSK for OFDM 256QAM, 64QAM, 16QAM, QPSK, BPSK
Number of Channel	WLAN	2.4GHz: 802.11b, 802.11g, 802.11n (HT20): 11 802.11n (HT40): 7 5.18 ~ 5.24GHz: 802.11a, 802.11n (HT20), 802.11ac (VHT20): 4 802.11n (HT40), 802.11ac (VHT40): 2 802.11ac (HT80): 1 5.745 ~ 5.825GHz: 802.11a, 802.11n (HT20), 802.11ac (VHT20): 5 802.11n (HT40), 802.11ac (VHT40): 2 802.11ac (VHT80): 1
Normal Voltage	12Vdc from adapter	

Underwriters Laboratories Taiwan Co., Ltd.

Building B and Building E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan
Telephone : +886-2-7737-3000
Facsimile (FAX) : +886-3-583-7948



Note:

1. The models difference table as below:

Main Model	Function				
	DSL	gfast	FXS	Eth-RJ45 WAN	Eth-SFP WAN
Vigor2765Vac	V	-	V	-	-
Series Model	Function difference				
	DSL	gfast	FXS	Eth-RJ45 WAN	Eth-SFP WAN
Vigor2765ac	V	-	-	-	-
Vigor2766ac	V	V	-	-	-
Vigor2766Vac	V	V	V	-	-
Vigor2135ac	-	-	-	V	-
Vigor2135Vac	-	-	V	V	-
Vigor2135Fac	-	-	-	-	V
Vigor2135FVac	-	-	V	-	V
Vigor2125ac	-	-	-	V	-
Vigor2125Vac	-	-	V	V	-
Vigor2125Fac	-	-	-	-	V
Vigor2125FVac	-	-	V	-	V

- The above models are declared for market purpose by the manufacturer, the difference between the main model and the series model is the combination of hardware design and appearance, there are no changes in RF-related parts, which will not affect RF characteristic.

2. The EUT provides two completed transmitters and two receivers.

Modulation Mode	Tx,Rx Function
802.11a	2TX,2RX
802.11b	2TX,2RX
802.11g	2TX,2RX
802.11n (HT20)	2TX,2RX
802.11n (HT40)	2TX,2RX
802.11ac (VHT20)	2TX,2RX
802.11ac (VHT40)	2TX,2RX
802.11ac (VHT80)	2TX,2RX

Underwriters Laboratories Taiwan Co., Ltd.

Building B and Building E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan
Telephone :+886-2-7737-3000
Facsimile (FAX) :+886-3-583-7948



3. The EUT contains following accessory devices

Product	Brand	Model	Description
AC Adapter	Channel Well Technology	2ABL024F US	Input: 100-240Vac, 0.8A, Output: 12Vdc, 2A Length: 1.5 m, non-shielded cable w/o ferrite core
RJ-45 Cable	Tung-Li	5U422-20	Length: 3 m, non-shielded cable
RJ-11 Cable	N/A	N/A	Length: 1.8 m, non-shielded cable, 6P4C
RJ-11 to RJ-45 Cable	N/A	N/A	Length: 2.2 m, non-shielded cable, 6P4C
RJ-45 to RJ-45 Cable	N/A	N/A	Length: 2.2 m, non-shielded cable, 6P4C

4. The above EUT information is declared by manufacturer and for more detailed features description, please refer the manufacturer's or user's manual.

Underwriters Laboratories Taiwan Co., Ltd.

Building B and Building E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan
Telephone :+886-2-7737-3000
Facsimile (FAX) :+886-3-583-7948



4.2. Description Of Available Antennas

Antenna	Brand Name	Model Name	Antenna Type	Antenna Gain(dBi)
WLAN 2.4GHz	Walsin	RFDPA131300SBLB805	Dipole	2.18
	Walsin	RFDPA131300SBLB805	Dipole	2.18

Antenna	Brand Name	Model Name	Antenna Type	Antenna Gain(dBi)
WLAN 5GHz	Walsin	RFDPA131300SBLB805	Dipole	4.45
	Walsin	RFDPA131300SBLB805	Dipole	4.45

Note: The above antenna information was provided from customer and for more detailed features description, please refer the manufacturer's specification or user's manual.

Underwriters Laboratories Taiwan Co., Ltd.

Building B and Building E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan
Telephone :+886-2-7737-3000
Facsimile (FAX) :+886-3-583-7948



5. Requirement

Limits for General Population/Uncontrolled Exposure

Limits for General Population/Uncontrolled Exposure				
Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-1.34	614	1.63	*100	30
1.34-30	824/f	2.19/f	*180/f ²	30
30-300	27.5	0.073	0.2	30
300-1500	--	--	f/1500	30
1500-100,000	--	--	1.0	30

Note 1: f = frequency in MHz, * means Plane-wave equivalent power density

Note 2: General population/uncontrolled exposures apply in situations in which the general public may be exposed, or in which persons that are exposed as a consequence of their employment may not be fully aware of the potential for exposure or cannot exercise control over their exposure.

Power Density (S) is calculated by the following formula:

$$S = (P * G) / 4\pi R^2$$

where: S = power density (in appropriate units, e.g. mW/ cm²)

P = power input to the antenna (in appropriate units, e.g., mW)

G = power gain of the antenna in the direction of interest relative to an isotropic radiator R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

Underwriters Laboratories Taiwan Co., Ltd.

Building B and Building E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan

Telephone : +886-2-7737-3000

Facsimile (FAX) : +886-3-583-7948



6. Radio Frequency Radiation Exposure Evaluation

Non-Beamforming Mode

WLAN 2.4GHz

WLAN 2.4GHz						
Evaluation Frequency	Max. Average Power	Directional Gain	Max. EIRP	Max. EIRP	Power density @ 20 cm	Limit
(MHz)	(dBm)	(dBi)	(dBm)	(mW)	(mW/cm ²)	(mW/cm ²)
2412 ~ 2462	24.86	5.19	30.05	1011.579	0.201	1

WLAN 5GHz

WLAN 5GHz						
Evaluation Frequency	Max. Average Power	Directional Gain	Max. EIRP	Max. EIRP	Power density @ 20 cm	Limit
(MHz)	(dBm)	(dBi)	(dBm)	(mW)	(mW/cm ²)	(mW/cm ²)
5180 ~ 5240	25.49	7.46	32.95	1972.423	0.392	1
5745 ~ 5825	25.16	7.46	32.62	1828.100	0.364	1

Beamforming Mode

WLAN 5GHz

WLAN 5GHz						
Evaluation Frequency	Max. Average Power	Directional Gain	Max. EIRP	Max. EIRP	Power density @ 20 cm	Limit
(MHz)	(dBm)	(dBi)	(dBm)	(mW)	(mW/cm ²)	(mW/cm ²)
5180 ~ 5240	24.65	7.46	32.11	1625.549	0.323	1
5745 ~ 5825	24.72	7.46	32.18	1651.962	0.329	1

Note:

1. Max. EIRP (dBm) = Max. Average power (dBm) + Antenna Gain (dBi)
2. Max. EIRP (mW) = $10^{(\text{Max. EIRP (dBm)} / 10)}$
3. Power density (mW/cm²) = Max. EIRP (mW) / [$4 \times \pi \times (\text{calculated distance})^2$], the calculated distance is 20 cm.

Conclusion:

The formula of calculated the MPE is:

$$\text{CPD1} / \text{LPD1} + \text{CPD2} / \text{LPD2} + \dots \text{etc.} < 1$$

CPD = Calculation power density

LPD = Limit of power density

WLAN 2.4GHz + WLAN 5GHz=0.201+0.392=0.593, therefore the maximum calculations of above situations are less than the “1” limit.

According to 47 CFR §2.1091, the RF exposure analysis concludes that the RF Exposure is FCC compliant.

Underwriters Laboratories Taiwan Co., Ltd.

Building B and Building E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan

Telephone :+886-2-7737-3000

Facsimile (FAX) :+886-3-583-7948

Doc No: 17-EM-F0864 / 3.0