

**IEEE C95.1
KDB 447498 D03
47 C.F.R. Part 1, Subpart I, Section 1.1310
47 C.F.R. Part 2, Subpart J, Section 2.1091**

RF EXPOSURE REPORT

For

VigorAP 902 Dual Band 11ac AP

Model: VigorAP 902

Trade Name: DrayTek

Issued to

DrayTek Corp.
No.26 Fu Shing Rd., HuKou County, Hsinchu Industrial Park,
Hsinchu, Taiwan 303 R.O.C

Issued by

Compliance Certification Services Inc.
No.11, Wugong 6th Rd., Wugu Dist.,
New Taipei City 24891, Taiwan. (R.O.C.)
<http://www.ccsrf.com>
service@ccsrf.com
Issued Date: November 11, 2015



Revision History

Rev.	Issue Date	Revisions	Effect Page	Revised By
00	2015/11/11	Initial Issue	ALL	Kelly Cheng

TABLE OF CONTENTS

1. LIMIT	4
2. EUT SPECIFICATION.....	4
3. TEST RESULTS.....	5
4. MAXIMUM PERMISSIBLE EXPOSURE.....	6

1. LIMIT

According to §15.247(i), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the Commission's guidelines. See § 1.1307(b)(1) of this chapter.

2. EUT SPECIFICATION

EUT	VigorAP 902 Dual Band 11ac AP
Model	VigorAP 902
Frequency band (Operating)	<input checked="" type="checkbox"/> 802.11b/g/n HT20: 2.412GHz ~ 2.462GHz 802.11n HT40: 2.422GHz ~ 2.452GHz 802.11a/n HT20: 5.180GHz ~ 5.320GHz / 5.745 ~ 5.825GHz 802.11n HT40: 5.190GHz ~ 5.310GHz / 5.755 ~ 5.795GHz 802.11ac VHT80: 5.210GHz ~ 5.290GHz / 5.775GHz <input type="checkbox"/> Others
Device category	<input type="checkbox"/> Portable (<20cm separation) <input checked="" type="checkbox"/> Mobile (>20cm separation) <input type="checkbox"/> Others
Exposure classification	<input type="checkbox"/> Occupational/Controlled exposure (S = 5mW/cm ²) <input checked="" type="checkbox"/> General Population/Uncontrolled exposure (S=1mW/cm ²)
Antenna Specification	5GHz: Antenna Gain : 3.88 dBi (Numeric gain 2.44) 2.4GHz: Antenna Gain : 1.81 dBi (Numeric gain 1.52)
Maximum Average output power	IEEE 802.11b Mode: 18.66 dBm (73.451 mW) IEEE 802.11g Mode: 20.90 dBm (123.027 mW) IEEE 802.11n HT 20 Mode: 21.61 dBm (144.877 mW) IEEE 802.11n HT 40 Mode: 16.37 dBm (43.351 mW) IEEE 802.11a Mode: 20.42 dBm (110.154 mW) IEEE 802.11n HT20 Mode: 23.12 dBm (205.116 mW) IEEE 802.11n HT40 Mode: 22.66 dBm (184.502 mW) IEEE 802.11ac VHT80 Mode: 23.45 dBm (221.309 mW)
Maximum Tune up Power	IEEE 802.11b Mode: 19.00 dBm (79.433 mW) IEEE 802.11g Mode: 21.00 dBm (125.893 mW) IEEE 802.11n HT 20 Mode: 21.80 dBm (151.356 mW) IEEE 802.11n HT 40 Mode: 17.00 dBm (50.119 mW) IEEE 802.11a Mode: 20.60 dBm (114.815 mW) IEEE 802.11n HT20 Mode: 23.50 dBm (223.872 mW) IEEE 802.11n HT40 Mode: 23.00 dBm (199.526 mW) IEEE 802.11ac VHT80 Mode: 23.60 dBm (229.087 mW)
Evaluation applied	<input checked="" type="checkbox"/> MPE Evaluation* <input type="checkbox"/> SAR Evaluation <input type="checkbox"/> N/A

3. TEST RESULTS

No non-compliance noted.

Calculation

Given $E = \frac{\sqrt{30 \times P \times G}}{d}$ & $S = \frac{E^2}{377}$

Where $E =$ Field strength in Volts / meter

$P =$ Power in Watts

$G =$ Numeric antenna gain

$d =$ Distance in meters

$S =$ Power density in milliwatts / square centimeter

Combining equations and re-arranging the terms to express the distance as a function of the remaining variables yields:

$$S = \frac{30 \times P \times G}{377d^2}$$

Changing to units of mW and cm, using:

$$P (mW) = P (W) / 1000 \text{ and}$$

$$d (cm) = d(m) / 100$$

Yields

$$S = \frac{30 \times (P/1000) \times G}{377 \times (d/100)^2} = 0.0796 \times \frac{P \times G}{d^2} \quad \text{Equation 1}$$

Where $d =$ Distance in cm

$P =$ Power in mW

$G =$ Numeric antenna gain

$S =$ Power density in mW / cm²

4. MAXIMUM PERMISSIBLE EXPOSURE

Substituting the MPE safe distance using $d = 20$ cm into Equation 1:

$$S = 0.000199 \times P \times G$$

Where $P =$ Power in mW

$G =$ Numeric antenna gain

$S =$ Power density in mW / cm²

IEEE 802.11b mode:

Ch.	Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm ²	Limit (mW/cm2)
1	2412	79.433	1.52	20	0.0240	1

IEEE 802.11g mode:

Ch.	Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm ²	Limit (mW/cm2)
6	2437	125.893	1.52	20	0.0381	1

IEEE 802.11n HT20 mode:

Ch.	Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm ²	Limit (mW/cm2)
6	2437	151.356	1.52	20	0.0458	1

IEEE 802.11n HT40 mode:

Ch.	Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm ²	Limit (mW/cm2)
6	2437	50.119	1.52	20	0.0152	1

IEEE 802.11a mode:

Ch.	Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm ²	Limit (mW/cm2)
165	5825	114.815	2.44	20	0.0557	1

IEEE 802.11n HT20 mode:

Ch.	Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm ²	Limit (mW/cm2)
157	5785	223.872	2.44	20	0.1087	1

IEEE 802.11n HT40 mode:

Ch.	Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm ²	Limit (mW/cm2)
159	5795	199.526	2.44	20	0.0969	1

IEEE 802.11acVHT80:mode:

Ch.	Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm ²	Limit (mW/cm2)
155	5775	229.087	2.44	20	0.1112	1