

### Standard Applicable:

According to §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

This is a Portable device with its physical nature to be used nearby, the distance between radiating structure and human is less than 20 cm.

As per KDB 447498 D01, The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq 50$  mm are determined by:

$$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})]^* [\sqrt{f(\text{GHz})}] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR, where}$$

f (GHz) is the RF channel transmit frequency in GHz  
 Power and distance are rounded to the nearest mW and mm before calculation  
 The result is rounded to one decimal place for comparison

### Measurement Result:

This is a portable device and the Max tune up power is (**3.55 mW**) lower than the threshold given and derived as above, where

$$= 3.55 \text{ (mW)} / 5 \text{ (mm)} * \sqrt{2.402 \text{ (GHz)}} = 1.10 < 3.00$$

As the result of calculation result indicates, the RF exposure generating from given transmitter (transmitter employed digital modulation) can be excluded from SAR measurement, and is deemed compliant with RF exposure as per FCC.

Type of Modulation	Frequency [MHz]	Output Power [dBm]	Target power [dBm]	Allowed tolerance [dB]	Max tune up power [dBm]	Max tune up power [mW]	Separation distance [mm]	RF exposure	Limit
BDR	2 402	5.14	3.50	± 2.00	5.50	3.55	5	1.10	3.00
	2 441	4.24	2.50	± 2.00	4.50	2.82	5	0.88	3.00
	2 480	3.60	2.00	± 2.00	4.00	2.51	5	0.79	3.00
EDR	2 402	2.81	1.00	± 2.00	3.00	2.00	5	0.62	3.00
	2 441	1.46	0.00	± 2.00	2.00	1.58	5	0.49	3.00
	2 480	0.58	-1.00	± 2.00	1.00	1.26	5	0.40	3.00