



# RF EXPOSURE REPORT

**REPORT NO.:** SA960709L12

**MODEL NO.:** SR297 SPEAKER, SR298  
SPEAKER, DS062R, DS063R

**ACCORDING:** FCC Guidelines for Human Exposure  
IEEE C95.1

**APPLICANT:** Acoustic Arc International Ltd.

**ADDRESS:** 802 causeway Bay Comm, Building, 1-5 Sugar  
Street, Hong Kong.

**ISSUED BY:** Advance Data Technology Corporation

**LAB ADDRESS:** No. 47, 14<sup>th</sup> Ling, Chia Pau Tsuen, Lin Kou  
Hsiang 244, Taipei Hsien, Taiwan, R.O.C.

**TEST LOCATION:** No. 19, Hwa Ya 2<sup>nd</sup> Rd., Wen Hwa Tsuen, Kwei  
Shan Hsiang, Taoyuan Hsien 333, Taiwan,  
R.O.C.



No evaluation required if power is below this threshold:

F (MHz)		mW
Low	2.40435	23.95
High	2.47194	

Maximum measured transmitter power:

Pout (dBm)		Pout (mW)
Conducted Power	7.58	5.73
EIRP Power	7.58	5.73

**\*\*NOTE:** The antenna is Chip antenna with 0dBi gain.

Threshold for no SAR evaluation is 23.95mW.

Transmitter power is 5.73mW.

Conclusion: No SAR evaluation required since Transmitter Power is below FCC threshold.