

<b>Prüfbericht-Nr.:</b> <i>Test report no.:</i>	<b>CN24UHMF 002</b>	<b>Auftrags-Nr.:</b> <i>Order no.:</i>	168490934	Seite 1 von 28 Page 1 of 28
<b>Kunden-Referenz-Nr.:</b> <i>Client reference no.:</i>	N/A	<b>Auftragsdatum:</b> <i>Order date:</i>	2024-06-26	
<b>Auftraggeber:</b> <i>Client:</i>	<b>BlueAnt Wireless</b> Suite 6, 861 Doncaster Road, Doncaster East, Victoria 3109, Australia			
<b>Prüfgegenstand:</b> <i>Test item:</i>	Bluetooth Speaker			
<b>Bezeichnung / Typ-Nr.:</b> <i>Identification / Type no.:</i>	X5i (Trademark: <b>BlueAnt</b> )			
<b>Auftrags-Inhalt:</b> <i>Order content:</i>	Test Report			
<b>Prüfgrundlage:</b> <i>Test specification:</i>	CFR47 FCC Part 15: Subpart C Section 15.247			
<b>Wareneingangsdatum:</b> <i>Date of sample receipt:</i>	2024-06-27	Please refer to Photo Document		
<b>Prüfmuster-Nr.:</b> <i>Test sample no.:</i>	A003762173-002 A003762173-003			
<b>Prüfzeitraum:</b> <i>Testing period:</i>	2024-07-02 - 2024-07-20			
<b>Ort der Prüfung:</b> <i>Place of testing:</i>	(refer to 2.1)			
<b>Prüflaboratorium:</b> <i>Testing laboratory:</i>	TÜV Rheinland (Shenzhen) Co., Ltd.			
<b>Prüfergebnis*:</b> <i>Test result*:</i>	Pass			
<b>geprüft von:</b> <i>tested by:</i>	<input checked="" type="checkbox"/> <u>Hardy Suo</u>	<b>genehmigt von:</b> <i>authorized by:</i>	<input checked="" type="checkbox"/> <u>Jonathan Li</u>	
<b>Datum:</b> <i>Date:</i>	2024-07-26	<b>Ausstellungsdatum:</b> <i>Issue date:</i>	2024-07-26	
<b>Stellung / Position:</b>	Sachverständige(r)/Expert	<b>Stellung / Position:</b>	Sachverständige(r)/Expert	
<b>Sonstiges /</b> <i>Other:</i>	FCC ID: VHF-BLUEANT-X5I			
<b>Zustand des Prüfgegenstandes bei Anlieferung:</b> <i>Condition of the test item at delivery:</i>	Prüfmuster vollständig und unbeschädigt <i>Test item complete and undamaged</i>			
* Legende:	P(ass) = entspricht o.g. Prüfgrundlage(n)	F(ail) = entspricht nicht o.g. Prüfgrundlage(n)	N/A = nicht anwendbar	N/T = nicht getestet
* Legend:	P(ass) = passed a.m. test specification(s)	F(ail) = failed a.m. test specification(s)	N/A = not applicable	N/T = not tested
<b>Dieser Prüfbericht bezieht sich nur auf das o.g. Prüfmuster und darf ohne Genehmigung der Prüfstelle nicht auszugsweise vervielfältigt werden. Dieser Bericht berechtigt nicht zur Verwendung eines Prüfzeichens.</b> <i>This test report only relates to the above mentioned test sample. Without permission of the test center this test report is not permitted to be duplicated in extracts. This test report does not entitle to carry any test mark.</i>				

Prüfbericht-Nr.: CN24UHMF 002  
Test report no.:

Seite 2 von 28  
Page 2 of 28

**Anmerkungen**  
*Remarks*

1	<p>Alle eingesetzten Prüfmittel waren zum angegebenen Prüfzeitraum gemäß eines festgelegten Kalibrierungsprogramms unseres Prüfhauses kalibriert. Sie entsprechen den in den Prüfprogrammen hinterlegten Anforderungen. Die Rückverfolgbarkeit der eingesetzten Prüfmittel ist durch die Einhaltung der Regelungen unseres Managementsystems gegeben. Detaillierte Informationen bezüglich Prüfkonditionen, Prüfequipment und Messunsicherheiten sind im Prüflabor vorhanden und können auf Wunsch bereitgestellt werden.</p> <p><i>The equipment used during the specified testing period was calibrated according to our test laboratory calibration program. The equipment fulfils the requirements included in the relevant standards. The traceability of the test equipment used is ensured by compliance with the regulations of our management system. Detailed information regarding test conditions, equipment and measurement uncertainty is available in the test laboratory and could be provided on request.</i></p>
2	<p>Wie vertraglich vereinbart, wurde dieses Dokument nur digital unterzeichnet. Der TÜV Rheinland hat nicht überprüft, welche rechtlichen oder sonstigen diesbezüglichen Anforderungen für dieses Dokument gelten. Diese Überprüfung liegt in der Verantwortung des Benutzers dieses Dokuments. Auf Verlangen des Kunden kann der TÜV Rheinland die Gültigkeit der digitalen Signatur durch ein gesondertes Dokument bestätigen. Diese Anfrage ist an unseren Vertrieb zu richten. Eine Umweltgebühr für einen solchen zusätzlichen Service wird erhoben. Informationen zur Verifizierung der Authentizität unserer Dokumente erhalten Sie auf folgender Webseite: <a href="http://go.tuv.com/digital-signature">go.tuv.com/digital-signature</a></p> <p><i>As contractually agreed, this document has been signed digitally only. TUV Rheinland has not verified and unable to verify which legal or other pertaining requirements are applicable for this document. Such verification is within the responsibility of the user of this document. Upon request by its client, TUV Rheinland can confirm the validity of the digital signature by a separate document. Such request shall be addressed to our Sales department. An environmental fee for such additional service will be charged. For information on verifying the authenticity of our documents, please visit the following website: <a href="http://go.tuv.com/digital-signature">go.tuv.com/digital-signature</a></i></p>
3	<p>Prüfklausel mit der Note * wurden an qualifizierte Unterauftragnehmer vergeben und sind unter der jeweiligen Prüfklausel des Berichts beschrieben. Abweichungen von Prüfspezifikation(en) oder Kundenanforderungen sind in der jeweiligen Prüfklausel im Bericht aufgeführt.</p> <p><i>Test clauses with remark of * are subcontracted to qualified subcontractors and described under the respective test clause in the report. Deviations of testing specification(s) or customer requirements are listed in specific test clause in the report.</i></p>
4	<p>Die Entscheidungsregel für Konformitätserklärungen basierend auf numerischen Messergebnissen in diesem Prüfbericht basiert auf der "Null-Grenzwert-Regel" und der "Einfachen Akzeptanz" gemäß ILAC G8:2019 und IEC Guide 115:2021, es sei denn, in der auf Seite 1 dieses Berichts genannten angewandten Norm ist etwas anderes festgelegt oder vom Kunden gewünscht. Dies bedeutet, dass die Messunsicherheit nicht berücksichtigt wird und daher auch nicht im Prüfbericht angegeben wird. Zu weiteren Informationen bezüglich des Risikos durch diese Entscheidungsregel siehe ILAC G8:2019.</p> <p><i>The decision rule for statements of conformity, based on numerical measurement results, in this test report is based on the "Zero Guard Band Rule" and "Simple Acceptance" in accordance with ILAC G8:2019 and IEC Guide 115:2021, unless otherwise specified in the applied standard mentioned on Page 1 of this report or requested by the customer. This means that measurement uncertainty is not taken in account and hence also not declared in the test report. For additional information to the resulting risk based of this decision rule please refer to ILAC G8:2019.</i></p>

## Test Summary

**5.1.1 ANTENNA REQUIREMENT***RESULT: Pass***5.1.2 MAXIMUM PEAK CONDUCTED OUTPUT POWER***RESULT: Pass***5.1.3 CONDUCTED POWER SPECTRAL DENSITY***RESULT: Pass***5.1.4 6dB BANDWIDTH***RESULT: Pass***5.1.5 99% BANDWIDTH***RESULT: Pass***5.1.6 20dB BANDWIDTH***RESULT: Pass***5.1.7 CARRIER FREQUENCY SEPARATION***RESULT: Pass***5.1.8 NUMBER OF HOPPING FREQUENCY***RESULT: Pass***5.1.9 TIME OF OCCUPANCY***RESULT: Pass***5.1.10 CONDUCTED SPURIOUS EMISSIONS MEASURED IN 100 KHz BANDWIDTH***RESULT: Pass***5.1.11 RADIATED SPURIOUS EMISSION***RESULT: Pass***5.1.12 CONDUCTED EMISSION ON AC MAINS***RESULT: Pass*

## Contents

<b>1</b>	<b>GENERAL REMARKS .....</b>	<b>5</b>
<b>1.1</b>	<b>COMPLEMENTARY MATERIALS .....</b>	<b>5</b>
<b>2</b>	<b>TEST SITES.....</b>	<b>6</b>
<b>2.1</b>	<b>TEST FACILITIES.....</b>	<b>6</b>
<b>2.2</b>	<b>LIST OF TEST AND MEASUREMENT INSTRUMENTS .....</b>	<b>6</b>
<b>2.3</b>	<b>TRACEABILITY.....</b>	<b>7</b>
<b>2.4</b>	<b>CALIBRATION .....</b>	<b>7</b>
<b>2.5</b>	<b>MEASUREMENT UNCERTAINTY .....</b>	<b>7</b>
<b>2.6</b>	<b>LOCATION OF ORIGINAL DATA .....</b>	<b>8</b>
<b>2.7</b>	<b>STATUS OF FACILITY USED FOR TESTING.....</b>	<b>8</b>
<b>3</b>	<b>GENERAL PRODUCT INFORMATION.....</b>	<b>9</b>
<b>3.1</b>	<b>PRODUCT FUNCTION AND INTENDED USE.....</b>	<b>9</b>
<b>3.2</b>	<b>RATINGS AND SYSTEM DETAILS .....</b>	<b>9</b>
<b>3.3</b>	<b>INDEPENDENT OPERATION MODES .....</b>	<b>11</b>
<b>3.4</b>	<b>NOISE GENERATING AND NOISE SUPPRESSING PARTS.....</b>	<b>11</b>
<b>3.5</b>	<b>SUBMITTED DOCUMENTS.....</b>	<b>11</b>
<b>4</b>	<b>TEST SET-UP AND OPERATION MODES .....</b>	<b>12</b>
<b>4.1</b>	<b>PRINCIPLE OF CONFIGURATION SELECTION.....</b>	<b>12</b>
<b>4.2</b>	<b>TEST OPERATION AND TEST SOFTWARE.....</b>	<b>12</b>
<b>4.3</b>	<b>SPECIAL ACCESSORIES AND AUXILIARY EQUIPMENT.....</b>	<b>12</b>
<b>4.4</b>	<b>COUNTERMEASURES TO ACHIEVE EMC COMPLIANCE.....</b>	<b>12</b>
<b>4.5</b>	<b>TEST SETUP DIAGRAM .....</b>	<b>13</b>
<b>5</b>	<b>TEST RESULTS.....</b>	<b>15</b>
<b>5.1</b>	<b>TRANSMITTER REQUIREMENT &amp; TEST SUITES.....</b>	<b>15</b>
<b>5.1.1</b>	<i>Antenna Requirement.....</i>	<i>15</i>
<b>5.1.2</b>	<i>Maximum Peak Conducted Output Power.....</i>	<i>16</i>
<b>5.1.3</b>	<i>Conducted Power Spectral Density.....</i>	<i>18</i>
<b>5.1.4</b>	<i>6dB Bandwidth .....</i>	<i>19</i>
<b>5.1.5</b>	<i>99% Bandwidth .....</i>	<i>20</i>
<b>5.1.6</b>	<i>20dB Bandwidth .....</i>	<i>21</i>
<b>5.1.7</b>	<i>Carrier Frequency Separation.....</i>	<i>22</i>
<b>5.1.8</b>	<i>Number of Hopping Frequency.....</i>	<i>23</i>
<b>5.1.9</b>	<i>Time of Occupancy .....</i>	<i>24</i>
<b>5.1.10</b>	<i>Conducted Spurious Emissions Measured in 100 kHz Bandwidth.....</i>	<i>25</i>
<b>5.1.11</b>	<i>Radiated Spurious Emission.....</i>	<i>26</i>
<b>5.1.12</b>	<i>Conducted Emission on AC Mains.....</i>	<i>27</i>
<b>6</b>	<b>PHOTOGRAPHS OF THE TEST SET-UP.....</b>	<b>28</b>
<b>7</b>	<b>LIST OF TABLES .....</b>	<b>28</b>

# 1 General Remarks

## 1.1 Complementary Materials

All attachments are integral parts of this test report. This applies especially to the following appendix:

Appendix A: Test Results of Bluetooth BR & EDR

Appendix B: Test Results of Bluetooth LE - Bluetooth Chip1

Appendix C: Test Results of Bluetooth LE - Bluetooth Chip2

Appendix D: Photographs of the Test Set-up

## 2 Test Sites

### 2.1 Test Facilities

**TÜV Rheinland (Shenzhen) Co., Ltd.**

No. 362 Huanguan Road Middle, Longhua District, 518110, Shenzhen, P. R. China.

FCC Accreditation Designation No.: 694916

ISED wireless device testing laboratory: 25069

**Shenzhen UnionTrust Quality and Technology Co., Ltd.**

Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China

A2LA Certificate Number: 4312.01

Remark: test Conducted Emission on AC Mains was performed at Shenzhen UnionTrust Quality and Technology Co., Ltd.

### 2.2 List of Test and Measurement Instruments

**Table 1: List of Test and Measurement Equipment**

Radio Spectrum Testing (SRD-Tonscend)						
Equip. No.	Description	Manufacturer	Model	Serial No.	Cal. Date	Cal. until
9039436	EXA Signal Analyzer, Multi-touch	Keysight	N9010B	MY60241175	22.09.2023	21.09.2024
9039437	MXG X-Series RF Vector Signal Generator	Keysight	N5182B	MY61250137	22.09.2023	21.09.2024
9039438	EXG X-Series Microwave Analog Signal Generator	Keysight	N5173B	MY61250141	22.09.2023	21.09.2024
9039439	DC Power Supply	Keysight	E3642A	MY61276100	22.09.2023	21.09.2024
9039440	Wireless Connectivity Tester	R&S	CMW270	102505	22.09.2023	21.09.2024
9039441	Power Control Unit	Tonscend	JS0806-4ADC	N/A	22.09.2023	21.09.2024
9039442	Automation Control Unit	Tonscend	JS0806-2	21C8060396	22.09.2023	21.09.2024
9039443	Test Software	Tonscend	JS1120-3	N/A	N/A	N/A
9039444	Control PC	Lenovo	TianYi510S-071MB	YLX23JMF	N/A	N/A
Unwanted Emission Testing (TS9975)						
Equip. No.	Description	Manufacturer	Model	Serial No.	Cal. Date	Cal. until
G1826021	EMI Test Receiver	R&S	ESR 7	102021	26.07.2023	25.07.2024
G1826023	Signal Analyzer	R&S	FSV 40	101439	26.07.2023	25.07.2024
G1826024	System Controller Interface	R&S	SCI-100	S10010038	N/A	N/A
G1826025	Filterbank	R&S	Wlan	100759	26.07.2023	25.07.2024
G1826026	OSP	R&S	OSP 120	102040	N/A	N/A

G1826028	Pre-amplifier	R&S	SCU08F1	08320031	26.07.2023	25.07.2024
G1826029	Amplifier	R&S	SCU-18F	180070	26.07.2023	25.07.2024
G1826030	Amplifier	R&S	SCU40A	100475	26.07.2023	25.07.2024
G1826031	Trilog Broadband Antenna (30 MHz - 7 GHz)	Schwarzbeck	VULB 9162	193	07.08.2022	06.08.2024
G1826032	Double-Ridged Antenna (1 -18 GHz)	ETS-LINDGREN	3117	00218717	07.08.2022	06.08.2024
G1826033	Wideband Ridged Horn Antenna (18-40 GHz)	Steatite	QMS-00880	19067	28.08.2022	27.08.2024
G1826034	Active Loop Antenna	Schwarzbeck	FMZB 1513	302	07.08.2022	06.08.2024
G1826036	Test software	R&S	EMC32 (V10.60.10)	N/A	N/A	N/A
G1826037	Control PC	Dell	OptiPlex 7050	36NV9P2	N/A	N/A
G1826433	3m Semi-Anechoic Chamber	Albatross	SAC-3m	APC17151-SAC	21.06.2024	20.06.2025

Kind of Equipment	Manufacturer	Type	S/N	Calibrated until
<b>Conducted Emission</b>				
LISN	R&S	ESH2-Z5	860014/024	26-Oct-2024
Receiver	R&S	ESR7	101181	26-Oct-2024
Pulse Limiter	R&S	ESH3-Z2	0357.8810.54	26-Oct-2024
Shielding room	ETS-Lindgren	843	Euroshiedpn-CT001270-1246	4-Nov-2024
Test Software	EZ-EMC	EZ-CON	Software Version: EMC-CON 3A1.1	

## 2.3 Traceability

All measurement equipment calibrations are traceable to NIM (National Institute of Metrology) or where calibration is performed in other countries, to equivalent nationally recognized standards organizations.

## 2.4 Calibration

Equipment requiring calibration is calibrated periodically by the manufacturer or according to manufacturer's specifications. Additionally all equipment is verified for proper performance on a regular basis using in house standards or comparisons.

## 2.5 Measurement Uncertainty

The estimated combined standard uncertainty for radiated emissions and conducted emissions measurements as below table.

**Table 2: Measurement Uncertainty**

Parameter	Uncertainty (k=2)
RF output power, conducted	± 0.99 dB
Occupied Channel Bandwidth	± 2.08 %
RF power density, conducted	± 0.99 dB
Unwanted Emissions, conducted	± 0.89 dB

All emissions, radiated	±4.17 dB
Conducted Emission, (9kHz to 150kHz)/(150kHz to 30MHz)	± 3.70 dB / ± 3.30 dB

## 2.6 Location of Original Data

The original copies of all test data taken during actual testing were attached at Appendix A & B & C & D of this report and delivered to the applicant. A copy has been retained in the TÜV Rheinland (Shenzhen) Co., Ltd. file for certification follow-up purposes.

## 2.7 Status of Facility Used for Testing

The TÜV Rheinland (Shenzhen) Co., Ltd. Test facility located at No. 362 Huanguan Road Middle, Longhua District, 518110, Shenzhen, P. R. China. is listed on the US Federal Communications Commission list of facilities approved to perform measurements.



### 3 General Product Information

#### 3.1 Product Function and Intended Use

The Product is a Bluetooth Speaker which supports Bluetooth dual mode function and has two Bluetooth chips that one is for Bluetooth dual mode and one is for Bluetooth LE.

For details refer to the User Manual, Technical Description and Circuit Diagram.

#### 3.2 Ratings and System Details

**Table 3: Technical Specification of EUT**

General Information of EUT	Value
Kind of Equipment:	Bluetooth Speaker
Type Designation:	X5i
Trademark:	<b>BlueAnt</b>
FCC ID:	VHF-BLUEANT-X5I
Operating Voltage:	AC 100-240V, 1.5A, or Bulit-in battery
Testing Voltage:	AC 120V, 60Hz
Operating Temperature Range:	0°C ~ +50 °C
Radiofrequency operating mode:	Bluetooth: operating within 2400-2483.5MHz, Classic Bluetooth (BR&EDR), Bluetooth BLE (1Mbps&2Mbps)
<b>Technical Specification of Bluetooth (dual mode)-Bluetooth Chip1</b>	
Operating Frequency:	2402 MHz to 2480 MHz
Type of Modulation:	GFSK, $\pi/4$ -DQPSK, 8DPSK
Channel Number:	BR & EDR mode: 79 channels, Low Energy mode: 40 channels
Channel Separation:	BR & EDR mode: 1MHz, Low Energy mode: 2MHz
Data Rate:	BR & EDR mode: 1Mbps, 2Mbps, 3Mbps Low Energy mode: 1Mbps, 2Mbps
Antenna Type:	Integral Antenna
Antenna Number:	1
Antenna Gain:	-0.68 dBi (Provided by the Client)
<b>Technical Specification of Bluetooth LE-Bluetooth Chip2</b>	
Operating Frequency:	2402 MHz to 2480 MHz
Type of Modulation:	GFSK
Channel Number:	Low Energy mode: 40 channels
Channel Separation:	Low Energy mode: 2MHz
Data Rate:	Low Energy mode: 1Mbps, 2Mbps
Antenna Type:	Integral Antenna
Antenna Number:	1
Antenna Gain:	-0.68 dBi (Provided by the Client)
Remark: Bluetooth (dual mode)-Bluetooth Chip1 and Bluetooth LE-Bluetooth Chip2 have different transmitter antennas.	

**Table 4: RF Channel and Frequency of Bluetooth BR & EDR**

RF Channel	Frequency (MHz)	RF Channel	Frequency (MHz)	RF Channel	Frequency (MHz)	RF Channel	Frequency (MHz)
<b>0</b>	<b>2402.00</b>	20	2422.00	40	2442.00	60	2462.00
1	2403.00	21	2423.00	41	2443.00	61	2463.00
2	2404.00	22	2424.00	42	2444.00	62	2464.00
3	2405.00	23	2425.00	43	2445.00	63	2465.00
4	2406.00	24	2426.00	44	2446.00	64	2466.00
5	2407.00	25	2427.00	45	2447.00	65	2467.00
6	2408.00	26	2428.00	46	2448.00	66	2468.00
7	2409.00	27	2429.00	47	2449.00	67	2469.00
8	2410.00	28	2430.00	48	2450.00	68	2470.00
9	2411.00	29	2431.00	49	2451.00	69	2471.00
10	2412.00	30	2432.00	50	2452.00	70	2472.00
11	2413.00	31	2433.00	51	2453.00	71	2473.00
12	2414.00	32	2434.00	52	2454.00	72	2474.00
13	2415.00	33	2435.00	53	2455.00	73	2475.00
14	2416.00	34	2436.00	54	2456.00	74	2476.00
15	2417.00	35	2437.00	55	2457.00	75	2477.00
16	2418.00	36	2438.00	56	2458.00	76	2478.00
17	2419.00	37	2439.00	57	2459.00	77	2479.00
18	2420.00	38	2440.00	58	2460.00	78	<b>2480.00</b>
19	2421.00	39	<b>2441.00</b>	59	2461.00		

Test frequencies are lowest channel: 2402 MHz, middle channel: 2441 MHz and highest channel: 2480 MHz for Bluetooth BR & EDR

**Table 5: RF Channel and Frequency of Bluetooth LE**

RF Channel	Frequency (MHz)	RF Channel	Frequency (MHz)	RF Channel	Frequency (MHz)	RF Channel	Frequency (MHz)
<b>0</b>	<b>2402</b>	10	2422	20	2442	30	2462
1	2404	11	2424	21	2444	31	2464
2	2406	12	2426	22	2446	32	2466
3	2408	13	2428	23	2448	33	2468
4	2410	14	2430	24	2450	34	2470
5	2412	15	2432	25	2452	35	2472
6	2414	16	2434	26	2454	36	2474
7	2416	17	2436	27	2456	37	2476
8	2418	18	2438	28	2458	38	2478
9	2420	<b>19</b>	<b>2440</b>	29	2460	<b>39</b>	<b>2480</b>

Test frequencies are lowest channel: 2402 MHz, middle channel: 2440 MHz and highest channel: 2480 MHz for Bluetooth LE

### 3.3 Independent Operation Modes

The basic operation modes are:

- A. On, Bluetooth transmitting mode (BR & EDR mode)
  - 1) Low Channel
  - 2) Middle Channel
  - 3) High Channel
- B. On, Bluetooth transmitting mode (BLE)
  - 1) Low Channel
  - 2) Middle Channel
  - 3) High Channel
- C. On, Transmitting on Hopping channel

### 3.4 Noise Generating and Noise Suppressing Parts

Refer to Circuit Diagram for further details.

### 3.5 Submitted Documents

- Application Form
- ID Label and Location Info
- User Manual
- Operation Description

## 4 Test Set-up and Operation Modes

### 4.1 Principle of Configuration Selection

**Radio Spectrum:** The equipment under test (EUT) was configured at its highest power output in order to measure its highest possible radiation and conducted level. The test modes were adapted accordingly in reference to the instructions for use.

**Emission:** The equipment under test (EUT) was configured to measure its highest possible radiation level. The test modes were adapted accordingly in reference to the instructions for use.

### 4.2 Test Operation and Test Software

Test operation refers to test setup in chapter 5. All tests were performed according to the procedures in ANSI C63.10: 2013.

According to clause 3.1, all tests were performed on model X5i in this report.

### 4.3 Special Accessories and Auxiliary Equipment

Table 6: List of Accessories and Auxiliary Equipment

Description	Manufacturer	Model	Remark
Laptop	Lenovo	T480	S/N: PF-16A6N8

### 4.4 Countermeasures to Achieve EMC Compliance

The test sample which has been tested contained the noise suppression parts as described in the Technical Construction File (TCF).

No additional measures were employed to achieve compliance.

## 4.5 Test Setup Diagram

Diagram of Measurement Configuration for Radiation Test (Below 1GHz)




Diagram of Measurement Configuration for Radiation Test (Above 1GHz)




Diagram of Measurement Configuration for Mains Conduction Measurement





Diagram of Measurement Configuration for Conducted Transmitter Measurement



## 5 Test Results

### 5.1 Transmitter Requirement & Test Suites

#### 5.1.1 Antenna Requirement

**RESULT:**

**Pass**

**Test Specification**

Test standard : FCC Part 15.247(b)(4) and Part 15.203

According to the manufacturer declared, the EUT has two Integral Antenna for Bluetooth Chip1 and Bluetooth Chip2 respective, the directional gain of antenna is -0.68 dBi, and the antenna connector is designed with permanent attachment and no consideration of replacement.

Therefore the EUT is considered sufficient to comply with the provision.

Refer to EUT Photo for further details.

## 5.1.2 Maximum Peak Conducted Output Power

**RESULT:****Pass****Test Specification**

Test standard	: FCC Part 15.247(b)(1)&(3)
Basic standard	: ANSI C63.10: 2013
Limits	: FHSS < 0.125 Watts, DSSS < 1.0 Watts
Kind of test site	: Shielded Room

**Test Setup**

Date of testing	: 2024-07-02 - 2024-07-20
Input voltage	: AC 120V, 60Hz
Operation mode	: A, B, C
Test channel	: Low / Middle / High
Ambient temperature	: 23.5 °C
Relative humidity	: 52.5 %
Atmospheric pressure	: 101 kPa

For details refer to following test result.



**Table 7: Test Result of Maximum Peak Conducted Output Power, Bluetooth BR & EDR - Bluetooth Chip1**

Test Mode	Test Channel (MHz)	Measured Peak Power		Limit (W)
		(dBm)	(W)	
GFSK (BR)	2402.0	-0.38	0.0009	< 0.125
	2441.0	-1.03	0.0008	
	2480.0	-1.34	0.0007	
8DPSK (EDR)	2402.0	0.20	0.0010	
	2441.0	-0.66	0.0009	
	2480.0	-1.00	0.0008	
<b>Maximum Measured Value</b>		<b>0.20</b>	<b>0.0010</b>	

**Table 8: Test Result of Maximum Peak Conducted Output Power, Bluetooth LE - Bluetooth Chip1**

Test Mode	Data Rate	Test Channel (MHz)	Measured Peak Power		Limit (W)
			(dBm)	(W)	
Bluetooth LE	1 Mbps	2402.0	-0.74	0.0008	< 1.0
		2440.0	-1.22	0.0008	
		2480.0	-1.61	0.0007	
	2 Mbps	2402.0	-0.56	0.0009	
		2440.0	-1.18	0.0008	
		2480.0	-1.61	0.0007	
<b>Maximum Measured Value</b>			<b>-0.56</b>	<b>0.0009</b>	

**Table 9: Test Result of Maximum Peak Conducted Output Power, Bluetooth LE - Bluetooth Chip2**

Test Mode	Data Rate	Test Channel (MHz)	Measured Peak Power		Limit (W)
			(dBm)	(W)	
Bluetooth LE	1 Mbps	2402.0	7.01	0.0050	< 1.0
		2440.0	6.65	0.0046	
		2480.0	6.40	0.0044	
	2 Mbps	2402.0	7.02	0.0050	
		2440.0	6.67	0.0046	
		2480.0	6.33	0.0043	
<b>Maximum Measured Value</b>			<b>7.02</b>	<b>0.0050</b>	

Note:

- 1) The cable loss is taken into account in results.
- 2) Antenna gain(G): -0.68 dBi for Bluetooth Chip1 & Bluetooth Chip2

### 5.1.3 Conducted Power Spectral Density

**RESULT:****Pass****Test Specification**

Test standard	: FCC Part 15.247(e)
Basic standard	: ANSI C63.10: 2013
Limits	: < 8 dBm / 3kHz
Kind of test site	: Shielded Room

**Test Setup**

Date of testing	: 2024-07-02 - 2024-07-20
Input voltage	: AC 120V, 60Hz
Operation mode	: B
Test channel	: Low / Middle / High
Ambient temperature	: 23.5 °C
Relative humidity	: 52.5 %
Atmospheric pressure	: 101 kPa

For the measurement records, refer to the appendix B, C.

### 5.1.4 6dB Bandwidth

**RESULT:****Pass****Test Specification**

Test standard	:	FCC Part 15.247(a)(2)
Basic standard	:	ANSI C63.10: 2013
Limits	:	> 500 KHz
Kind of test site	:	Shielded Room

**Test Setup**

Date of testing	:	2024-07-02 - 2024-07-20
Input voltage	:	AC 120V, 60Hz
Operation mode	:	B
Test channel	:	Low / Middle / High
Ambient temperature	:	23.5 °C
Relative humidity	:	52.5 %
Atmospheric pressure	:	101 kPa

For the measurement records, refer to the appendix B, C.

Prüfbericht - Nr.: **CN24UHMF 002**  
Test Report No.:Seite 20 von 28  
Page 20 of 28

### 5.1.5 99% Bandwidth

**RESULT:****Pass****Test Specification**

Test standard : FCC Part 15.247(a)  
Basic standard : ANSI C63.10: 2013  
Kind of test site : Shielded Room

**Test Setup**

Date of testing : 2024-07-02 - 2024-07-20  
Input voltage : AC 120V, 60Hz  
Operation mode : A, B, C  
Test channel : Low / Middle / High  
Ambient temperature : 23.5 °C  
Relative humidity : 52.5 %  
Atmospheric pressure : 101 kPa

For the measurement records, refer to the appendix A, B, C.

Prüfbericht - Nr.: **CN24UHMF 002**  
Test Report No.:Seite 21 von 28  
Page 21 of 28

### 5.1.6 20dB Bandwidth

**RESULT:****Pass****Test Specification**

Test standard : FCC Part 15.247(a)(1)  
Basic standard : ANSI C63.10: 2013  
Kind of test site : Shielded Room

**Test Setup**

Date of testing : 2024-07-02 - 2024-07-20  
Input voltage : AC 120V, 60Hz  
Operation mode : A  
Test channel : Low / Middle / High  
Ambient temperature : 23.5 °C  
Relative humidity : 52.5 %  
Atmospheric pressure : 101 kPa

For the measurement records, refer to the appendix A.

### 5.1.7 Carrier Frequency Separation

**RESULT:****Pass****Test Specification**

Test standard	: FCC Part 15.247(a)(1)
Basic standard	: ANSI C63.10: 2013
Limits	: $\geq 25\text{kHz}$ or 2/3 of 20dB bandwidth, whichever is greater
Kind of test site	: Shielded Room

**Test Setup**

Date of testing	: 2024-07-02 - 2024-07-20
Input voltage	: AC 120V, 60Hz
Operation mode	: C
Test channel	: Low / Middle / High
Ambient temperature	: 23.5 °C
Relative humidity	: 52.5 %
Atmospheric pressure	: 101 kPa

For the measurement records, refer to the appendix A.

### 5.1.8 Number of Hopping Frequency

**RESULT:****Pass****Test Specification**

Test standard	:	FCC part 15.247(a)(1)(iii)
Basic standard	:	ANSI C63.10: 2013
Limits	:	≥ 15 non-overlapping channels
Kind of test site	:	Shielded Room

**Test Setup**

Date of testing	:	2024-07-02 - 2024-07-20
Input voltage	:	AC 120V, 60Hz
Operation mode	:	A
Ambient temperature	:	23.5 °C
Relative humidity	:	52.5 %
Atmospheric pressure	:	101 kPa

For the measurement records, refer to the appendix A.

### 5.1.9 Time of Occupancy

**RESULT:****Pass****Test Specification**

Test standard	:	FCC part 15.247(a)(1)(iii)
Basic standard	:	ANSI C63.10: 2013
Limits	:	< 0.4s
Kind of test site	:	Shielded Room

**Test Setup**

Date of testing	:	2024-07-02 - 2024-07-20
Input voltage	:	AC 120V, 60Hz
Operation mode	:	A
Test channel	:	Low / Middle / High
Ambient temperature	:	23.5 °C
Relative humidity	:	52.5 %
Atmospheric pressure	:	101 kPa

For the measurement records, refer to the appendix A.



## 5.1.10 Conducted Spurious Emissions Measured in 100 kHz Bandwidth

**RESULT:****Pass****Test Specification**

Test standard	: FCC Part 15.247(d)
Basic standard	: ANSI C63.10: 2013
Limits	: 20dB (below that in the 100kHz bandwidth within the band that contains the highest level of the desired power); In addition, radiated emissions which fall in the restricted bands, must also comply with the radiated emission limits specified in 15.209(a)
Kind of test site	: Shielded Room

**Test Setup**

Date of testing	: 2024-07-02 - 2024-07-20
Input voltage	: AC 120V, 60Hz
Operation mode	: A, B, C
Test channel	: Low / Middle / High
Ambient temperature	: 23.5 °C
Relative humidity	: 52.5 %
Atmospheric pressure	: 101 kPa

Test results of 100kHz Bandwidth of Frequency Band Edge by Conducted method refer to test plots, and compliance is achieved as well.

For the measurement records, refer to the appendix A, B, C.

## 5.1.11 Radiated Spurious Emission

**RESULT:****Pass****Test Specification**

Test standard	: FCC Part 15.247(d) & FCC Part 15.205
Basic standard	: ANSI C63.10: 2013
Limits	: Refer to 15.209(a) of FCC part 15.247(d)
Kind of test site	: 3m Semi-anechoic Chamber

**Test Setup**

Date of testing	: 2024-07-02 - 2024-07-20
Input voltage	: AC 120V, 60Hz
Operation mode	: A, B, C
Test channel	: Low / Middle / High
Ambient temperature	: Refer to test result
Relative humidity	: Refer to test result
Atmospheric pressure	: 101 kPa

**Remark:**

Testing was carried out within frequency range 9kHz to the tenth harmonics. Only the worst case spurious emissions configuration of the each mode were reported.

For the measurement records, refer to the appendix A, B, C.

## 5.1.12 Conducted Emission on AC Mains

**RESULT:****Pass****Test Specification**

Test standard	: FCC Part 15.207(a)
Basic standard	: ANSI C63.10: 2013
Frequency range	: 0.15 – 30MHz
Classification	: Class B
Limits	: FCC Part 15.207(a)
Kind of test site	: Shielded Room

**Test Setup**

Date of testing	: 2024-07-18
Input voltage	: AC 120V, 60Hz
Operation mode	: A, B, C
Earthing	: Not connected
Ambient temperature	: Refer to test result
Relative humidity	: Refer to test result
Atmospheric pressure	: 101 kPa

**Remark:**

Testing was carried out all operation modes, only the worst case configuration of the each mode were reported.

For the measurement records, refer to the appendix A, B, C.

## 6 Photographs of the Test Set-Up

For photographs of the test set-up, refer to the appendix D.

## 7 List of Tables

Table 1: List of Test and Measurement Equipment.....	6
Table 2: Measurement Uncertainty.....	7
Table 3: Technical Specification of EUT.....	9
Table 4: RF Channel and Frequency of Bluetooth BR & EDR.....	10
Table 5: RF Channel and Frequency of Bluetooth LE.....	10
Table 6: List of Accessories and Auxiliary Equipment.....	12
Table 7: Test Result of Maximum Peak Conducted Output Power, Bluetooth BR & EDR - Bluetooth Chip1.....	17
Table 8: Test Result of Maximum Peak Conducted Output Power, Bluetooth LE - Bluetooth Chip1.....	17
Table 9: Test Result of Maximum Peak Conducted Output Power, Bluetooth LE - Bluetooth Chip2.....	17