



**Spectrum Research &  
Testing Lab., Inc.**  
No. 101-10, Ling 8,  
Shan-Tong Li, Chung-Li  
City, Taoyuan, Taiwan

# TEST REPORT

Reference No.: A07082312  
Report No.: FCCA07082312  
FCC ID: VHVBTvh1000  
Page: 1 of 48  
Date: Sep. 10, 2007

Product Name: Bluetooth Mono Headset  
Model Number: VH-1000  
Applicant: Vencer Co., Ltd.  
20F-1, No.77, Sec.1, Hsin Tai Wu Rd., Hsi Chih,  
Taipei Hsien, Taiwan, 221  
Date of Receipt: Aug. 23, 2007  
Finished date of Test: Sep. 08, 2007  
Applicable Standards: 47 CFR Part 15, Subpart C  
ANSI C63.4:2003

We, **Spectrum Research & Testing Laboratory Inc.**, hereby certify that one sample of the above was tested in our laboratory with positive results according to the above-mentioned standards. The records in the report are an accurate account of the results. Details of the results are given in the subsequent pages of this report.

Tested By: John Yu, Date: Sep/10/2007  
(John Yu)

Approved By: Johnson Ho, Date: 9/10/2007  
(Johnson Ho, Director)



**Spectrum Research &  
Testing Lab., Inc.**  
No. 101-10, Ling 8,  
Shan-Tong Li, Chung-Li  
City, Taoyuan, Taiwan

# TEST REPORT

Reference No.: A07082312  
Report No.: FCCA07082312  
FCC ID: VHVBTVH1000  
Page: 2 of 48  
Date: Sep. 10, 2007

## TABLE OF CONTENTS

1. DOCUMENT POLICY AND TEST STATEMENT.....	4
1.1 DOCUMENT POLICY .....	4
1.2 TEST STATEMENT .....	4
1.3 EUT MODIFICATION.....	4
2. DESCRIPTION OF EUT AND TEST MODE .....	5
2.1 GENERAL DESCRIPTION OF EUT .....	5
2.2 DESCRIPTION OF SUPPORT UNIT .....	5
2.3 DESCRIPTION OF TEST MODE .....	6
3. DESCRIPTION OF APPLIED STANDARDS .....	6
4. TECHNICAL CHARACTERISTICS TEST .....	7
4.1 CHANNEL SEPARATION TEST .....	7
4.1.1 LIMIT .....	7
4.1.2 TEST EQUIPMENT .....	7
4.1.3 TEST SET-UP.....	7
4.1.4 TEST PROCEDURE.....	7
4.1.5 EUT OPERATING CONDITION.....	8
4.1.6 TEST RESULT.....	8
4.2 20DB BANDWIDTH .....	12
4.2.2 LIMIT .....	12
4.2.2 TEST EQUIPMENT .....	12
4.2.3 TEST SET-UP.....	12
4.2.4 TEST PROCEDURE.....	12
4.2.5 TEST RESULT.....	13
4.3 QUANTITY OF HOPPING CHANNEL TEST .....	16
4.3.1 LIMIT .....	16
4.3.2 TEST EQUIPMENT .....	16
4.3.3 TEST SET-UP.....	16
4.3.4 TEST PROCEDURE.....	16
4.3.5 EUT OPERATING CONDITION.....	16
4.3.6 TEST RESULT.....	17
4.4 TIME OF OCCUPANCY (DWELL TIME).....	18
4.4.1 LIMIT .....	18
4.4.2 TEST EQUIPMENT .....	18
4.4.3 TEST SET-UP.....	18
4.4.4 TEST PROCEDURE.....	18
4.4.5 EUT OPERATING CONDITION.....	18
4.4.6 TEST RESULT.....	19
4.5 CONDUCTED EMISSION .....	23
4.5.1 LIMIT .....	23
4.5.2 TEST EQUIPMENT .....	23
4.5.3 TEST SETUP .....	24

 <p><b>Spectrum Research &amp; Testing Lab., Inc.</b> No. 101-10, Ling 8, Shan-Tong Li, Chung-Li City, Taoyuan, Taiwan</p>	<h1>TEST REPORT</h1>	Reference No.: A07082312 Report No.: FCCA07082312 FCC ID: VHVBTVH1000 Page:3 of 48 Date: Sep. 10, 2007
---	----------------------	--

4.5.4 TEST PROCEDURE .....	24
4.5.5 EUT OPERATING CONDITION.....	24
4.5.6 TEST RESULT .....	25
4.6 RADIATED EMISSION TEST .....	26
4.6.1 LIMIT .....	26
4.6.2 TEST EQUIPMENT.....	27
4.6.3 TEST SET-UP.....	28
4.6.4 TEST PROCEDURE.....	28
4.6.5 EUT OPERATING CONDITION.....	28
4.6.6 RADIATED EMISSION TEST RESULT .....	29
4.7 PEAK POWER TEST .....	34
4.7.1 LIMIT .....	34
4.7.2 TEST EQUIPMENT .....	34
4.7.3 TEST SET-UP.....	35
4.7.4 TEST PROCEDURE.....	35
4.6.5 EUT OPERATING CONDITION.....	35
4.7.6 TEST RESULT .....	35
4.8 BAND EDGE TEST .....	39
4.8.1 LIMIT .....	39
4.8.2 TEST EQUIPMENT .....	39
4.8.3 TEST SET-UP.....	40
4.8.4 TEST PROCEDURE.....	41
4.8.5 EUT OPERATING CONDITION.....	41
4.8.6 TEST RESULT .....	41
5 ANTENNA APPLICATION .....	44
5.1 ANTENNA REQUIREMENT .....	44
5.2 RESULT .....	44
6. PHOTOS OF TESTING .....	45
7. TERMS OF ABBREVIATION .....	48



**Spectrum Research &  
Testing Lab., Inc.**  
No. 101-10, Ling 8,  
Shan-Tong Li, Chung-Li  
City, Taoyuan, Taiwan

# TEST REPORT

Reference No.: A07082312  
Report No.: FCCA07082312  
FCC ID: VHVBTvh1000  
Page: 4 of 48  
Date: Sep. 10, 2007

## 1. DOCUMENT POLICY AND TEST STATEMENT

### 1.1 DOCUMENT POLICY

- The report shall not be reproduced except in full, without the written approval of SRT Lab, Inc.

### 1.2 TEST STATEMENT

- The test results in the report apply only to the unit tested by SRT Lab.
- There was no deviation from the requirements of test standards during the test.
- AC power source, 120 VAC/60 Hz, was used during the test.

### 1.3 EUT MODIFICATION

- No modification in SRT Lab.

 <p><b>Spectrum Research &amp; Testing Lab., Inc.</b> No. 101-10, Ling 8, Shan-Tong Li, Chung-Li City, Taoyuan, Taiwan</p>	<h1>TEST REPORT</h1>	Reference No.: A07082312 Report No.: FCCA07082312 FCC ID: VHVBTVH1000 Page:5 of 48 Date: Sep. 10, 2007
---	----------------------	--

## 2. DESCRIPTION OF EUT AND TEST MODE

### 2.1 GENERAL DESCRIPTION OF EUT

PRODUCT	Bluetooth Mono Headset
MODEL NO.	VH-1000
POWER SUPPLY	DC 3.7 V, 0.02A
FREQUENCY BAND	2400MHz ~2483.5MHz
CARRIER FREQUENCY	CH0:2402MHz~CH78:2480MHz
NUMBER OF CHANNEL	79
CHANNEL SPACING	1 MHz
RATED RF OUTPUT POWER	0dBm
MODULATION TYPE	GFSK, II/4DQPSK, 8DPSK
DUTY CYCLE	50%
MODE OF OPERATION	duplex
BIT RATE OF TRANSMISSION	2.1 Mbps
ANTENNA TYPE	Ceramic Chip ANT
ANTENNA GAIN	-2 dBi
OPERATING TEMPERATURE	-10~55°C
CHANNEL BANDWIDTH	1MHz

**NOTE :**

For more detailed information, please refer to the EUT's specification or user's manual provided by manufacturer.

### 2.2 DESCRIPTION OF SUPPORT UNIT

The transmitter part of EUT was tested with a PC system and configured by the requirement of ANSI C63.4. All interface ports were connected to the appropriate support units via specific cables. The support units and cables are listed below.

No	Device	Brand	Model #	FCC ID/DoC	Cable
1	Mobile Phone	SonyEricsson	Z550i	PY7A1022015	N/A
2	N/A				

**NOTE :** For the actual test configuration, please refer to the photos of testing.



**Spectrum Research &  
Testing Lab., Inc.**  
No. 101-10, Ling 8,  
Shan-Tong Li, Chung-Li  
City, Taoyuan, Taiwan

## TEST REPORT

Reference No.: A07082312  
Report No.: FCCA07082312  
FCC ID: VHVBTVH1000  
Page:6 of 48  
Date: Sep. 10, 2007

### 2.3 DESCRIPTION OF TEST MODE

79 channels are provided by EUT. Three channels of lower, medium and higher were chosen for test.

Channel	Frequency (MHz)
0	2402
39	2441
78	2480

#### NOTE :

1. Below 1 GHz, the channel 0, 39 and 78 were pre-tested in chamber. The channel 0, worst case one, was chosen for radiated emission test.
2. Above 1 GHz, the channel 0, 39 and 78 were tested individually.

### 3. DESCRIPTION OF APPLIED STANDARDS

The EUT is a kind of wireless product and to be connected with a PC system for normal use. According to the specifications provided by the applicant, it must comply with the requirements of the following standards:

47 CFR Part 15, Subpart C

ANSI C63.4: 2003

All tests have been performed and recorded as the above standards.

 <p><b>Spectrum Research &amp; Testing Lab., Inc.</b> No. 101-10, Ling 8, Shan-Tong Li, Chung-Li City, Taoyuan, Taiwan</p>	<p><b>TEST REPORT</b></p>	<p>Reference No.: A07082312 Report No.: FCCA07082312 FCC ID: VHVBTVH1000 Page: 7 of 48 Date: Sep. 10, 2007</p>
---	---------------------------	--

#### 4. TECHNICAL CHARACTERISTICS TEST

##### 4.1 CHANNEL SEPARATION TEST

###### 4.1.1 LIMIT

FCC Part15, Subpart C Section 15.247(a)(1). Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.

Frequency Range (MHz)	Limit(kHz)
902-928	>25kHz
2400-2483.5	>25kHz
5725-5850	>25kHz


###### 4.1.2 TEST EQUIPMENT

The following test equipment was used during the radiated emission test :

Equipment/ Facilities	Specifications	Manufacturer	Model#/ Serial#	Due Date of Cal. & Cal. Center
SPECTRUM	9kHz-7GHz	ROHDE & SCHWARZ	FSP7/ 839511/010	MAR. 2008 ETC

**NOTE:** The calibration interval of the above test equipment is one year and the calibrations are traceable to NML/ROC and NIST/USA.

###### 4.1.3 TEST SET-UP



The EUT was connected to a spectrum through a  $50\Omega$  RF cable.

###### 4.1.4 TEST PROCEDURE

The EUT was operating in hopping mode or could be controlled its channel.  
Printed out the test result from the spectrum by hard copy function.



**Spectrum Research &  
Testing Lab., Inc.**  
No. 101-10, Ling 8,  
Shan-Tong Li, Chung-Li  
City, Taoyuan, Taiwan

## TEST REPORT

Reference No.: A07082312  
Report No.: FCCA07082312  
FCC ID: VHVBTVH1000  
Page: 8 of 48  
Date: Sep. 10, 2007

### 4.1.5 EUT OPERATING CONDITION

1. Set the EUT under transmission condition continuously at a specific channel frequency.
2. The EUT was set to the highest available power level.

### 4.1.6 TEST RESULT

Temperature:	25°C	Humidity:	65%RH
Spectrum Detector:	PK	Tested by:	John Yu
Test Result:	PASS	Tested Date:	Aug. 27, 2007

Channel Number	Channel Frequency (MHz)	Separation Read Value (kHz)	Minimum Limit(20dB Bandwidth) (kHz)
0	2402	1004.000	25
39	2441	1008.000	25
78	2480	1004.000	25




**Spectrum Research &  
Testing Lab., Inc.**  
No. 101-10, Ling 8,  
Shan-Tong Li, Chung-Li  
City, Taoyuan, Taiwan

# TEST REPORT

Reference No.: A07082312  
Report No.: FCCA07082312  
FCC ID: VHVBTvh1000  
Page: 9 of 48  
Date: Sep. 10, 2007

CH0:



Comment: Channel Separation CH00  
Date: 27.AUG.2007 18:03:08




**Spectrum Research &  
Testing Lab., Inc.**  
No. 101-10, Ling 8,  
Shan-Tong Li, Chung-Li  
City, Taoyuan, Taiwan

# TEST REPORT

Reference No.: A07082312  
Report No.: FCCA07082312  
FCC ID: VHVBTvh1000  
Page: 10 of 48  
Date: Sep. 10, 2007

CH39:



Comment: Channel Separation CH39  
Date: 27.AUG.2007 18:07:00




**Spectrum Research &  
Testing Lab., Inc.**  
No. 101-10, Ling 8,  
Shan-Tong Li, Chung-Li  
City, Taoyuan, Taiwan

# TEST REPORT

Reference No.: A07082312  
Report No.: FCCA07082312  
FCC ID: VHVBTvh1000  
Page:11 of 48  
Date: Sep. 10, 2007

CH78:



Comment: Channel Separation CH78  
Date: 27.AUG.2007 18:35:17

 <p><b>Spectrum Research &amp; Testing Lab., Inc.</b> No. 101-10, Ling 8, Shan-Tong Li, Chung-Li City, Taoyuan, Taiwan</p>	<h1>TEST REPORT</h1>	Reference No.: A07082312 Report No.: FCCA07082312 FCC ID: VHVBTvh1000 Page:12 of 48 Date: Sep. 10, 2007
---	----------------------	---

## 4.2 20dB Bandwidth

### 4.2.2 LIMIT

Frequency Range (MHz)	Quantity of Hopping Channel	Limit(kHz)			
		50	25	15	75
902-928	<250	>250	NA	NA	
2400-2483.5	NA	NA	>1000	<1000	

### 4.2.2 TEST EQUIPMENT

The following test equipment was used during the test:

Equipment/ Facilities	Specifications	Manufacturer	Model#/ Serial#	Due Date of Cal. & Cal. center
SPECTRUM	9kHz-7GHz	ROHDE & SCHWARZ	FSP7/ 839511/010	APR. 2008 R&S

**NOTE:** The calibration interval of the above test equipment is one year and the calibrations are traceable to NML/ROC and NIST/USA.

### 4.2.3 TEST SET-UP



The EUT was connected to a spectrum through a  $50\Omega$  RF cable.

### 4.2.4 TEST PROCEDURE

The EUT was operated in hopping mode or any specific channel.  
Printed out the test result from the spectrum by hard copy function.



**Spectrum Research &  
Testing Lab., Inc.**  
No. 101-10, Ling 8,  
Shan-Tong Li, Chung-Li  
City, Taoyuan, Taiwan

# TEST REPORT


Reference No.: A07082312  
Report No.: FCCA07082312  
FCC ID: VHVBTVH1000  
Page:13 of 48  
Date: Sep. 10, 2007

## 4.2.5 TEST RESULT

Temperature:	25°C	Humidity:	65%RH
Spectrum Detector:	PK	Tested by:	John Yu
Test Result:	PASS	Tested Date:	Aug.27, 2007

Channel Number	Channel Frequency (MHz)	20dB Down Bandwidth (kHz)
0	2402	894
39	2441	921
78	2480	921

CH0:



Comment: Down 20dB Bandwidth CH00  
Date: 27.AUG.2007 15:15:53




**Spectrum Research &  
Testing Lab., Inc.**  
No. 101-10, Ling 8,  
Shan-Tong Li, Chung-Li  
City, Taoyuan, Taiwan

# TEST REPORT

Reference No.: A07082312  
Report No.: FCCA07082312  
FCC ID: VHVBTVH1000  
Page:14 of 48  
Date: Sep. 10, 2007

CH39:



Comment: Down 20dB Bandwidth CH39  
Date: 27.AUG.2007 15:12:49




**Spectrum Research &  
Testing Lab., Inc.**  
No. 101-10, Ling 8,  
Shan-Tong Li, Chung-Li  
City, Taoyuan, Taiwan

# TEST REPORT

Reference No.: A07082312  
Report No.: FCCA07082312  
FCC ID: VHVBTvh1000  
Page: 15 of 48  
Date: Sep. 10, 2007

CH78:



Comment: Down 20dB Bandwidth CH78  
Date: 27.AUG.2007 15:18:44

 <p><b>Spectrum Research &amp; Testing Lab., Inc.</b> No. 101-10, Ling 8, Shan-Tong Li, Chung-Li City, Taoyuan, Taiwan</p>	<h1>TEST REPORT</h1>	Reference No.: A07082312 Report No.: FCCA07082312 FCC ID: VHVBTvh1000 Page:16 of 48 Date: Sep. 10, 2007
---	----------------------	---

## 4.3 QUANTITY OF HOPPING CHANNEL TEST

### 4.3.1 LIMIT

FCC Part15, Subpart C Section 15.247.

Frequency Range (MHz)	Limit (Quantity of Hopping Channel)			
	20dB Bandwidth <250kHz	20dB Bandwidth >250kHz	20dB Bandwidth <1MHz	20dB Bandwidth >1MHz
902-928	50	25	N/A	N/A
2400-2483.5	N/A	N/A	75	15
5725-5850	N/A	N/A	75	N/A


### 4.3.2 TEST EQUIPMENT

The following test equipment was used during the test:

Equipment/ Facilities	Specifications	Manufacturer	Model#/ Serial#	Due Date of Cal. & Cal. Center
SPECTRUM	9kHz-7GHz	ROHDE & SCHWARZ	FSP7/ 839511/010	MAR. 2008 ETC

**NOTE:** The calibration interval of the above test equipment is one year and the calibrations are traceable to NML/ROC and NIST/USA.

### 4.3.3 TEST SET-UP



The EUT was connected to a spectrum through a  $50\Omega$  RF cable.

### 4.3.4 TEST PROCEDURE

The EUT was operating in hopping mode or could be controlled its channel.  
Printed out the test result from the spectrum by hard copy function.

### 4.3.5 EUT OPERATING CONDITION

1. Set the EUT under frequency hopping transmission condition.
2. The EUT was set to the highest available power level.



**Spectrum Research &  
Testing Lab., Inc.**  
No. 101-10, Ling 8,  
Shan-Tong Li, Chung-Li  
City, Taoyuan, Taiwan

# TEST REPORT



Reference No.: A07082312  
Report No.: FCCA07082312  
FCC ID: VHVBTvh1000  
Page:17 of 48  
Date: Sep. 10, 2007

## 4.3.6 TEST RESULT

Temperature:	25°C	Humidity:	65%RH
Spectrum Detector:	PK	Tested by:	John Yu
Test Result:	PASS	Tested Date:	Aug. 27, 2007

Hopping Channel Frequency Range(MHz)	Quantity of Hopping Channel Read Value	Quantity of Hopping Channel Limit
2402~2480	79	75

CH0-CH78



Comment: Hopping Channel  
Date: 27.AUG.2007 17:50:23

 <p><b>Spectrum Research &amp; Testing Lab., Inc.</b> No. 101-10, Ling 8, Shan-Tong Li, Chung-Li City, Taoyuan, Taiwan</p>	<h1>TEST REPORT</h1>	Reference No.: A07082312 Report No.: FCCA07082312 FCC ID: VHVBTvh1000 Page:18 of 48 Date: Sep. 10, 2007
---	----------------------	---

#### 4.4 TIME OF OCCUPANCY (Dwell Time)

##### 4.4.1 LIMIT

FCC Part15, Subpart C Section 15.247.

Frequency Range (MHz)	Limit (ms)		
	20dB Bandwidth <250kHz(50Channel)	20dB Bandwidth >250kHz(25Channel)	20dB Bandwidth <1MHz(75Channel)
902-928	400(20s)	400(10s)	NA
2400-2483.5	NA	NA	400(30s)
5725-5850	NA	NA	400(30s)

**NOTE:** The “()” is all channel's average time of occupancy.


##### 4.4.2 TEST EQUIPMENT

The following test equipment was used during the test:

Equipment/ Facilities	Specifications	Manufacturer	Model#/ Serial#	Due Date of Cal. & Cal. Center
SPECTRUM	9kHz-7GHz	ROHDE & SCHWARZ	FSP7/ 839511/010	MAR. 2008 ETC

**NOTE:** The calibration interval of the above test equipment is one year and the calibrations are traceable to NML/ROC and NIST/USA.

##### 4.4.3 TEST SET-UP



The EUT was connected to a spectrum through a  $50\Omega$  RF cable.

##### 4.4.4 TEST PROCEDURE

The EUT was operating in hopping mode or could be controlled its channel.  
Printed out the test result from the spectrum by hard copy function.

##### 4.4.5 EUT OPERATING CONDITION

Same as section 4.1.5 of this report.



**Spectrum Research &  
Testing Lab., Inc.**  
No. 101-10, Ling 8,  
Shan-Tong Li, Chung-Li  
City, Taoyuan, Taiwan

## TEST REPORT

Reference No.: A07082312  
Report No.: FCCA07082312  
FCC ID: VHVBTvh1000  
Page:19 of 48  
Date: Sep. 10, 2007

### 4.4.6 TEST RESULT

Temperature: 25°C Humidity: 65%RH  
Spectrum Detector: PK Tested by: John Yu  
Test Result: PASS Tested Date: Aug. 27, 2007

Channel Number	Channel Frequency (MHz)	Pulse Time (μs)	Period Time (s)	Time of Occupancy (Dwell Time) (ms)	Average Time of Occupancy Limit (ms)
0	2402.00	390	31.6	123.24	400
39	2441.00	398	31.6	57.512	400
78	2480.00	394	31.6	124.504	400




**Spectrum Research &  
Testing Lab., Inc.**  
No. 101-10, Ling 8,  
Shan-Tong Li, Chung-Li  
City, Taoyuan, Taiwan

# TEST REPORT

Reference No.: A07082312  
Report No.: FCCA07082312  
FCC ID: VHVBTvh1000  
Page: 20 of 48  
Date: Sep. 10, 2007

CH0:



Comment: Dwell Time CH00  
Date: 27.AUG.2007 17:13:37




**Spectrum Research &  
Testing Lab., Inc.**  
No. 101-10, Ling 8,  
Shan-Tong Li, Chung-Li  
City, Taoyuan, Taiwan

# TEST REPORT

Reference No.: A07082312  
Report No.: FCCA07082312  
FCC ID: VHVBTVH1000  
Page:21 of 48  
Date: Sep. 10, 2007

Ch39:






**Spectrum Research &  
Testing Lab., Inc.**  
No. 101-10, Ling 8,  
Shan-Tong Li, Chung-Li  
City, Taoyuan, Taiwan

# TEST REPORT

Reference No.: A07082312  
Report No.: FCCA07082312  
FCC ID: VHVBTvh1000  
Page:22 of 48  
Date: Sep. 10, 2007

CH78:



Comment: Dwell Time CH78  
Date: 27.AUG.2007 17:19:33

 <p><b>Spectrum Research &amp; Testing Lab., Inc.</b> No. 101-10, Ling 8, Shan-Tong Li, Chung-Li City, Taoyuan, Taiwan</p>	<p><b>TEST REPORT</b></p>	<p>Reference No.: A07082312 Report No.: FCCA07082312 FCC ID: VHVBTVH1000 Page:23 of 48 Date: Sep. 10, 2007</p>
---	---------------------------	--

## 4.5 CONDUCTED EMISSION

### 4.5.1 LIMIT

FREQUENCY (MHz)	Class A (dB $\mu$ V)		Class B (dB $\mu$ V)	
	Quasi-peak	Average	Quasi-peak	Average
0.15 - 0.5	79	66	66 - 56	56 - 46
0.5 - 5.0	73	60	56	46
5.0 - 30.0	73	60	60	50

**NOTE:**

1. The lower limit shall apply at the transition frequencies.
2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50 MHz.

### 4.5.2 TEST EQUIPMENT


The following test equipment was used for the test:

EQUIPMENT/ FACILITIES	SPECIFICATIONS	MANUFACTURER	MODEL#/ SERIAL#	DUE DATE OF CAL. & CAL. CENTER
EMI TEST RECEIVER	9 KHZ TO 30 MHZ	ROHDE & SCHWARZ	ESHS30/ 826003/008	OCT. 2007 ETC
LISN (for EUT)	50 $\mu$ H, 50 ohm	FCC	FCC-LISN-50-25-2/ 01017	OCT. 2007 ETC
LISN (for Peripheral)	50 $\mu$ H, 50 ohm	FCC	FCC-LISN-50-25-2/ 01018	NOV. 2007 ETC
50 ohm TERMINATOR	50 ohm	HP	11593A/ 2	OCT. 2007 ETC
COAXIAL CABLE	5m	SUNCITY	CABLE 05/ #5-5M	NOV. 2007 SRT
ISOLATION TRANSFORMER	N/A	APC	AFC-11015/ F102040016	N/A
FILTER	2 LINE, 30A	FIL.COIL	FC-943/ 771	N/A
GROUND PLANE	2.3M (H) x 2.4M (W)	SRT	N/A	N/A
GROUND PLANE	2.4M (H) x 2.4M (W)	SRT	N/A	N/A

**NOTE:** The calibration interval of the above test equipment is one year and the calibrations are traceable to NML/ROC and NIST/USA.



### 4.5.3 TEST SETUP



**NOTE:**

1. The EUT was put on a wooden table with 0.8m height above ground plane, and 0.4m away from reference ground plane (> 2mx2m).
2. For the actual test configuration, please refer to the photos of testing.
3. The serial no. of the LISN connected to EUT is 951318.
4. The serial no. of the LISN connected to support units is 924839.

### 4.5.4 TEST PROCEDURE

The EUT was tested according to the requirement of ANSI C63.4: 2003 and CISPR22:2006. The frequency spectrum from 0.15 MHz to 30 MHz was investigated. The LISN used was 50 ohm/50μH as specified. All readings were quasi-peak and average values with 10 kHz resolution bandwidth of the test receiver. The EUT system was operated in all typical methods by users. Both lines of the power mains of EUT were measured and the cables connected to EUT and support units were moved to find the maximum emission levels for each frequency.

### 4.5.5 EUT OPERATING CONDITION

The EUT was linking with a mobile phone in testing period.

 <p><b>Spectrum Research &amp; Testing Lab., Inc.</b> No. 101-10, Ling 8, Shan-Tong Li, Chung-Li City, Taoyuan, Taiwan</p>	<h1>TEST REPORT</h1>	Reference No.: A07082312 Report No.: FCCA07082312 FCC ID: VHVBTVH1000 Page:25 of 48 Date: Sep. 10, 2007
---	----------------------	---

#### 4.5.6 TEST RESULT

Temperature:	25°C	Humidity:	62%RH
Frequency Range:	0.15 – 30 MHz	Tested Mode:	Link
Receiver Detector:	Q.P. and AV.	Tested By:	John Yu
		Tested Date:	Aug. 28, 2007

Power Line Measured : Line

Freq. (MHz)	Correct. Factor (dB)	Reading Value (dB $\mu$ V)		Emission Level (dB $\mu$ V)		Limit (dB $\mu$ V)		Margin (dB)	
		Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
0.372	0.27	43.28	29.77	43.55	30.04	59.66	49.66	-16.38	-19.89
0.495	0.25	39.80	23.93	40.05	24.18	56.14	46.14	-16.34	-22.21
0.5	0.24	39.60	25.26	39.84	25.50	56.00	46.00	-16.40	-20.74
1.408	0.15	31.76	13.64	31.91	13.79	56.00	46.00	-24.24	-32.36
10.836	0.23	25.86	4.67	26.09	4.90	60.00	50.00	-34.14	-45.33
15.8	0.27	12.86	-2.89	13.13	-2.62	60.00	50.00	-47.14	-52.89

Power Line Measured : Neutral

Freq. (MHz)	Correct. Factor (dB)	Reading Value (dB $\mu$ V)		Emission Level (dB $\mu$ V)		Limit (dB $\mu$ V)		Margin (dB)	
		Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
0.495	0.25	43.62	27.28	43.87	27.53	56.14	46.14	-12.52	-18.87
0.501	0.24	43.68	29.11	43.92	29.35	56.00	46.00	-12.32	-16.89
0.504	0.24	43.60	28.97	43.84	29.21	56.00	46.00	-12.40	-17.03
1.250	0.14	35.92	16.23	36.06	16.37	56.00	46.00	-20.08	-29.77
10.765	0.23	25.34	3.76	25.57	3.99	60.00	50.00	-34.66	-46.24
15.523	0.26	20.46	-0.11	20.72	0.15	60.00	50.00	-39.54	-50.11

#### NOTE :

1. Measurement uncertainty is +/-2dB
2. Emission level = Reading value + Correction factor
3. Correction Factor = Cable loss + Insertion loss of LISN
4. Margin value = Emission level - Limit
5. The emission of other frequencies was very low against the limit.
6. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.

 <p><b>Spectrum Research &amp; Testing Lab., Inc.</b> No. 101-10, Ling 8, Shan-Tong Li, Chung-Li City, Taoyuan, Taiwan</p>	<h1>TEST REPORT</h1>	Reference No.: A07082312 Report No.: FCCA07082312 FCC ID: VHVBTVH1000 Page:26 of 48 Date: Sep. 10, 2007
---	----------------------	---

## 4.6 RADIATED EMISSION TEST

### 4.6.1 LIMIT

FCC Part15, Subpart C Section 15.209 limit of radiated emission measurement for frequency below 1000 MHz. The emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

FREQUENCY (MHz)	DISTANCE(m)	FIELD STRENGTH (dB $\mu$ V/m)
30 – 88	3	40.0
88 - 216	3	43.5
216 - 960	3	46.0
ABOVE 960	3	54.0

**NOTE:**

1. In the emission tables above, the tighter limit applies at the band edges.
2. Distance refers to the distance between measuring instrument, antenna, and the closest point of any part of the device or system.

FCC Part 15, Subpart 15.35(b) limit of radiated emission for frequency above 1000MHz

FREQUENCY (MHz)	Class A (dB $\mu$ V/m) (at 3m)		Class B (dB $\mu$ V/m) (at 3m)	
	PK.	AV.	PK.	AV.
Above 1000	80.0	60.0	74.0	54.0

FCC Part 15, Subpart C Section 15.249. The field strength of emissions from intentional radiators operated within these frequency bands shall comply with the following:

FUNDAMENTAL FREQUENCY (MHz)	FIELD STRENGTH OF FUNDAMENTAL (dB $\mu$ V/m) (at 3m)		FIELD STRENGTH OF HARMONICS (dB $\mu$ V/m) (at 3m)	
	PK.	AV.	PK.	AV.
902-928	114	94	74.0	54.0
2400-2483.5	114	94	74.0	54.0
5725-5875	114	94	74.0	54.0
24000-24250	128	108	88	68

 <p><b>Spectrum Research &amp; Testing Lab., Inc.</b> No. 101-10, Ling 8, Shan-Tong Li, Chung-Li City, Taoyuan, Taiwan</p>	<p><b>TEST REPORT</b></p>	<p>Reference No.: A07082312 Report No.: FCCA07082312 FCC ID: VHVBTVH1000 Page:27 of 48 Date: Sep. 10, 2007</p>
---	---------------------------	--

#### 4.6.2 TEST EQUIPMENT

The following test equipment was used during the radiated emission test:


EQUIPMENT/ FACILITIES	SPECIFICATIONS	MANUFACTURER	MODEL#/ SERIAL#	DUE DATE OF CAL. & CAL. CENTER
EMI TEST RECEIVER	9kHz TO 2.75 GHz	ROHDE & SCHWARZ	ESCS30/ 830245/012	OCT. 2007 ETC
BI-LOG ANTENNA	25 MHz TO 2 GHz	EMCO	3143/ 9509-1152	JUN. 2008 SRT
PRE-AMPLIFIER	1 GHz TO 26.5 GHz	HP	8449B/ 3008A01019	AUG. 2008 ETC
HORN ANTENNA	1 GHz TO 18 GHz	EMCO	3115/ 9602-4681	DEC. 2007 ETC
OATS	3 – 10 M MEASUREMENT	SRT	SRT-1	DEC. 2007 SRT
COAXIAL CABLE	25M	SUNCITY	J400-25M-2NP/ #153-25M	JUN. 2008 SRT
FILTER	2 LINE, 30A	FIL.COIL	FC-943/ 869	N/A
FREQUENCY CONVERTER	N/A	APC	AFC-2KBB/ F100030031	AUG. 2008 SRT
SPECTRUM	9kHz TO 40GHz	ROHDE& SCHWARZ	FSP40/ 100093	STP. 2008 ETC

**NOTE:**

1. The calibration interval of the above test equipment is one year and the calibrations are traceable to NML/ROC and NIST/USA.
2. The Open Area Test Site (SRT-1) is registered by FCC with No. 90957 and VCCI with No. R-1081.
3. The Open Area Test Site (SRT-2) is registered by FCC with No. 98458 and VCCI with No. R-1168.



### 4.6.3 TEST SET-UP



#### NOTE :

1. The EUT system was put on a wooden table with 0.8m heights above a ground plane.
2. For the actual test configuration, please refer to the photos of testing.

### 4.6.4 TEST PROCEDURE

The EUT was tested according to the requirement of ANSI C63.4:2003 and CISPR 22:2006. The measurements were made at an open area test site with 10 meter measurement distance under 1 GHz and with 3m distance above 1GHz. The frequency spectrum measured started from 30 MHz. Under 1 GHz, all readings were quasi-peak values with 120 kHz resolution bandwidth of the test receiver. Above 1 GHz, the measurements were made at an open area test site with 3 meter measurement distance and all readings were peak or average values with 1 MHz resolution bandwidth of the test receiver. The EUT system was operated in all typical methods by users. The cables connected to EUT and support units were moved to find the maximum emission levels for each frequency.

First, Find the margin or higher points at least 6 points by software, then use manual to find the maximum data. The procedure is referred on the test procedure of SRT LAB.

### 4.6.5 EUT OPERATING CONDITION

Same as section 4.1.5 of this report.



**Spectrum Research &  
Testing Lab., Inc.**  
No. 101-10, Ling 8,  
Shan-Tong Li, Chung-Li  
City, Taoyuan, Taiwan

# TEST REPORT

Reference No.: A07082312  
Report No.: FCCA07082312  
FCC ID: VHVBTVH1000  
Page:29 of 48  
Date: Sep. 10, 2007

## 4.6.6 RADIATED EMISSION TEST RESULT

Temperature:	27°C	Humidity:	63%RH
Frequency Range:	30M – 1GHz	Measured Distance:	3m
Receiver Detector:	Q.P.	Tested Mode:	TX
Tested By:	John Yu	Tested Date:	Aug. 28, 2007

Antenna Polarization: Horizontal

Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Reading Data (dB $\mu$ V)	Emission Level (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)
69.7730	1.56	7.17	26.9	35.6	40.0	-4.4
397.6300	3.58	15.40	22.3	41.3	46.0	-4.7
533.4280	4.29	18.96	16.2	39.4	46.0	-6.6
666.3340	4.85	20.52	16.3	41.7	46.0	-4.3
716.7620	5.08	22.04	15.1	42.2	46.0	-3.8
797.2570	5.32	22.80	14.8	42.9	46.0	-3.1

Antenna Polarization: Vertical

Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Reading Data (dB $\mu$ V)	Emission Level (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)
37.7640	1.22	11.54	24.2	37.0	40.0	-3.0
131.8220	2.05	8.22	30.1	40.4	43.5	-3.1
398.6210	3.59	15.40	22.1	41.1	46.0	-4.9
532.4730	4.28	18.94	18.8	42.0	46.0	-4.0
644.0190	4.74	19.94	14.9	39.6	46.0	-6.4
796.2970	5.32	22.80	14.1	42.2	46.0	-3.8

### NOTE :

1. Measurement uncertainty is +/-2dB.
2. \*\*: Measurement does not apply for this frequency.
3. Emission Level = Reading Value + Ant. Factor + Cable Loss.
4. The field strength of other emission frequencies were very low against the limit.



**Spectrum Research &  
Testing Lab., Inc.**  
No. 101-10, Ling 8,  
Shan-Tong Li, Chung-Li  
City, Taoyuan, Taiwan

# TEST REPORT

Reference No.: A07082312  
Report No.: FCCA07082312  
FCC ID: VHVBTVH1000  
Page:30 of 48  
Date: Sep. 10, 2007

Temperature:	27°C	Humidity:	63%RH
Frequency Range:	30M – 1GHz	Measured Distance:	3m
Receiver Detector:	Q.P.	Tested Mode:	RX
Tested By:	John Yu	Tested Date:	Aug. 28, 2007

Antenna Polarization: Horizontal

Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Reading Data (dB $\mu$ V)	Emission Level (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)
69.4720	1.56	7.17	14.6	23.3	40.0	-16.7
398.5200	3.59	15.40	13.9	32.9	46.0	-13.1
535.4150	4.30	19.00	10.8	34.1	46.0	-11.9
666.3340	4.85	20.52	8.1	33.5	46.0	-12.5
716.3310	5.08	22.04	7.6	34.7	46.0	-11.3
797.3100	5.32	22.80	7.7	35.8	46.0	-10.2

Antenna Polarization: Vertical

Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Reading Data (dB $\mu$ V)	Emission Level (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)
37.7660	1.22	11.54	10.1	22.9	40.0	-17.1
133.5120	2.06	8.66	17.1	27.8	43.5	-15.7
399.0100	3.59	15.40	13.3	32.3	46.0	-13.7
533.4880	4.29	18.96	8.8	32.0	46.0	-14.0
644.0230	4.74	19.94	6.9	31.6	46.0	-14.4
796.2990	5.32	22.80	7.2	35.3	46.0	-10.7

**NOTE :**

1. Measurement uncertainty is +/-2dB.
2. \*\*: Measurement does not apply for this frequency.
3. Emission Level = Reading Value + Ant. Factor + Cable Loss.
4. The field strength of other emission frequencies were very low against the limit.

 <p><b>Spectrum Research &amp; Testing Lab., Inc.</b> No. 101-10, Ling 8, Shan-Tong Li, Chung-Li City, Taoyuan, Taiwan</p>	<h1>TEST REPORT</h1>	Reference No.: A07082312 Report No.: FCCA07082312 FCC ID: VHVBTVH1000 Page:31 of 48 Date: Sep. 10, 2007
---	----------------------	---

Temperature:	27°C	Humidity:	63%RH
Frequency Range:	1 – 25GHz	Measured Distance:	3m
Receiver Detector:	PK. or AV.	Tested Mode:	CH0-TX
Tested By:	John Yu	Tested Date:	Aug. 28, 2007

Antenna Polarization: Horizontal

Frequency (MHz)	Corret Factor (dB)	Antenna Factor (dB/m)	Reading (dB $\mu$ V)		Emission (dB $\mu$ V/m)		Limit (dB $\mu$ V/m)		Margin (dB)	
			PK	AV	PK	AV	PK	AV	PK	AV
2480.00	-32.19	28.73	91.7	60.4	88.2	56.9	N/A	N/A	N/A	N/A
2476.30	-32.20	28.15	51.3	33.7	47.3	29.7	74.0	54.0	-26.7	-24.3
2484.10	-32.19	28.17	56.8	34.2	52.8	30.2	74.0	54.0	-21.2	-23.8
2504.30	-32.13	28.22	47.6	*	43.7	*	74.0	54.0	-30.3	*
4960.00	-30.26	33.77	49.2	*	52.7	*	74.0	54.0	-21.3	*
7440.00	-28.95	36.45	41.4	*	48.9	*	74.0	54.0	-25.1	*

Antenna Polarization: Vertical

Frequency (MHz)	Corret Factor (dB)	Antenna Factor (dB/m)	Reading (dB $\mu$ V)		Emission (dB $\mu$ V/m)		Limit (dB $\mu$ V/m)		Margin (dB)	
			PK	AV	PK	AV	PK	AV	PK	AV
2480.00	-32.19	28.16	99.8	62.7	95.8	58.7	N/A	N/A	N/A	N/A
2476.06	-32.20	28.15	58.6	34.2	54.6	30.2	74.0	54.0	-19.4	-23.8
2484.10	-32.19	28.17	59.4	32.9	55.4	28.9	74.0	54.0	-18.6	-25.1
2504.25	-32.13	28.22	49.7	*	45.8	*	74.0	54.0	-28.2	*
4960.00	-30.26	33.77	54.6	32.9	58.1	36.4	74.0	54.0	-15.9	-17.6
7440.00	-28.95	36.45	44.2	*	51.7	*	74.0	54.0	-22.3	*

**NOTE :**

1. Measurement uncertainty is +/-2dB.
2. \*\*: Measurement does not apply for this frequency.
3. Emission Level = Reading Value + Ant. Factor + Cable Loss.
4. The field strength of other emission frequencies were very low against the limit.

 <p><b>Spectrum Research &amp; Testing Lab., Inc.</b> No. 101-10, Ling 8, Shan-Tong Li, Chung-Li City, Taoyuan, Taiwan</p>	<h1>TEST REPORT</h1>	Reference No.: A07082312 Report No.: FCCA07082312 FCC ID: VHVBTVH1000 Page:32 of 48 Date: Sep. 10, 2007
---	----------------------	---

Temperature:	27°C	Humidity:	63%RH
Frequency Range:	1 – 25GHz	Measured Distance:	3m
Receiver Detector:	PK. Or AV.	Tested Mode:	CH39-TX
Tested By:	John Yu	Tested Date:	Aug. 28, 2007

Antenna Polarization: Horizontal

Frequency (MHz)	Corret Factor (dB)	Antenna Factor (dB/m)	Reading (dB $\mu$ V)		Emission (dB $\mu$ V/m)		Limit (dB $\mu$ V/m)		Margin (dB)	
			PK	AV	PK	AV	PK	AV	PK	AV
1192.34	-33.99	24.62	62.9	40.6	53.5	31.2	74.0	54.0	-20.5	-22.8
3007.89	-32.15	31.02	52.8	*	51.7	*	74.0	54.0	-22.3	*
4892.00	-30.24	33.71	50.6	*	54.1	*	74.0	54.0	-19.9	*
5419.02	-29.43	33.97	47.9	*	52.4	*	74.0	54.0	-21.6	*
6792.81	-29.12	35.68	45.7	*	52.3	*	74.0	54.0	-21.7	*
7814.64	-28.74	36.88	44.9	*	53.0	*	74.0	54.0	-21.0	*

Antenna Polarization: Vertical

Frequency (MHz)	Corret Factor (dB)	Antenna Factor (dB/m)	Reading (dB $\mu$ V)		Emission (dB $\mu$ V/m)		Limit (dB $\mu$ V/m)		Margin (dB)	
			PK	AV	PK	AV	PK	AV	PK	AV
1322.62	-33.35	24.91	62.7	40.5	54.3	32.1	74.0	54.0	-19.7	-21.9
2995.47	-32.13	30.97	55.3	31.2	54.1	30.0	74.0	54.0	-19.9	-24.0
4934.53	-30.24	33.75	50.1	*	53.6	*	74.0	54.0	-20.4	*
5767.81	-29.44	34.05	46.9	*	51.5	*	74.0	54.0	-22.5	*
6506.40	-29.14	35.11	47.2	*	53.2	*	74.0	54.0	-20.8	*
7512.80	-29.00	36.51	42.4	*	49.9	*	74.0	54.0	-24.1	*

**NOTE :**

1. Measurement uncertainty is +/-2dB.
2. \*\*: Measurement does not apply for this frequency.
3. Emission Level = Reading Value + Ant. Factor + Cable Loss.
4. The field strength of other emission frequencies were very low against the limit.

 <p><b>Spectrum Research &amp; Testing Lab., Inc.</b> No. 101-10, Ling 8, Shan-Tong Li, Chung-Li City, Taoyuan, Taiwan</p>	<h1>TEST REPORT</h1>	Reference No.: A07082312 Report No.: FCCA07082312 FCC ID: VHVBTVH1000 Page:33 of 48 Date: Sep. 10, 2007
---	----------------------	---

Temperature:	27°C	Humidity:	63%RH
Frequency Range:	1 – 25GHz	Measured Distance:	3m
Receiver Detector:	PK. Or AV.	Tested Mode:	CH78-TX
Tested By:	John Yu	Tested Date:	Aug. 28, 2007

Antenna Polarization: Horizontal

Frequency (MHz)	Corret Factor (dB)	Antenna Factor (dB/m)	Reading (dB $\mu$ V)		Emission (dB $\mu$ V/m)		Limit (dB $\mu$ V/m)		Margin (dB)	
			PK	AV	PK	AV	PK	AV	PK	AV
1188.48	-34.05	24.61	59.8	*	50.4	*	74.0	54.0	-23.6	*
3009.04	-32.15	31.03	55.7	30.5	54.6	29.4	74.0	54.0	-19.4	-24.6
4886.57	-30.25	33.71	47.6	*	51.1	*	74.0	54.0	-22.9	*
5669.18	-29.42	34.03	51.9	*	56.5	*	74.0	54.0	-17.5	*
6818.12	-29.16	35.74	42.5	*	49.0	*	74.0	54.0	-25.0	*
7741.26	-28.84	36.79	42.8	*	50.8	*	74.0	54.0	-23.2	*

Antenna Polarization: Vertical

Frequency (MHz)	Corret Factor (dB)	Antenna Factor (dB/m)	Reading (dB $\mu$ V)		Emission (dB $\mu$ V/m)		Limit (dB $\mu$ V/m)		Margin (dB)	
			PK	AV	PK	AV	PK	AV	PK	AV
1322.59	-33.35	24.91	62.1	42.0	53.7	33.6	74.0	54.0	-20.3	-20.4
2995.47	-32.13	30.97	57.6	33.4	56.4	32.2	74.0	54.0	-17.6	-21.8
3943.74	-30.35	32.32	49.1	*	51.1	*	74.0	54.0	-22.9	*
5767.81	-29.44	34.05	49.5	*	54.1	*	74.0	54.0	-19.9	*
6509.32	-29.15	35.12	42.7	*	48.7	*	74.0	54.0	-25.3	*
7512.60	-29.00	36.51	42.9	*	50.4	*	74.0	54.0	-23.6	*

**NOTE :**

1. Measurement uncertainty is +/-2dB.
2. \*\*: Measurement does not apply for this frequency.
3. Emission Level = Reading Value + Ant. Factor + Cable Loss.
4. The field strength of other emission frequencies were very low against the limit.

 <p><b>Spectrum Research &amp; Testing Lab., Inc.</b> No. 101-10, Ling 8, Shan-Tong Li, Chung-Li City, Taoyuan, Taiwan</p>	<h1>TEST REPORT</h1>	Reference No.: A07082312 Report No.: FCCA07082312 FCC ID: VHVBTvh1000 Page:34 of 48 Date: Sep. 10, 2007
---	----------------------	---

## 4.7 PEAK POWER TEST

### 4.7.1 LIMIT

FCC Part15, Subpart C Section 15.247.

Frequency Range (MHz)	Limit(w)				
	Quantity of Hopping Channel	50	25	15	75
902-928	1(30dBm)	0.125(21dBm)	NA	NA	NA
2400-2483.5	NA	NA	0.125(21dBm)	1(30dBm)	
5725-5850	NA	NA	NA	NA	1(30dBm)

### 4.7.2 TEST EQUIPMENT

The following test equipment was used during the test :

Equipment/ Facilities	Specifications	Manufacturer	Model#/ Serial#	Due Date of Cal. & Cal. Center
SPECTRUM	9kHz-7GHz	ROHDE & SCHWARZ	FSP7/ 839511/010	JUN. 2008 ETC
POWER METER	N/A	BOONTON	4232A/ 29001	JAN 2008 ETC
POWER SENSOR	DC-18GHz 0.3 $\mu$ W-100mW 50 $\Omega$	BOONTON	51011-EMC/ 31184	JUN. 2008 ETC

**NOTE:** The calibration interval of the above test equipment is one year and the calibrations are traceable to NML/ROC and NIST/USA.




**Spectrum Research &  
Testing Lab., Inc.**  
No. 101-10, Ling 8,  
Shan-Tong Li, Chung-Li  
City, Taoyuan, Taiwan

## TEST REPORT

Reference No.: A07082312  
Report No.: FCCA07082312  
FCC ID: VHVBTVH1000  
Page:35 of 48  
Date: Sep. 10, 2007

### 4.7.3 TEST SET-UP



The EUT was connected to a spectrum through a  $50\Omega$  RF cable.

### 4.7.4 TEST PROCEDURE

The EUT was operating in hopping mode or could control its channel.  
Printed out the test result from the spectrum by hard copy function.  
Recorded the read value of the power meter.

### 4.6.5 EUT OPERATING CONDITION

Same as section 4.1.5 of this report.

### 4.7.6 TEST RESULT

Temperature:	25°C	Humidity:	65%RH
Spectrum Detector:	PK	Tested by:	John Yu
Test Result:	PASS	Tested Date:	Aug. 27, 2007

Channel Number	Channel Frequency (MHz)	Peak Output Power (dBm)	Peak Power Limit (dBm)
0	2402.0000	-3.51	30
39	2441.0000	-2.31	30
78	2480.0000	-2.07	30




**Spectrum Research &  
Testing Lab., Inc.**  
No. 101-10, Ling 8,  
Shan-Tong Li, Chung-Li  
City, Taoyuan, Taiwan

# TEST REPORT

Reference No.: A07082312  
Report No.: FCCA07082312  
FCC ID: VHVBTvh1000  
Page:36 of 48  
Date: Sep. 10, 2007

CH0:



Comment: Peak Power CH00  
Date: 27.AUG.2007 16:21:32




**Spectrum Research &  
Testing Lab., Inc.**  
No. 101-10, Ling 8,  
Shan-Tong Li, Chung-Li  
City, Taoyuan, Taiwan

# TEST REPORT

Reference No.: A07082312  
Report No.: FCCA07082312  
FCC ID: VHVBTvh1000  
Page:37 of 48  
Date: Sep. 10, 2007

CH39:



Comment: Peak Power CH39  
Date: 27.AUG.2007 16:22:26




**Spectrum Research &  
Testing Lab., Inc.**  
No. 101-10, Ling 8,  
Shan-Tong Li, Chung-Li  
City, Taoyuan, Taiwan

# TEST REPORT

Reference No.: A07082312  
Report No.: FCCA07082312  
FCC ID: VHVBTvh1000  
Page:38 of 48  
Date: Sep. 10, 2007

CH78:



Comment: Peak Power CH78  
Date: 27.AUG.2007 16:23:41

 <p><b>Spectrum Research &amp; Testing Lab., Inc.</b> No. 101-10, Ling 8, Shan-Tong Li, Chung-Li City, Taoyuan, Taiwan</p>	<p><b>TEST REPORT</b></p>	<p>Reference No.: A07082312 Report No.: FCCA07082312 FCC ID: VHVBTVH1000 Page:39 of 48 Date: Sep. 10, 2007</p>
---	---------------------------	--

## 4.8 BAND EDGE TEST

### 4.8.1 LIMIT

FCC Part15, Subpart C Section 15.249 (c), Emission radiated outside of the specified frequency bands, except for harmonics, shall attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in Section 15.209, whichever is the lesser attenuation.

Operating Frequency Range (MHz)	Limit (dB $\mu$ V/m)	
	Peak	Average
902-928		
2400-2483.5	74	54
5725-5850		

### 4.8.2 TEST EQUIPMENT

The following test equipment was used during the test :

Equipment/ Facilities	Specification	Manufacturer	Model#/ Serial#	Due Date of Cal. & Cal. Center
SPECTRUM	9kHz-7GHz	ROHDE & SCHWARZ	FSP7/ 839511/010	JUN. 2008 R&S
SPECTRUM	9KHz-40GHz	ROHDE & SCHWARZ	FSP40/ 100093	SEP. 2008 ETC
PRE-AMPLIFIER	1GHz-26.5GHz Gain:30dB	HP	8449B/ 3008A01019	NOV. 2007 ETC
BI-LOG ANTENNA	25 MHz TO 2 GHz	EMCO	3142/ 9701-1124	FEB. 2008 SRT
HORN ANTENNA	1GHz to 18GHz	EMCO	3115/ 9602-4681	DEC. 2007 ETC
OATS	3 - 10 M measurement	SRT	SRT-1	APR. 2008 SRT

**NOTE:** The calibration interval of the above test equipment is one year and the calibrations are traceable to NML/ROC and NIST/USA.




**Spectrum Research &  
Testing Lab., Inc.**  
No. 101-10, Ling 8,  
Shan-Tong Li, Chung-Li  
City, Taoyuan, Taiwan

# TEST REPORT

Reference No.: A07082312  
Report No.: FCCA07082312  
FCC ID: VHVBTvh1000  
Page:40 of 48  
Date: Sep. 10, 2007


## 4.8.3 TEST SET-UP

### FOR RF CONDUCTED TEST (dBc)



The EUT was connected to the spectrum through a  $50\Omega$  RF cable.

### FOR RADIATED EMISSION TEST



#### NOTE :

1. The EUT system was put on a wooden table with 0.8m heights above a ground plane.
2. For the actual test configuration, please refer to the photos of testing.

 <p><b>Spectrum Research &amp; Testing Lab., Inc.</b> No. 101-10, Ling 8, Shan-Tong Li, Chung-Li City, Taoyuan, Taiwan</p>	<p><b>TEST REPORT</b></p>	<p>Reference No.: A07082312 Report No.: FCCA07082312 FCC ID: VHVBTVH1000 Page:41 of 48 Date: Sep. 10, 2007</p>
---	---------------------------	--

#### 4.8.4 TEST PROCEDURE

1. The EUT was operating in hopping mode or could be controlled its channel.  
Printed out the test result from the spectrum by hard copy function.
2. The EUT was tested according to the requirement of ANSI C63.4 and CISPR 22. The measurements were made at an open area test site with 10 meter measurement distance under 1 GHz and with 3m distance above 1GHz. The frequency spectrum measured started from 30 MHz. Under 1 GHz. All readings were quasi-peak values with 120 kHz resolution bandwidth of the test receiver. Above 1 GHz, the measurements were made at an open area test site with 3 meter measurement distance and all readings were peak and average values with 1 MHz resolution bandwidth of the test receiver. The EUT system was operated in all typical methods by users. The cables connected to EUT and support units were moved to find the maximum emission levels for each frequency.

#### 4.8.5 EUT OPERATING CONDITION

Same as section 4.1.5 of this report.

#### 4.8.6 TEST RESULT

Temperature:	24°C	Humidity:	57%RH
Spectrum Detector:	PK & AV	Tested by:	John Yu
Test Result:	PASS	Tested Date:	Aug. 29, 2007

##### 1. Conducted emission test

Frequency (MHz)	PEAK POWER OUTPUT (dBm)	Emission read Value(dBm)	Result of Band edge (dBc)	Band edge LIMIT (dBc)
<2400	-3.90	-28.55	24.65	>20dBc
>2480	-2.64	-29.34	26.7	>20dBc

##### 2. Radiated emission test

Frequency (MHz)	Antenna polarization (H/V)	Reading (dBuV)		Emission (dBuV/m)		Band edge Limit (dBuV/m)	
		PK	AV	PK	AV	PK	AV
<2400	H	23.6	*	21.8	*	74.0	54.0
>2483.5	V	22.8	*	20.5	*	74.0	54.0




**Spectrum Research &  
Testing Lab., Inc.**  
No. 101-10, Ling 8,  
Shan-Tong Li, Chung-Li  
City, Taoyuan, Taiwan

# TEST REPORT

Reference No.: A07082312  
Report No.: FCCA07082312  
FCC ID: VHVBTvh1000  
Page:42 of 48  
Date: Sep. 10, 2007

CH0: (for Conducted emission only)



Comment: Band Edge Lower  
Date: 27.AUG.2007 16:44:03




**Spectrum Research &  
Testing Lab., Inc.**  
No. 101-10, Ling 8,  
Shan-Tong Li, Chung-Li  
City, Taoyuan, Taiwan

# TEST REPORT

Reference No.: A07082312  
Report No.: FCCA07082312  
FCC ID: VHVBTvh1000  
Page:43 of 48  
Date: Sep. 10, 2007

CH78: (for Conducted emission only)



Comment: Band Edge Upper  
Date: 27.AUG.2007 16:53:58



**Spectrum Research &  
Testing Lab., Inc.**  
No. 101-10, Ling 8,  
Shan-Tong Li, Chung-Li  
City, Taoyuan, Taiwan

## TEST REPORT

Reference No.: A07082312  
Report No.: FCCA07082312  
FCC ID: VHVBTvh1000  
Page:44 of 48  
Date: Sep. 10, 2007

## 5 ANTENNA APPLICATION

### 5.1 Antenna requirement

The EUT's antenna is met the requirement of FCC part15C section15.203 and 15.204.

### 5.2 Result

The EUT's antenna used a Ceramic Chip antenna and integrated on PCB. The antenna's gain is -2 dBi and meets the requirement.



**Spectrum Research &  
Testing Lab., Inc.**  
No. 101-10, Ling 8,  
Shan-Tong Li, Chung-Li  
City, Taoyuan, Taiwan

# TEST REPORT

Reference No.: A07082312  
Report No.: FCCA07082312  
FCC ID: VHVBTvh1000  
Page:48 of 48  
Date: Sep. 10, 2007

## 7. TERMS OF ABBREVIATION

AV.	Average detection
AZ(°)	Turn table azimuth
Correct.	Correction
EL(m)	Antenna height (meter)
EUT	Equipment Under Test
Horiz.	Horizontal direction
LISN	Line Impedance Stabilization Network
NSA	Normalized Site Attenuation
Q.P.	Quasi-peak detection
SRT Lab	Spectrum Research & Testing Laboratory, Inc.
Vert.	Vertical direction