

FCC TEST REPORT

Client Name : Elexa Consumer Products, Inc.
Address : 2275 HALF DAY RD STE 160, STE 160, Bannockburn,
Illinois, United States 60015
Product Name : Leak sensor
Date : Dec. 09, 2020



Shenzhen Anbotek Compliance Laboratory Limited

Contents

1. General Information.....	5
1.1. Client Information.....	5
1.2. Description of Device (EUT).....	5
1.3. Auxiliary Equipment Used During Test.....	6
1.4. Description of Test Modes.....	6
1.5. List of channels.....	7
1.6. Description Of Test Setup.....	8
1.7. Test Equipment List.....	9
1.8. Measurement Uncertainty.....	10
1.9. Description of Test Facility.....	10
2. Summary of Test Results.....	11
3. Conducted Emission Test.....	12
3.1. Test Standard and Limit.....	12
3.2. Test Setup.....	12
3.3. Test Procedure.....	12
3.4. Test Data.....	12
4. Radiation Spurious Emission and Band Edge.....	13
4.1. Test Standard and Limit.....	13
4.2. Test Setup.....	13
4.3. Test Procedure.....	14
4.4. Test Data.....	15
5. Maximum Peak Output Power Test.....	21
5.1. Test Standard and Limit.....	21
5.2. Test Setup.....	21
5.3. Test Procedure.....	21
5.4. Test Data.....	21
6. 20DB Occupy Bandwidth Test.....	24
6.1. Test Standard.....	24
6.2. Test Setup.....	24
6.3. Test Procedure.....	24
6.4. Test Data.....	24
7. Carrier Frequency Separation Test.....	27
7.1. Test Standard and Limit.....	27
7.2. Test Setup.....	27
7.3. Test Procedure.....	27
7.4. Test Data.....	27
8. Number of Hopping Channel Test.....	30
8.1. Test Standard and Limit.....	30

8.2. Test Setup..... 30

8.3. Test Procedure..... 30

8.4. Test Data..... 30

9. Dwell Time Test..... 32

9.1. Test Standard and Limit..... 32

9.2. Test Setup..... 32

9.3. Test Procedure..... 32

9.4. Test Data..... 32

10. 100kHz Bandwidth of Frequency Band Edge Requirement..... 36

10.1. Test Standard and Limit..... 36

10.2. Test Setup..... 36

10.3. Test Procedure..... 36

10.4. Test Data..... 36

11. Antenna Requirement..... 40

11.1. Test Standard and Requirement..... 40

11.2. Antenna Connected Construction..... 40

APPENDIX I -- TEST SETUP PHOTOGRAPH..... 41

APPENDIX II -- EXTERNAL PHOTOGRAPH..... 41

APPENDIX III -- INTERNAL PHOTOGRAPH..... 41

TEST REPORT

Applicant : Elexa Consumer Products, Inc.
Manufacturer : Elexa Consumer Products, Inc.
Product Name : Leak sensor
Model No. : LWGLD1
Trade Mark : N.A.
Rating(s) : Input: DC 3.0V, 2400mAh Battery inside

Test Standard(s) : FCC Part15 Subpart C 2019, Section 15.247

Test Method(s) : ANSI C63.10: 2013, KDB558074 D01 DTS Meas Guidance v05r02

The device described above is tested by Shenzhen Anbotek Compliance Laboratory Limited to determine the maximum emission levels emanating from the device and the severe levels of the device can endure and its performance criterion. The measurement results are contained in this test report and Shenzhen Anbotek Compliance Laboratory Limited is assumed full of responsibility for the accuracy and completeness of these measurements. Also, this report shows that the EUT (Equipment Under Test) is technically compliant with the FCC Part 15 Subpart C requirements.

This report applies to above tested sample only and shall not be reproduced in part without written approval of Shenzhen Anbotek Compliance Laboratory Limited.

Date of receipt

May 12, 2020

Date of Test


May 12~29, 2020

Prepared by



(Engineer / Yilia Zhong)

Reviewer



(Supervisor / Bibo Zhang)

Approved & Authorized Signer



(Manager / Kingkong Jin)

1. General Information

1.1. Client Information

Applicant	:	Elexa Consumer Products, Inc.
Address	:	2275 HALF DAY RD STE 160, STE 160, Bannockburn, Illinois, United States 60015
Manufacturer	:	Elexa Consumer Products, Inc.
Address	:	2275 HALF DAY RD STE 160, STE 160, Bannockburn, Illinois, United States 60015
Factory	:	Elexa Consumer Products, Inc.
Address	:	2275 HALF DAY RD STE 160, STE 160, Bannockburn, Illinois, United States 60015

1.2. Description of Device (EUT)

Product Name	:	Leak sensor	
Model No.	:	LWGLD1	
Trade Mark	:	N.A.	
Test Power Supply	:	DC 3.0V Battery inside	
Test Sample No.	:	1-2-1(Normal Sample), 1-2-2(Engineering Sample)	
Product Description	:	Operation Frequency:	902.3-914.9MHz 903-914.2MHz
		Number of Channel:	64 Channels 8 Channels
		Modulation Type:	LORA
		Antenna Type:	Spring Antenna
		Antenna Gain(Peak):	0 dBi
Remark: 1) For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.			

1.3. Auxiliary Equipment Used During Test

N/A

1.4. Description of Test Modes

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

TEST MODE:

Mode 1	LORA	CH01	TX Only
Mode 2		CH33	
Mode 3		CH64	

Note:

- (1) The measurements are performed at the highest, middle, lowest available channels.
- (2)The data rate was set in 1Mbps for radiated emission due to the highest RF output power.


1.5. List of channels

Channel	Freq. (MHz)	Channel	Freq. (MHz)	Channel	Freq. (MHz)	Channel	Freq. (MHz)	Channel	Freq. (MHz)
1	902.3	14	904.9	27	907.5	40	910.1	53	912.7
2	902.5	15	905.1	28	907.7	41	910.3	54	912.9
3	902.7	16	905.3	29	907.9	42	910.5	55	913.1
4	902.9	17	905.5	30	908.1	43	910.7	56	913.3
5	903.1	18	905.7	31	908.3	44	910.9	57	913.5
5	903.3	19	905.9	32	908.5	45	911.1	58	913.7
7	903.5	20	906.1	33	908.7	46	911.3	59	913.9
8	903.7	21	906.3	34	908.9	47	911.5	60	914.1
9	903.9	22	906.5	35	909.1	48	911.7	61	914.3
10	904.1	23	906.7	36	909.3	49	911.9	62	914.5
11	905.1	24	906.9	37	909.5	50	912.1	63	914.7
12	904.5	25	907.1	38	909.7	51	912.3	64	914.9
13	904.7	26	907.3	39	909.9	52	912.5		

Note:

1. The engineering test program was provided and the EUT was programmed to be in continuously transmitting mode.

1.6. Description Of Test Setup



1.7. Test Equipment List

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	L.I.S.N. Artificial Mains Network	Rohde & Schwarz	ENV216	100055	Nov. 04, 2019	1 Year
2.	EMI Test Receiver	Rohde & Schwarz	ESPI3	101604	Nov. 04, 2019	1 Year
3.	RF Switching Unit	Compliance Direction	RSU-M2	38303	Nov. 04, 2019	1 Year
4.	MAX Spectrum Analysis	Agilent	N9020A	MY51170037	Nov. 04, 2019	1 Year
5.	Preamplifier	SKET Electronic	BK1G18G30 D	KD17503	Nov. 04, 2019	1 Year
6.	Double Ridged Horn Antenna	Instruments corporation	GTH-0118	351600	Nov. 01, 2019	1 Year
7.	Bilog Broadband Antenna	Schwarzbeck	VULB9163	VULB 9163-289	Nov. 01, 2019	1 Year
8.	Loop Antenna	Schwarzbeck	FMZB1519B	00053	Nov. 01, 2019	1 Year
9.	Horn Antenna	A-INFO	LB-180400-K F	J211060628	Nov. 01, 2019	1 Year
10.	Pre-amplifier	SONOMA	310N	186860	Nov. 04, 2019	1 Year
11.	EMI Test Software EZ-EMC	SHURPLE	N/A	N/A	N/A	N/A
12.	RF Test Control System	YIHENG	YH3000	2017430	Nov. 04, 2019	1 Year
13.	Power Sensor	DAER	RPR3006W	15I00041SN045	Nov. 04, 2019	1 Year
14.	Power Sensor	DAER	RPR3006W	15I00041SN046	Nov. 04, 2019	1 Year
15.	MXA Spectrum Analysis	Agilent	N9020A	MY51170037	Nov. 04, 2019	1 Year
16.	MXG RF Vector Signal Generator	Agilent	N5182A	MY48180656	Nov. 04, 2019	1 Year
17.	Signal Generator	Agilent	E4421B	MY41000743	Nov. 04, 2019	1 Year
18.	DC Power Supply	LW	TPR-6420D	374470	Nov. 04, 2019	1 Year
19.	Constant Temperature Humidity Chamber	ZHONGJIAN	ZJ-KHWS80 B	N/A	Nov. 04, 2019	1 Year

1.8. Measurement Uncertainty

Radiation Uncertainty	:	Ur = 3.9 dB (Horizontal)
		Ur = 3.8 dB (Vertical)
Conduction Uncertainty	:	Uc = 3.4 dB

1.9. Description of Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

FCC-Registration No.: 184111

Shenzhen Anbotek Compliance Laboratory Limited, EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration No. 184111, September 30, 2020.

ISED-Registration No.: 8058A

Shenzhen Anbotek Compliance Laboratory Limited, EMC Laboratory has been registered and fully described in a report filed with the (ISED) Innovation, Science and Economic Development Canada. The acceptance letter from the ISED is maintained in our files. Registration 8058A, September 30, 2020.

Test Location

Shenzhen Anbotek Compliance Laboratory Limited.

1/F, Building D, Sogood Science and Technology Park, Sanwei community, Hangcheng Street, Bao'an District, Shenzhen, Guangdong, China.518102

2. Summary of Test Results

Standard Section	Test Item	Result
15.203/15.247(c)	Antenna Requirement	PASS
15.207	Conducted Emission	N/A
15.205/15.209	Spurious Emission	PASS
15.247(b)(1)	Conducted Peak Output Power	PASS
15.247(a)(1)	20dB Occupied Bandwidth	PASS
15.247(a)(1)	Carrier Frequencies Separation	PASS
15.247(a)(1)	Hopping Channel Number	PASS
15.247(a)(1)	Dwell Time	PASS
15.247(d)	Band Edge	PASS
Remark: "N/A" is an abbreviation for Not Applicable.		


3. Conducted Emission Test

3.1. Test Standard and Limit

Test Standard	FCC Part15 Section 15.207		
	Frequency	Maximum RF Line Voltage (dBuV)	
		Quasi-peak Level	Average Level
Test Limit	150kHz~500kHz	66 ~ 56 *	56 ~ 46 *
	500kHz~5MHz	56	46
	5MHz~30MHz	60	50

Remark: (1) *Decreasing linearly with logarithm of the frequency.
 (2) The lower limit shall apply at the transition frequency.

3.2. Test Setup



3.3. Test Procedure

The EUT system is connected to the power mains through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm coupling impedance for the EUT system. Please refer the block diagram of the test setup and photographs. Both sides of AC line are checked to find out the maximum conducted emission. In order to find the maximum emission levels, the relative positions of equipment and all of the interface cables shall be changed according to FCC ANSI C63.10-2013 on Conducted Emission Measurement.

The bandwidth of test receiver (ESCI) set at 9kHz.

The frequency range from 150kHz to 30MHz is checked.

3.4. Test Data

The EUT is powered by DC 3.0V Battery inside inside, so there is no need to conduct this test.

4. Radiation Spurious Emission and Band Edge

4.1. Test Standard and Limit

Test Standard	FCC Part15 C Section 15.209 and 15.205				
Test Limit	Frequency (MHz)	Field strength (microvolt/meter)	Limit (dBuV/m)	Remark	Measurement distance (m)
	0.009MHz~0.490MHz	2400/F(kHz)	-	-	300
	0.490MHz-1.705MHz	24000/F(kHz)	-	-	30
	1.705MHz-30MHz	30	-	-	30
	30MHz~88MHz	100	40.0	Quasi-peak	3
	88MHz~216MHz	150	43.5	Quasi-peak	3
	216MHz~960MHz	200	46.0	Quasi-peak	3
	960MHz~1000MHz	500	54.0	Quasi-peak	3
	Above 1000MHz	500	54.0	Average	3
-		-	74.0	Peak	3

Remark:

(1)The lower limit shall apply at the transition frequency.

(2) 15.35(b), Unless otherwise specified, the limit on peak radio frequency emissions is 20dB above the maximum permitted average emission limit applicable to the equipment under test. This peak limit applies to the total peak emission level radiated by the device.

4.2. Test Setup




Figure 1. Below 30MHz




Figure 2. 30MHz to 1GHz




Figure 3. Above 1 GHz

4.3. Test Procedure

For below 1GHz: The EUT is placed on a turntable, which is 0.8m above the ground plane.

For above 1GHz: The EUT is placed on a turntable, which is 1.5m above the ground plane.

The turn table can rotate 360 degrees to determine the position of the maximum emission level. The EUT is set 3 meters away from the receiving antenna which is mounted on a antenna tower. The antenna can be moved up and down from 1 to 4 meters to find out the maximum emission level. Rotated the EUT through three orthogonal axes to determine the maximum emissions, both horizontal and vertical polarization of the antenna are set on test. The EUT is tested in 9*6*6 Chamber. The device is evaluated in xyz orientation.

For the radiated emission test above 1GHz:

Shenzhen Anbotek Compliance Laboratory Limited

Code:AB-RF-05-a

Address: 1/F., Building D, Sogood Science and Technology Park, Sanwei Community, Hangcheng Street, Bao'an District, Shenzhen, Guangdong, China.
Tel: (86) 755-26066440 Fax: (86) 755-26014772 Email: service@anbotek.com

Hotline
400-003-0500
www.anbotek.com

Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.

For 9kHz to 150kHz, Set the spectrum analyzer as:

RBW = 200Hz, VBW = 1kHz, Detector= Quasi-Peak, Trace mode= Max hold, Sweep- auto couple.

For 150kHz to 30MHz, Set the spectrum analyzer as:

RBW = 9kHz, VBW = 30kHz, Detector= Quasi-Peak, Trace mode= Max hold, Sweep- auto couple.

For 30MHz to 1000MHz, Set the spectrum analyzer as:

RBW = 100kHz, VBW = 300kHz, Detector= Quasi-Peak, Trace mode= Max hold, Sweep- auto couple.

For above 1GHz, Set the spectrum analyzer as:

RBW = 1MHz, VBW = 1MHz, Detector= Peak, Trace mode= Max hold, Sweep- auto couple.

RBW = 1MHz, VBW = 10Hz, Detector= Average, Trace mode= Max hold, Sweep- auto couple.

4.4. Test Data

PASS

During the test, Pre-scan all kind of the place mode (X-axis, Y-axis, Z-axis), and found the X-axis is the worst case.


The test results of 9kHz-30MHz was attenuated more than 20dB below the permissible limits, so the results don't record in the report.

During the test, pre-scan all the modes, and found the middle channel which is the worst case, only the worst case is recorded in the report.



Test Results (30~1000MHz)


Test Mode: Mode 2
 Power Source: DC 3.0V Battery inside
 Polarization: Vertical
 Temp.(°C)/Hum.(%RH): 24.7°C/48%RH



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Detector	Height (cm)	degree (deg)	Remark
1	33.2112	28.35	-16.61	11.74	40.00	-28.26	QP	100	0	
2	48.5016	30.64	-14.63	16.01	40.00	-23.99	QP	100	360	
3	77.8654	32.42	-17.98	14.44	40.00	-25.56	QP	100	0	
4	135.9822	33.35	-19.79	13.56	43.50	-29.94	QP	100	360	
5	181.2834	31.89	-18.18	13.71	43.50	-29.79	QP	100	360	
6	323.3204	30.18	-12.74	17.44	46.00	-28.56	QP	100	0	

Test Results (30~1000MHz)

Test Mode: Mode 2
 Power Source: DC 3.0V Battery inside
 Polarization: Horizontal
 Temp.(°C)/Hum.(%RH): 24.7°C/48%RH



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Detector	Height (cm)	degree (deg)	Remark
1	49.7068	30.04	-14.81	15.23	40.00	-24.77	QP	100	0	
2	66.9669	29.33	-19.11	10.22	40.00	-29.78	QP	100	360	
3	112.9196	32.91	-21.44	11.47	43.50	-32.03	QP	100	0	
4	144.8418	32.20	-20.81	11.39	43.50	-32.11	QP	100	360	
5	262.8955	33.13	-17.67	15.46	46.00	-30.54	QP	100	0	
6	351.7079	30.89	-12.98	17.91	46.00	-28.09	QP	100	360	

Test Results (1GHz-25GHz)

Low Channel


Frequency	Antenna	Reading	Cable Loss	Ant Factor	Amplifier	Level	Limits	Margin	Det.
(MHz)	Pol.	(dBuV/m)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	Mode
1804.6000	H	50.31	7.39	28.73	26.31	60.12	74	-13.88	PK
1804.6000	H	38.96	7.39	28.73	26.31	48.77	54	-5.23	AV
2706.9000	H	48.83	8.10	29.71	27.01	59.63	74	-14.37	PK
2706.9000	H	35.73	8.10	29.71	27.01	46.53	54	-7.47	AV
3609.2000	H	--	--	--	--	--	--	--	PK
3609.2000	H	--	--	--	--	--	--	--	AV
1804.6000	V	48.38	7.39	28.73	26.31	58.19	74	-15.81	PK
1804.6000	V	35.48	7.39	28.73	26.31	45.29	54	-8.71	AV
2706.9000	V	48.56	8.10	29.71	27.01	59.36	74	-14.64	PK
2706.9000	V	35.82	8.10	29.71	27.01	46.62	54	-7.38	AV
3609.2000	V	--	--	--	--	--	--	--	PK
3609.2000	V	--	--	--	--	--	--	--	AV

Middle Channel

Shenzhen Anbotek Compliance Laboratory Limited

Address: 1/F., Building D, Sogood Science and Technology Park, Sanwei Community, Hangcheng Street, Bao'an District, Shenzhen, Guangdong, China.
Tel: (86) 755-26066440 Fax: (86) 755-26014772 Email: service@anbotek.com

Code: AB-RF-05-a

 Hotline
400-003-0500
www.anbotek.com

Frequency	Antenna	Reading	Cable Loss	Ant Factor	Amplifier	Level	Limits	Margin	Det.
(MHz)	Pol.	(dBuV/m)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	Mode
1817.4000	H	47.81	7.41	28.72	26.31	57.63	74	-16.37	PK
1817.4000	H	38.27	7.41	28.72	26.31	48.09	54	-5.91	AV
2726.1000	H	45.15	8.11	29.71	27.01	55.96	74	-18.04	PK
2726.1000	H	34.3	8.11	29.71	27.01	45.11	54	-8.89	AV
3634.8000	H	--	--	--	--	--	--	--	PK
3634.8000	H	--	--	--	--	--	--	--	AV
1817.4000	V	48.57	7.41	28.72	26.31	58.39	74	-15.61	PK
1817.4000	V	39.53	7.41	28.72	26.31	49.35	54	-4.65	AV
2726.1000	V	48.41	8.11	29.71	27.01	59.22	74	-14.78	PK
2726.1000	V	38.12	8.11	29.71	27.01	48.93	54	-5.07	AV
3634.8000	V	--	--	--	--	--	--	--	PK
3634.8000	V	--	--	--	--	--	--	--	AV

High Channel

Shenzhen Anbotek Compliance Laboratory Limited

Address: 1/F., Building D, Sogood Science and Technology Park, Sanwei Community, Hangcheng Street, Bao'an District, Shenzhen, Guangdong, China.
Tel: (86) 755-26066440 Fax: (86) 755-26014772 Email: service@anbotek.com

Code: AB-RF-05-a

 Hotline
400-003-0500
www.anbotek.com

Frequency	Antenna	Reading	Cable Loss	Ant Factor	Amplifier	Level	Limits	Margin	Det.
(MHz)	Pol.	(dBuV/m)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	Mode
1829.8000	H	49.55	7.43	28.69	26.31	59.36	74	-14.64	PK
1829.8000	H	37.3	7.43	28.69	26.31	47.11	54	-6.89	AV
2744.7000	H	45.4	8.15	29.84	27.01	56.38	74	-17.62	PK
2744.7000	H	36.28	8.15	29.84	27.01	47.26	54	-6.74	AV
3659.6000	H	--	--	--	--	--	--	--	PK
3659.6000	H	--	--	--	--	--	--	--	AV
1829.8000	V	47.3	7.43	28.69	26.31	57.11	74	-16.89	PK
1829.8000	V	38.48	7.43	28.69	26.31	48.29	54	-5.71	AV
2744.7000	V	48.23	8.15	29.84	27.01	59.21	74	-14.79	PK
2744.7000	V	36.94	8.15	29.84	27.01	47.92	54	-6.08	AV
3659.6000	V	--	--	--	--	--	--	--	PK
3659.6000	V	--	--	--	--	--	--	--	AV

Remark:

1. Level = Reading + Cable Loss+Ant Factor-Amplifier
2. "--" Mark indicated Background Noise Level

Radiated Band Edge:

Frequency (MHz)	Read Level (dBuV/m)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Pol.	Det
902.3000	42.05	22.45	4.48	31.33	37.65	46.00	-8.35	H	QP
914.9000	42.38	22.59	4.54	31.35	38.16	46.00	-7.84	H	QP
902.3000	41.35	22.45	4.48	31.33	36.95	46.00	-9.05	V	QP
914.9000	41.66	22.59	4.54	31.35	37.44	46.00	-8.56	V	QP

5. Maximum Peak Output Power Test


5.1. Test Standard and Limit

Test Standard	FCC Part15 C Section 15.247 (b)(2)& (b)(4)
---------------	--

The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

For frequency hopping systems operating in the 902-928 MHz band: 1 watt for systems employing at least 50 hopping channels; and, 0.25 watts for systems employing less than 50 hopping channels, but at least 25 hopping channels, as permitted under paragraph (a)(1)(i) of this section.

5.2. Test Setup




5.3. Test Procedure

- The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram above,
- Spectrum Setting:
 - RBW > the 20 dB bandwidth of the emission being measured
 - Span = approximately 5 times the 20 dB bandwidth, centered on a hopping channel
 - VBW ≥ RBW
 - Sweep = auto
 - Detector function = peak
 - Trace = max hold


5.4. Test Data

Test Item	: Max. peak output power	Test Mode	: CH Low ~ CH High
Test Voltage	: DC 3.0V Battery inside	Temperature	: 23.1°C
Test Result	: PASS	Humidity	: 52%RH


Channel Frequency (MHz)	Peak Power output (dBm)	Limit (dBm)	Results
902.3	14.844	30	PASS
908.7	14.784	30	PASS
914.9	14.729	30	PASS



Low Channel



Middle Channel




High Channel

6. 20DB Occupy Bandwidth Test

6.1. Test Standard

Test Standard	FCC Part15 C Section 15.247 (a)(1)
---------------	------------------------------------

6.2. Test Setup



6.3. Test Procedure


Using the following spectrum analyzer settings:

1. Span= approximately 2 to 3 times the 20dB bandwidth, centered on a hopping channel.
2. Set the RBW = 30 kHz.
3. Set the VBW = 100 kHz.
4. Sweep time = auto couple.
5. Detector function = peak.
6. Trace mode = max hold.
7. Allow trace to fully stabilize.


6.4. Test Data

Test Item	: 20dB BW	Test Mode	: CH Low ~ CH High
Test Voltage	: DC 3.0V Battery inside	Temperature	: 23.1°C
Test Result	: PASS	Humidity	: 52%RH


Channel	Frequency(MHz)	20dB Down BW(kHz)	Limit(MHz)	Verdict
Low	902.3	139.4	0.250	PASS
Middle	908.7	139.7	0.250	PASS
High	914.9	139.3	0.250	PASS



Low



Middle




High

7. Carrier Frequency Separation Test

7.1. Test Standard and Limit

Test Standard	FCC Part15 C Section 15.247 (a)(1)
Test Limit	a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater

7.2. Test Setup



7.3. Test Procedure


The EUT must have its hopping function enabled. Using the following spectrum analyzer settings:

1. Span= Wide enough to capture the peaks of two adjacent channels
2. Set the RBW = 30 kHz.
3. Set the VBW = 100 kHz.
4. Sweep time = auto couple.
5. Detector function = peak.
6. Trace mode = max hold.
7. Allow trace to fully stabilize.


7.4. Test Data

Test Item	: Frequency Separation	Test Mode	: CH Low ~ CH High
Test Voltage	: DC 3.0V Battery inside	Temperature	: 23.1°C
Test Result	: PASS	Humidity	: 52%RH


Channel	Frequency (MHz)	Separation Read Value (kHz)	Limit (kHz)	Verdict
Low Channel	902.3	200	139.4	PASS
Adjacency Channel	902.5			
Middle Channel	908.7	200	139.7	PASS
Adjacency Channel	908.5			
High Channel	914.9	200	139.3	PASS
Adjacency Channel	914.7			



Low



Middle




High

8. Number of Hopping Channel Test

8.1. Test Standard and Limit

Test Standard	FCC Part15 C Section 15.247 (a)(1)
Test Limit	≥50 channels

8.2. Test Setup



8.3. Test Procedure


The EUT must have its hopping function enabled. Using the following spectrum analyzer setting:

1. Span= the frequency band of operation
2. Set the RBW = 100kHz.
3. Set the VBW = 300kHz.
4. Sweep time = auto couple.
5. Detector function = peak.
6. Trace mode = max hold.
7. Allow trace to fully stabilize.

8.4. Test Data

Test Item	: Number of Hopping Frequency	Test Mode	: CH Low ~ CH High
Test Voltage	: DC 3.0V Battery inside	Temperature	: 23.1℃
Test Result	: PASS	Humidity	: 52%RH

Hopping Channel Frequency Range(MHz)	Quantity of Hopping Channel	Limit	Verdict
902.3-914.9	64	≥50	PASS




9. Dwell Time Test

9.1. Test Standard and Limit

Test Standard	FCC Part15 C Section 15.247 (a)(1)
Test Limit	0.4 sec

9.2. Test Setup



9.3. Test Procedure


The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:

1. Span= zero span, centered on a hopping channel
2. Set the RBW = 1 MHz.
3. Set the VBW = 1 MHz.
4. Sweep time = as necessary to capture the entire dwell time per hopping channel.
5. Detector function = peak.
6. Trace mode = max hold.
7. Allow trace to fully stabilize.


9.4. Test Data

Test Item	: Time of Occupancy	Test Mode	: CH Low ~ CH High
Test Voltage	: DC 3.0V Battery inside	Temperature	: 23.1°C
Test Result	: PASS	Humidity	: 52%RH


Frequency (MHz)	Test period (s)	Number of Bursts per Hopping Period	Burst Duration (ms)	Dwell time (s)	Limit (s)
902.3	20	3	105.0	0.315	0.4
908.7	20	3	106.0	0.318	0.4
914.9	20	3	105.0	0.315	0.4




Low channel
Burst Durration




Low channel
Number of Bursts




Middle channel
Burst Duration



Middle channel



High channel
Burst Durration




High channel
Number of Bursts

10. 100kHz Bandwidth of Frequency Band Edge Requirement

10.1. Test Standard and Limit

Test Standard	FCC Part15 C Section 15.247 (d)
Test Limit	in any 100 kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator in operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in 15.209(a).

10.2. Test Setup



10.3. Test Procedure

The EUT must have its hopping/Non-hopping function enabled. Using the following spectrum analyzer setting:


1. Set the RBW = 100kHz.
2. Set the VBW = 300kHz.
3. Sweep time = auto couple.
4. Detector function = peak.
5. Trace mode = max hold.
6. Allow trace to fully stabilize.

10.4. Test Data


Test Item	: Band edge
Test Voltage	: DC 3.0V Battery inside
Test Result	: PASS

Test Mode	: CH Low ~ CH High
Temperature	: 23.1°C
Humidity	: 52%RH

For Hopping Mode




Lowest




Highest


For Non-Hopping Mode




Lowest




Highest



Low



Mid



High

11. Antenna Requirement

11.1. Test Standard and Requirement

Test Standard	FCC Part15 Section 15.203 /247(c)
Requirement	<p>1) 15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.</p> <p>2) 15.247(c) (1)(i) requirement: Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna</p>

11.2. Antenna Connected Construction

The antenna is Spring Antenna which permanently attached, and the best case gain of the antenna is 0 dBi. It complies with the standard requirement.

APPENDIX I -- TEST SETUP PHOTOGRAPH

Please refer to separated files for Test Setup Photos of the EUT.

APPENDIX II -- EXTERNAL PHOTOGRAPH

Please refer to separated files for External Photos of the EUT.

APPENDIX III -- INTERNAL PHOTOGRAPH

Please refer to separated files for Internal Photos of the EUT.

----- End of Report -----