

# **FCC Part 15 Test Report**

*For*

**Power Tilt LCD/Plasma Mount WIRELESS TRANSMITTER**

**Model Name: MCL/SMM-T**

**Brand Name: LEVEL MOUNT**

**FCC ID: VII-MCLSMM-T**

**Report No.: AGC10200909SZ05E6**

**Date of Issue: Sep.18, 2009**

*Prepared For*

**ELEXA Consumer Products Inc.**

**6200N.Hiawatha Ave., 8th Floor, Chicago, USA**

TEL: 86-755-2748 8680

FAX: 86-755-2960 3745

*Prepared By*

**Attestation of Global Compliance Co., Ltd.**

**2F., No.2 Building, Huafeng No.1 Technical Industrial Park, Sanwei,**

**Xixiang, Baoan District, Shenzhen**

TEL: 86-755-2908 1966

FAX: 86-755-2600 8484

## VERIFICATION OF COMPLIANCE

Applicant:	ELEXA Consumer Products Inc.
	6200N.Hiawatha Ave., 8th Floor, Chicago, USA
Manufacturer:	Shenzhen JWL Electronics Co., Ltd.
	C and D Block, XiRong Industrial Estate, Gushu, XiXiang Avenue, BaoAn District, Shenzhen
Product Description:	Power Tilt LCD/Plasma Mount WIRELESS TRANSMITTER
Brand Name:	LEVEL MOUNT
Model Number:	MCL/SMM-T
File Number:	AGC10200909SZ05E6
Date of Test:	Sep.10 to Sep.18, 2009

### We hereby certify that:

The above equipment was tested by Attestation of Global Compliance Co., Ltd. The data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C 63.4:2003. The sample tested as described in this report is in compliance with the FCC Rules Part 15.

The test results of this report relate only to the tested sample identified in this report.

Checked By: Jekey Zhang  
Jekey Zhang      Sep.18, 2009

Authorized By King Zhang  
King Zhang      Sep.18, 2009

## TABLE OF CONTENTS

<b>1. GENERAL INFORMATION</b> .....	<b>4</b>
1.1 PRODUCT DESCRIPTION.....	4
1.2 RELATED SUBMITTAL(S) / GRANT (S) .....	5
1.3 TEST METHODOLOGY .....	5
1.4 TEST FACILITY .....	5
1.5 SPECIAL ACCESSORIES .....	5
1.6 EQUIPMENT MODIFICATIONS.....	5
<b>2. SYSTEM TEST CONFIGURATION</b> .....	<b>6</b>
2.1 EUT CONFIGURATION.....	6
2.2 EUT EXERCISE.....	6
2.3 GENERAL TECHNICAL REQUIREMENTS.....	6
2.4 CONFIGURATION OF TESTED SYSTEM.....	6
<b>3. SUMMARY OF TEST RESULTS</b> .....	<b>7</b>
<b>4. DESCRIPTION OF TEST MODES</b> .....	<b>8</b>
<b>5. CONDUCTED LIMITS (NOT APPLICABLE)</b> .....	<b>9</b>
5.1 PROVISIONS APPLICABLE.....	9
5.2 MEASUREMENT PROCEDURE.....	9
5.3 TEST SETUP BLOCK DIAGRAM.....	10
5.4 TEST EQUIPMENT USED .....	10
5.5 TEST RESULT .....	11
<b>6. FREQUENCY TOLERANCE</b> .....	<b>12</b>
6.1 PROVISIONS APPLICABLE.....	12
6.2 MEASUREMENT PROCEDURE.....	12
6.3 TEST SETUP BLOCK DIAGRAM.....	12
6.4 MEASUREMENT EQUIPMENT USED:.....	12
6.5 MEASUREMENT RESULT.....	13
<b>7. RADIATED EMISSION</b> .....	<b>14</b>
7.1 PROVISIONS APPLICABLE.....	14
7.2 MEASUREMENT PROCEDURE.....	14
7.3 TEST SETUP BLOCK DIAGRAM.....	14
7.4 MEASUREMENT EQUIPMENT USED:.....	15
<b>8. THE DURATION OF EACH TRANSMISSION</b> .....	<b>错误！未定义书签。</b>
8.1 PROVISIONS APPLICABLE.....	17
8.2 TEST SETUP.....	17

**8.3 MEASUREMENT INSTRUMENTS.....17**

**APPENDIX I..... 18**

**PHOTOGRAPHS OF SETUP ..... 18**

**APPENDIX II..... 20**

**EXTERNAL VIEW OF EUT..... 20**

## 1. GENERAL INFORMATION

### 1.1 PRODUCT DESCRIPTION

The EUT is a short rang, lower power, Power Tilt LCD/Plasma Mount WIRELESS TRANSMITTER. It is designed by way of utilizing the MSK modulation achieves the system operating.

A major technical description of EUT is described as following:

Power Supply	DC4.5V by battery					
Transmitter Frequency	433.9 MHz (only one channel)					
Transmit Power	0.8 dBm					
Modulation Technique	MSK					
Bandwidth of Channels	203.936KHz					
Duration of each transmission	1.042S					
Antenna Type	A permanent fixed antenna, which is built-in, designed as an indispensable part of the EUT					
Size of EUT:	Length	14.6cm	Width	About 4.4cm	Height	2.6cm

## **1.2 RELATED SUBMITTAL(S) / GRANT (S)**

This submittal(s) (test report) is intended for **FCC ID: VII-MCLSMM-T** filing to comply with the FCC Part 15 requirements.

## **1.3 TEST METHODOLOGY**

The radiated emission testing was performed according to the procedures of ANSI C 63.4: 2003 and FCC CFR 47 Rules of 15.207,15.209, 15.231

## **1.4 TEST FACILITY**

The test site used to collect the radiated data is located on the address of ACCURATE TECHNOLOGY CO., LTD.

At F1, Bldg.A, Changyuan New Material Port, Keyuan Rd., Science & Industry Park,Nanshan District, 518057 Shenzhen, P.R. China.. The test site is constructed and calibrated to meet the FCC requirements in documents ANSI C63.4: 2003.

FCC register No.: 752051

## **1.5 SPECIAL ACCESSORIES**

Not available for this EUT intended for grant.

## **1.6 EQUIPMENT MODIFICATIONS**

Not available for this EUT intended for grant.

**2. SYSTEM TEST CONFIGURATION**

**2.1 EUT CONFIGURATION**

The EUT configuration for testing is installed on RF field strength measurement to meet the Commission’s requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

**2.2 EUT EXERCISE**

The Transmitter was operated in the normal operating mode. The TX frequency was fixed which was for the purpose of the measurements.

**2.3 GENERAL TECHNICAL REQUIREMENTS**

- (1). Section 15.207: Conducted Limits (Not applicable)
- (2). Section 15.209: Radiated Emission Limits
- (3). Section 15.231: Spurious Emission Limits
- (4). Section 15.231: The Duration of Each Transmission

**2.4 CONFIGURATION OF TESTED SYSTEM**

Fig. 2-1 Configuration of Tested System



Table 2-1 Equipment Used in Tested System

Item	Equipment	Model No.	Identifier	Note
1	Power Tilt LCD/Plasma Mount WIRELESS TRANSMITTER	MCL/SMM-T	FCC ID: VII-MCLSMM-T	EUT
--	--	--	--	--
--	--	--	--	--

### 3. SUMMARY OF TEST RESULTS

<b>FCC Rules</b>	<b>Description Of Test</b>	<b>Result</b>
§15.207	Conducted Emission	N/A
§15.209	Radiated Emission Limits	Compliant
§15.231	Spurious Emission Limits	Compliant
§15.231	The Duration of Each Transmission	Compliant



#### **4. DESCRIPTION OF TEST MODES**

The EUT (Power Tilt LCD/Plasma Mount WIRELESS TRANSMITTER) has been tested under normal operating condition.

## 5. CONDUCTED LIMITS (Not applicable)

### 5.1 PROVISIONS APPLICABLE

For an intentional radiator that is designed to be connected to the public utility (AC) power line, the, the radio frequency voltage that is conducted back onto the AC power line on any frequencies within the band 150 KHz to 30 MHz shall not exceed the limits in the following table, as measured using a 50uH/50 ohms line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the boundary between the frequencies ranges.


Frequency of Emission (MHz)	Conducted Limit(dBuV)	
	Quasi-Peak	Average
0.15 – 0.5	66 to 56 *	56 to 46 *
0.5 – 5	56	46
5 – 30	60	50

\* Decreases with the logarithm of the frequency.

### 5.2 MEASUREMENT PROCEDURE

- (1) The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. When the EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.4 (see Test Facility for the dimensions of the ground plane used). When the EUT is a floor-standing equipment, it is placed on the ground plane which has a 3-12 mm non-conductive covering to insulate the EUT from the ground plane.
- (2) Support equipment, if needed, was placed as per ANSI C63.4.
- (3) All I/O cables were positioned to simulate typical actual usage as per ANSI C63.4.
- (4) The EUT received AC120V/60Hz power through a Line Impedance Stabilization Network (LISN) which supplied power source and was grounded to the ground plane.
- (5) All support equipments received AC power from a second LISN, if any.
- (6) The EUT test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
- (7) Analyzer / Receiver scanned from 150kHz to 30MHz for emissions in each of the test modes.  
During the above scans, the emissions were maximized by cable manipulation.

**5.3 TEST SETUP BLOCK DIAGRAM**



**5.4 TEST EQUIPMENT USED**

Conducted Emission Test Site				
Name of Equipment	Manufacturer	Model	Serial Number	Cal. Date
EMI Test Receiver	HP	8546A/85460A	3625A00349 3448A00325	2009/10
LISN	AFJ	LS16	16010222119	2009/04

## 5.5 TEST RESULT

N/A

## 6. FREQUENCY TOLERANCE

### 6.1 PROVISIONS APPLICABLE


According to Section 15.231(c), The bandwidth of the emission shall be no wider than 0.25% of the center frequency for devices operating above 70 MHz and below 900 MHz. For devices operating above 900 MHz, the emission shall be no wider than 0.5% of the center frequency. Bandwidth is determined at the points 20 dB down from the modulated carrier.

$$\text{Limit: } 433.9\text{MHz} \times 0.25\% = 1.08\text{MHz}$$

### 6.2 MEASUREMENT PROCEDURE

- 1). The EUT was placed on a turntable which is 0.8m above ground plane.
- 2). The EUT was operated with signal modulated.
- 3). Set SPA Center Frequency = fundamental frequency, RBW=VBW=51KHz, Span=500kHz
- 4). Set SPA Max hold. Mark peak, -20dB


### 6.3 TEST SETUP BLOCK DIAGRAM



### 6.4 MEASUREMENT EQUIPMENT USED:

3M ANECHOIC CHAMBER RADIATION TEST SITE					
EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LAST CAL.	CAL DUE.
EMI Test Receiver	R&S	ESCS30	--	04/16/2009	04/15/2010
AMPLIFIER	HP	HP8447E	--	04/16/2009	04/15/2010
ANTENNA	Sunol Sciences Corp.	JB3	--	04/16/2009	04/15/2010
Horn ANTENNA	ETS	3117	--	04/16/2009	04/15/2010
Spectrum Analyzer	Agilent	E4440A	--	04/16/2009	04/15/2010

6.5 MEASUREMENT RESULT



bandwidth	LIMIT	RESULT
203.936KHz	1.08MHz	PASS

## 7. RADIATED EMISSION


### 7.1 PROVISIONS APPLICABLE

According to Section 15.231(b), Where F is the frequency in MHz, the formulas for calculating the maximum permitted fundamental field strengths are as follows: for the band 130-174 MHz,  $\mu\text{V/m}$  at 3 meters =  $56.81818(F) - 6136.3636$ ; for the band 260-470 MHz,  $\mu\text{V/m}$  at 3 meters =  $41.6667(F) - 7083.3333$ . The maximum permitted unwanted emission level is 20 dB below the maximum permitted fundamental level.

### 7.2 MEASUREMENT PROCEDURE

- (1) On a test site, the EUT shall be placed on a turntable, and in the position closest to the normal use as declared by the user.
- (2) The test antenna shall be oriented initially for vertical polarization located 3m from the EUT to correspond to the transmitter.
- (3) The output of the antenna shall be connected to the measuring receiver and either a peak or quasi-peak detector was used for the measurement as indicated on the report. The detector selection is based on how close the emission level was approaching the limit.
- (4) The transmitter shall be switched on; if possible, without the modulation and the measurement receiver shall be tuned to the frequency of the transmitter under test.
- (5) The test antenna shall be raised and lowered through the specified range of height until the measuring receiver detects a maximum signal level.
- (6) The transmitter shall then be rotated through  $360^\circ$  in the horizontal plane, until the maximum signal level is detected by the measuring receiver.
- (7) The test antenna shall be raised and lowered again through the specified range of height until the measuring receiver detects a maximum signal level.
- (8) The maximum signal level detected by the measuring receiver shall be recorded.
- (9) The measurement shall be repeated with the test antenna set to horizontal polarization
- (10) According to the above steps, three orthogonal planes (x, y, z) are operated.

### 7.3 TEST SETUP BLOCK DIAGRAM



**7.4 MEASUREMENT EQUIPMENT USED:**

<b>3M ANECHOIC CHAMBER RADIATION TEST SITE</b>					
<b>EQUIPMENT TYPE</b>	<b>MFR</b>	<b>MODEL NUMBER</b>	<b>SERIAL NUMBER</b>	<b>LAST CAL.</b>	<b>CAL DUE.</b>
EMI Test Receiver	R&S	ESCS30	--	04/16/2009	04/15/2010
AMPLIFIER	HP	HP8447E	--	04/16/2009	04/15/2010
ANTENNA	Sunol Sciences Corp.	JB3	--	04/16/2009	04/15/2010
Horn ANTENNA	ETS	3117	--	04/16/2009	04/15/2010
Spectrum Analyzer	Agilent	E4440A	--	04/16/2009	04/15/2010



## 7.5 MEASUREMENT RESULTS

### X ORTHOGONAL PLANE IS THE STATE DATA OF THREE ORTHOGONAL PLANES (X, Y, Z)

RADIATED EMISSION – HORIZONTAL (30MHZ TO 5GHZ)							
Frequency	Antenna Pol.	Field Strength	Field Strength	Limit(PK)	Limit(QP)	Limit(AV)	State
GHz	H/V	dBuV/m (PK)	dBuV/m (AV)	dBuV/m	dBuV/m	dBuV/m	
433.900	H	82.07	50.18	100.82	--	80.82	pass
867.900	H	42.80	31.46	80.82	--	60.82	pass
1301.700	H	48.79	39.10	74.00	--	54.00	pass
1735.600	H	--	--	80.82	--	60.82	pass
3037.300	H	--	--	80.82	--	60.82	pass
4339.000	H	--	--	74.00	--	54.00	pass
--	H	--	--	74.00	--	54.00	pass

RADIATED EMISSION - VERTICAL(30MHZ TO 5GHZ)							
Frequency	Antenna Pol.	Field Strength	Field Strength	Limit(PK)	Limit(QP)	Limit(AV)	State
GHz	H/V	dBuV/m (PK)	dBuV/m (AV)	dBuV/m	dBuV/m	dBuV/m	
433.900	V	81.64	49.78	100.82	--	80.82	pass
867.900	V	42.07	31.09	80.82	--	60.82	pass
1301.700	V	48.98	38.12	74.00	--	54.00	pass
1735.600	V	--	--	80.82	--	60.82	pass
3037.300	V	--	--	80.82	--	60.82	pass
4339.000	V	--	--	74.00	--	54.00	pass
--	H	--	--	74.00	--	54.00	pass

Note:

“-” indicate the test value is much lower to limit

**8. THE DURATION OF EACH TRANSMISSION**

**8.1 PROVISIONS APPLICABLE**

8.1.1 According to Section 15.231(b), A manually operated transmitter shall employ a switch that will automatically deactivate the transmitter within not more than 5 seconds of being released.

**8.2 TEST SETUP**


The same as 6.3

**8.3 MEASUREMENT INSTRUMENTS**

The same as 6.4

**8.4 MEASUREMENT RESULT**

THE DURATION OF EACH TRANSMISSION



THE DURATION OF EACH TRANSMISSION	LIMIT	RESULT
1.042s	5s	PASS

# **APPENDIX I**

## **PHOTOGRAPHS OF SETUP**

### RADIATED TEST SETUP



## **APPENDIX II**

# **EXTERNAL VIEW OF EUT**

TOP VIEW OF EUT



BOTTOM VIEW OF EUT



LEFT VIEW OF EUT



RIGHT VIEW OF EUT



FRONT VIEW OF EUT



BACK VIEW OF EUT






INTERNAL VIEW OF EUT – 1



INTERNAL VIEW OF EUT – 2



---END OF REPORT---