

MPE REPORT

FCC ID: VII-WFMZ1

Date of issue: June 19, 2019

Report Number:	MTi190618E125
Sample Description:	WiFi Mouser
Model(s):	WFMZ1
Applicant:	Elexa Consumer Products, Inc.
Address:	2275 Half Day Road, Suite 160, Bannockburn, IL60015, United States.
Date of Test:	May 31, 2019 to June 19, 2019

Shenzhen Microtest Co., Ltd.

<http://www.mtitest.com>

TEST RESULT CERTIFICATION	
Applicant's name:	Elexa Consumer Products, Inc.
Address:	2275 Half Day Road, Suite 160, Bannockburn, IL60015, United States.
Manufacture's Name:	Elexa Consumer Products, Inc.
Address:	2275 Half Day Road, Suite 160, Bannockburn, IL60015, United States.
Product name:	WiFi Mouser
Trademark:	Dome
Model and/or type reference .:	WFMZ1
Serial Model.....:	N/A
RF Exposure Procedures.....:	KDB 447498 D01 v06

This device described above has been tested by Shenzhen Microtest Co., Ltd and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

Tested by:



Jone Lee

June 19, 2019

Reviewed by:



Blue Zheng

June 19, 2019

Approved by:



Smith Chen

June 19, 2019

RF EXPOSURE EVALUATION

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) Radiation as specified in §1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposure				
0.3-3.0	614	1.63	*100	6
3.0-30	1842/f	4.89/f	*900/f ²	6
30-300	61.4	0.163	1.0	6
300-1,500			f/300	6
1,500-100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*100	30
1.34-30	824/f	2.19/f	*180/f ²	30
30-300	27.5	0.073	0.2	30
300-1,500			f/1500	30
1,500-100,000			1.0	30

f = frequency in MHz * = Plane-wave equivalent power density

MPE Calculation Method

Friis transmission formula: $P_d = (P_{out} * G) / (4 * \pi * R^2)$

Where

P_d = Power density in mW/cm²

P_{out} = output power to antenna in mW

G = Numeric gain of the antenna relative to isotropic antenna

π = 3.1415926

R = distance between observation point and center of the radiator in cm (20cm)

P_d the limit of MPE, 1mW/cm². If we know the maximum gain of the antenna and total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

Measurement Result

WIFI:

Operation Frequency: WIFI 802.11b/g/n HT20: 2412-2462MHz,

Power density limited: 1mW/ cm²

Antenna Type: Wifi Antenna: PCB Antenna;

WIFI antenna gain: 1dBi

R=20cm

$mW=10^{(dBm/10)}$

antenna gain Numeric= $10^{(dBi/10)}=10^{(1/10)}=1.26$

Channel Freq. (MHz)	modulation	conducted power	Tune-up power	Max		Antenna	Evaluation result at 20cm	Power density Limits
		(dBm)	(dBm)	tune-up power		Gain	Power density(mW/cm ²)	(mW/cm ²)
		Ant A	Ant A	(dBm)	(mW)	Numeric		
2412	802.11b	14.24	14±1	15	31.622777	1.26	0.00793	1
2437		13.85	14±1	15	31.622777	1.26	0.00793	1
2462		13.53	14±1	15	31.622777	1.26	0.00793	1
2412	802.11g	12.94	12±1	13	19.952623	1.26	0.00500	1
2437		12.99	12±1	13	19.952623	1.26	0.00500	1
2462		11.03	12±1	13	19.952623	1.26	0.00500	1
2412	802.11n H20	12.89	9±1	10	10	1.26	0.00251	1
2437		12.84	9±1	10	10	1.26	0.00251	1
2462		12.92	9±1	10	10	1.26	0.00251	1

Conclusion:

For the max result: 0.00793 ≤ 1.0 for 1g SAR, No SAR is required.

----END OF REPORT----