

## RF EXPOSURE EVALUATION

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency(RF) Radiation as specified in §1.1307(b)

FCC ID: **VIP-VX3020**

### EUT Specification

<b>EUT</b>	Mobile DVD Player with FM/AM Tuner
<b>Frequency band (Operating)</b>	<input type="checkbox"/> WLAN: 2.412GHz ~ 2.462GHz <input type="checkbox"/> WLAN: 5.18GHz ~ 5.32GHz / 5.50GHz ~ 5.70GHz <input type="checkbox"/> WLAN: 5.745GHz ~ 5825GHz <input checked="" type="checkbox"/> Others
<b>Device category</b>	<input type="checkbox"/> Portable (<20cm separation) <input checked="" type="checkbox"/> Mobile (>20cm separation) <input type="checkbox"/> Others ____
<b>Exposure classification</b>	<input type="checkbox"/> Occupational/Controlled exposure (S = 5mW/cm <sup>2</sup> ) <input checked="" type="checkbox"/> General Population/Uncontrolled exposure (S=1mW/cm <sup>2</sup> )
<b>Antenna diversity</b>	<input checked="" type="checkbox"/> Single antenna <input type="checkbox"/> Multiple antennas <input type="checkbox"/> Tx diversity <input type="checkbox"/> Rx diversity <input type="checkbox"/> Tx/Rx diversity
<b>Max. output power</b>	1.13dBm (0.001297W)
<b>Antenna gain (Max)</b>	0 dBi
<b>Evaluation applied</b>	<input checked="" type="checkbox"/> MPE Evaluation <input type="checkbox"/> SAR Evaluation

Limits for Maximum Permissible Exposure(MPE)

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density(mW/cm <sup>2</sup> )	Average Time
<b>(A) Limits for Occupational/Control Exposures</b>				
300-1500	--	--	F/300	6
1500-100000	--	--	5	6
<b>(B) Limits for General Population/Uncontrol Exposures</b>				
300-1500	--	--	F/1500	6
1500-100000	--	--	1	30

## Friis transmission formula: $P_d = \frac{P_{out} * G}{4 * \pi * R^2}$

Where

$P_d$  = Power density in  $mW/cm^2$

$P_{out}$  = output power to antenna in Mw

$G$  = gain of antenna in linear scale

$\pi$  = 3.1416

$R$  = distance between observation point and center of the radiator in cm

$P_d$  the limit of MPE,  $1mW/cm^2$ . If we know the maximum gain of the antenna and total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

## Measurement Result

Operating Mode	Channel Frequency (MHz)	Output Peak power (mW)	Antenna Gain (dBi)	Power density at 20cm ( $mW/cm^2$ )	Power density Limits ( $mW/cm^2$ )
op-mode 1	2402	1.177	0	0.000234	1
op-mode 2	2441	1.297	0	0.000258	1
op-mode 3	2480	1.028	0	0.000205	1
op-mode 6	2402	0.891	0	0.000177	1
op-mode 7	2441	1.044	0	0.000208	1
op-mode 8	2480	0.762	0	0.000152	1
op-mode 10	2402	0.926	0	0.000184	1
op-mode 11	2441	1.083	0	0.000215	1
op-mode 12	2480	0.799	0	0.000159	1

Signature:



Print: Sam Lv

Title: Manager

Company: DONGGUAN EMTEK CO., LTD.

Address: No.281, Guantai Road, Nancheng District,  
Dongguan, Guangdong, China

Date: 2014-1-20