

	Equipment in test PLB : Kannad XS3-GPS	INTESPACE Reference E7555-RTCM
---	---	-----------------------------------

CHAPTER 12

AUXILIARY RADIO-LOCATING DEVICE TRANSMITTER TEST



Manufacturer : MARTEC_OPALE.

Beacon Model :
XS3_GPS

INTESPACE Reference

E7555-RTCM

**12.1 - ELECTRICAL AND FUNCTIONAL TEST OF 121,5 MHZ
AT THREE CONSTANT TEMPERATURE**

	Manufacturer : MARTEC_OPALE. Beacon Model : XS3_GPS	INTESPACE Reference E7555-RTCM
---	--	---

12.1.1 TEST SPECIFICATIONS AND PROGRAMME

Following section A12.0 of RTCM Recommended Standards for 406 MHz Satellite PLBs (Version 1.1 Feb 4, 2003) :

- Perform following measurements.
- Carrier frequency
- Modulation frequency
- Transmitter duty cycle
- Sweep repetition rate
- Modulation duty cycle
- Modulation factor

Note : These tests are performed during the COSPAS-SARSAT Type Approval tests (chapter 10)

12.1.2 EQUIPMENT UNDER TEST

Beacon Unit : 1/2 (with 50 ohm output)
 Name : MARTEC OPALE
 Type : XS3_GPS
 Number : UT1

12.1.3 TEST SITE

INTESPACE Laboratory.

12.1.4 TEST EQUIPMENT

- Climatic chamber : CLIMATS F.C.H. – Type: Austral 137H60/1,5E - S/N: S4880.
- Argos - Cospas/Sarsat Test Bench



Manufacturer : MARTEC_OPALÉ.
Beacon Model :
XS3_GPS

INTESPACE Reference
E7555-RTCM

12.1.5. RESULTS OF HOMING TRANSMITTER TESTS

Beacon Unit : 1/2 (with 50 ohm output)
Name : MARTEC / KANNAD
Type : XS3 GPS
Number : UT1

			T min. - 20° C	T amb. 22° C	T max + 55° C
1 - OPERATING LIFETIME AT MINIMUM TEMPERATURE	24H	≈ 28 h			
2 - CARRIER FREQUENCY	* 121500 kHz± 5 kHz	121.5028	121.5017	121.5008	
3 - PEAK ENVELOPE OUTPUT POWER ** (into 50 Ohms load)	14 dBm + 6/- 2 dBm	19 dBm	18.9 dBm	18.5 dBm	
4 - TRANSMITTER DUTY CYCLE	continuous	Cont.	Cont.	Cont.	
5 - MODULATION FREQUENCY	300 to 1 600 Hz	490 to 1390	490 to 1310	490 to 1310	
6 - MODULATION DUTY CYCLE	33 % - 55 %	52 %	53 %	53 %	
7 - MODULATION FACTOR	> 0.85	. > 0.85	> 0.85	> 0.85	
8 - SWEEP REPETITION RATE	2 Hz - 4 Hz	3.0 Hz	3.1 Hz	3.1 Hz	
9 - HOMING TRANSMISSION CODING *	Bits 112 = 1	1	1	1	

* See data and graphs of results on chapter 10 "Cospas-Sarsat Type Approval Tests Report"

12.1.6. SPECTRUM MEASUREMENT RESULTS

See graphs of results on chapter 10 "Cospas-Sarsat Type Approval Tests Report" and chapter 9 "Spurious Emission Test"



Manufacturer : MARTEC_OPALE.

Beacon Model :
XS3_GPS

INTESPACE Reference

E7555-RTCM

12.2- HOMING RADIATED OUTPUT POWER ON UUT 2/3

	Manufacturer : MARTEC_OPALE. Beacon Model : XS3_GPS	INTESPACE Reference E7555-RTCM
---	--	--

12.2.1 - ADMINISTRATION

- 12.2.1.1 WORK ORDER : Reference: E7555-RTCM
 12.2.1.2 TEST TEAM : François Esquevin
 12.2.1.3 SCHEDULE : 22 November 2007

12.2.2 - PURPOSE

The radiation tests of the dedicated radio beacon are performed in INTESPACE EMC Laboratory in compliance with the test methods described in Section A12.3 of RTCM Recommended Standards for 406 MHz Satellite PLBs (Version 1.1 Feb 4, 2003)

Frequency tested : 121.5 MHz.

12.2.3 - RADIO BEACON IDENTIFICATIONS

Beacon Unit	:	2/2 (normal fitted PLB)
Name	:	MARTEC / KANNAD
Type	:	XS3 GPS
Number	:	UT2
Antenna	:	Kannad Integrated Antenna

12.2.4 - TEST SITE DESCRIPTION

Tests are performed in an anechoic chamber (size 16 m x 10 m x 11 m) .
 Walls, ceiling and doors are lined with EMERSON CUMING foams VHP 36 and VHP 26 type.
 The PLB is placed as shown on figures n° 1 and n° 2 next pages .




FIGURE 1



Manufacturer : MARTEC_OPALE.

Beacon Model :
XS3_GPS

INTESPACE Reference

E7555-RTCM




FIGURE B2a : Equipment Test Set-Up For BEACON Antenna Test .

	Manufacturer : MARTEC_OPALÉ. Beacon Model : XS3_GPS	INTESPACE Reference E7555-RTCM
---	--	---

12.2.5 - TEST METHOD

According Section A12.3 of RTCM Recommended Standards for 406 MHz Satellite PLBs (Version 1.1 Feb 4, 2003) :

- 1/ The elevation angle between 5° and 20° which produces a maximum gain is determined with the EUT at an arbitrary azimuth .
- 2/ The PEP is measured and the elevation angle is noted (between 5° to 20°) and is remain fixed for the remainder of the test .
- 3/ The remaining 12 measurements of PEIRP is obtained by rotating the EUT in increments of 30° ± 3° .
For each measurements the EUT PEIRP is computed using the following equation :

$$\text{PEIRP} = \text{LOG}^{-1} [(P_{\text{REC}} - G_{\text{REC}} + L_c + L_p)/10] \quad (\text{Equation A})$$

Where :

P_{rec} = Measured Power level from spectrum analyzer (dBm)
 G_{rec} = Antenna gain of search antenna (dB)
 L_c = Receive system attenuator and cable loss (dB)
 L_p = Free space propagation loss (dB)

- 4/ The median value of PEIRP is compared to the specified PEIRP to be in the range 25 mW to 100 mW (14 dBm to 20 dBm)

12.2.6 - TEST MEASUREMENT EQUIPMENTS

Search Antenna

- 121.5 MHz test : EMCO 3121C DB2 S/N 9904 1430

SPECTRUM ANALYSER

- R/S ESMI

CABLES

- 20 m cable SUCOFLEX type 100 - cable loss at 121.5 MHz : 1.9 dB



Manufacturer : MARTEC_OPALE.

Beacon Model :
XS3_GPS



INTESPACE Reference

E7555-RTCM

12.2.7 - PLB MECHANICAL SET UP

PLB 0° axis is identified by the antenna position (see figure) is the rotation center of azimuth angle.

A conductive aluminium paper is used to assure a good conductivity between beacon float level and the ground plane.





Manufacturer : MARTEC_OPALÉ.
Beacon Model :
XS3_GPS

INTESPACE Reference
E7555-RTCM

12.2.8- TESTS RESULTS

Following the Equation (A), 12 value of EUT PERP are computed at 20° (maximum level) of elevation angle

Azimut Angle	PEIRP (dBm)
0	14,64
30	14,94
60	15,04
90	15,54
120	14,84
150	15,14
130	15,14
210	15,04
240	15,04
270	14,64
300	14,84
330	15,14
PEIRP variation	0.9dB
Mean value	14.99 dBm

The PERP measured and computed are in conformance with specification required :

14 dBm \leq PERP \leq 20 dBm
and
PEIRP Azimuth Variation $<$ 6 dB