



Manufacturer : MARTEC.
Beacon Model : Kannad
Auto/Auto GPS/Manual/Manual
GPS/Manual+/Manual+ GPS

INTESPACE Reference
E6668-RTCM Rev1

PARAMÈTRES TO BE MEASURED DURING TESTS	RANGE OF SPECIFICATION	UNITS	TEST RESULTS			COMMENTS
			T min. ($\pm 3^{\circ}\text{C}$) (-30°C)	T amb. ($\pm 3^{\circ}\text{C}$) (22°C)	T max. ($\pm 3^{\circ}\text{C}$) (40°C)	
18. HUMIDITY TEST (A18.0) • Aliveness Test : * Carrier frequency * Power Output	406.028 \pm 0.001 35-39	MHz dBm		UUT7	406.027764 36.4	Chapter 18 11 august 2006
19. ORIENTATION TEST (A19.0) VERTICAL • Aliveness Test : * Carrier frequency * Power Output	406.028 \pm 0.001 35-39	MHz dBm		UUT7 406.027875 38.3		Chapter 19 18 may 2006
UPSIDE DOWN • Aliveness Test : * Carrier frequency * Power Output	406.028 \pm 0.001 35-39	MHz dBm		406.027825 37.3		12 june 2006
HORIZONTAL • Aliveness Test : * Carrier frequency * Power Output	406.028 \pm 0.001 35-39	MHz dBm		406.027820 36.9		15 june 2006