



TEST REPORT

Date: 2010-08-18

Report No.: 60.870.10.013.01F

Applicant: Audiovox Accessories Corporation.
111 Congressional Blvd., Suite 350 Carmel, IN
46032, USA.

Description of Samples: Model name: 2.4GHz Wireless 2.1ch Headphone System
(Transmitter)
Brand name: ---
Model no.: AWD211
FCCID: VIX-24G-AWD211-TX

Date Samples Received: 2010-07-08

Date Tested: 2010-07-22 to 2010-08-16

Investigation Requested: FCC Part 15 Subpart C, Section 15.247

Conclusions: The submitted product COMPLIED with the requirements of Federal Communications Commission [FCC] Rules and Regulations Part 15. The tests were performed in accordance with the standards described above and on Section 2.2 in this Test Report.

Remarks: ----

Checked by:

Approved by:-

Sandy Leung
Project Engineer
Wireless & Telecom department

Nicolas Cheng
Assistant Project Manager
Wireless & Telecom department

CONTENT:

Cover	Page 1 of 30	
Content	Page 2-3 of 30	
<u>1.0</u>	<u>General Details</u>	
1.1	Test Laboratory	Page 4 of 30
1.2	Applicant Details	Page 4 of 30
1.3	Equipment Under Test [EUT]	Page 5 of 30
1.4	Equipment Modification	Page 5 of 30
1.5	Related Submittal(s) Grants	Page 5 of 30
<u>2.0</u>	<u>Technical Details</u>	
2.1	Investigations Requested	Page 6 of 30
2.2	Test Standards and Results Summary	Page 6 of 30
<u>3.0</u>	<u>Test Methodology</u>	
3.1	Radiated Emission	Page 7 of 30
3.2	Field Strength Calculation	Page 7 of 30
3.3	Conducted Emission	Page 7 of 30
<u>4.0</u>	<u>Test Results</u>	
4.1	Number of Frequency Hopping	Page 8 of 30
4.2	20dB Bandwidth Measurement	Page 9-10 of 30
4.3	Hopping Channel Carrier Frequency Separation	Page 11 of 30
4.4	Average Time of Occupancy	Page 12-13 of 30
4.5	Pseudorandom Hopping Algorithm	Page 14 of 30
4.6	Band Edge Measurement	Page 15-16 of 30
4.7	Maximum Output Power	Page 17-18 of 30
4.8	Out of Band Emissions and Emissions in Restricted Bands	Page 19-25 of 30
4.9	Conducted Emission on AC Mains	Page 26-28 of 30

5.0 RF Exposure Compliance Requirement

Page 29 of 30

6.0 List of Measurement Equipments

Page 30 of 30

Appendix A

Photos of Test Setup

Appendix B

External EUT Photos

Appendix C

Internal EUT Photos

1.0 General Details

1.1 Test Laboratory

EMC Laboratory registered by FCC with
FCC Registration Number: 90656

**1.2 Applicant Details
Applicant**

Audiovox Accessories Corporation.

111 Congressional Blvd., Suite 350 Carmel, IN 46032
USA.

Manufacturer

Acoustic Arc International Ltd.

Unit 311B, 3/F., IC Development Centre, NO.6
Science Park West Avenue, Hong Kong Science
Park, Shatin, N.T. Hong Kong

1.3 Equipment Under Test [EUT]

Description of EUT

Product Description:	2.4GHz Wireless 2.1ch Headphone System (Transmitter)
Model No.:	AWD211
Brand Name:	---
FCCID:	VIX-24G-AWD211-TX
Rating:	- DC 6.0V, 300mA powered by AC/DC power adaptor
Operated Frequency:	2404 - 2478 MHz
No. of Operated Channel:	19
Accessories and Auxiliary Equipments:	-AC/DC power adaptor.
Antenna Type:	Integral
Manufacture of Antenna:	Acoustic Arc International Ltd.
Antenna Gain:	0dBi
Antenna Model:	N/A

General Operation of EUT

The Equipment Under Test (EUT) is a transmitter of the wireless headphone system operated at 2.4GHz.

FHSS Operation Principle:

This module is controlled by microchip to generate Pseudorandom Frequency Hopping Sequence, this module support 19 hopping channels. Refer to section 4.5 of this report to have more detail of Pseudorandom Hopping Algorithm.

1.4 Equipment Modification

No modification was conducted on the tested sample by TUV SUD Hong Kong Ltd.

1.5 Related Submittal(s) Grants

RF transmitting function of this EUT is subjected to the application of FCC Certification.

2.0 Technical Details

2.1 Investigations Requested

Perform ElectroMagnetic Interference measurement in accordance with FCC 47CFR [Codes of Federal Regulations] Part 15: 2008 and ANSI C63.4: 2003 for FCC Verification

2.2 Test Standards and Results Summary Tables

Test Condition	Test Requirement	Test Result	
		Pass	N/A
Number of Frequency Hopping	Section 15.247 (a1)	<input checked="" type="checkbox"/>	<input type="checkbox"/>
20dB Bandwidth Measurement	Section 15.247 (a1)	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Hopping Channel Carrier Frequency Separation	Section 15.247 (a1)	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Average Time of Occupancy	Section 15.247 (a1)	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Pseudorandom Hopping Algorithm	Section 15.247 (a1)	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Band Edge Measurement	Section 15.247	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Maximum Output Power	Section 15.247 (b1)	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Out of Band Emission	Section 15.247 (d)	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Radiated Emission in Restricted Band	Section 15.247 (d)	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Conducted Emission on AC Mains	Section 15.207	<input checked="" type="checkbox"/>	<input type="checkbox"/>
RF Exposure	Section 15.247 (i)	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Antenna Requirement	Section 15.203	<input checked="" type="checkbox"/> See note 1	<input type="checkbox"/>

Note 1 : The EUT uses a permanently attached antenna, which in accordance to Section 15.203, is considered sufficient to comply with the provisions of this section.

Remark: N/A - Not Applicable

3.0 Test Methodology

3.1 Radiated Emission

The sample was placed 0.8m above the ground plane on a standard emission test site *. Measurements in both horizontal and vertical polarities were performed. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, rotating turntable, varying antenna height from 1m to 4m in both horizontal and vertical polarizations. The emissions worst-case are shown in Test Results of the following pages.

*On a standard emission test site with a metal ground plane filed with the FCC pursuant to section 2.948 of the FCC rules, with Registration Number: 90656.

3.2 Field Strength Calculation

The field strength at 3 m was established by adding the meter reading of the spectrum analyzer to the factors associated with antenna correction factor, cable loss, preamplifiers and filter attenuation.

The equation is expressed as follow:

$$\text{FS} = \text{R} + \text{System Factor}$$
$$\text{System Factor} = \text{AF} + \text{CF} + \text{FA} - \text{PA}$$

Where FS = Net Field Strength in dBuV/m at 3 meters.

R = Reading of Spectrum Analyzer / Test Receiver in dBuV.

AF = Antenna Factor in dB.

CF = Cable Attenuation Factor in dB.

FA = Filter Attenuation Factor in dB.

PA = Preamplifier Factor in dB.

FA and PA are only be used for the measuring frequency above 1 GHz.

3.3 Conducted Emissions

The test was performed in accordance with ANSI C63.4: 2003, with the following: initial measurements were performed in peak and average detection modes on the live line of personal computer, any emissions recorded within 30dB of the relevant limit lines were re-measured using quasi-peak and average detection on the live and neutral lines with the worst case recorded in the table of results.

4.0 Test Results

4.1 Number of Hopping Frequency

Test Requirement:	FCC part 15 section 15.247 (a1)(iii)
Test Date:	2010-07-28
Mode of Operation:	Transmitting mode.
Detector Function:	Max Hold

Result: PASS

Measured Result :


Operating Channel Frequency in sequence:

2404 ; 2408 ; 2412 ; 2417 ; 2420 ; 2424 ; 2428 ; 2433
2436 ; 2440 ; 2444 ; 2449 ; 2452 ; 2456 ; 2460 ; 2465
2469 ; 2474 ; 2478

Limit for Number of Hopping Channel [Section 15.247 (a1)(iii)]

At least 15 non-overlapping channels for 2400-2483.5MHz.

Figure 1 – Result data graph shows the number of operation channels:



4.2 20dB Bandwidth Measurement

Test Requirement: FCC part 15 section 15.247 (a1)
 Test Date: 2010-07-28
 Mode of Operation: Transmitting mode.
 Detector Function: Max Hold

Test Setup:

The bandwidth is measured at an amplitude level reduced from the reference level by a specified ratio. The reference level is the level of the highest amplitude signal observed from the transmitter at the fundamental frequency. Once the reference level is established, the equipment is conditioned with typical modulating signal to produce the worst-case (i.e. the widest) bandwidth.

Channel	Measured frequency (GHz)	20dB Bandwidth (MHz)
Lowest	2.404	3.19
Middle	2.440	3.16
Highest	2.478	3.19

This result is used for checking the hopping channel carrier frequencies separation.

Figure 2 – Result data graph shows 20 dB bandwidth, CF = 2.404GHz, BW = 3.19MHz




Figure 3 – Result data graph shows 20 dB bandwidth, CF = 2.440GHz, BW = 3.16MHz





Figure 4 – Result data graph shows 20 dB bandwidth, CF = 2.478GHz, BW = 3.19MHz



4.3 Hopping Channel Carrier Frequency Separation

Test Requirement:	FCC part 15 section 15.247 (a1)
Test Date:	2010-07-28
Mode of Operation:	Transmitting mode.
Detector Function:	Max Hold

Result: PASS

Measured Result :


Refer to the delta marker, the frequency separation between two adjacent channels is 4.05MHz, therefore, the requirement of channel separated by a two-third of the 20dB bandwidth of the hopping channel is applied.

According to the test result shown in section 4.2, the maximum 20dB bandwidth is 3.19MHz, so the hopping channel separation of this EUT is found to comply with the requirement.

Limits for Hopping Channel Separation [Section 15.247 (a1)]:

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25kHz or the 20dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5MHz band may have hopping channel carrier frequencies that are separated by 25KHz or two-thirds of the 20dB bandwidth of the hopping channel, whichever is greater.

Figure 5 – Result data graph shows the channel separation:



Report No.: 60.870.10.013.01F

4.4 Average Time of Channel Occupancy

Test Requirement:	FCC part 15 section 15.247 (a1)(iii)
Test Date:	2010-08-04
Mode of Operation:	Transmitting mode.
Detector Function:	Zero span, Sweep time 1s

Result : PASS

Measured Result :

During each transmission, only 19 channels will be used.

Occupancy defined time = 19 channels \times 0.4s = 7.6s

One set of pulses = 1.7ms

Ten set of pulses within 400ms : 1.7ms \times 10 = 17ms

Therefore, the average channel occupancy times (ms)

= 17ms \times 19

So, total transmitting time is 0.323s.

Limits for Average Time of Occupancy [Section 15.247 (a1)(iii)]:

The average time of occupancy on any channel shall not be greater than 0.4 second within a period of 0.4 seconds multiplied by the number of hopping channels employed.

Figure 6 – Result data graph shows 400ms with 10 pulses.





Figure 7 – Result data graph zooms into detail, one big pulse is built with 1.7ms.



4.5 Pseudorandom Hopping Algorithm

Pseudorandom Frequency Hopping

AWD211 uses FHSS technology with 19 hopping frequencies. Each channel frequency is selected from a pseudorandom ordered list of hopping frequencies, from 2404MHz to 2478MHz with separating in 4MHz apart from each of the channels. A single data frame is transmitted on each frequency location before skipping to the next hopping frequency in the list.

The transmitter will generate the adaptive hopping sequence and transmit hopping information to the receiver. The receiver will shift frequency following this hopping information. Therefore the system has the ability to keep frequency channel switch in synchronization.

The hopping sequence is generated by the transmitter. Therefore the different transmitters will generate the different hopping sequences. Besides, AWD211 has a unique user ID for link registration and the transmitted hopping information is encrypted. If user ID is not match, no other FHSS system can join the link with the devices. If no decryption ability, other FHSS system will not follow the hopping sequence to shift frequency.

Frequency use is equally used on average.

Frequency list (in MHz) :

2404 ; 2408 ; 2412 ; 2417 ; 2420 ; 2424 ; 2428 ; 2433
2436 ; 2440 ; 2444 ; 2449 ; 2452 ; 2456 ; 2460 ; 2465
2469 ; 2474 ; 2478

Requirement for Pseudorandom Hopping Algorithm [Section 15.247 (a1)]:

The channel frequencies shall be selected from a pseudorandom ordered list of hopping frequencies. Each frequency must be used equally on average by the transmitter.

4.6 Band Edge Measurement

Test Requirement:	FCC part 15 section 15.247
Test Date:	2010-07-28
Mode of Operation:	Transmitting mode.
Detector Function:	Max Hold

Result: PASS

Measured Result :

Refer to the figure 8 and 9, it shows the frequency of lower band edge and upper band edge is 2.404GHz and 2.478GHz separately.

Limits of Band Edge for Carrier Frequencies Operated within the Bands [Section 15.247]:

The carrier frequencies should operate within 2400-2483.5MHz.

Figure 8 – Result data graph shows the frequency of lowest channel.






Figure 9 – Result data graph shows the frequency of highest channel.



4.7 Maximum Output Power

Test Requirement:	FCC part 15 section 15.247 (a1)
Test Method:	ANSI C63.4:2003
Test Date:	2010-07-28
Mode of Operation:	Transmitting mode.
Detector Function:	Peak
Measurement BW:	RBW 5MHz ; VBW 10MHz

Test Setup:



Report No.: 60.870.10.013.01F

Result : PASS

Frequency (MHz)	Output Power		Max. Output Power (mW)
	(dBuV/m)	(V/m)	
Lowest Channel : 2404	109.88	0.3119	29.18
Middle Channel : 2440	107.37	0.2336	16.37
Highest Channel : 2478	105.92	0.1977	11.73
Limit	116.20	0.645	125.0

Calculate the transmitter's peak power using the following equation:

$$E = \frac{\sqrt{30PG}}{d}$$

Where: E is the measured maximum fundamental field strength in V/m, utilizing a RBW \geq the 20 dB bandwidth of the emission, VBW > RBW, peak detector function. Follow the procedures in C63.4-2003 with respect to maximizing the emission.

G is the numeric gain of the transmitting antenna with reference to an isotropic radiator. This antenna gain declared by manufacture is 0dBi, antenna is PCB integrated in the actual use. 0dBi logarithmic terms convert to numeric result is nearly 1. So, we apply G =1.0.

d is the distance in meters from which the field strength was measured.

P is the power in watts for which you are solving:

$$P = \frac{(E*d)^2}{30G}$$


Limits for Maximum Output Power [Section 15.247 (a1)(iii)]:

For frequency hopping systems employing at least 75 hopping channels: 1 Watt
For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 Watts

4.8 Out of Band Emissions and Emissions in Restricted Bands

Test Requirement:	FCC part 15 section 15.247 (d)
Test Method:	ANSI C63.4:2003
Test Date:	2010-07-28
Mode of Operation:	Transmitting mode
Detector Function:	Peak
Measurement BW:	RBW 100KHz ; VBW 300KHz

Test Setup:



Report No.: 60.870.10.013.01F

Result : PASS

Out of Frequency Band Emissions:

For out of band emissions that are close to or exceed 20dB attenuation requirement, and emission falls into restricted band, radiated emission was performed in order to show compliance with the general radiated emission requirement.

Result Summary:

Refer to Figure 10 to 13 for the emission data graph, result shows that the significant emissions detected are with more than 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power.

Limits for Out of Frequency Band Emission [Section 15.247 (d)]:

In any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power. Attenuation below the general limits specified in Section 15.209(a) is not required.

Limit for Radiated Emission Falling in Restricted Bands [Section 15.209]:

Frequency (MHz)	Field Strength [$\mu\text{V}/\text{m}$]	Field Strength [$\text{dB}\mu\text{V}/\text{m}$]
30-88	100	40.0
88-216	150	43.5
216-960	200	46.0
Above 960	500	54.0

Radiated emissions, which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209.

The emission limits shown in the above table are based on measurement employing a CISPR quasi-peak detector and above 1000MHz are based on measurements employing an average detector.

Report No.: 60.870.10.013.01F

Result : PASS

All Emission and Emissions Fall into Restricted Band were recorded as below:

Radiated Emissions							
	Emissions Frequency MHz	E-Field Polarity	Reading dBuV/m	System Factor dB	Field strength at 3m dBuV/m	Limit dBuV/m	Delta to Limit dBuV/m
Lowest Channel							
PK	*4808.23	V	67.21	1.99	69.20	74.00	-4.80
AV		V	41.63	1.99	43.62	54.00	-10.38
PK	*4808.23	H	69.01	1.99	71.00	74.00	-3.00
AV		H	44.36	1.99	46.35	54.00	-7.65
Middle Channel							
PK	*4880.32	H	68.41	1.99	70.40	74.00	-3.60
AV		H	42.56	1.99	44.55	54.00	-9.45
PK	*4880.32	V	65.71	1.99	67.70	74.00	-6.30
AV		V	39.86	1.99	41.85	54.00	-12.15
Highest Channel							
PK	*4956.25	V	65.88	2.32	68.20	74.00	-5.80
AV		V	40.03	2.32	42.35	54.00	-11.65
PK	*4956.25	V	63.58	2.32	65.90	74.00	-8.10
AV		V	37.73	2.32	40.05	54.00	-13.95
Spurious Emissions							
QP	30.21	V	10.22	13.58	23.80	40.00	-16.20
QP	36.93	V	15.24	12.16	27.40	40.00	-12.60
QP	46.89	V	15.90	10.20	26.10	40.00	-13.90
QP	336.02	V	17.83	15.17	33.00	46.00	-13.00
QP	600.03	V	11.05	20.25	31.30	46.00	-14.70
QP	36.90	H	1.94	12.16	14.10	40.00	-25.90
QP	46.77	H	9.20	10.20	19.40	40.00	-20.60
QP	336.01	H	27.63	15.17	42.80	46.00	-3.20
QP	408.02	H	21.19	17.21	38.40	46.00	-7.60

Refer to Figure 10 to 13 shows the worst case channel's emission data graph from 30MHz-26GHz.

Result Summary:

- 1) Communication mode: All other emissions are more than 20dB below FCC part 15.209 limit.
- 2) No further spurious emissions found between 30 MHz and lowest internal used/generated frequency and from 30MHz to 1GHz.

Remarks:

1. " * " Radiated emissions which fall in the restricted bands as defined in Section 15.205(a).
2. Emission level with more than 20dB below the FCC required limit is not mentioned in table.
3. Delta to Limit = Field strength (dBuV/m) – Limit (dBuV/m).
4. Calculated measurement uncertainty: 9kHz -30MHz: 1.8dB.
30MHz -1GHz: 5.2dB.
1GHz -18GHz: 5.1dB.

Figure 10 – Radiated emission data graph (Vertical polarization, 30MHz-1GHz)






Figure 11 – Radiated emission data graph (Vertical polarization, 1GHz-26GHz)



Remark: Only background noise was measured from 13GHz-26GHz.

Figure 12 – Radiated emission data graph (Horizontal polarization, 30MHz-1GHz)






Figure 13 – Radiated emission data graph (Horizontal polarization, 1GHz-26GHz)



Remark: Only background noise was measured from 13GHz-26GHz.

Report No.: 60.870.10.013.01F

4.9 Conducted Emissions (0.15MHz to 30MHz)

Test Requirement: FCC part 15 Section 15.207 Class B
Test Method: ANSI C63.4:2003
Test Date: 2010-08-10
Mode of Operation: Transmitting mode (The worst case)
Detector Function: CISPR Quasi Peak
Measurement BW: 100 kHz
Worst Case Channel: 1

Results: PASS

- Refer Figure 14 for the result data graph.

Limits for Conducted Emission [Section 15.207]:


Frequency Range [MHz]	Quasi-Peak Limit [dB μ V]	Average Limit [dB μ V]
0.15-0.5	66 to 56*	56 to 46*
0.5-5.0	56	46
5.0-30.0	60	50

* Decreases with the logarithm of the frequency.


Remarks:

Calculated measurement uncertainty: ± 2.8 dB

Figure 14– Result data graph shows the conducted emission



Phase Live



Phase Neutral

Report No.: 60.870.10.013.01F

Refer to the following page for the result details:

Frequency (MHz)	Detector (QP/AV)	Phase	Result (dB μ V)	Limit (dB μ V)	Margin
0.600	QP	L	45.00	56.00	-11.00
	AV	L	32.60	46.00	-13.40
2.346	QP	L	43.70	56.00	-12.30
	AV	L	22.10	46.00	-23.90
3.210	QP	L	45.10	56.00	-10.90
	AV	L	20.80	46.00	-25.20
4.710	QP	L	49.60	56.00	-6.40
	AV	L	30.20	46.00	-15.80
5.406	QP	L	50.80	60.00	-9.20
	AV	L	31.80	50.00	-18.20
19.734	QP	L	51.50	60.00	-8.50
	AV	L	32.80	50.00	-17.20
4.311	QP	N	50.90	56.00	-5.10
	AV	N	30.50	46.00	-15.50
5.412	QP	N	52.70	60.00	-7.30
	AV	N	32.20	50.00	-17.80
18.845	QP	N	47.10	60.00	-12.90
	AV	N	27.30	50.00	-22.70
1.806	QP	N	45.80	56.00	-10.20
	AV	N	24.30	46.00	-21.70
1.302	QP	N	47.20	56.00	-8.80
	AV	N	29.00	46.00	-17.00
0.600	QP	N	46.50	56.00	-9.50
	AV	N	31.80	46.00	-14.20

Report No.: 60.870.10.013.01F

5.0 RF Exposure Compliance Requirement

Test Requirement: FCC part 15 section 15.247 (i)
 Test Method: FCC part 15 section 1.1307 (b1)
 OET Bulletin 65, Edition 01-01

Results: PASS

Systems operation under the provision of this section shall be operated in a manner that ensures the public is not exposed to radio frequency energy levels in excess of the Commission's guideline,

The EUT is considered as a mobile device according to OET Bulletin 65, Edition 01-01, therefore distance to human body of min. 20cm is determined.

Frequency Band:	2.402GHz ~2.479GHz
Device Category:	<input type="checkbox"/> Portable (< 20cm separation) <input checked="" type="checkbox"/> Mobile (>20cm separation) <input type="checkbox"/> Others :
Exposure Classification:	<input type="checkbox"/> Occupational/ Controlled exposure <input checked="" type="checkbox"/> General Population / Uncontrolled exposure
Max. Output Power	29.18mW
Antenna Gain	0dBi (Numeric gain:1)
Evaluation Applied:	<input checked="" type="checkbox"/> MPE Evaluation <input type="checkbox"/> SAR Evaluation

MPE calculation:

The radiated (EIRP) = 29.18 mW

The power density at 20cm from the antenna : = $EIRP / 4\pi R^2$
 = 0.0058mW / cm²

Limits for General Population/Uncontrolled Exposure [OET Bulletin 65, Edition 01-01]:

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f ²)*	30
30-300	27.5	0.073	0.2	30
300-1500	--	--	f/1500	30
1500-100,000	--	--	1.0	30

6.0 List of Measurement Equipment

Radiated Emission

Test Equipment	Manufacturer	Model No.	S/N	Cal Date	Due Date
HORN ANTENNA	EMCO	3115	9002-3351	16 Apr 10	16 Apr 12
SEMI-ANECHOIC CHAMBER	Frankonia	N/A	N/A	27 Apr 10	27 Apr 11
BI-CONICAL ANTENNA	R&S	HK116	100241	13 Apr 10	13 Apr 12
EMI TEST RECEIVER	R&S	ESU26	100050	25 May 10	25 May 11
ACTIVE LOOP ANTENNA	EMCO	6502	9107-2651	6 Feb 10	6 Feb 11
LOG PERIODIC ANTENNA	R&S	HL223	841516/020	13 Apr 10	13 Apr 12
SPECTRUM ANALYZER	Advantest	R3272	72420848	23 Mar 10	23 Mar 11

Conducted Emission

Test Equipment	Manufacturer	Model No.	S/N	Cal Date	Due Date
TEST RECEIVER	R&S	ESHS30	847115/005	24 Aug 09	24 Aug 10
LISN	R&S	ESH3-Z5	849876/027	24 Aug 09	24 Aug 10
RF Voltage Probe	Schwarzbeck	TK9416	N/A	13 Feb 10	13 Feb 11

N/A Not Applicable or Not Available