

Cover Letter-Wireless Charger Approval

Date: 2021-4-26

Gentlemen:

There's a *Conference Hub* that would like to have your authorization as an Inductive wireless power transfer applications approval.

The specific product as below, *Conference Hub*, with its designed features and specified description, meets special requirements for KDB 680106 D01 section 5.2 requirements.

| Company: | Voxx Accessories Corp. |
|---------------|------------------------|
| Product Name: | Conference Hub |
| Model Number: | ARVS10 |
| FCC ID: | VIXARVS10 |

| KDB 680106 D01 Section 5.2 Requirements | Product Technical Specification | Result |
|--|------------------------------------|----------|
| a) Power transfer frequency is less that 1 MHz | 114.4kHz - 143.6kHz | Complied |
| b) Output power from each primary coil is less than | 5W, 7.5W, 10W | Complied |
| or equal to 15 watts. | | |
| c) The transfer system includes only single primary | | Complied |
| and secondary coils. This includes charging systems | | |
| that may have multiple primary coils and clients | | |
| that are able to detect and allow coupling only | | |
| between individual pairs of coils | | |
| d) Client device is placed directly in contact with | | Complied |
| the transmitter. | | |
| e) Mobile exposure conditions only | For inductive applications where | Complied |
| | the primary does not physically | |
| | attach to the client, and it is | |
| | intended for desktop use, the | |
| | desktop guidance in KDB 680106 | |
| | D01 may be applied | |
| f) The aggregate H-field strengths at 15 cm | Please refer to RF exposure report | Complied |
| surrounding the device and 20 cm above the top | | |
| surface from all simultaneous transmitting coils are | | |
| demonstrated to be less than 50% of the MPE limit. | | |

Sincerely, Print Name: Paul Tinaphong

Title: Senior V.P.

Signature: Paul Tinaphong

On behalf of Company: Voxx Accessories Corp.

Telephone: (317)2187301

E-mail: ptinaphong@voxxintl.com