

FCC RF EXPOSURE REPORT

FCC ID: VIXHPA230

Project No. : 1712C100
Equipment : Bluetooth Wireless Earbuds
Model : HPA230
Applicant : Paul Tinaphong
**Address : 3502 Woodview Trace, suite 220, Indianapolis,
Indiana, United States, 46268**

**According: : FCC Guidelines for Human Exposure IEEE
C95.1 & KDB447498 D01**

B T L I N C .

No.3, Jinshagang 1st Road, Shixia, Dalang Town, Dongguan, China.
TEL: +86-769-8318-3000 FAX: +86-769-8319-6000

Table for Filed Antenna

Ant.	Manufacturer	Model Name	Antenna Type	Connector	Gain(dBi)
1	N/A	N/A	Chip	N/A	4.97

GENERAL CONCLUSION:

Maximum measured transmitter power:

OutputPower (dBm)	Output Power (mW)	Limit (mW)
0.63	1.156	10

According to FCC KDB447498 D01 V06, Appendix A, SAR Test Exclusion Thresholds for 100 MHz – 6 GHz and ≤ 50 mm

The maximum measured output peak power of this EUT is 1.156mW, less than 10mW at 5mm distance.

Conclusion: No SAR evaluation required since transmitter power is below FCC threshold