

Report No.: FYCR220500016703

Page: 1 of 10

1 Cover Page

RF Exposure Report

Application No.: FYCR2205000167AT **Applicant**: Voxx Accessories Corp.

Address of Applicant: 3502 Woodview Trace Suite 220, Indianapolis, Indiana 46268 United

States

Manufacturer: Voxx Accessories Corp.

Address of Manufacturer: 3502 Woodview Trace Suite 220, Indianapolis, Indiana 46268 United

Factory: States
States
Smart Glory Electronics (ShenZhen) Co., Ltd

Building Four, No.63, Zhangqi Road, Qiping Village, Daping Community,

Address of Factory: Guanlan Street, Longhua New District, Shenzhen

Equipment Under Test (EUT):

EUT Name: Wireless Soothing Projector

Model No.: PNP80

Trade mark: Project Nursery FCC ID: VIXPNP80

Standard(s): FCC Rules 47 CFR §2.1093

KDB 447498 D04 interim General RF Exposure Guidance v01

Date of Receipt: 2022-05-13

Date of Test: 2022-05-17 to 2022-05-24

Date of Issue: 2022-05-26

Test Result: Pass*

Kidd Yang EMC Laboratory Manager



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions [Ferms-and-Conditions.aspx and, for electronic Documents at http://www.sgs.com/en/Terms-and-Conditions-and-Conditions-and-Condi

^{*} In the configuration tested, the EUT complied with the standards specified above.



Report No.: FYCR220500016703

Page: 2 of 10

	Revision Record							
Version	Chapter	Date	Modifier	Remark				
01		2022-05-26		Original				

Authorized for issue by:		
	Tree Zhan	
	Tree Zhan/Project Engineer	
	WinkeyWarg	
	Winkey Wang/Reviewer	



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions agry and, for electronic format documents, subject to Terms and Conditions of Electronic Documents at http://www.sgs.com/en/Iffsms-and-Conditions/Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction document. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawfull and offenders may be prosecuted to the fullest ent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Fuyong lab. Xiniong TechnoPark, Fenglang Road, Fuyong Subdishird, Bao'an, Sherzhen, China 518103 t (86–755) 88663988 f (86–755) 26710594 www.sggroup.com.cn 中国・深圳・宝安区福永街道风塘大道鑫龙科技园福永实验室 邮编:518103 t (86–755) 88663988 f (86–755) 26710594 sgs.china@sgs.com



Report No.: FYCR220500016703

Page: 3 of 10

2 Contents

		F	Page
1	COV	/ER PAGE	1
2	CON	NTENTS	3
3	GEN	NERAL INFORMATION	4
	3.1	GENERAL DESCRIPTION OF E.U.T.	4
	3.2	DETAILS OF E.U.T.	4
	3.3	SEPARATION DISTANCE	4
	3.4	TEST LOCATION	5
	3.5	TEST FACILITY	5
4	FCC	RADIOFREQUENCY RADIATION EXPOSURE LIMITS	6
	4.1	BLANKET 1 MW BLANKET EXEMPTION	6
	4.2	MPE-BASED EXEMPTION	6
	4.3	SAR-BASED EXEMPTION	
5	MEA	ASUREMENT AND CALCULATION	.10
	5.1	MAXIMUM TRANSMIT POWER	.10
	5.2	RF EXPOSURE CALCULATION	.10



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions, asps.yand. for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions ferms-en-Document aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawfull and offenders may be prosecuted to the fullest ent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Flyong lab. Kinong TechnoPark, Ferglang Road, Flyong Subdistint, Bao'an, Shenzhen, China 518103 t (86-755) 88663988 f (86-755) 26710594 www.sgsgroup.com.cn 中国・深圳・宝安区福永街道凤塘大道鑫龙科技园福永实验室 邮编: 518103 t (86-755) 88663988 f (86-755) 26710594 sgs.china@sgs.com



Report No.: FYCR220500016703

Page: 4 of 10

3 General Information

	□ Portable device □
Product Type:	☐ Mobile device
	☐ Fixed device

3.2 Details of E.U.T.

O.E Details of E.O.T.				
Power Supply:	AC adapter:			
	Model: NLA030060W1A6			
	Input: 100-240V 50/60Hz 0.2A Max.			
	Output: 6V 300mA			
	or 3 x 1.5V AAA batteries.			
Cable(s):	DC cable 180cm unshielded			
Operation Frequency:	2402MHz to 2480MHz			
Bluetooth Version:	V5.2 Classic			
Modulation Type:	GFSK, pi/4DQPSK, 8DPSK			
Number of Channels:	79			
Channel Spacing:	1MHz			
Spectrum Spread				
Technology:	Frequency Hopping Spread Spectrum(FHSS)			
Antenna Type:	PCB Antenna			
Antenna Gain:	0dBi			

3.3 Separation Distance

Minimum test separation distance: 5mm

Remark: This minimum test separation distance is determined by the smallest distance from the antenna and radiating structures or outer surface of the device, according to the host form factor, exposure conditions and platform requirements, to any part of the body or extremity of a user or bystander.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents as subject to Terms and Conditions feelectronic Document as fully. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawfull and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Fuyong lab. Xinlong TechnoPark, Fengtang Road, Fuyong Subdistrict, Bao'an, Shenzhen, China 518103 t (86-755) 88663988 f (86-755) 26710594 www.sgsgroup.com.cn 中国·深圳·宝安区福永街道风塘大道鑫龙科技园福永实验室 邮编: 518103 t (86-755) 88663988 f (86-755) 26710594 sgs.china@sgs.com



Report No.: FYCR220500016703

Page: 5 of 10

3.4 Test Location

All tests were performed at:

Compliance Certification Services (Kunshan) Inc. Shenzhen branch.

Fuyong lab. Xinlong TechnoPark, Fengtang Road, Fuyong Subdistrict, Bao'an, Shenzhen, China

Tel: +86 755 8866 3988 Fax: +86 755 2671 0594

No tests were sub-contracted.

3.5 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

A2LA (Certificate No. 6606.01)

Compliance Certification Services (Kunshan) Inc. Shenzhen branch is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 6606.01.

• FCC -Designation Number: CN1322

Compliance Certification Services (Kunshan) Inc. Shenzhen branch has been recognized as an accredited testing laboratory.

Designation Number: CN1322. Test Firm Registration Number: 718073

• Innovation, Science and Economic Development Canada

Compliance Certification Services (Kunshan) Inc. Shenzhen branch has been recognized by ISED as an accredited testing laboratory.

CAB identifier: CN0129.

IC#: 28189.





Report No.: FYCR220500016703

Page: 6 of 10

4 FCC Radiofrequency radiation exposure limits

Test exemptions apply for devices used in general population/uncontrolled exposure environments, according to the SAR-based, or MPE-based exemption thresholds.

4.1 Blanket 1 mW Blanket Exemption

The 1 mW Blanket Exemption of §1.1307(b)(3)(i)(A) applies for single fixed, mobile, and portable RF sources with available maximum time-averaged power of no more than 1 mW, regardless of separation distance.

The 1-mW blanket exemption applies at separation distances less than 0.5 cm, including where there is no separation. This exemption shall not be used in conjunction with other exemption criteria other than those for multiple RF sources in paragraph §1.1307(b)(3)(ii)(A).

The 1-mW exemption is independent of service type and covers the full range of 100 kHz to 100 GHz, but it shall not be used in conjunction with other exemption criteria or in devices with higher-power transmitters operating in the same time-averaging period. Exposure from such higher-power transmitters would invalidate the underlying assumption that exposure from the lower-power transmitter is the only contributor to SAR in the relevant volume of tissue.

4.2 MPE-based Exemption

General frequency and separation-distance dependent MPE-based effective radiated power (ERP) thresholds are in Table B.1 [Table 1 of §1.1307(b)(1)(i)(C)] to support an exemption from further evaluation from 300 kHz through 100 GHz.

Table B.1—Thresholds For Single RF Sources Subject to Routine Environmental Evaluation

RF Source Frequency			Minimum Distance			Threshold ERP
f∟ MHz		f _H MHz	λ∟ / 2π		λ _H / 2π	W
0.3	_	1.34	159 m	-	35.6 m	1,920 R ²
1.34	_	30	35.6 m	-	1.6 m	3,450 R ² /f ²
30	_	300	1.6 m	-	159 mm	3.83 R ²
300	_	1,500	159 mm	-	31.8 mm	0.0128 R ² f
1,500	_	100,000	31.8 mm	_	0.5 mm	19.2R ²

Subscripts L and H are low and high; λ is wavelength.

From §1.1307(b)(3)(i)(C), modified by adding Minimum Distance columns.

The table applies to any RF source (i.e. single fixed, mobile, and portable transmitters) and specifies power and distance criteria for each of the five frequency ranges used for the MPE limits. These criteria apply at separation distances from any part of the radiating structure of at least $\lambda/2\pi$. The thresholds are



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx.and, for electronic format documents at <a href="http://www.sgs.com/en/Terms-and-Conditions-and-Conditions-and-Cond

Fulyong lab. Xiniong TechnoPark, Fenglang Road, Fulyong Subdistrict, Bao'an, Shenzhen, China 518103 t (86-755) 88663988 f (86-755) 26710594 www.sgsgroup.com.cn 中国・深圳・宝安区福永街道凤塘大道鑫龙科技园福永实验室 邮编: 518103 t (86-755) 88663988 f (86-755) 26710594 sgs.china@sgs.com



Report No.: FYCR220500016703

Page: 7 of 10

based on the general population MPE limits with a single perfect reflection, outside of the reactive near-field, and in the main beam of the radiator.

For mobile devices that are not exempt per Table B.1 [Table 1 of §1.1307(b)(1)(i)(C)] at distances from 20 cm to 40 cm and in 0.3 GHz to 6 GHz, evaluation of compliance with the exposure limits in §1.1310 is necessary if the ERP of the device is greater than *ERP*_{20cm} in Formula (B.1) [repeated from §2.1091(c)(1); also in §1.1307(b)(1)(i)(B)].

$$P_{\text{th }}(\text{mW}) = ERP_{20 \text{ cm }}(\text{mW}) = \begin{cases} 2040f & 0.3 \text{ GHz} \le f < 1.5 \text{ GHz} \\ \\ 3060 & 1.5 \text{ GHz} \le f \le 6 \text{ GHz} \end{cases}$$
(B. 1)

If the ERP is not easily obtained, then the available maximum time-averaged power may be used (i.e., without consideration of ERP only if the physical dimensions of the radiating structure(s) do not exceed the electrical length of $\lambda/4$ or if the antenna gain is less than that of a half-wave dipole.

SAR-based exemptions are constant at separation distances between 20 cm and 40 cm to avoid discontinuities in the threshold when transitioning between SAR-based and MPE-based exemption criteria at 40 cm, considering the importance of reflections.

Limit calculation							
Frequency range Frequency(MHz) $R(\lambda/2\pi)(m)$ Threshold ERP(W)							
300~1500MHz	915	0.0522	0.032				
1500~100000MHz	2480	0.0193	0.007				

4.3 SAR-based Exemption

SAR-based thresholds are derived based on frequency, power, and separation distance of the RF source. The formula defines the thresholds in general for either available maximum time-averaged power or maximum time-averaged ERP, whichever is greater.

If the ERP of a device is not easily determined, such as for a portable device with a small form factor, the applicant may use the available maximum time-averaged power exclusively if the device antenna or radiating structure does not exceed an electrical length of $\lambda/4$.

As for devices with antennas of length greater than $\lambda/4$ where the gain is not well defined, but always less than that of a half-wave dipole (length $\lambda/2$), the available maximum time-averaged power generated by the device may be used in place of the maximum time-averaged ERP, where that value is not known. The separation distance is the smallest distance from any part of the antenna or radiating structure for all persons, during operation at the applicable ERP. In the case of mobile or portable devices, the separation distance is from the outer housing of the device where it is closest to the antenna.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.apx, and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx.
Attention is drawn to the limitation of liability, indemnification and jurisdiction issues define therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, rigery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: C.P. Doccheck @ Company C.P. Do

Fuyong lab. Xinlong TechnoPark, Fergiang Road, Fuyong Subdishird, Bao'an, Shenzhen, Chira 518103 t (86-755) 88663988 f (86-755) 26710594 www.sgsgroup.com.cn 中国·深圳·宝安区福永街道风塘大道鑫龙科技园福永实验室 邮编: 518103 t (86-755) 88663988 f (86-755) 26710594 sgs.china@sgs.com



Report No.: FYCR220500016703

Page: 8 of 10

The SAR-based exemption formula of $\S1.1307(b)(3)(i)(B)$, repeated here as Formula (B.2), applies for single fixed, mobile, and portable RF sources with available maximum time-averaged power or effective radiated power (ERP), whichever is greater, of less than or equal to the threshold P_{th} (mW).

This method shall only be used at separation distances from 0.5 cm to 40 cm and at frequencies from 0.3 GHz to 6 GHz (inclusive). P_{th} is given by Formula (B.2).

$$P_{\text{th}} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}} (d/20 \text{ cm})^x & d \le 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \le 40 \text{ cm} \end{cases}$$
(B. 2)

where

$$x = -\log_{10}\left(\frac{60}{ERP_{20 \text{ cm}}\sqrt{f}}\right)$$

and f is in GHz, d is the separation distance (cm), and ERP_{20cm} is per Formula (B.1).



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printe overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.apx and, for electronic format documents subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx.Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined herein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document one on toxonerate parties to a transaction from exercising all their rights and obligations under the transaction document. This document cannot be reproduce except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or faisification of the content of appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-75) 83071443 or and 10 Certificate.

Fuyong lab. Xinlong TechnoPark, Fergiang Road, Fuyong Subdishird, Bao'an, Shenzhen, Chira 518103 t (86-755) 88663988 f (86-755) 26710594 www.sgsgroup.com.cn 中国·深圳·宝安区福永街道风塘大道鑫龙科技园福永实验室 邮编: 518103 t (86-755) 88663988 f (86-755) 26710594 sgs.china@sgs.com



Report No.: FYCR220500016703

Page: 9 of 10

Example values shown in Table B.2 are for illustration only.

Table B.2—Example Power Thresholds (mW)

Frequency				•	Distanc	ce(mm)				
(MHz)	5	10	15	20	25	30	35	40	45	50
300	39	65	88	110	129	148	166	184	201	217
450	22	44	67	89	112	135	158	180	203	226
835	9	25	44	66	90	116	145	175	207	240
1900	3	12	26	44	66	92	122	157	195	236
2450	3	10	22	38	59	83	111	143	179	219
3600	2	8	18	32	49	71	96	125	158	195
5800	1	6	14	25	40	58	80	106	136	169

Limit calculation							
Frequency range(GHz) Frequency(GHz) X Distance(cm) Pth (mW)							
0.3~1.5 0.915 1.474 0.5 8 .							
1.5~6	2.48	1.905	0.5	2.717			



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.apx.and, for electronic format documents subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.apx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits to Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 50 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 83071443

Flyong lab. Kinong TechnoPark, Ferglang Road, Flyong Subdistint, Bao'an, Shenzhen, China 518103 t (86-755) 88663988 f (86-755) 26710594 www.sgsgroup.com.cn 中国・深圳・宝安区福永街道凤塘大道鑫龙科技园福永实验室 邮编: 518103 t (86-755) 88663988 f (86-755) 26710594 sgs.china@sgs.com



Report No.: FYCR220500016703

Page: 10 of 10

5 Measurement and Calculation

5.1 Maximum transmit power

The Power Data is based on the RF Test Report FYCR220500016702.

Test Mode	Test Channel	EIRP[dBm]	EIRP (mW)
ВТ	2402	2.54	1.79
ВТ	2441	3.13	2.06
BT	2480	3.18	2.08

5.2 RF Exposure Calculation

The Max EIRP is 2.08mW. The best case gain of the antenna is 0.00dBi.

Remark: we used the maximum power between the conducted power and ERP/EIRP to perform RF exposure exemption evaluation.

	Evaluation method	Exempt Limit(mW)	Verdict
	Blanket 1 mW Blanket Exemption	1mW	N/A
	MPE-based Exemption(ERP)	7mW(ERP)	N/A
\boxtimes	SAR-based Exemption(<i>P</i> th)	2.7mW	Yes

So, the device is to qualify for SAR test exemption, the exemption report is in lieu of the SAR report.

-- End of the Report--



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printe overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.apx and, for electronic format documents subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx.Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined herein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document one on toxonerate parties to a transaction from exercising all their rights and obligations under the transaction document. This document cannot be reproduce except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or faisification of the content of appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-75) 83071443 or and 10 Certificate.

Fuyong lab. Xinlong TechnoPark, Fergiang Road, Fuyong Subdishird, Bao'an, Shenzhen, Chira 518103 t (86-755) 88663988 f (86-755) 26710594 www.sgsgroup.com.cn 中国·深圳·宝安区福永街道风塘大道鑫龙科技园福永实验室 邮编: 518103 t (86-755) 88663988 f (86-755) 26710594 sgs.china@sgs.com