

FCC PART 15C TEST REPORT FOR CERTIFICATION
On Behalf of

Voxx Accessories Corp.

Wireless Speaker

Model Number: SP891B

FCC ID: VIXSP891B

Prepared for : Voxx Accessories Corp.
3502 Woodview Trace, Suite 220, Indianapolis,
IN 46268

Prepared By : EST Technology Co., Ltd.
Santun(guantai Road), Houjie Town, DongGuan City,
GuangDong, China.

Tel: 86-769-83081888-808

Report Number: ESTE-R1411007
Date of Test : Oct 29,2014~ Nov 10, 2014
Date of Report : Nov 11, 2014

TABLE OF CONTENTS

Description	Page
TEST REPORT VERIFICATION.....	3
1. GENERAL INFORMATION.....	5
1.1. Description of Device (EUT).....	5
2. SUMMARY OF TEST.....	6
2.1. Summary of test result.....	6
2.2. Test Facilities.....	7
2.3. Assistant equipment used for test.....	8
2.4. Block Diagram.....	8
2.5. Test mode.....	9
2.6. Channel List for Bluetooth.....	9
2.7. Test Equipment.....	10
3. MAXIMUM PEAK OUTPUT POWER.....	11
3.1. Limit.....	11
3.2. Test Procedure.....	11
3.3. Test Result.....	11
3.4. Test Data.....	12
4. 20 DB BANDWIDTH.....	16
4.1. Limit.....	16
4.2. Test Procedure.....	16
4.3. Test Result.....	16
4.4. Test Data.....	17
5. CARRIER FREQUENCY SEPARATION.....	21
5.1. Limit.....	21
5.2. Test Procedure.....	21
5.3. Test Result.....	21
5.4. Test Data.....	22
6. NUMBER OF HOPPING CHANNEL.....	26
6.1. Limit.....	26
6.2. Test Procedure.....	26
6.3. Test Result.....	26
6.4. Test Data.....	27
7. DWELL TIME.....	29
7.1. Limit.....	29
7.2. Test Procedure.....	29
7.3. Test Result.....	29
7.4. Test Data.....	30
8. RADIATED EMISSIONS.....	33
8.1. Limit.....	33
8.2. Block Diagram of Test setup.....	34
8.3. Test Procedure.....	34
8.4. Test Result.....	34

- 8.5. Test Data 35
- 9. BAND EDGE COMPLIANCE 71
 - 9.1. Limit 71
 - 9.2. Block Diagram of Test setup 71
 - 9.3. Test Procedure 71
 - 9.4. Test Result 71
 - 9.5. Test Data 72
- 10. POWER LINE CONDUCTED EMISSIONS 88
 - 10.1. Limit 88
 - 10.2. Test Procedure 88
- 11. ANTENNA REQUIREMENTS 91
 - 11.1. Limit 91
 - 11.2. Result 91
- 12. TEST SETUP PHOTO 92
- 13. PHOTOS OF EUT 94

Test Report Verification

Applicant:	Voxx Accessories Corp.		
Address:	3502 Woodview Trace, Suite 220, Indianapolis, IN 46268		
Manufacturer Address:	Guangzhou Changjia Electronic Co., Ltd. Bo-ying Industrial Garden, Taishi Industrial Zone, Yuwotou, Dongchong Town, Nansha district, Guangzhou, China		
E.U.T:	Wireless Speaker		
Model Number:	SP891B (comes in color variations, but are electrically and mechanically the same the only difference is the color)		
Power Supply:	DC 3.7V From Internal Battery DC 5V From USB for Charging		
Test Voltage:	DC 3.7V		
Trade Name:	808	Serial No.:	-----
Date of Receipt:	Oct 29, 2014	Date of Test:	Oct 29, 2014~ Nov 10, 2014
Test Specification:	FCC Rules and Regulations Part 15 Subpart C:2013 ANSI C63.4:2009		
Test Result:	<p>The device described above is tested by EST Technology Co., Ltd.. The measurement results were contained in this test report and EST Technology Co., Ltd. was assumed full responsibility for the accuracy and completeness of these measurements. Also, this report shows that the EUT to be technically compliance with the ETSI EN FCC Rules and Regulations Part 15 Subpart C requirements.</p> <p style="text-align: right;">This report applies to above tested sample only and shall not be reproduced in part without written approval of EST Technology Co., Ltd. Date: Nov 11, 2014</p>		
Prepared by:	Tested by:	Approved by:	
			
Ada / Assistant	Tony.Tang/ Engineer	IcemanHu / Manager	
Other Aspects:	None.		
Abbreviations: OK/P=passed fail/F=failed n.a/N=not applicable E.U.T=equipment under tested			
This test report is based on a single evaluation of one sample of above mentioned products ,It is not permitted to be duplicated in extracts without written approval of EST Technology Co., Ltd.			



1. GENERAL INFORMATION

1.1. Description of Device (EUT)

Product Name	: Wireless Speaker
Model Number	: SP891B
FCC ID	: VIXSP891B
Operation frequency	: 2402MHz~2480MHz
Number of channel	: 79
Antenna	: Internal antenna, 0 dBi gain
Modulation	: FHSS (GFSK, $\pi/4$ -DQPSK, 8-DPSK)
Sample Type	: Prototype production

2. SUMMARY OF TEST

2.1. Summary of test result

Description of Test Item	Standard	Results
Maximum Peak Output Power	FCC Part 15: 15.247(b)(1) DA 00-705	PASS
20dB Bandwidth	FCC Part 15: 15.215 DA 00-705	PASS
Carrier Frequency Separation	FCC Part 15: 15.247(a)(1) DA 00-705	PASS
Number Of Hopping Channel	FCC Part 15: 15.247(a)(1)(iii) DA 00-705	PASS
Dwell Time	FCC Part 15: 15.247(a)(1)(iii) DA 00-705	PASS
Radiated Emission	FCC Part 15: 15.209 FCC Part 15: 15.247(d) ANSI C63.4: 2003 DA 00-705	PASS
Band Edge Compliance	FCC Part 15: 15.247(d) DA 00-705	PASS
Power Line Conducted Emissions	FCC Part 15: 15.207 ANSI C63.4: 2009 DA 00-705	PASS
Antenna requirement	FCC Part 15: 15.203	PASS

2.2. Test Facilities

EMC Lab	:	Certificated by CNAL, CHINA Registration No.: L5288 Date of registration: October 28, 2011
		Certificated by FCC, USA Registration No.: 989591 Date of registration: November 20, 2013
		Certificated by Industry Canada Registration No.: 9405A-1 Date of registration: January 03, 2013
		Certificated by VCCI, Japan Registration No.: R-3663 & C-4103 Date of registration: July 25, 2011
		Certificated by TUV Rheinland, Germany Registration No.: UA 50195514 0001 Date of registration: January 07, 2011
		Certificated by TUV/PS, Shenzhen Registration No.: SCN1017 Date of registration: January 27, 2011
		Certificated by Intertek ETL SEMKO Registration No.: 2011-RTL-L1-18 Date of registration: April 28, 2011
		Certificated by Siemic, Inc. Registration No.: SLCN021 Date of registration: November 8, 2011
		Certificated by Nemko, Hong Kong Registration No.: 175193 Date of registration: May 4, 2011
Name of Firm	:	EST Technology Co., Ltd.
Site Location	:	San Tun Management Zone, Houjie Town, Dongguan, Guangdong, China

2.3. Assistant equipment used for test

2.3.1. PC

Manufacturer	:	DELL
M/N	:	Laititude E6420
Adapter	:	M/N: DA90PM111
		Input: AC 100-240V~50/60Hz 1.5A
		Output: DC 19.5V/4.62A

2.4. Block Diagram

For radiated emissions test: EUT was placed on a turn table, which is 0.8 meter high above ground. EUT was be set into BT test mode by software before test.



(EUT: Wireless Speaker)

2.5. Test mode

The test software was used to control EUT work in Continuous TX mode, and select test channel, wireless mode

Mode	Channel	Frequency
GFSK	Low	2402MHz
	Middle	2441MHz
	High	2480MHz
8-DPSK	Low	2402MHz
	Middle	2441MHz
	High	2480MHz

2.6. Channel List for Bluetooth

Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)
1	2402	2	2403	3	2404	4	2405
5	2406	6	2407	7	2408	8	2409
9	2410	10	2411	11	2412	12	2413
13	2414	14	2415	15	2416	16	2417
17	2418	18	2419	19	2420	20	2421
21	2422	22	2423	23	2424	24	2425
25	2426	26	2427	27	2428	28	2429
29	2430	30	2431	31	2432	32	2433
33	2434	34	2435	35	2436	36	2437
37	2438	38	2439	39	2440	40	2441
41	2442	42	2443	43	2444	44	2445
45	2446	46	2447	47	2448	48	2449
49	2450	50	2451	51	2452	52	2453
53	2454	54	2455	55	2456	56	2457
57	2458	58	2459	59	2460	60	2461
61	2462	62	2463	63	2464	64	2465
65	2466	66	2467	67	2468	68	2469
69	2470	70	2471	71	2472	72	2473
73	2474	74	2475	75	2476	76	2477
77	2478	78	2479	79	2480	-	-

2.7. Test Equipment

2.7.1. For conducted emission test

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
EMI Test Receiver	Rohde & Schwarz	ESHS30	832354	June,28,14	1 Year
Artificial Mains Networ	Rohde & Schwarz	ENV216	101260	June,28,14	1 Year
Pulse Limiter	Rohde & Schwarz	ESH3-Z2	101100	June,28,14	1 Year

2.7.2. For radiated emission test(30-1000MHz)

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
EMI Test Receiver	Rohde & Schwarz	ESVS10	100004	June,28,14	1 Year
Spectrum Analyzer	Agilent	E4411B	MY5014069 7	June,28,14	1 Year
Bilog Antenna	Teseq	CBL 6111D	27090	June,28,14	1 Year
Signal Amplifier	Agilent	310N	187037	June,28,14	1 Year

2.7.3. For radiated emission test(above 1GHz)

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
Horn Antenna	SCHWARZB ECK	BBHA 9120 D	BBHA9120D1 002	June,28,1 4	1 Year
Signal Amplifier	SCHWARZB ECK	BBV9718	9718-212	June,28,1 4	1 Year
Spectrum Analyzer	Agilent	E4408B	MY44211139	June,28,1 4	1 Year
RF Cable	Hubersuhner	RG 214/U	513423	June,28,1 4	1 Year

3. MAXIMUM PEAK OUTPUT POWER

3.1. Limit

For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts, the e.i.r.p shall not exceed 4W

3.2. Test Procedure


The transmitter output (antenna port) was connected to the spectrum analyzer

3.3. Test Result


EUT: Wireless Speaker					
M/N: SP891B					
Test date: 2014-11-07		Test site: RF site		Tested by: Tony Tang	
Mode	Freq (MHz)	Result (dBm)	Limit		Margin (dB)
			dBm	W	
GFSK	2402	0.139	21.00	0.125	20..861
	2441	-0.362	21.00	0.125	21.362
	2480	-1.268	21.00	0.125	22.268
8-DPSK	2402	-0.983	21.00	0.125	21.983
	2441	-1.494	21.00	0.125	22.494
	2480	-2.394	21.00	0.125	23.394
Conclusion: PASS					

3.4. Test Data


GFSK 2402 MHz




GFSK 2441 MHz




GFSK 2480 MHz




8-DPSK 2402 MHz



8-DPSK 2441 MHz



8-DPSK 2480 MHz



4. 20 DB BANDWIDTH

4.1. Limit

Intentional radiators operating under the alternative provisions to the general emission limits, as contained in §§ 15.217 through 15.257 and in Subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated.

4.2. Test Procedure


The transmitter output was coupled to a spectrum analyzer via a antenna. The bandwidth of the fundamental frequency was measured by spectrum analyzer with 30kHz RBW and 100kHz VBW. The 20dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 20dB.

4.3. Test Result


EUT: Wireless Speaker				
M/N: SP891B				
Test date: 2014-11-07		Test site: RF site		Tested by: Tony Tang
Mode	Freq (MHz)	20dB Bandwidth (MHz)	Limit (kHz)	Conclusion
GFSK	2402	1.053	/	PASS
	2441	1.059	/	PASS
	2480	1.047	/	PASS
8-DPSK	2402	1.340	/	PASS
	2441	1.341	/	PASS
	2480	1.336	/	PASS

4.4. Test Data


GFSK 2402MHz




GFSK 2441MHz




GFSK 2480MHz




8-DPSK 2402MHz



8-DPSK 2441MHz



8-DPSK 2480MHz



5. CARRIER FREQUENCY SEPARATION

5.1. Limit

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW

5.2. Test Procedure


The transmitter output was coupled to a spectrum analyzer via a antenna. The carrier frequency was measured by spectrum analyzer with 100kHz RBW and 100kHz VBW.

5.3. Test Result


EUT: Wireless Speaker				
M/N: SP891B				
Test date: 2014-11-07		Test site: RF site		Tested by: Tony Tang
Mode	Channel	Channel separation (MHz)	Limit	Conclusion
GFSK	Low CH	1.000	> 2/3 of the 20dB Bandwidth or 25[kHz](whichever is greater)	PASS
	Mid CH	1.000		PASS
	High CH	1.000		PASS
8-DPSK	Low CH	1.013		PASS
	Mid CH	1.006		PASS
	High CH	1.006		PASS

5.4. Test Data


GFSK
Low Channel




Mid Channel




High Channel




8-DPSK Low Channel



Mid Channel



High Channel



6. NUMBER OF HOPPING CHANNEL

6.1. Limit

Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels

6.2. Test Procedure




The transmitter output was coupled to a spectrum analyzer via a antenna. The number of hopping channel was measured by spectrum analyzer with 300kHz RBW and 300kHz VBW.

6.3. Test Result




EUT: Wireless Speaker			
M/N: SP891B			
Test date: 2014-11-07		Test site: RF site	Tested by: Tony.Tang
Mode	Number of hopping channel	Limit	Conclusion
GFSK	79	>15	PASS
8-DPSK	79	>15	PASS

6.4. Test Data

GFSK



8-DPSK



7. DWELL TIME

7.1. Limit

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

7.2. Test Procedure

(1.)Connect EUT antenna output to spectrum analyzer by RF cable.

(2.)Measure the hopping number and on time of each pulse with spectrum analyzer in zero span Set, and calculate dwell time formula Dwell time=total hops*pulses on time.

DH1 Packet permit maximum $1600/79/2=10.12$ hops per second in each channel(1 time slot RX,1 time slot TX).So, total hops is $10.12*31.6=320.0$

DH3 Packet permit maximum $1600/79/4=5.06$ hops per second in each channel(3 time slot RX,1time slot TX).So, total hops is $5.06*31.6=160.0$

DH5 Packet permit maximum $1600/79/6=3.37$ hops per second in each channel(5 time slot RX,1time slot TX).So, total hops is $3.37*31.6=106.6$

3DH1 Packet permit maximum $1600/79/2=10.12$ hops per second in each channel(1 time slot RX,1 time slot TX).So, total hops is $10.12*31.6=320.0$

3DH3 Packet permit maximum $1600/79/4=5.06$ hops per second in each channel(3 time slot RX,1time slot TX).So, total hops is $5.06*31.6=160.0$


3DH5 Packet permit maximum $1600/79/6=3.37$ hops per second in each channel(5 time slot RX,1time slot TX).So, total hops is $3.37*31.6=106.6$

7.3. Test Result


EUT : Wireless Speaker M/N :SP891B Test Date :2014-11-07 Test Engineer :Tony					
Mode	Dwell time	Pulses on time	Total hops	Limit	Conclusion
DH1	137.60ms	0.43ms	320.0	<400ms	PASS
DH3	275.20ms	1.72ms	160.0	<400ms	PASS
DH5	309.14ms	2.90ms	106.6	<400ms	PASS
3DH1	128.00ms	0.40ms	320.0	<400ms	PASS
3DH3	273.60ms	1.71ms	160.0	<400ms	PASS
3DH5	311.27ms	2.92ms	106.6	<400ms	PASS
Note Dwell time :total hops*pulses on time					

7.4. Test Data


DH1 pulses on time:0.43ms




DH3 pulses on time:1.72ms




DH5 pulses on time:2.90ms




3DH1 pulses on time:0.40ms



3DH3 pulses on time:1.71ms



3DH5 pulses on time:2.92ms



8. RADIATED EMISSIONS

8.1. Limit

All the emissions appearing within 15.205 restricted frequency bands shall not exceed the limits shown in 15.209, all the other emissions shall be at least 20dB below the fundamental emissions, or comply with 15.209 limits.


15.205 Restricted frequency band

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 - 156.52525	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.7 - 156.9	2690 - 2900	22.01 - 23.12
8.41425 - 8.41475	162.0125 - 167.17	3260 - 3267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	240 - 285	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	322 - 335.4	3600 - 4400	(²)

15.209 Limit

FREQUENCY MHz	DISTANCE Meters	FIELD STRENGTHS LIMIT	
		μV/m	dB(μV)/m
30 ~ 88	3	100	40.0
88 ~ 216	3	150	43.5
216 ~ 960	3	200	46.0
960 ~ 1000	3	500	54.0
Above 1000	3	74.0 dB(μV)/m (Peak) 54.0 dB(μV)/m (Average)	

8.2. Block Diagram of Test setup



8.3. Test Procedure

EUT was placed on a turn table, which is 0.8 meter high above ground. The turn table can rotate 360 degrees to determine the position of the maximum emission level. Power on the EUT and let it working in test mode, then test it. EUT is set 3 meters away from the receiving antenna, which is mounted on a antenna tower. The antenna can be moved up and down between 1 meter and 4 meters to find out the maximum emission level. Both horizontal and vertical polarization of the antenna are set on test.

The bandwidth of the EMI test receiver (R&S ESVS10) is set at 120kHz for frequency range from 30MHz to 1000 MHz.

The bandwidth of the Spectrum’s VBW is set at 1MHz and RBW is set at 1MHz for peak emissions measurement above 1GHz and 1MHz RBW, 10Hz VBW for average emissions measure above 1GHz

- PEAK detector, 1MHz/1MHz for PAEK measurement,
- PEAK detector, 1MHz/10Hz for Average measurement

The frequency range from 30MHz to 10th harmonic (25GHz) are checked.


8.4. Test Result

30MHz—25GHz Radiated emissison Test result
EUT: Wireless Speaker
M/N: SP891B
Power: DC 3.7V
Test date: 2014-11-02~11-05 Test site: 3m Chamber Tested by: Tony Tang
Test mode: Tx Mode
Pass

- Note: 1、 For emissions above 1GHz, if peak level comply with average limit, then the average level is deemed to comply with average limit.
- 2、 The frequency 2402MHz 、 2441MHz and 2480MHz is fundamental frequency which no limit, the limit on plots is automatically generated by the software, it's not fundamental limit, we can't remove it.

8.5. Test Data


30 MHz – 1000 MHz



```


Site no.       : 3m Chamber                Data no. : 179
Dis. / Ant.   : 3m 27137                 Ant. pol. : HORIZONTAL
Limit        : FCC PART 15 B
Env. / Ins.   : Temp:25.6';Humi:56%;Press:101.52kPa
Engineer     : Tony
EUT          : Wireless Speaker
Power        : DC 3.7V
M/N          : SP891B
Test Mode    : GFSK TX 2402MHz
    
```

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Emission Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	48.43	8.37	0.98	17.12	26.47	40.00	13.53	QP
2	111.48	10.60	1.44	14.60	26.64	43.50	16.86	QP
3	119.24	11.11	1.42	17.01	29.54	43.50	13.96	QP
4	159.98	10.36	1.71	12.48	24.55	43.50	18.95	QP
5	230.79	9.49	2.05	22.67	34.21	46.00	11.79	QP
6	264.74	12.94	2.28	11.96	27.18	46.00	18.82	QP




Site no. : 3m Chamber Data no. : 180
 Dis. / Ant. : 3m 27137 Ant. pol. : VERTICAL
 Limit : FCC PART 15 B
 Env. / Ins. : Temp:25.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : Wireless Speaker
 Power : DC 3.7V
 M/N : SP891B
 Test Mode : GFSK TX 2402MHz

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Emission				Remark
				Reading (dBuV)	Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	
1	227.88	9.46	2.09	13.15	24.70	46.00	21.30	QP
2	397.63	15.96	2.68	5.99	24.63	46.00	21.37	QP
3	436.43	16.18	2.84	17.14	36.16	46.00	9.84	QP
4	478.14	17.40	3.07	9.21	29.68	46.00	16.32	QP
5	516.94	17.95	3.15	10.93	32.03	46.00	13.97	QP
6	596.48	19.54	3.35	6.37	29.26	46.00	16.74	QP




Site no. : 3m Chamber Data no. : 181
 Dis. / Ant. : 3m 27137 Ant. pol. : VERTICAL
 Limit : FCC PART 15 B
 Env. / Ins. : Temp:25.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : Wireless Speaker
 Power : DC 3.7V
 M/N : SP891B
 Test Mode : GFSK TX 2441MHz

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Emission Reading (dBUV)	Emission			Remark
					Level (dBUV/m)	Limits (dBUV/m)	Margin (dB)	
1	227.88	9.46	2.09	14.08	25.63	46.00	20.37	QP
2	397.63	15.96	2.68	6.54	25.18	46.00	20.82	QP
3	436.43	16.18	2.84	17.19	36.21	46.00	9.79	QP
4	478.14	17.40	3.07	8.70	29.17	46.00	16.83	QP
5	516.94	17.95	3.15	13.19	34.29	46.00	11.71	QP
6	596.48	19.54	3.35	6.16	29.05	46.00	16.95	QP




Site no. : 3m Chamber Data no. : 182
 Dis. / Ant. : 3m 27137 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15 B
 Env. / Ins. : Temp:25.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : Wireless Speaker
 Power : DC 3.7V
 M/N : SP891B
 Test Mode : GFSK TX 2441MHz

Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Reading (dBUV)	Emission		Margin (dB)	Remark	
				Level (dBUV/m)	Limits (dBUV/m)			
1	48.43	8.37	0.98	12.16	21.51	40.00	18.49	QP
2	114.39	10.85	1.42	13.92	26.19	43.50	17.31	QP
3	124.09	11.31	1.53	12.46	25.30	43.50	18.20	QP
4	164.83	9.77	1.66	10.89	22.32	43.50	21.18	QP
5	225.94	9.47	1.99	21.70	33.16	46.00	12.84	QP
6	264.74	12.94	2.28	10.26	25.48	46.00	20.52	QP




Site no. : 3m Chamber Data no. : 183
 Dis. / Ant. : 3m 27137 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15 B
 Env. / Ins. : Temp:25.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : Wireless Speaker
 Power : DC 3.7V
 M/N : SP891B
 Test Mode : GFSK TX 2480MHz

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Emission			Remark
					Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	
1	48.43	8.37	0.98	14.65	24.00	40.00	16.00	QP
2	109.54	10.44	1.40	13.52	25.36	43.50	18.14	QP
3	119.24	11.11	1.42	11.66	24.19	43.50	19.31	QP
4	174.53	8.99	1.68	12.45	23.12	43.50	20.38	QP
5	232.73	9.59	2.08	23.62	35.29	46.00	10.71	QP
6	256.98	12.63	2.17	12.65	27.45	46.00	18.55	QP




Site no. : 3m Chamber Data no. : 184
 Dis. / Ant. : 3m 27137 Ant. pol. : VERTICAL
 Limit : FCC PART 15 B
 Env. / Ins. : Temp:25.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : Wireless Speaker
 Power : DC 3.7V
 M/N : SP891B
 Test Mode : GFSK TX 2480MHz

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Emission				Remark
				Reading (dBuV)	Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	
1	227.88	9.46	2.09	14.26	25.81	46.00	20.19	QP
2	397.63	15.96	2.68	7.30	25.94	46.00	20.06	QP
3	436.43	16.18	2.84	18.29	37.31	46.00	8.69	QP
4	478.14	17.40	3.07	8.00	28.47	46.00	17.53	QP
5	518.88	17.96	3.15	14.21	35.32	46.00	10.68	QP
6	596.48	19.54	3.35	6.30	29.19	46.00	16.81	QP



Site no. : 3m Chamber Data no. : 185
 Dis. / Ant. : 3m 27137 Ant. pol. : VERTICAL
 Limit : FCC PART 15 B
 Env. / Ins. : Temp:25.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : Wireless Speaker
 Power : DC 3.7V
 M/N : SP891B
 Test Mode : 8-DPSK TX 2402MHz


	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	227.88	9.46	2.09	14.26	25.81	46.00	20.19	QP
2	397.63	15.96	2.68	7.30	25.94	46.00	20.06	QP
3	436.43	16.18	2.84	19.29	38.31	46.00	7.69	QP
4	478.14	17.40	3.07	8.00	28.47	46.00	17.53	QP
5	518.88	17.96	3.15	14.21	35.32	46.00	10.68	QP
6	596.48	19.54	3.35	5.30	28.19	46.00	17.81	QP



```


Site no.       : 3m Chamber                Data no. : 186
Dis. / Ant.    : 3m 27137                 Ant. pol. : HORIZONTAL
Limit         : FCC PART 15 B
Env. / Ins.    : Temp:25.6';Humi:56%;Press:101.52kPa
Engineer      : Tony
EUT           : Wireless Speaker
Power         : DC 3.7V
M/N           : SP891B
Test Mode     : 8-DPSK TX 2402MHz
    
```

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Reading (dBUV)	Emission Level (dBUV/m)	Limits (dBUV/m)	Margin (dB)	Remark
1	114.39	10.85	1.42	9.97	22.24	43.50	21.26	QP
2	155.13	10.67	1.69	10.34	22.70	43.50	20.80	QP
3	225.94	9.47	1.99	21.67	33.13	46.00	12.87	QP
4	232.73	9.59	2.08	20.02	31.69	46.00	14.31	QP
5	250.19	11.82	2.11	15.01	28.94	46.00	17.06	QP
6	256.98	12.63	2.17	11.83	26.63	46.00	19.37	QP




Site no. : 3m Chamber Data no. : 187
 Dis. / Ant. : 3m 27137 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15 B
 Env. / Ins. : Temp:25.6%;Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : Wireless Speaker
 Power : DC 3.7V
 M/N : SP891B
 Test Mode : 8-DPSK TX 2441MHz

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Emission		Margin (dB)	Remark	
				Reading (dBuV)	Level (dBuV/m)			
1	48.43	8.37	0.98	14.28	23.63	40.00	16.37	QP
2	114.39	10.85	1.42	13.46	25.73	43.50	17.77	QP
3	121.18	11.20	1.40	12.40	25.00	43.50	18.50	QP
4	162.89	10.01	1.67	12.95	24.63	43.50	18.87	QP
5	232.73	9.59	2.08	20.25	31.92	46.00	14.08	QP
6	264.74	12.94	2.28	12.11	27.33	46.00	18.67	QP




Site no. : 3m Chamber Data no. : 188
 Dis. / Ant. : 3m 27137 Ant. pol. : VERTICAL
 Limit : FCC PART 15 B
 Env. / Ins. : Temp:25.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : Wireless Speaker
 Power : DC 3.7V
 M/N : SP891B
 Test Mode : 8-DPSK TX 2441MHz

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	230.79	9.49	2.05	12.04	23.58	46.00	22.42	QP
2	397.63	15.96	2.68	7.60	26.24	46.00	19.76	QP
3	439.34	16.23	2.89	17.87	36.99	46.00	9.01	QP
4	478.14	17.40	3.07	7.95	28.42	46.00	17.58	QP
5	518.88	17.96	3.15	12.91	34.02	46.00	11.98	QP
6	599.39	19.58	3.47	7.86	30.91	46.00	15.09	QP



Site no. : 3m Chamber Data no. : 189
 Dis. / Ant. : 3m 27137 Ant. pol. : VERTICAL
 Limit : FCC PART 15 B
 Env. / Ins. : Temp:25.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : Wireless Speaker
 Power : DC 3.7V
 M/N : SP891B
 Test Mode : 8-DPSK TX 2480MHz


No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Emission			Remark
					Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	
1	230.79	9.49	2.05	13.56	25.10	46.00	20.90	QP
2	397.63	15.96	2.68	7.30	25.94	46.00	20.06	QP
3	439.34	16.23	2.89	18.30	37.42	46.00	8.58	QP
4	478.14	17.40	3.07	8.75	29.22	46.00	16.78	QP
5	518.88	17.96	3.15	12.78	33.89	46.00	12.11	QP
6	599.39	19.58	3.47	10.34	33.39	46.00	12.61	QP



Site no. : 3m Chamber Data no. : 190
 Dis. / Ant. : 3m 27137 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15 B
 Env. / Ins. : Temp:25.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : Wireless Speaker
 Power : DC 3.7V
 M/N : SP891B
 Test Mode : 8-DPSK TX 2480MHz

Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Reading (dBUV)	Emission		Margin (dB)	Remark	
				Level (dBUV/m)	Limits (dBUV/m)			
1	51.34	6.92	0.89	13.03	20.84	40.00	19.16	QP
2	225.94	9.47	1.99	17.66	29.12	46.00	16.88	QP
3	233.70	9.64	2.09	15.57	27.30	46.00	18.70	QP
4	256.98	12.63	2.17	10.00	24.80	46.00	21.20	QP
5	315.18	13.39	2.42	5.21	21.02	46.00	24.98	QP
6	512.09	17.94	3.19	2.38	23.51	46.00	22.49	QP


1000 MHz – 18000MHz



Site no. : 3m Chamber Data no. : 193
 Dis. / Ant. : 3m ANT 1-18G Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:25.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : Wireless Speaker
 Power : DC 3.7V
 M/N : SP891B
 Test Mode : GFSK TX 2402MHz

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBUV)	Emission Level (dBUV/m)	Limits (dBUV/m)	Margin (dB)	Remark
1	2402.00	27.61	6.62	34.18	94.85	94.90	74.00	-20.90	Peak
2	4804.00	31.25	11.77	31.81	37.20	48.41	74.00	25.59	Peak
3	6508.00	34.25	12.23	32.03	33.44	47.89	74.00	26.11	Peak
4	8004.00	37.01	11.40	31.22	32.01	49.20	74.00	24.80	Peak
5	9653.00	37.98	11.67	31.89	32.25	50.01	74.00	23.99	Peak
6	14549.00	41.77	10.92	33.26	30.26	49.69	74.00	24.31	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 194
 Dis. / Ant. : 3m ANT 1-18G Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:25.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : Wireless Speaker
 Power : DC 3.7V
 M/N : SP891B
 Test Mode : GFSK TX 2402MHz

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2402.00	27.61	6.62	34.18	91.27	91.32	74.00	-17.32	Peak
2	4808.00	31.25	11.77	31.81	34.40	45.61	74.00	28.39	Peak
3	7188.00	36.43	11.53	32.14	34.73	50.55	74.00	23.45	Peak
4	9313.00	37.94	11.62	32.15	33.13	50.54	74.00	23.46	Peak
5	11149.00	39.42	11.18	33.94	32.74	49.40	74.00	24.60	Peak
6	14549.00	41.77	10.92	33.26	31.50	50.93	74.00	23.07	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 197
 Dis. / Ant. : 3m ANT 1-18G Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:25.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : Wireless Speaker
 Power : DC 3.7V
 M/N : SP891B
 Test Mode : GFSK IX 2441MHz

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2441.00	27.60	6.67	34.12	92.56	92.71	74.00	-18.71	Peak
2	4825.00	31.28	11.84	31.83	35.97	47.26	74.00	26.74	Peak
3	7324.00	36.55	11.57	31.99	34.17	50.30	74.00	23.70	Peak
4	9874.00	38.15	11.62	31.77	31.37	49.37	74.00	24.63	Peak
5	10894.00	39.41	11.29	33.46	32.33	49.57	74.00	24.43	Peak
6	14464.00	41.85	10.93	32.96	29.99	49.81	74.00	24.19	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 198
 Dis. / Ant. : 3m ANT 1-18G Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:25.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : Wireless Speaker
 Power : DC 3.7V
 M/N : SP891B
 Test Mode : GFSK TX 2441MHz

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2441.00	27.60	6.67	34.12	97.35	97.50	74.00	-23.50	Peak
2	4774.00	31.20	11.62	31.79	35.46	46.49	74.00	27.51	Peak
3	7154.00	36.25	11.52	32.21	33.89	49.45	74.00	24.55	Peak
4	9364.00	38.02	11.64	32.06	34.04	51.64	74.00	22.36	Peak
5	9993.00	38.12	11.59	31.78	34.38	52.31	74.00	21.69	Peak
6	14464.00	41.85	10.93	32.96	32.14	51.96	74.00	22.04	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 199
 Dis. / Ant. : 3m ANT 1-18G Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:25.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : Wireless Speaker
 Power : DC 3.7V
 M/N : SP891B
 Test Mode : GFSK TX 2480MHz

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Emission		Limits (dBuV/m)	Margin (dB)	Remark
					Reading (dBuV)	Level (dBuV/m)			
1	2480.00	27.58	6.71	34.03	94.89	95.15	74.00	-21.15	Peak
2	5318.00	31.71	12.21	32.27	34.90	46.55	74.00	27.45	Peak
3	7426.00	36.56	11.60	31.95	34.25	50.46	74.00	23.54	Peak
4	8684.00	37.32	11.45	32.43	33.97	50.31	74.00	23.69	Peak
5	11149.00	39.42	11.18	33.94	32.21	48.87	74.00	25.13	Peak
6	14498.00	41.88	10.93	33.08	30.97	50.70	74.00	23.30	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 200
 Dis. / Ant. : 3m ANT 1-18G Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:25.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : Wireless Speaker
 Power : DC 3.7V
 M/N : SP891B
 Test Mode : GFSK TX 2480MHz

Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Emission			Margin (dB)	Remark
				Reading (dBuV)	Level (dBuV/m)	Limits (dBuV/m)		
1	27.58	6.71	34.03	92.92	93.18	74.00	-19.18	Peak
2	31.54	12.59	32.00	34.90	47.03	74.00	26.97	Peak
3	36.68	11.47	31.40	33.72	50.47	74.00	23.53	Peak
4	38.33	11.52	32.01	33.01	50.85	74.00	23.15	Peak
5	39.62	11.47	34.86	32.05	48.28	74.00	25.72	Peak
6	41.80	10.92	32.78	30.05	49.99	74.00	24.01	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 209
 Dis. / Ant. : 3m ANT 1-18G Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:25.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : Wireless Speaker
 Power : DC 3.7V
 M/N : SP891B
 Test Mode : 8-DPSK TX 2402MHz

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBUV)	Emission Level (dBUV/m)	Limits (dBUV/m)	Margin (dB)	Remark
1	2402.00	27.61	6.62	34.18	85.87	85.92	74.00	-11.92	Peak
2	4842.00	31.31	11.92	31.85	35.19	46.57	74.00	27.43	Peak
3	6984.00	35.46	11.51	32.47	31.82	46.32	74.00	27.68	Peak
4	8259.00	36.67	11.43	31.53	32.80	49.37	74.00	24.63	Peak
5	10044.00	38.18	11.56	31.85	32.06	49.95	74.00	24.05	Peak
6	14498.00	41.88	10.93	33.08	30.55	50.28	74.00	23.72	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 210
 Dis. / Ant. : 3m ANT 1-18G Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:25.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : Wireless Speaker
 Power : DC 3.7V
 M/N : SP891B
 Test Mode : 8-DPSK TX 2402MHz

Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission			Margin (dB)	Remark
					Level (dBuV/m)	Limits (dBuV/m)			
1	27.61	6.62	34.18	86.51	86.56	74.00	-12.56	Peak	
2	31.31	11.92	31.85	34.34	45.72	74.00	28.28	Peak	
3	36.54	11.61	31.93	33.17	49.39	74.00	24.61	Peak	
4	37.24	11.45	32.31	34.05	50.43	74.00	23.57	Peak	
5	39.45	11.29	33.52	32.01	49.23	74.00	24.77	Peak	
6	41.48	10.91	33.56	31.11	49.94	74.00	24.06	Peak	


Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 213
 Dis. / Ant. : 3m ANT 1-18G Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:25.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : Wireless Speaker
 Power : DC 3.7V
 M/N : SP891B
 Test Mode : 8-DPSK TX 2441MHz

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading Level (dBuV)	Emission		Margin (dB)	Remark
						Level (dBuV/m)	Limits (dBuV/m)		
1	2441.00	27.60	6.67	34.12	89.38	89.53	74.00	-15.53	Peak
2	4978.00	31.52	12.52	31.99	34.65	46.70	74.00	27.30	Peak
3	8004.00	37.01	11.40	31.22	32.03	49.22	74.00	24.78	Peak
4	10214.00	38.48	11.47	32.17	31.69	49.47	74.00	24.53	Peak
5	11183.00	39.40	11.15	34.00	31.17	47.72	74.00	26.28	Peak
6	14549.00	41.77	10.92	33.26	29.60	49.03	74.00	24.97	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 214
 Dis. / Ant. : 3m ANT 1-18G Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:25.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : Wireless Speaker
 Power : DC 3.7V
 M/N : SP891B
 Test Mode : 8-DPSK TX 2441MHz

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBUV)	Emission Level (dBUV/m)	Limits (dBUV/m)	Margin (dB)	Remark
1	2441.00	27.60	6.67	34.12	86.63	86.78	74.00	-12.78	Peak
2	4859.00	31.34	11.99	31.88	36.32	47.77	74.00	26.23	Peak
3	7324.00	36.55	11.57	31.99	33.41	49.54	74.00	24.46	Peak
4	9109.00	37.59	11.51	32.42	33.29	49.97	74.00	24.03	Peak
5	10333.00	38.68	11.40	32.40	32.48	50.16	74.00	23.84	Peak
6	14498.00	41.88	10.93	33.08	30.87	50.60	74.00	23.40	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 215
 Dis. / Ant. : 3m ANT 1-18G Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:25.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : Wireless Speaker
 Power : DC 3.7V
 M/N : SP891B
 Test Mode : 8-DPSK TX 2480MHz

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2480.00	27.58	6.71	34.03	84.25	84.51	74.00	-10.51	Peak
2	5964.00	32.70	12.11	32.28	34.33	46.86	74.00	27.14	Peak
3	8004.00	37.01	11.40	31.22	33.16	50.35	74.00	23.65	Peak
4	10163.00	38.39	11.50	32.08	33.05	50.86	74.00	23.14	Peak
5	10843.00	39.35	11.30	33.36	32.45	49.74	74.00	24.26	Peak
6	14192.00	41.63	10.91	33.39	31.33	50.48	74.00	23.52	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.




Site no. : 3m Chamber Data no. : 216
 Dis. / Ant. : 3m ANT 1-18G Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:25.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : Wireless Speaker
 Power : DC 3.7V
 M/N : SP891B
 Test Mode : 8-DPSK TX 2480MHz

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBUV)	Emission Level (dBUV/m)	Limits (dBUV/m)	Margin (dB)	Remark
1	2480.00	27.58	6.71	34.03	85.59	85.85	74.00	-11.85	Peak
2	5063.00	31.58	12.51	32.11	34.77	46.75	74.00	27.25	Peak
3	7358.00	36.56	11.58	31.99	33.21	49.36	74.00	24.64	Peak
4	9534.00	37.97	11.70	31.92	32.31	50.06	74.00	23.94	Peak
5	10673.00	39.17	11.30	33.04	31.72	49.15	74.00	24.85	Peak
6	14498.00	41.88	10.93	33.08	30.45	50.18	74.00	23.82	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.


18000MHz – 25000MHz



Site no. : 3m Chamber Data no. : 203
 Dis. / Ant. : 3m ANT ABOVE 18G Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:25.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : Wireless Speaker
 Power : DC 3.7V
 M/N : SP891B
 Test Mode : GFSK TX 2402MHz

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading Level (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	19911.00	46.07	19.58	36.62	11.93	40.96	74.00	33.04	Peak
2	23005.00	45.60	21.15	33.85	12.46	45.36	74.00	28.64	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 204
 Dis. / Ant. : 3m ANT ABOVE 18G Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:25.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : Wireless Speaker
 Power : DC 3.7V
 M/N : SP891B
 Test Mode : GFSK TX 2402MHz

Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Emission		Limits (dBuV/m)	Margin (dB)	Remark	
				Reading (dBuV)	Level (dBuV/m)				
1	20135.00	46.07	19.74	36.59	12.19	41.41	74.00	32.59	Peak
2	21591.00	45.95	20.39	35.26	12.77	43.85	74.00	30.15	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 205
 Dis. / Ant. : 3m ANT ABOVE 18G Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:25.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : Wireless Speaker
 Power : DC 3.7V
 M/N : SP891B
 Test Mode : GFSK TX 2441MHz

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBUV)	Emission Level (dBUV/m)	Limits (dBUV/m)	Margin (dB)	Remark
1	20996.00	46.30	20.13	35.80	16.12	46.75	74.00	27.25	Peak
2	23292.00	45.66	21.41	33.53	16.22	49.76	74.00	24.24	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 206
 Dis. / Ant. : 3m ANT ABVOE 18G Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:25.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : Wireless Speaker
 Power : DC 3.7V
 M/N : SP891B
 Test Mode : GFSK TX 2441MHz

Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission			Remark	
					Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)		
1	20436.00	46.01	19.88	36.32	15.33	44.90	74.00	29.10	Peak
2	22193.00	45.74	20.68	34.69	15.27	47.00	74.00	27.00	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.




```

Site no.       : 3m Chamber                      Data no. : 207
Dis. / Ant.    : 3m ANT ABVOE 18G              Ant. pol. : HORIZONTAL
Limit         : FCC PART 15C PEAK
Env. / Ins.    : Temp:25.6';Humi:56%;Press:101.52kPa
Engineer      : Tony
EUT           : Wireless Speaker
Power         : DC 3.7V
M/N           : SP891B
Test Mode     : GFSK TX 2480MHz
    
```

Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Emission		Limits (dBuV/m)	Margin (dB)	Remark	
				Reading (dBuV)	Level (dBuV/m)				
1	20723.00	46.14	20.01	36.05	16.28	46.38	74.00	27.62	Peak
2	23096.00	45.62	21.23	33.74	14.81	47.92	74.00	26.08	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 208
 Dis. / Ant. : 3m ANT ABOVE 18G Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:25.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : Wireless Speaker
 Power : DC 3.7V
 M/N : SP891B
 Test Mode : GFSK TX 2480MHz

Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission			Remark	
					Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)		
1	21115.00	46.22	20.18	35.69	14.64	45.35	74.00	28.65	Peak
2	23369.00	45.67	21.48	33.46	13.94	47.63	74.00	26.37	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 219
 Dis. / Ant. : 3m ANT ABOVE 18G Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:25.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : Wireless Speaker
 Power : DC 3.7V
 M/N : SP891B
 Test Mode : 8-DPSK TX 2402MHz

	Ant.	Cable	Amp	Emission					
Freq.	Factor	Loss	Factor	Reading	Level	Limits	Margin	Remark	
(MHz)	(dB/m)	(dB)	(dB)	(dBuV)	(dBuV/m)	(dBuV/m)	(dB)		
1	20254.00	46.05	19.79	36.48	14.80	44.16	74.00	29.84	Peak
2	22417.00	45.78	20.81	34.45	14.84	46.98	74.00	27.02	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 220
 Dis. / Ant. : 3m ANT ABOVE 18G Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:25.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : Wireless Speaker
 Power : DC 3.7V
 M/N : SP891B
 Test Mode : 8-DPSK TX 2402MHz

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	20884.00	46.23	20.08	35.91	14.19	44.59	74.00	29.41	Peak
2	23803.00	45.64	21.87	33.01	14.02	48.52	74.00	25.48	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 221
 Dis. / Ant. : 3m ANT ABOVE 18G Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:25.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : Wireless Speaker
 Power : DC 3.7V
 M/N : SP891B
 Test Mode : 8-DPSK TX 2441MHz

Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission		Margin (dB)	Remark
					Level (dBuV/m)	Limits (dBuV/m)		
1 20443.00	46.01	19.88	36.30	15.91	45.50	74.00	28.50	Peak
2 22151.00	45.73	20.65	34.74	16.14	47.78	74.00	26.22	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 222
 Dis. / Ant. : 3m ANT ABOVE 18G Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:25.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : Wireless Speaker
 Power : DC 3.7V
 M/N : SP891B
 Test Mode : 8-DPSK TX 2441MHz

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	20583.00	46.04	19.94	36.18	14.23	44.03	74.00	29.97	Peak
2	22221.00	45.74	20.69	34.66	14.24	46.01	74.00	27.99	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 223
 Dis. / Ant. : 3m ANT ABOVE 18G Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:25.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : Wireless Speaker
 Power : DC 3.7V
 M/N : SP891B
 Test Mode : 8-DPSK TX 2480MHz

Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission		Margin (dB)	Remark	
					Level (dBuV/m)	Limits (dBuV/m)			
1	21129.00	46.22	20.19	35.69	14.21	44.93	74.00	29.07	Peak
2	23649.00	45.67	21.73	33.17	13.48	47.71	74.00	26.29	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 224
 Dis. / Ant. : 3m ANT ABOVE 18G Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:25.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : Wireless Speaker
 Power : DC 3.7V
 M/N : SP891B
 Test Mode : 8-DPSK TX 2480MHz

Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBUV)	Emission		Margin (dB)	Remark	
					Level (dBUV/m)	Limits (dBUV/m)			
1	21178.00	46.20	20.21	35.64	13.29	44.06	74.00	29.94	Peak
2	22942.00	45.62	21.11	33.90	13.18	46.01	74.00	27.99	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.

9. BAND EDGE COMPLIANCE

9.1. Limit

All the lower and upper band-edges emissions appearing within 2310MHz to 2390MHz and 2483.5MHz to 2500MHz restricted frequency bands shall not exceed the limits shown in 15.209, all the other emissions outside operation frequency band 2400MHz to 2483.5MHz shall be at least 20dB below the fundamental emissions, or comply with 15.209 limits.

9.2. Block Diagram of Test setup



9.3. Test Procedure

EUT was placed on a turn table, which is 0.8 meter high above ground. The turn table can rotate 360 degrees to determine the position of the maximum emission level. Power on the EUT and let it working in test mode, then test it. EUT is set 3 meters away from the receiving antenna, which is mounted on a antenna tower. The antenna can be moved up and down between 1 meter and 4 meters to find out the maximum emission level. Both horizontal and vertical polarization of the antenna are set on test.

Set the spectrum analyzer in the following setting in order to capture the lower and upper band-edges of emissions

Peak : RBW = 1MHz, VBW = 1MHz, Detector=PEAK detector, Sweep time = auto.

AV : RBW = 1MHz, VBW = 10Hz, Detector=PEAK detector, Sweep time = auto .


9.4. Test Result

EUT: Wireless Speaker
M/N: SP891B
Power: DC 3.7V
Test date: 2014-11-05 Test site: 3m Chamber Tested by: Tony Tang
Test mode: Tx Mode (Hopping On & No Hopping)
Pass

Note: 1、 For emissions above 1GHz, if peak level comply with average limit, then the average level is deemed to comply with average limit.

2、 The frequency 2402MHz 、 2441MHz and 2480MHz is fundamental frequency which no limit, the limit on plots is automatically generated by the software, it's not fundamental limit, we can't remove it.

9.5. Test Data




```

Site no.       : 3m Chamber                Data no. : 195
Dis. / Ant.   : 3m ANT 1-18G             Ant. pol.: HORIZONTAL
Limit         : FCC PART 15C PEAK
Env. / Ins.   : Temp:25.6';Humi:56%;Press:101.52kPa
Engineer      : Tony
EUT           : Wireless Speaker
Power         : DC 3.7V
M/N           : SP891B
Test Mode     : GFSK TX 2402MHz(No Hopping)
    
```

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2333.77	27.73	6.54	34.23	36.13	36.17	74.00	37.83	Peak
2	2390.00	27.64	6.62	34.19	40.54	40.61	74.00	33.39	Peak
3	2401.97	27.61	6.62	34.18	92.45	92.50	74.00	-18.50	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.




```

Site no.       : 3m Chamber                      Data no. : 196
Dis. / Ant.   : 3m ANT 1-18G                   Ant. pol. : VERTICAL
Limit         : FCC PART 15C PEAK
Env. / Ins.   : Temp:25.6';Humi:56%;Press:101.52kPa
Engineer      : Tony
EUT           : Wireless Speaker
Power         : DC 3.7V
M/N           : SP891B
Test Mode     : GFSK TX 2402MHz(No Hopping)
    
```

Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Emission		Limits (dBUV/m)	Margin (dB)	Remark
				Reading (dBUV)	Level (dBUV/m)			
1	27.67	6.60	34.20	44.90	44.97	74.00	29.03	Peak
2	27.64	6.62	34.19	44.75	44.82	74.00	29.18	Peak
3	27.61	6.62	34.18	95.80	95.85	74.00	-21.85	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 201
 Dis. / Ant. : 3m ANT 1-18G Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:25.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : Wireless Speaker
 Power : DC 3.7V
 M/N : SP891B
 Test Mode : GFSK TX 2480MHz(No Hopping)

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBUV)	Emission Level (dBUV/m)	Limits (dBUV/m)	Margin (dB)	Remark
1	2479.93	27.58	6.71	34.03	94.08	94.34	74.00	-20.34	Peak
2	2483.50	27.58	6.71	34.03	50.49	50.75	74.00	23.25	Peak
3	2487.80	27.58	6.73	34.03	47.35	47.63	74.00	26.37	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 202
 Dis. / Ant. : 3m ANT 1-18G Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:25.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : Wireless Speaker
 Power : DC 3.7V
 M/N : SP891B
 Test Mode : GFSK TX 2480MHz(No Hopping)

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2479.98	27.58	6.71	34.03	96.20	96.46	74.00	-22.46	Peak
2	2483.50	27.58	6.71	34.03	52.34	52.60	74.00	21.40	Peak
3	2485.23	27.58	6.71	34.03	51.10	51.36	74.00	22.64	Peak
4	2488.23	27.58	6.73	34.03	49.44	49.72	74.00	24.28	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 211
 Dis. / Ant. : 3m ANT 1-18G Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:25.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : Wireless Speaker
 Power : DC 3.7V
 M/N : SP891B
 Test Mode : 8-DPSK TX 2402MHz(No Hopping)

Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Emission		Limits (dBuV/m)	Margin (dB)	Remark
				Reading (dBuV)	Level (dBuV/m)			
1	27.64	6.60	34.19	46.04	46.09	74.00	27.91	Peak
2	27.64	6.62	34.19	45.81	45.88	74.00	28.12	Peak
3	27.61	6.62	34.18	92.60	92.65	74.00	-18.65	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 212
 Dis. / Ant. : 3m ANT 1-18G Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:25.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : Wireless Speaker
 Power : DC 3.7V
 M/N : SP891B
 Test Mode : 8-DPSK TX 2402MHz(No Hopping)

	Ant.	Cable	Amp	Emission					
Freq.	Factor	Loss	Factor	Reading	Level	Limits	Margin	Remark	
(MHz)	(dB/m)	(dB)	(dB)	(dBUV)	(dBUV/m)	(dBUV/m)	(dB)		
1	27.70	6.58	34.22	38.66	38.72	74.00	35.28	Peak	
2	27.64	6.62	34.19	40.04	40.11	74.00	33.89	Peak	
3	27.61	6.62	34.18	88.69	88.74	74.00	-14.74	Peak	


Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 217
 Dis. / Ant. : 3m ANT 1-18G Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:25.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : Wireless Speaker
 Power : DC 3.7V
 M/N : SP891B
 Test Mode : 8-DPSK TX 2480MHz(No Hopping)

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2479.73	27.58	6.71	34.03	91.45	91.71	74.00	-17.71	Peak
2	2483.50	27.58	6.71	34.03	50.45	50.71	74.00	23.29	Peak
3	2484.10	27.58	6.71	34.03	51.32	51.58	74.00	22.42	Peak
4	2486.93	27.58	6.71	34.03	41.67	41.93	74.00	32.07	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.




```

Site no.       : 3m Chamber                Data no. : 218
Dis. / Ant.   : 3m ANT 1-18G             Ant. pol. : VERTICAL
Limit         : FCC PART 15C PEAK
Env. / Ins.   : Temp:25.6';Humi:56%;Press:101.52kPa
Engineer      : Tony
EUT           : Wireless Speaker
Power         : DC 3.7V
M/N           : SP891B
Test Mode     : 8-DPSK TX 2480MHz(No Hopping)
    
```

	Ant.	Cable	Amp	Emission					
Freq. (MHz)	Factor (dB/m)	Loss (dB)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark	
1	27.58	6.71	34.03	90.33	90.59	74.00	-16.59	Peak	
2	27.58	6.71	34.03	49.69	49.95	74.00	24.05	Peak	
3	27.58	6.71	34.03	51.60	51.86	74.00	22.14	Peak	
4	27.58	6.71	34.03	43.93	44.19	74.00	29.81	Peak	


Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 225
 Dis. / Ant. : 3m ANT 1-18G Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:25.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : Wireless Speaker
 Power : DC 3.7V
 M/N : SP891B
 Test Mode : GFSK TX 2402MHz(Hopping On)

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBUV)	Emission Level (dBUV/m)	Limits (dBUV/m)	Margin (dB)	Remark
1	2367.87	27.67	6.58	34.20	45.14	45.19	74.00	28.81	Peak
2	2390.00	27.64	6.62	34.19	42.02	42.09	74.00	31.91	Peak
3	2404.94	27.61	6.64	34.18	93.55	93.62	74.00	-19.62	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 226
 Dis. / Ant. : 3m ANT 1-18G Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:25.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : Wireless Speaker
 Power : DC 3.7V
 M/N : SP891B
 Test Mode : GFSK TX 2402MHz(Hopping On)

Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission		Margin (dB)	Remark	
					Level (dBuV/m)	Limits (dBuV/m)			
1	2358.52	27.67	6.58	34.20	49.66	49.71	74.00	24.29	Peak
2	2390.00	27.64	6.62	34.19	42.42	42.49	74.00	31.51	Peak
3	2401.97	27.61	6.62	34.18	93.55	93.60	74.00	-19.60	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 227
 Dis. / Ant. : 3m ANT 1-18G Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:25.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : Wireless Speaker
 Power : DC 3.7V
 M/N : SP891B
 Test Mode : GFSK TX 2480MHz (Hopping On)

Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Emission		Limits (dBuV/m)	Margin (dB)	Remark	
				Reading (dBuV)	Level (dBuV/m)				
1	2478.98	27.58	6.71	34.03	95.52	95.78	74.00	-21.78	Peak
2	2483.50	27.58	6.71	34.03	49.52	49.78	74.00	24.22	Peak
3	2488.30	27.58	6.73	34.03	49.64	49.92	74.00	24.08	Peak
4	2491.68	27.58	6.73	34.03	49.78	50.06	74.00	23.94	Peak
5	2496.30	27.57	6.73	34.00	49.95	50.25	74.00	23.75	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 228
 Dis. / Ant. : 3m ANT 1-18G Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:25.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : Wireless Speaker
 Power : DC 3.7V
 M/N : SP891B
 Test Mode : GFSK TX 2480MHz(Hopping On)

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Emission		Limits (dBuV/m)	Margin (dB)	Remark
					Reading (dBuV)	Level (dBuV/m)			
1	2479.10	27.58	6.71	34.03	94.45	94.71	74.00	-20.71	Peak
2	2483.50	27.58	6.71	34.03	48.02	48.28	74.00	25.72	Peak
3	2484.10	27.58	6.71	34.03	50.79	51.05	74.00	22.95	Peak
4	2497.05	27.57	6.73	34.00	47.46	47.76	74.00	26.24	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.




```

Site no.       : 3m Chamber                Data no. : 229
Dis. / Ant.   : 3m ANT 1-18G             Ant. pol.: VERTICAL
Limit        : FCC PART 15C PEAK
Env. / Ins.   : Temp:25.6';Humi:56%;Press:101.52kPa
Engineer     : Tony
EUT          : Wireless Speaker
Power        : DC 3.7V
M/N          : SP891B
Test Mode    : 8-DPSK TX 2402MHz(Hopping On)
    
```

Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Emission		Limits (dBuV/m)	Margin (dB)	Remark
				Reading (dBuV)	Level (dBuV/m)			
1	27.67	6.60	34.20	44.08	44.15	74.00	29.85	Peak
2	27.64	6.62	34.19	47.58	47.65	74.00	26.35	Peak
3	27.64	6.62	34.19	41.34	41.41	74.00	32.59	Peak
4	27.61	6.64	34.18	88.85	88.92	74.00	-14.92	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 230
 Dis. / Ant. : 3m ANT 1-18G Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:25.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : Wireless Speaker
 Power : DC 3.7V
 M/N : SP891B
 Test Mode : 8-DPSK TX 2402MHz (Hopping On)

Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Emission		Limits (dBuV/m)	Margin (dB)	Remark
				Reading (dBuV)	Level (dBuV/m)			
1	27.73	6.56	34.23	44.49	44.55	74.00	29.45	Peak
2	27.67	6.60	34.20	44.90	44.97	74.00	29.03	Peak
3	27.64	6.62	34.19	41.77	41.84	74.00	32.16	Peak
4	27.61	6.64	34.18	88.04	88.11	74.00	-14.11	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 231
 Dis. / Ant. : 3m ANT 1-18G Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:25.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : Wireless Speaker
 Power : DC 3.7V
 M/N : SP891B
 Test Mode : 8-DPSK TX 2480MHz (Hopping On)

Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBUV)	Emission		Limits (dBUV/m)	Margin (dB)	Remark
					Level (dBUV/m)	(dBUV/m)			
1	2478.80	27.58	6.71	34.03	93.16	93.42	74.00	-19.42	Peak
2	2483.50	27.58	6.71	34.03	51.39	51.65	74.00	22.35	Peak
3	2483.85	27.58	6.71	34.03	51.51	51.77	74.00	22.23	Peak
4	2490.55	27.58	6.73	34.03	49.23	49.51	74.00	24.49	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 232
 Dis. / Ant. : 3m ANT 1-18G Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:25.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : Wireless Speaker
 Power : DC 3.7V
 M/N : SP891B
 Test Mode : 8-DPSK TX 2480MHz(Hopping On)

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBUV)	Emission Level (dBUV/m)	Limits (dBUV/m)	Margin (dB)	Remark
1	2479.80	27.58	6.71	34.03	88.38	88.64	74.00	-14.64	Peak
2	2483.50	27.58	6.71	34.03	46.07	46.33	74.00	27.67	Peak
3	2484.05	27.58	6.71	34.03	50.79	51.05	74.00	22.95	Peak
4	2484.60	27.58	6.71	34.03	50.31	50.57	74.00	23.43	Peak
5	2486.60	27.58	6.71	34.03	46.32	46.58	74.00	27.42	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.

10. POWER LINE CONDUCTED EMISSIONS

10.1. Limit

Frequency	Maximum RF Line Voltage	
	Quasi-Peak Level dB(μV)	Average Level dB(μV)
150kHz ~ 500kHz	66 ~ 56*	56 ~ 46*
500kHz ~ 5MHz	56	46
5MHz ~ 30MHz	60	50

Notes: 1. * Decreasing linearly with logarithm of frequency.
 2. The lower limit shall apply at the transition frequencies.

10.2. Test Procedure

The EUT was placed on a non-metallic table, 80cm above the ground plane. The EUT was charged from PC's USB port which connected to the power mains through a line impedance stabilization network (L.I.S.N. 1#).. Both sides of AC line are checked to find out the maximum conducted emission. In order to find the maximum emission levels, the relative positions of equipment and all of the interface cables shall be changed according to ANSI C63.4: 2009 on Conducted Emission Test.


The bandwidth of test receiver (R & S ESHS30) is set at 10kHz.

The frequency range from 150kHz to 30MHz is checked.

10.3. Test Result


0.15MHz—30MHz Conducted emission Test result	
EUT: Wireless Speaker	M/N:SP891B
Power: DC 5V From PC Input AC 120V/60Hz	
Test date: 2014-11-05 Test site: 3m Chamber Tested by: Tony.Tang	
Test mode: Tx Mode	
Pass	

10.4. Test data



Site no. : EST Conduction Shielded Room Data no. : 393
 Limit : FCC PART 15B QP LINE Phase : LINE
 Env. / Ins. : Temp:24.3'C Humi:58% Press:101.50kPa
 Engineer : Tony
 EUT : Wireless Speaker
 Power : DC 5V From PC Input AC 120V/60Hz
 M/N : SP891B
 Test Mode : TX Mode

	Freq. (MHz)	LISN Factor (dB)	Cable Loss (dB)	Emission Reading (dBuV)	Emission Level (dBuV)	Limits (dBuV)	Margin (dB)	Remark
1	0.18	9.61	9.80	27.17	46.58	64.42	17.84	QP
2	0.18	9.61	9.80	18.17	37.58	54.42	16.84	Average
3	0.25	9.61	9.82	23.37	42.80	61.86	19.06	QP
4	0.25	9.61	9.82	17.37	36.80	51.86	15.06	Average
5	0.44	9.61	9.81	19.44	38.86	57.07	18.21	QP
6	0.44	9.61	9.81	7.44	26.86	47.07	20.21	Average
7	0.58	9.60	9.82	20.38	39.80	56.00	16.20	QP
8	0.58	9.60	9.82	9.38	28.80	46.00	17.20	Average
9	3.45	9.63	9.85	23.32	42.80	56.00	13.20	QP
10	3.45	9.63	9.85	11.32	30.80	46.00	15.20	Average
11	5.19	9.65	9.85	24.35	43.85	60.00	16.15	QP
12	5.19	9.65	9.85	16.35	35.85	50.00	14.15	Average



Site no. : EST Conduction Shielded RoomData no. : 395
 Limit : FCC PART 15B QP LINE Phase : NEUTRAL
 Env. / Ins. : Temp:24.3'C Humi:58% Press:101.50kPa
 Engineer : Tony
 EUT : Wireless Speaker
 Power : DC 5V From PC Input AC 120V/60Hz
 M/N : SP891B
 Test Mode : TX Mode

	Freq. (MHz)	LISN Factor (dB)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV)	Limits (dBuV)	Margin (dB)	Remark
1	0.18	9.56	9.80	26.66	46.02	64.33	18.31	QP
2	0.18	9.56	9.80	18.66	38.02	54.33	16.31	Average
3	0.24	9.60	9.82	23.68	43.10	62.00	18.90	QP
4	0.24	9.60	9.82	16.68	36.10	52.00	15.90	Average
5	0.56	9.60	9.82	20.62	40.04	56.00	15.96	QP
6	0.56	9.60	9.82	9.62	29.04	46.00	16.96	Average
7	0.78	9.62	9.81	23.10	42.53	56.00	13.47	QP
8	0.78	9.62	9.81	7.10	26.53	46.00	19.47	Average
9	2.64	9.63	9.84	24.32	43.79	56.00	12.21	QP
10	2.64	9.63	9.84	7.32	26.79	46.00	19.21	Average
11	5.62	9.65	9.85	24.93	44.43	60.00	15.57	QP
12	5.62	9.65	9.85	17.93	37.43	50.00	12.57	Average

11. ANTENNA REQUIREMENTS

11.1. Limit



For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

11.2. Result

The antennas used for this product are integral Patch Antenna and that no antenna other than that furnished by the responsible party shall be used with the device, the maximum peak gain of the transmit antenna is only 0dBi.

12. TEST SETUP PHOTO


Conducted Test



Radiated Test (30-1000 MHz)




Radiated Test (1000-25000 MHz)



13. PHOTOS OF EUT

External Photos
M/N: SP891B




External Photos
M/N: SP891B





External Photos
M/N: SP891B



Internal Photos
M/N: SP891B



Internal Photos
M/N: SP891B



Bluetooth
Antenna

Internal Photos
M/N: SP891B

