



Radio Test Report

FCC ID: VJA-RJ1301

IC: 7382A-RJ1301

This report concerns (check one) : ☒ Original Grant ☐ Class II Change

Issued Date : Mar. 03, 2014
Project No. : 1402132
Equipment : Mini PCI Radio Module, 2x2 IEEE 802.11
b/g/n ,2.4 GHz
Model Name : RJ-1301
Applicant : RAJANT CORPORATION
Address : 400 EAST KING STREET, MALVERN PA
19355

Tested by: Neutron Engineering Inc. EMC Laboratory
Date of Receipt: Feb. 18, 2014
Date of Test: Feb. 18, 2014 ~ Feb. 28, 2014

Testing Engineer: Josh Lin
(Josh Lin)

Technical Manager: Jeff Yang
(Jeff Yang)

Authorized Signatory: Andy Chiu
(Andy Chiu)

Neutron Engineering Inc.
B1, No. 37, Lane 365, YangGuang St.,
NeiHu District 114, Taipei, Taiwan.
TEL: +886-2-2657-3299
FAX: +886-2-2657-3331



**Declaration**

Neutron represents to the client that testing is done in accordance with standard procedures as applicable and that test instruments used has been calibrated with the standards traceable to National Measurement Laboratory (**NML**) of **R.O.C.**, or National Institute of Standards and Technology (**NIST**) of **U.S.A.**

Neutron's reports apply only to the specific samples tested under conditions. It is manufacture's responsibility to ensure that additional production units of this model are manufactured with the identical electrical and mechanical components. **Neutron** shall have no liability for any declarations, inferences or generalizations drawn by the client or others from **Neutron** issued reports.

Neutron's reports must not be used by the client to claim product endorsement by the authorities or any agency of the Government.

This report is the confidential property of the client. As a mutual protection to the clients, the public and **Neutron-self**, extracts from the test report shall not be reproduced except in full with **Neutron's** authorized written approval.

Neutron's laboratory quality assurance procedures are in compliance with the **ISO Guide 17025** requirements, and accredited by the conformity assessment authorities listed in this test report.

Limitation

For the use of the authority's logo is limited unless the Test Standard(s)/Scope(s)/Item(s) mentioned in this test report is (are) included in the conformity assessment authorities acceptance respective.



Table of Contents

REPORT ISSUED HISTORY	6
1 CERTIFICATION	7
2 SUMMARY OF TEST RESULTS	8
2.1 TEST FACILITY	9
2.2 MEASUREMENT UNCERTAINTY	9
3 GENERAL INFORMATION	10
3.1 GENERAL DESCRIPTION OF EUT	10
3.2 DESCRIPTION OF TEST MODES	12
3.3 TABLE OF PARAMETERS OF TEXT SOFTWARE SETTING	13
3.4 BLOCK DIAGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED	14
3.5 DESCRIPTION OF SUPPORT UNITS	15
4 CONDUCTED EMISSION	16
4.1 LIMIT	16
4.2 MEASUREMENT INSTRUMENTS LIST	16
4.3 TEST PROCEDURES	17
4.4 TEST SETUP LAYOUT	17
4.5 DEVIATION FROM TEST STANDARD	17
4.6 EUT OPERATING CONDITIONS	18
4.7 TEST RESULTS	19
5 ANTENNA CONDUCTED SPURIOUS EMISSION	21
5.1 LIMIT	21
5.2 MEASUREMENT INSTRUMENTS LIST	21
5.3 TEST PROCEDURES	21
5.4 TEST SETUP LAYOUT	21
5.5 DEVIATION FROM TEST STANDARD	21
5.6 EUT OPERATING CONDITIONS	21
5.7 TEST RESULTS	22
6 6 DB BANDWIDTH	54
6.1 LIMIT	54
6.2 MEASUREMENT INSTRUMENTS LIST	54
6.3 TEST PROCEDURES	54
6.4 TEST SETUP LAYOUT	54
6.5 DEVIATION FROM TEST STANDARD	54
6.6 EUT OPERATING CONDITIONS	54
6.7 TEST RESULTS	55
7 MAXIMUM PEAK CONDUCTED OUTPUT POWER	71
7.1 LIMIT	71
7.2 MEASUREMENT INSTRUMENTS LIST	71



Table of Contents

7.3	TEST PROCEDURES	71
7.4	TEST SETUP LAYOUT	71
7.5	DEVIATION FROM TEST STANDARD	71
7.6	EUT OPERATING CONDITIONS	71
7.7	TEST RESULTS	72
8	RADIATED SPURIOUS EMISSION (9 KHZ TO 1 GHZ)	82
8.1	LIMIT	82
8.2	MEASUREMENT INSTRUMENTS LIST	83
8.3	MEASURING INSTRUMENTS SETTING	83
8.4	TEST PROCEDURES	84
8.5	DEVIATION FROM TEST STANDARD	84
8.6	TEST SETUP LAYOUT	84
8.7	EUT OPERATING CONDITIONS	85
8.8	TEST RESULTS	86
9	RADIATED SPURIOUS EMISSION (ABOVE 1 GHZ)	88
9.1	LIMIT	88
9.2	MEASUREMENT INSTRUMENTS LIST	89
9.3	MEASURING INSTRUMENTS SETTING	89
9.4	TEST PROCEDURES	90
9.5	DEVIATION FROM TEST STANDARD	90
9.6	TEST SETUP LAYOUT	90
9.7	EUT OPERATING CONDITIONS	91
9.8	TEST RESULTS	92
9.9	TEST RESULTS (RESTRICTED BANDS)	164
10	POWER SPECTRAL DENSITY	188
10.1	LIMIT	188
10.2	MEASUREMENT INSTRUMENTS LIST	188
10.3	TEST PROCEDURES	188
10.4	TEST SETUP LAYOUT	188
10.5	DEVIATION FROM TEST STANDARD	188
10.6	EUT OPERATING CONDITIONS	188
10.7	TEST RESULTS	189
11	RF EXPOSURE COMPLIANCE	207
11.1	LIMIT	207
11.2	MEASUREMENT INSTRUMENTS LIST	207
11.3	MPE CALCULATION METHOD	207
11.4	TEST SETUP LAYOUT	208
11.5	DEVIATION FROM TEST STANDARD	208



Table of Contents

11.6	EUT OPERATING CONDITIONS	208
11.7	TEST RESULTS	209
12	EUT TEST PHOTO	215

**REPORT ISSUED HISTORY**

Revised Version No.	Description	Issued Date
-	Initial Issue.	Mar. 03, 2014



1 CERTIFICATION

Equipment : Mini PCI Radio Module, 2x2 IEEE 802.11 b/g/n ,2.4 GHz
Brand Name : Rajant Corporation
Model Name : RJ-1301
Applicant : RAJANT CORPORATION
Date of Test : Feb. 18, 2014 ~ Feb. 28, 2014
Standards : RSS-210, Issue 8: 2010
FCC Part 15, Subpart C: 2012
ANSI C63.4: 2009

The above equipment has been tested and found compliance with the requirement of the relative standards by Neutron Engineering Inc. EMC Laboratory.

The test data, data evaluation, and equipment configuration contained in our test report (Ref No. NEI-FCCP-1-1402132) were obtained utilizing the test procedures, test instruments, test sites that has been accredited by the Authority of TAF according to the ISO-17025 quality assessment standard and technical standard(s).



2. SUMMARY OF TEST RESULTS

RSS-210, Issue 8: 2010; FCC Part 15, Subpart C: 2012			
Standard Clause		Test Item	Result
RSS-210	FCC Part 15, Subpart C		
NOTE (2)	15.207	Conducted Emission	PASS
A8.5	15.247 (c)	Antenna conducted Spurious Emission	PASS
A8.2 (a)	15.247 (a)(2)	6 dB Bandwidth	PASS
A8.4 (4)	15.247 (b)	Maximum Peak Conducted Output Power	PASS
NOTE (3)	15.247 (c)	Radiated Spurious Emission	PASS
A8.2 (b)	15.247 (d)(e)	Power Spectral Density	PASS
NOTE (4)	15.205	Restricted Bands	PASS
NOTE (5)	15.203	Antenna Requirement	PASS
NOTE (6)	1.1307 1.1310 2.1091 2.1093	RF Exposure Compliance	PASS

NOTE:

- (1) N/A: denotes test is not applicable in this Test Report
- (2) Reference standerads is RSS-GEN 7.2.4
- (3) Reference standerads is RSS-GEN 7.2.5
- (4) Reference standerads is RSS-GEN 7.2.2
- (5) Reference standerads is RSS-GEN 7.1.2
- (6) Reference standerads is RSS-102

**2.1 TEST FACILITY**

The test facilities used to collect the test data in this report:

Conducted emission Test:

C02: 1F., No. 61, Ln. 77, Sing-ai Rd., Neihu Dist., Taipei City 114, Taiwan (R.O.C.)

Radiated emission Test (Below 1 GHz):

CB08: 1F., No. 61, Ln. 77, Sing-ai Rd., Neihu Dist., Taipei City 114, Taiwan (R.O.C.)

Radiated emission Test (Above 1 GHz):

CB08: 1F., No. 61, Ln. 77, Sing-ai Rd., Neihu Dist., Taipei City 114, Taiwan (R.O.C.)

2.2 MEASUREMENT UNCERTAINTY

The measurement uncertainty is not specified by FCC/Industry Canada rules and for reference only.

The reported uncertainty of measurement $y \pm U$, where expanded uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately **95%**.

The measurement instrumentation uncertainty considerations contained in CISPR 16-4-2.

A. Conducted emission test:

Test Site	Measurement Frequency Range	U , (dB)	NOTE
C02	150 kHz ~ 30 MHz	2.59	

B. Radiated emission test:

Test Site	Item	Measurement Frequency Range	Uncertainty	NOTE
CB08	Radiated emission at 3m	Horizontal Polarization	30 - 200MHz	3.35 dB
		Horizontal Polarization	200 - 1000MHz	3.11 dB
		Horizontal Polarization	1 - 18GHz	3.97 dB
		Horizontal Polarization	18 - 40GHz	4.01 dB
	Radiated emission at 3m	Vertical Polarization	30 - 200MHz	3.22 dB
		Vertical Polarization	200 - 1000MHz	3.24 dB
		Vertical Polarization	1 - 18GHz	4.05 dB
		Vertical Polarization	18 - 40GHz	4.04 dB

Our calculated Measurement Instrumentation Uncertainty is shown in the tables above. These are our U_{lab} values in CISPR 16-4-2 terminology.

Since Table 1 of CISPR 16-4-2 has values of measurement instrumentation uncertainty, called U_{CISPR} , as follows:

Conducted Disturbance (mains port) – 150 kHz – 30 MHz: 3.6 dB

Radiated Disturbance (electric field strength on an open area test site or alternative test site) – 30 MHz – 1000 MHz: 5.2 dB

It can be seen that our U_{lab} values are smaller than U_{CISPR} .

If U_{lab} is less than or equal to U_{CISPR} , then:

- compliance is deemed to occur if no measured disturbance level exceeds the disturbance limit;
- non-compliance is deemed to occur if any measured disturbance level exceeds the disturbance limit.

If U_{lab} is greater than U_{CISPR} , then:

- compliance is deemed to occur if no measured disturbance level, increased by $(U_{lab} - U_{CISPR})$, exceeds the disturbance limit;
- non-compliance is deemed to occur if any measured disturbance level, increased by $(U_{lab} - U_{CISPR})$, exceeds the disturbance limit.



3 GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

Equipment	Mini PCI Radio Module, 2x2 IEEE 802.11 b/g/n ,2.4 GHz	
Brand Name	Rajant Corporation	
Model Name	RJ-1301	
OEM Brand/Model Name	VIZMONET/ RJ-1301	
Model Difference	N/A	
Product Description	Operation Frequency	2412~2462 MHz
	Modulation Type	IEEE 802.11b: DSSS (CCK, DQPSK, DBPSK) IEEE 802.11g: OFDM,(64 QAM, 16 QAM, QPSK, BPSK) IEEE 802.11n: OFDM(64 QAM, 16 QAM, QPSK, BPSK)
	Bit Rate of Transmitter	IEEE 802.11b: 11/5.5/2/1 Mbps IEEE 802.11g: 54/48/36/24/18/12/9/6 Mbps IEEE 802.11n: up to 150 Mbps
	Number Of Channel	Please refer to the Note 2.
	Antenna Designation	Please refer to the Note 3.
	Antenna Gain(Peak)	Please refer to the Note 3.
	Maximum Conducted Output Power	IEEE 802.11b: 25.10 dBm (0.3236 W) IEEE 802.11g: 26.62 dBm (0.4592 W) IEEE 802.11n (20 MHz): 26.72 dBm (0.4699 W)-1TX IEEE 802.11n (40 MHz): 25.52 dBm (0.3565 W)-1TX IEEE 802.11n (20 MHz): 27.89 dBm (0.6147 W)-2TX IEEE 802.11n (40 MHz): 27.12 dBm (0.5157 W)-2TX
	More details of EUT technical specification, please refer to the User's Manual.	
Power Source	Supplied from PC.	
Power Rating	Please refer to the User's Manual	
Connecting I/O Port(s)	Please refer to the User's Manual	



NOTE:

1. For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.
2. Channel List:

IEEE 802.11b/g/n (20MHz)					
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
01	2412	05	2432	09	2452
02	2417	06	2437	10	2457
03	2422	07	2442	11	2462
04	2427	08	2447		

IEEE 802.11n (40MHz)					
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
03	2422	06	2437	09	2452
04	2427	07	2442		
05	2432	08	2447		

3. Table for Filed Antenna

Ant.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)
1	PCTEL	BOA24005NM-RJT	DIPOLE OMNI-DIRECTIO NAL	N-Type	5dBi
2	PCTEL	BOA24005NM-RJT	DIPOLE OMNI-DIRECTIO NAL	N-Type	5dBi



3.2 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generated from EUT, the test system was pre-scanning tested based on the consideration of following EUT operation mode or test configuration mode which possibly have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Test Items	IEEE	Mode	Data Rate	Channel	Note
Conducted Emission	802.11b	DSSS	1 Mbps	06	
Antenna conducted Spurious Emission	802.11b	DSSS	1 Mbps	01/06/11	
	802.11g	OFDM	6 Mbps	01/06/11	
	802.11n (20 MHz)	BPSK	MCS0	01/06/11	
	802.11n (40 MHz)	BPSK	MCS0	03/06/09	
6 dB Bandwidth	802.11b	DSSS	1 Mbps	01/06/11	
	802.11g	OFDM	6 Mbps	01/06/11	
	802.11n (20 MHz)	BPSK	MCS0	01/06/11	
	802.11n (40 MHz)	BPSK	MCS0	03/06/09	
Maximum Peak Conducted Output Power	802.11b	DSSS	1 Mbps	01/06/11	
	802.11g	OFDM	6 Mbps	01/06/11	
	802.11n (20 MHz)	BPSK	MCS0	01/06/11	
	802.11n (40 MHz)	BPSK	MCS0	03/06/09	
Radiated Spurious Emission (30 MHz to 1 GHz)	802.11n (20 MHz)	OFDM	MCS0	06	
Radiated Spurious Emission (above 1 GHz)	802.11b	DSSS	1 Mbps	01/06/11	
	802.11g	OFDM	6 Mbps	01/06/11	
	802.11n (20 MHz)	BPSK	MCS0	01/06/11	
	802.11n (40 MHz)	BPSK	MCS0	03/06/09	
Restricted Bands	802.11b	DSSS	1 Mbps	01/11	
	802.11g	OFDM	6 Mbps	01/11	
	802.11n (20 MHz)	BPSK	MCS0	01/11	
	802.11n (40 MHz)	BPSK	MCS0	03/09	
Antenna Requirement	---		---	---	
RF Exposure Compliance	---		---	---	

NOTE: The measurements are performed at the highest, middle, lowest available channels.

**3.3 TABLE OF PARAMETERS OF TEXT SOFTWARE SETTING**

During testing channel & power controlling software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product.


IEEE	802.11b			802.11g		
Test software Version	ART v0.9 b34			ART v0.9 b34		
Frequency	2412 MHz	2437 MHz	2462 MHz	2412 MHz	2437 MHz	2462 MHz
Parameter	12	14	11.5	11	14	14

IEEE	802.11n (20 MHz)-1TX			802.11n (40 MHz) -1TX		
Test software Version	ART v0.9 b34			ART v0.9 b34		
Frequency	2412 MHz	2437 MHz	2462 MHz	2422 MHz	2437 MHz	2452 MHz
Parameter	8	14	13	7	11	12

IEEE	802.11n (20 MHz) -2TX			802.11n (40 MHz) -2TX		
Test software Version	ART v0.9 b34			ART v0.9 b34		
Frequency	2412 MHz	2437 MHz	2462 MHz	2422 MHz	2437 MHz	2452 MHz
Parameter	8	11	11	6	11	11



3.4 BLOCK DIAGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED



**3.5 DESCRIPTION OF SUPPORT UNITS**

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	FCC ID/IC	Series No.	Note
E-1	Mini PCI Radio Module, 2x2 IEEE 802.11 b/g/n ,2.4 GHz	Rajant Corporation	RJ-1301	FCC ID: VJA-RJ1301 IC: 7382A-RJ1301	N/A	EUT

Item	Shielded Type	Ferrite Core	Length	Note
N/A	-	-	-	-

NOTE: The support equipment was authorized by Declaration of Conformity (DOC).



4 CONDUCTED EMISSION

4.1 LIMIT

FREQUENCY (MHz)	Class A (dBuV)		Class B (dBuV)	
	Quasi-peak	Average	Quasi-peak	Average
0.15 - 0.5	79.00	66.00	66 - 56 *	56 - 46 *
0.50 - 5.0	73.00	60.00	56.00	46.00
5.0 - 30.0	73.00	60.00	60.00	50.00

NOTE:

1. The tighter limit applies at the band edges.
2. The limit of " * " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.
3. The test result calculated as following:
Measurement Value = Reading Level + Correct Factor
Correct Factor = Insertion Loss + Cable Loss + Attenuator Factor(if use)
Margin Level = Measurement Value – Limit Value

4.2 MEASUREMENT INSTRUMENTS LIST

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	LISN	Schwarzbeck	NSLK 8127	8127685	Feb. 23, 2015
2	Test Cable	TIMES	CFD300-NL	C01	Jun. 16, 2014
3	EMI Test Receiver	Agilent	N9038A	MY51210215	Mar. 21, 2014
4	Measurement Software	EZ	EZ_EMC (Version NB-02A)	N/A	N/A

NOTE: **N/A**: denotes No Model Name, No Serial No. or No Calibration specified.


4.3 TEST PROCEDURES

- The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- LISN at least 80 cm from nearest part of EUT chassis.
- For the actual test configuration, please refer to the related Item –EUT Test Photos.

NOTE:

- Reading in which marked as Peak, QP or AVG means measurements by using are Quasi-Peak or Average Mode with Detector BW=9 kHz (6 dB Bandwidth).
- All readings are Peak Mode value unless otherwise stated QP or AVG in column of Note. If the Peak or QP Mode Measured value compliance with the QP Limits and lower than AVG Limits, the EUT shall be deemed to meet both QP & AVG Limits and then only Peak or QP Mode was measured, but AVG Mode didn't perform.

4.4 TEST SETUP LAYOUT



4.5 DEVIATION FROM TEST STANDARD

No deviation



4.6 EUT OPERATING CONDITIONS


The EUT used during radiated and/or conducted emission measurement was designed to exercise in a manner similar to a typical use.



4.7 TEST RESULTS

EUT	Mini PCI Radio Module, 2x2 IEEE 802.11 b/g/n ,2.4 GHz	Model Name	RJ-1301
Temperature	24°C	Relative Humidity	46%
Test Voltage	AC 120V/60Hz		
Test Mode	IEEE 802.11b/2437 MHz		

Phase: Line




No. Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1	0.1720	40.45	9.04	49.49	64.86	-15.37	peak	
2	0.2477	38.47	8.71	47.18	61.83	-14.65	peak	
3	0.4088	36.11	7.83	43.94	57.67	-13.73	peak	
4 *	0.5270	33.97	8.58	42.55	56.00	-13.45	peak	
5	0.8780	31.86	9.40	41.26	56.00	-14.74	peak	
6	1.0220	31.93	9.68	41.61	56.00	-14.39	peak	



EUT	Mini PCI Radio Module, 2x2 IEEE 802.11 b/g/n ,2.4 GHz	Model Name	RJ-1301
Temperature	24°C	Relative Humidity	46%
Test Voltage	AC 120V/60Hz		
Test Mode	IEEE 802.11b/2437 MHz		

Phase: Neutral



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1		0.1800	41.81	9.78	51.59	64.49	-12.90	peak	
2	*	0.1923	40.97	10.22	51.19	63.94	-12.75	peak	
3		0.2477	38.39	9.23	47.62	61.83	-14.21	peak	
4		0.3200	37.54	7.82	45.36	59.71	-14.35	peak	
5		0.4508	35.65	8.15	43.80	56.86	-13.06	peak	
6		1.0937	33.37	9.66	43.03	56.00	-12.97	peak	



5 ANTENNA CONDUCTED SPURIOUS EMISSION

5.1 LIMIT

Test Item	Frequency Range (MHz)	Limit
Antenna conducted Spurious Emission	30-25000	20 dB less than the peak value of fundamental frequency

5.2 MEASUREMENT INSTRUMENTS LIST

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Spectrum Analyzer	R&S	FSP-30	100854	Sep. 08, 2014

NOTE: **N/A**: denotes No Model Name, No Serial No. or No Calibration specified.

5.3 TEST PROCEDURES

- The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- Spectrum Setting: RBW= 100KHz, VBW=100KHz, Sweep time = Auto.

5.4 TEST SETUP LAYOUT



5.5 DEVIATION FROM TEST STANDARD

No deviation

5.6 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 4.6 Unless otherwise a special operating condition is specified in the follows during the testing.


**5.7 TEST RESULTS**

EUT	Mini PCI Radio Module, 2x2 IEEE 802.11 b/g/n ,2.4 GHz	Model Name	RJ-1301
Temperature	26°C	Relative Humidity	46%
Test Voltage	AC 120V/60Hz		
Test Mode	IEEE 802.11b		

Channel of Worst Data			
The max. radio frequency power in any 100 kHz bandwidth outside the frequency band		The max. radio frequency power in any 100 kHz bandwidth within the frequency band.	
FREQUENCY(MHz)	POWER(dBm)	FREQUENCY(MHz)	POWER(dBm)
2397.00	-27.73	2487.60	-47.00
Result			
In any 100kHz bandwidth outside the frequency band, the radio frequency power is at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power.			




IEEE 802.11b/The max. radio frequency power in any 100kHz bandwidth outside the frequency band



Date: 14.FEB.2014 17:30:27


IEEE 802.11b/The max. radio frequency power in any 100 kHz bandwidth within the frequency band



Date: 14.FEB.2014 21:06:48




IEEE 802.11b/2412 MHz/10 Harmonic of the frequency




Date: 14.FEB.2014 17:29:58

IEEE 802.11b/2437 MHz/10 Harmonic of the frequency



Date: 14.FEB.2014 17:40:21



Date: 14.FEB.2014 17:47:15




EUT	Mini PCI Radio Module, 2x2 IEEE 802.11 b/g/n ,2.4 GHz	Model Name	RJ-1301
Temperature	26°C	Relative Humidity	46%
Test Voltage	AC 120V/60Hz		
Test Mode	IEEE 802.11g		

Channel of Worst Data			
The max. radio frequency power in any 100kHz bandwidth outside the frequency band		The max. radio frequency power in any 100 kHz bandwidth within the frequency band.	
FREQUENCY(MHz)	POWER(dBm)	FREQUENCY(MHz)	POWER(dBm)
2400.00	-28.20	2483.60	-45.24
Result			
In any 100kHz bandwidth outside the frequency band, the radio frequency power is at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power.			




IEEE 802.11g/The max. radio frequency power in any
100kHz bandwidth outside the frequency band



Date: 14.FEB.2014 21:14:56


IEEE 802.11g/The max. radio frequency power in any
100 kHz bandwidth within the frequency band



Date: 14.FEB.2014 21:29:39




IEEE 802.11g/2412 MHz/10 Harmonic of the frequency




Date: 14.FEB.2014 21:14:31

IEEE 802.11g/2437 MHz/10 Harmonic of the frequency



Date: 14.FEB.2014 21:21:07



Date: 14.FEB.2014 21:29:13




EUT	Mini PCI Radio Module, 2x2 IEEE 802.11 b/g/n ,2.4 GHz	Model Name	RJ-1301
Temperature	26°C	Relative Humidity	46%
Test Voltage	AC 120V/60Hz		
Test Mode	IEEE 802.11n (20 MHz)-1TX		

Channel of Worst Data			
The max. radio frequency power in any 100kHz bandwidth outside the frequency band		The max. radio frequency power in any 100 kHz bandwidth within the frequency band.	
FREQUENCY(MHz)	POWER(dBm)	FREQUENCY(MHz)	POWER(dBm)
2400.00	-29.25	2484.20	-47.17
Result			
In any 100kHz bandwidth outside the frequency band, the radio frequency power is at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power.			




IEEE 802.11n (20 MHz)/The max. radio frequency power in any 100kHz bandwidth outside the frequency band



Date: 14.FEB.2014 21:40:48


IEEE 802.11n (20 MHz)/The max. radio frequency power in any 100 kHz bandwidth within the frequency band



Date: 14.FEB.2014 22:07:29




IEEE 802.11n (20 MHz)/2412 MHz/10 Harmonic of the frequency



Date: 14.FEB.2014 21:40:23


IEEE 802.11n (20 MHz)/2437 MHz/10 Harmonic of the frequency



Date: 14.FEB.2014 21:51:09



IEEE 802.11n (20 MHz)/2462 MHz/10 Harmonic of the frequency



Date: 14.FEB.2014 22:05:57




EUT	Mini PCI Radio Module, 2x2 IEEE 802.11 b/g/n ,2.4 GHz	Model Name	RJ-1301
Temperature	26°C	Relative Humidity	46%
Test Voltage	AC 120V/60Hz		
Test Mode	IEEE 802.11n (40 MHz)-1TX		

Channel of Worst Data			
The max. radio frequency power in any 100kHz bandwidth outside the frequency band		The max. radio frequency power in any 100 kHz bandwidth within the frequency band.	
FREQUENCY(MHz)	POWER(dBm)	FREQUENCY(MHz)	POWER(dBm)
2400.00	-34.56	2488.00	-40.41
Result			
In any 100kHz bandwidth outside the frequency band, the radio frequency power is at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power.			




IEEE 802.11n (40 MHz)/The max. radio frequency power in any 100kHz bandwidth outside the frequency band



Date: 14.FEB.2014 22:15:52


IEEE 802.11n (40 MHz)/The max. radio frequency power in any 100 kHz bandwidth within the frequency band



Date: 14.FEB.2014 22:29:53




IEEE 802.11n (40 MHz)/2422 MHz/10 Harmonic of the frequency



Date: 14.FEB.2014 22:15:03


IEEE 802.11n (40 MHz)/2437 MHz/10 Harmonic of the frequency



Date: 14.FEB.2014 22:21:55



IEEE 802.11n (40 MHz)/2452 MHz/10 Harmonic of the frequency



Date: 14.FEB.2014 22:28:47




EUT	Mini PCI Radio Module, 2x2 IEEE 802.11 b/g/n ,2.4 GHz	Model Name	RJ-1301
Temperature	26°C	Relative Humidity	46%
Test Voltage	AC 120V/60Hz		
Test Mode	IEEE 802.11n (20 MHz)-2TX-ANT 1		

Channel of Worst Data			
The max. radio frequency power in any 100kHz bandwidth outside the frequency band		The max. radio frequency power in any 100 kHz bandwidth within the frequency band.	
FREQUENCY(MHz)	POWER(dBm)	FREQUENCY(MHz)	POWER(dBm)
2400.00	-30.19	2484.60	-47.83
Result			
In any 100kHz bandwidth outside the frequency band, the radio frequency power is at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power.			




IEEE 802.11n (20 MHz)/The max. radio frequency power in any 100kHz bandwidth outside the frequency band



Date: 14.FEB.2014 22:51:43


IEEE 802.11n (20 MHz)/The max. radio frequency power in any 100 kHz bandwidth within the frequency band



Date: 14.FEB.2014 23:21:58




IEEE 802.11n (20 MHz)/2412 MHz/10 Harmonic of the frequency



Date: 14.FEB.2014 22:49:25


IEEE 802.11n (20 MHz)/2437 MHz/10 Harmonic of the frequency



Date: 14.FEB.2014 23:12:18



IEEE 802.11n (20 MHz)/2462 MHz/10 Harmonic of the frequency



Date: 14.FEB.2014 23:21:13




EUT	Mini PCI Radio Module, 2x2 IEEE 802.11 b/g/n ,2.4 GHz	Model Name	RJ-1301
Temperature	26°C	Relative Humidity	46%
Test Voltage	AC 120V/60Hz		
Test Mode	IEEE 802.11n (20 MHz)-2TX-ANT 2		

Channel of Worst Data			
The max. radio frequency power in any 100kHz bandwidth outside the frequency band		The max. radio frequency power in any 100 kHz bandwidth within the frequency band.	
FREQUENCY(MHz)	POWER(dBm)	FREQUENCY(MHz)	POWER(dBm)
2400.00	-29.31	2494.60	-47.35
Result			
In any 100kHz bandwidth outside the frequency band, the radio frequency power is at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power.			




IEEE 802.11n (20 MHz)/The max. radio frequency power in any 100kHz bandwidth outside the frequency band



Date: 14.FEB.2014 23:29:09


IEEE 802.11n (20 MHz)/The max. radio frequency power in any 100 kHz bandwidth within the frequency band



Date: 14.FEB.2014 23:40:03




IEEE 802.11n (20 MHz)/2412 MHz/10 Harmonic of the frequency



Date: 14.FEB.2014 21:40:23


IEEE 802.11n (20 MHz)/2437 MHz/10 Harmonic of the frequency



Date: 14.FEB.2014 23:34:13



IEEE 802.11n (20 MHz)/2462 MHz/10 Harmonic of the frequency



Date: 14.FEB.2014 23:39:14




EUT	Mini PCI Radio Module, 2x2 IEEE 802.11 b/g/n ,2.4 GHz	Model Name	RJ-1301
Temperature	26°C	Relative Humidity	46%
Test Voltage	AC 120V/60Hz		
Test Mode	IEEE 802.11n (40 MHz)-2TX-ANT 1		

Channel of Worst Data			
The max. radio frequency power in any 100kHz bandwidth outside the frequency band		The max. radio frequency power in any 100 kHz bandwidth within the frequency band.	
FREQUENCY(MHz)	POWER(dBm)	FREQUENCY(MHz)	POWER(dBm)
2400.00	-35.61	2484.40	-42.37
Result			
In any 100kHz bandwidth outside the frequency band, the radio frequency power is at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power.			




IEEE 802.11n (40 MHz)/The max. radio frequency power in any 100kHz bandwidth outside the frequency band



Date: 15.FEB.2014 00:12:29


IEEE 802.11n (40 MHz)/The max. radio frequency power in any 100 kHz bandwidth within the frequency band




Date: 15.FEB.2014 00:31:29



IEEE 802.11n (40 MHz)/2422 MHz/10 Harmonic of the frequency




IEEE 802.11n (40 MHz)/2437 MHz/10 Harmonic of the frequency





IEEE 802.11n (40 MHz)/2452 MHz/10 Harmonic of the frequency



Date: 15.FEB.2014 00:29:48




EUT	Mini PCI Radio Module, 2x2 IEEE 802.11 b/g/n ,2.4 GHz	Model Name	RJ-1301
Temperature	26°C	Relative Humidity	46%
Test Voltage	AC 120V/60Hz		
Test Mode	IEEE 802.11n (40 MHz)-2TX-ANT 2		

Channel of Worst Data			
The max. radio frequency power in any 100kHz bandwidth outside the frequency band		The max. radio frequency power in any 100 kHz bandwidth within the frequency band.	
FREQUENCY(MHz)	POWER(dBm)	FREQUENCY(MHz)	POWER(dBm)
2400.00	-37.49	2485.20	-47.59
Result			
In any 100kHz bandwidth outside the frequency band, the radio frequency power is at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power.			




IEEE 802.11n (40 MHz)/The max. radio frequency power in any 100kHz bandwidth outside the frequency band



Date: 14.FEB.2014 23:53:53


IEEE 802.11n (40 MHz)/The max. radio frequency power in any 100 kHz bandwidth within the frequency band



Date: 15.FEB.2014 00:03:43




IEEE 802.11n (40 MHz)/2422 MHz/10 Harmonic of the frequency



Date: 14.FEB.2014 23:52:36


IEEE 802.11n (40 MHz)/2437 MHz/10 Harmonic of the frequency



Date: 14.FEB.2014 23:58:17



IEEE 802.11n (40 MHz)/2452 MHz/10 Harmonic of the frequency



Date: 15.FEB.2014 00:03:13



6.6 DB BANDWIDTH

6.1 LIMIT

Test Item	Frequency Range (MHz)	Limit
Bandwidth	2400-2483.5	$\geq 500\text{KHz}$ (6dB bandwidth)

6.2 MEASUREMENT INSTRUMENTS LIST


Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Spectrum Analyzer	R&S	FSP-30	100854	Sep. 08, 2014

NOTE: **N/A**: denotes No Model Name, No Serial No. or No Calibration specified.

6.3 TEST PROCEDURES

- The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below.
- Spectrum Setting: RBW= 100KHz, VBW=100KHz, Sweep time = Auto.

6.4 TEST SETUP LAYOUT



6.5 DEVIATION FROM TEST STANDARD

No deviation

6.6 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 4.6 Unless otherwise a special operating condition is specified in the follows during the testing.




6.7 TEST RESULTS

EUT	Mini PCI Radio Module, 2x2 IEEE 802.11 b/g/n ,2.4 GHz	Model Name	RJ-1301
Temperature	26°C	Relative Humidity	46%
Test Voltage	AC 120V/60Hz		
Test Mode	IEEE 802.11b/2412 MHz, 2437 MHz, 2462 MHz		

Frequency	6 dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Limit	Result
2412 MHz	12.27	15.80	>=500 kHz	PASS
2437 MHz	10.62	15.65	>=500 kHz	PASS
2462 MHz	10.14	14.92	>=500 kHz	PASS


IEEE 802.11b/2412 MHz/6 dB and 99% Occupied Bandwidth



Date: 14.FEB.2014 17:30:14




IEEE 802.11b/2437 MHz/6 dB and 99% Occupied Bandwidth



Date: 14.FEB.2014 17:42:51

IEEE 802.11b/2462 MHz/6 dB and 99% Occupied Bandwidth




Date: 14.FEB.2014 21:05:08



EUT	Mini PCI Radio Module, 2x2 IEEE 802.11 b/g/n ,2.4 GHz	Model Name	RJ-1301
Temperature	26°C	Relative Humidity	46%
Test Voltage	AC 120V/60Hz		
Test Mode	IEEE 802.11g/2412 MHz, 2437 MHz, 2462 MHz		

Frequency	6 dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Limit	Result
2412 MHz	16.41	16.60	>=500 kHz	PASS
2437 MHz	15.73	16.56	>=500 kHz	PASS
2462 MHz	14.93	16.36	>=500 kHz	PASS


IEEE 802.11g/2412 MHz/6 dB and 99% Occupied Bandwidth



Date: 14.FEB.2014 21:14:44




IEEE 802.11g/2437 MHz/6 dB and 99% Occupied Bandwidth



Date: 14.FEB.2014 21:22:29

IEEE 802.11g/2462 MHz/6 dB and 99% Occupied Bandwidth




Date: 14.FEB.2014 21:29:28



EUT	Mini PCI Radio Module, 2x2 IEEE 802.11 b/g/n ,2.4 GHz	Model Name	RJ-1301
Temperature	26°C	Relative Humidity	46%
Test Voltage	AC 120V/60Hz		
Test Mode	IEEE 802.11n (20 MHz)/2412 MHz, 2437 MHz, 2462 MHz-1TX		

Frequency	6 dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Limit	Result
2412 MHz	17.33	17.72	>=500 kHz	PASS
2437 MHz	17.57	17.64	>=500 kHz	PASS
2462 MHz	15.41	17.52	>=500 kHz	PASS

IEEE 802.11n (20 MHz)/2412 MHz/6 dB and 99% Occupied Bandwidth



Date: 14.FEB.2014 21:40:37



RBW 100 kHz Delta 1 [T1]
 VBW 300 kHz -2.20 dB
 Att 30 dB
 SWT 2.5 ms 15.411576806 MHz

20 Offset 0.5 dB
 DB 6.77 dBm
 T1 1
 T2 2
 T3 3
 T4 4
 T5 5
 T6 6
 T7 7
 T8 8
 T9 9
 T10 10
 T11 11
 T12 12
 T13 13
 T14 14
 T15 15
 T16 16
 T17 17
 T18 18
 T19 19
 T20 20
 T21 21
 T22 22
 T23 23
 T24 24
 T25 25
 T26 26
 T27 27
 T28 28
 T29 29
 T30 30
 T31 31
 T32 32
 T33 33
 T34 34
 T35 35
 T36 36
 T37 37
 T38 38
 T39 39
 T40 40
 T41 41
 T42 42
 T43 43
 T44 44
 T45 45
 T46 46
 T47 47
 T48 48
 T49 49
 T50 50
 T51 51
 T52 52
 T53 53
 T54 54
 T55 55
 T56 56
 T57 57
 T58 58
 T59 59
 T60 60
 T61 61
 T62 62
 T63 63
 T64 64
 T65 65
 T66 66
 T67 67
 T68 68
 T69 69
 T70 70
 T71 71
 T72 72
 T73 73
 T74 74
 T75 75
 T76 76
 T77 77
 T78 78
 T79 79
 T80 80
 T81 81
 T82 82
 T83 83
 T84 84
 T85 85
 T86 86
 T87 87
 T88 88
 T89 89
 T90 90
 T91 91
 T92 92
 T93 93
 T94 94
 T95 95
 T96 96
 T97 97
 T98 98
 T99 99
 T100 100
 T101 101
 T102 102
 T103 103
 T104 104
 T105 105
 T106 106
 T107 107
 T108 108
 T109 109
 T110 110
 T111 111
 T112 112
 T113 113
 T114 114
 T115 115
 T116 116
 T117 117
 T118 118
 T119 119
 T120 120
 T121 121
 T122 122
 T123 123
 T124 124
 T125 125
 T126 126
 T127 127
 T128 128
 T129 129
 T130 130
 T131 131
 T132 132
 T133 133
 T134 134
 T135 135
 T136 136
 T137 137
 T138 138
 T139 139
 T140 140
 T141 141
 T142 142
 T143 143
 T144 144
 T145 145
 T146 146
 T147 147
 T148 148
 T149 149
 T150 150
 T151 151
 T152 152
 T153 153
 T154 154
 T155 155
 T156 156
 T157 157
 T158 158
 T159 159
 T160 160
 T161 161
 T162 162
 T163 163
 T164 164
 T165 165
 T166 166
 T167 167
 T168 168
 T169 169
 T170 170
 T171 171
 T172 172
 T173 173
 T174 174
 T175 175
 T176 176
 T177 177
 T178 178
 T179 179
 T180 180
 T181 181
 T182 182
 T183 183
 T184 184
 T185 185
 T186 186
 T187 187
 T188 188
 T189 189
 T190 190
 T191 191
 T192 192
 T193 193
 T194 194
 T195 195
 T196 196
 T197 197
 T198 198
 T199 199
 T200 200
 T201 201
 T202 202
 T203 203
 T204 204
 T205 205
 T206 206
 T207 207
 T208 208
 T209 209
 T210 210
 T211 211
 T212 212
 T213 213
 T214 214
 T215 215
 T216 216
 T217 217
 T218 218
 T219 219
 T220 220
 T221 221
 T222 222
 T223 223
 T224 224
 T225 225
 T226 226
 T227 227
 T228 228
 T229 229
 T230 230
 T231 231
 T232 232
 T233 233
 T234 234
 T235 235
 T236 236
 T237 237
 T238 238
 T239 239
 T240 240
 T241 241
 T242 242
 T243 243
 T244 244
 T245 245
 T246 246
 T247 247
 T248 248
 T249 249
 T250 250
 T251 251
 T252 252
 T253 253
 T254 254
 T255 255
 T256 256
 T257 257
 T258 258
 T259 259
 T260 260
 T261 261
 T262 262
 T263 263
 T264 264
 T265 265
 T266 266
 T267 267
 T268 268
 T269 269
 T270 270
 T271 271
 T272 272
 T273 273
 T274 274
 T275 275
 T276 276
 T277 277
 T278 278
 T279 279
 T280 280
 T281 281
 T282 282
 T283 283
 T284 284
 T285 285
 T286 286
 T287 287
 T288 288
 T289 289
 T290 290
 T291 291
 T292 292
 T293 293
 T294 294
 T295 295
 T296 296
 T297 297
 T298 298
 T299 299
 T300 300
 T301 301
 T302 302
 T303 303
 T304 304
 T305 305
 T306 306
 T307 307
 T308 308
 T309 309
 T310 310
 T311 311
 T312 312
 T313 313
 T314 314
 T315 315
 T316 316
 T317 317
 T318 318
 T319 319
 T320 320
 T321 321
 T322 322
 T323 323
 T324 324
 T325 325
 T326 326
 T327 327
 T328 328
 T329 329
 T330 330
 T331 331
 T332 332
 T333 333
 T334 334
 T335 335
 T336 336
 T337 337
 T338 338
 T339 339
 T340 340
 T341 341
 T342 342
 T343 343
 T344 344
 T345 345
 T346 346
 T347 347
 T348 348


Date: 14.FEB.2014 22:07:15



EUT	Mini PCI Radio Module, 2x2 IEEE 802.11 b/g/n ,2.4 GHz	Model Name	RJ-1301
Temperature	26°C	Relative Humidity	46%
Test Voltage	AC 120V/60Hz		
Test Mode	IEEE 802.11n (40 MHz)/2422 MHz, 2437 MHz, 2452 MHz-1TX		

Frequency	6 dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Limit	Result
2422 MHz	35.13	35.84	>=500 kHz	PASS
2437 MHz	26.35	35.92	>=500 kHz	PASS
2452 MHz	35.85	36.16	>=500 kHz	PASS


IEEE 802.11n (40 MHz)/2422 MHz/6 dB and 99% Occupied Bandwidth



Date: 14.FEB.2014 22:15:41



IEEE 802.11n (40 MHz)/2452 MHz/6 dB and 99% Occupied Bandwidth






EUT	Mini PCI Radio Module, 2x2 IEEE 802.11 b/g/n ,2.4 GHz	Model Name	RJ-1301
Temperature	26°C	Relative Humidity	46%
Test Voltage	AC 120V/60Hz		
Test Mode	IEEE 802.11n (20 MHz)/2412 MHz, 2437 MHz, 2462 MHz-2TX-ANT 1		

Frequency	6 dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Limit	Result
2412 MHz	17.68	17.76	>=500 kHz	PASS
2437 MHz	16.45	17.68	>=500 kHz	PASS
2462 MHz	16.33	17.60	>=500 kHz	PASS


IEEE 802.11n (20 MHz)/2412 MHz/6 dB and 99% Occupied Bandwidth



Date: 14.FEB.2014 22:51:30




IEEE 802.11n (20 MHz)/2437 MHz/6 dB and 99% Occupied Bandwidth



Date: 14.FEB.2014 23:12:54

IEEE 802.11n (20 MHz)/2462 MHz/6 dB and 99% Occupied Bandwidth




Date: 14.FEB.2014 23:21:40



EUT	Mini PCI Radio Module, 2x2 IEEE 802.11 b/g/n ,2.4 GHz	Model Name	RJ-1301
Temperature	26°C	Relative Humidity	46%
Test Voltage	AC 120V/60Hz		
Test Mode	IEEE 802.11n (20 MHz)/2412 MHz, 2437 MHz, 2462 MHz-2TX-ANT 2		

Frequency	6 dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Limit	Result
2412 MHz	17.77	17.76	>=500 kHz	PASS
2437 MHz	17.72	17.72	>=500 kHz	PASS
2462 MHz	16.37	17.60	>=500 kHz	PASS


IEEE 802.11n (20 MHz)/2412 MHz/6 dB and 99% Occupied Bandwidth



Date: 14.FEB.2014 23:28:59




IEEE 802.11n (20 MHz)/2437 MHz/6 dB and 99% Occupied Bandwidth



Date: 14.FEB.2014 23:34:30

IEEE 802.11n (20 MHz)/2462 MHz/6 dB and 99% Occupied Bandwidth




Date: 14.FEB.2014 23:39:52



EUT	Mini PCI Radio Module, 2x2 IEEE 802.11 b/g/n ,2.4 GHz	Model Name	RJ-1301
Temperature	26°C	Relative Humidity	46%
Test Voltage	AC 120V/60Hz		
Test Mode	IEEE 802.11n (40 MHz)/2422 MHz, 2437 MHz, 2452 MHz-2TX-ANT 1		

Frequency	6 dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Limit	Result
2422 MHz	34.97	35.76	>=500 kHz	PASS
2437 MHz	35.07	35.92	>=500 kHz	PASS
2452 MHz	35.77	36.00	>=500 kHz	PASS


IEEE 802.11n (40 MHz)/2422 MHz/6 dB and 99% Occupied Bandwidth



Date: 15.FEB.2014 00:12:15




IEEE 802.11n (40 MHz)/2437 MHz/6 dB and 99% Occupied Bandwidth



Date: 15.FEB.2014 00:22:36

IEEE 802.11n (40 MHz)/2452 MHz/6 dB and 99% Occupied Bandwidth




Date: 15.FEB.2014 00:30:53



EUT	Mini PCI Radio Module, 2x2 IEEE 802.11 b/g/n ,2.4 GHz	Model Name	RJ-1301
Temperature	26°C	Relative Humidity	46%
Test Voltage	AC 120V/60Hz		
Test Mode	IEEE 802.11n (40 MHz)/2422 MHz, 2437 MHz, 2452 MHz-2TX-ANT 2		

Frequency	6 dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Limit	Result
2422 MHz	35.13	35.92	>=500 kHz	PASS
2437 MHz	35.15	36.00	>=500 kHz	PASS
2452 MHz	33.29	35.92	>=500 kHz	PASS

IEEE 802.11n (40 MHz)/2422 MHz/6 dB and 99% Occupied Bandwidth



Date: 14.FEB.2014 23:53:42



Ref 20 dBm Att 30 dB RBW 100 kHz Delta 1 [T1] VBW 300 kHz -9.03 dBm SWT 5 ms 33.233013174 MHz

Offset 0.5 dB

OBW 35.92000000 MHz
Marker 1 [T1]
Temp 1 [T1] 2.43376487 GHz
Temp 2 [T2] 2.48068000 GHz
-9.03 dBm

D1 1.19 dBm
D2 1.19 dBm

F1 F2

Center 2.452 GHz Span 40 MHz

Date: 15.FEB.2014 00:03:31



7 MAXIMUM PEAK CONDUCTED OUTPUT POWER

7.1 LIMIT

Test Item	Frequency Range (MHz)	Limit
Maximum Peak Conducted Output Power	2400-2483.5	1 watt or 30 dBm

7.2 MEASUREMENT INSTRUMENTS LIST


Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Spectrum Analyzer	R&S	FSP-30	100854	Sep. 08, 2014

NOTE: **N/A**: denotes No Model Name, No Serial No. or No Calibration specified.

7.3 TEST PROCEDURES

- The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- Spectrum Setting: RBW= 3 MHz, VBW= 3 MHz, Sweep time = Auto.

7.4 TEST SETUP LAYOUT



7.5 DEVIATION FROM TEST STANDARD

No deviation

7.6 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 5.6 Unless otherwise a special operating condition is specified in the follows during the testing.

**7.7 TEST RESULTS**

EUT	Mini PCI Radio Module, 2x2 IEEE 802.11 b/g/n ,2.4 GHz	Model Name	RJ-1301
Temperature	26°C	Relative Humidity	46%
Test Voltage	AC 120V/60Hz		
Test Mode	IEEE 802.11b/2412 MHz, 2437 MHz, 2462 MHz		

Frequency	Peak Output Power		Limit		Result
	(dBm)	(W)	(dBm)	(W)	
2412 MHz	23.34	0.2158	30	1	PASS
2437 MHz	25.10	0.3236	30	1	PASS
2462 MHz	22.02	0.1592	30	1	PASS

**Neutron Engineering Inc.**

EUT	Mini PCI Radio Module, 2x2 IEEE 802.11 b/g/n ,2.4 GHz	Model Name	RJ-1301
Temperature	26°C	Relative Humidity	46%
Test Voltage	AC 120V/60Hz		
Test Mode	IEEE 802.11g/2412 MHz, 2437 MHz, 2462 MHz		

Frequency	Peak Output Power		Limit		Result
	(dBm)	(W)	(dBm)	(W)	
2412 MHz	24.89	0.3083	30	1	PASS
2437 MHz	26.62	0.4592	30	1	PASS
2462 MHz	26.08	0.4055	30	1	PASS



Neutron Engineering Inc.

EUT	Mini PCI Radio Module, 2x2 IEEE 802.11 b/g/n ,2.4 GHz	Model Name	RJ-1301
Temperature	26°C	Relative Humidity	46%
Test Voltage	AC 120V/60Hz		
Test Mode	IEEE 802.11n (20 MHz)/2412 MHz, 2437 MHz, 2462 MHz-1TX		

Frequency	Peak Output Power		Limit		Result
	(dBm)	(W)	(dBm)	(W)	
2412 MHz	22.52	0.1786	30	1	PASS
2437 MHz	26.72	0.4699	30	1	PASS
2462 MHz	25.78	0.3784	30	1	PASS



EUT	Mini PCI Radio Module, 2x2 IEEE 802.11 b/g/n ,2.4 GHz	Model Name	RJ-1301
Temperature	26°C	Relative Humidity	46%
Test Voltage	AC 120V/60Hz		
Test Mode	IEEE 802.11n (40 MHz)/2422 MHz, 2437 MHz, 2452 MHz-1TX		

Frequency	Peak Output Power		Limit		Result
	(dBm)	(W)	(dBm)	(W)	
2422 MHz	22.29	0.1694	30	1	PASS
2437 MHz	25.10	0.3236	30	1	PASS
2452 MHz	25.52	0.3565	30	1	PASS



EUT	Mini PCI Radio Module, 2x2 IEEE 802.11 b/g/n ,2.4 GHz	Model Name	RJ-1301
Temperature	26°C	Relative Humidity	46%
Test Voltage	AC 120V/60Hz		
Test Mode	IEEE 802.11n (20 MHz)/2412 MHz, 2437 MHz, 2462 MHz-2TX-ANT 1		

Frequency	Peak Output Power		Limit		Result
	(dBm)	(W)	(dBm)	(W)	
2412 MHz	22.44	0.1754	-	-	PASS
2437 MHz	25.11	0.3243	-	-	PASS
2462 MHz	24.60	0.2884	-	-	PASS



EUT	Mini PCI Radio Module, 2x2 IEEE 802.11 b/g/n ,2.4 GHz	Model Name	RJ-1301
Temperature	26°C	Relative Humidity	46%
Test Voltage	AC 120V/60Hz		
Test Mode	IEEE 802.11n (20 MHz)/2412 MHz, 2437 MHz, 2462 MHz-2TX-ANT 2		

Frequency	Peak Output Power		Limit		Result
	(dBm)	(W)	(dBm)	(W)	
2412 MHz	22.58	0.1811	-	-	PASS
2437 MHz	24.63	0.2904	-	-	PASS
2462 MHz	24.30	0.2692	-	-	PASS



EUT	Mini PCI Radio Module, 2x2 IEEE 802.11 b/g/n ,2.4 GHz	Model Name	RJ-1301
Temperature	26°C	Relative Humidity	46%
Test Voltage	AC 120V/60Hz		
Test Mode	IEEE 802.11n (20 MHz)/2412 MHz, 2437 MHz, 2462 MHz-2TX-Total		

Frequency	Peak Output Power		Limit		Result
	(dBm)	(W)	(dBm)	(W)	
2412 MHz	25.52	0.3565	28	0.6310	PASS
2437 MHz	27.89	0.6147	28	0.6310	PASS
2462 MHz	27.46	0.5576	28	0.6310	PASS

NOTE:

- The MIMO test requirement, RF conducted output power shall measure each transmitter chain by using channel power method.
And after obtain each individual transmitter chain power, then sum the output power by using the following formula:

$$((\text{dBm}/\text{Chain 1})/10^{\wedge}\text{Log}) + ((\text{dBm}/\text{Chain 2})/10^{\wedge}\text{log}) + ((\text{dBm}/\text{ChainN})/10^{\wedge}\text{log}) = \text{Combined peak output power in mW.}$$
- Antenna Gain = 5dBi.



EUT	Mini PCI Radio Module, 2x2 IEEE 802.11 b/g/n ,2.4 GHz	Model Name	RJ-1301
Temperature	26°C	Relative Humidity	46%
Test Voltage	AC 120V/60Hz		
Test Mode	IEEE 802.11n (40 MHz)/2422 MHz, 2437 MHz, 2452 MHz-2TX-ANT 1		

Frequency	Peak Output Power		Limit		Result
	(dBm)	(W)	(dBm)	(W)	
2422 MHz	20.03	0.1007	-	-	PASS
2437 MHz	24.38	0.2742	-	-	PASS
2452 MHz	24.03	0.2529	-	-	PASS



EUT	Mini PCI Radio Module, 2x2 IEEE 802.11 b/g/n ,2.4 GHz	Model Name	RJ-1301
Temperature	26°C	Relative Humidity	46%
Test Voltage	AC 120V/60Hz		
Test Mode	IEEE 802.11n (40 MHz)/2422 MHz, 2437 MHz, 2452 MHz-2TX-ANT 2		

Frequency	Peak Output Power		Limit		Result
	(dBm)	(W)	(dBm)	(W)	
2422 MHz	19.48	0.0887	-	-	PASS
2437 MHz	23.83	0.2415	-	-	PASS
2452 MHz	23.65	0.2317	-	-	PASS



EUT	Mini PCI Radio Module, 2x2 IEEE 802.11 b/g/n ,2.4 GHz	Model Name	RJ-1301
Temperature	26°C	Relative Humidity	46%
Test Voltage	AC 120V/60Hz		
Test Mode	IEEE 802.11n (40 MHz)/2422 MHz, 2437 MHz, 2452 MHz-2TX-Total		

Frequency	Peak Output Power		Limit		Result
	(dBm)	(W)	(dBm)	(W)	
2422 MHz	22.77	0.1894	28	0.6310	PASS
2437 MHz	27.12	0.5157	28	0.6310	PASS
2452 MHz	26.85	0.4847	28	0.6310	PASS

NOTE:

- The MIMO test requirement, RF conducted output power shall measure each transmitter chain by using channel power method.
And after obtain each individual transmitter chain power, then sum the output power by using the following formula:

$$((\text{dBm}/\text{Chain 1})/10^{\wedge}\text{Log}) + ((\text{dBm}/\text{Chain 2})/10^{\wedge}\text{log}) + ((\text{dBm}/\text{ChainN})/10^{\wedge}\text{log}) = \text{Combined peak output power in mW.}$$
- Antenna Gain = 5dBi.



8 RADIATED SPURIOUS EMISSION (9 KHZ TO 1 GHZ)

8.1 LIMIT

20 dB in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequency Range: 9 kHz to 1 GHz		
FREQUENCY (MHz)	Field Strength (micровolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(kHz)	300
0.490~1.705	24000/F(kHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

Frequency Range: above 1 GHz				
FREQUENCY (MHz)	Class A (dBuV/m) (at 3m)		Class B (dBuV/m) (at 3m)	
	PEAK	AVERAGE	PEAK	AVERAGE
above 1 GHz	80	60	74	54

NOTE:

1. The limit for radiated test was performed according to FCC PART 15B.
2. The tighter limit applies at the band edges.
3. Emission level (dBuV/m)=20log Emission level (uV/m).
4. The test result calculated as following:
 Measurement Value = Reading Level + Correct Factor
 Correct Factor = Antenna Factor + Cable Loss – Amplifier Gain(if use)
 Margin Level = Measurement Value – Limit Value



8.2 MEASUREMENT INSTRUMENTS LIST

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Spectrum Analyzer	R&S	FSP-30	100854	Sep. 08, 2014
2	Horn Antenna	Schwarzbeck	BBHA 9120	D-325	Apr. 15, 2014
3	Microwave Pre-amplifier	Agilent	8449B	3008A01714	Apr. 16, 2014
4	Microflex Cable	Harbour industries	27478LL142	1m	May. 13, 2014
5	Microflex Cable	EMC	S104-SMA	8m	May. 13, 2014
6	Microflex Cable	Harbour industries	27478LL142	3m	May. 13, 2014
7	Test Cable	LMR	LMR-400	12m	May. 14, 2014
8	Test Cable	LMR	LMR-400	3m	May. 14, 2014
9	Pre-Amplifier	Anritsu	MH648A	M92649	Jun. 18, 2014
10	Log-Bicon Antenna	Schwarzbeck	VULB9168-352	9168-352	Jun. 11, 2014
11	Preamplifier With Adaptor	EMC	EMC2654045	980030	Feb. 18, 2014
12	Horn Antenna	Schwarzbeck	BBHA 9170	187	Dec. 23, 2014

Remark: "N/A" denotes No Model Name, No Serial No. or No Calibration specified.

8.3 MEASURING INSTRUMENTS SETTING

EMI Test Receiver	Parameter Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP



8.4 TEST PROCEDURES

- The measuring distance of at 3 m shall be used for measurements at frequency up to 1 GHz. For frequencies above 1 GHz, any suitable measuring distance may be used.
- The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3m Semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- The height of the equipment or of the substitution antenna shall be 0.8 m; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
- For the actual test configuration, please refer to the related Item –EUT Test Photos.
- The testing follows the guidelines in ANSI C63.4 and FCC Public Notice DA 00-705 Measurement Guidelines. In case the emission is fail due to the used RBW/VBW is too wide, marker-delta method of FCC Public Notice DA 00-705 will be followed.


NOTE:

- Reading in which marked as QP or Peak means measurements by using are Quasi-Peak Mode with Detector BW=120 kHz; SPA setting in RBW=100 kHz, VBW =100 kHz, Swp. Time = 0.3 sec./ MHz.
- All readings are Peak unless otherwise stated QP in column of Note. Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform.

8.5 DEVIATION FROM TEST STANDARD

No deviation

8.6 TEST SETUP LAYOUT





8.7 EUT OPERATING CONDITIONS


The EUT tested system was configured as the statements of 5.6 Unless otherwise a special operating condition is specified in the follows during the testing.



8.8 TEST RESULTS

EUT	Mini PCI Radio Module, 2x2 IEEE 802.11 b/g/n ,2.4 GHz	Model Name	RJ-1301
Temperature	26°C	Relative Humidity	60%
Test Voltage	AC 120V/60Hz		
Test Mode	IEEE 802.11b/2437 MHz		

Polarization: Vertical




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1		132.8200	52.87	-15.54	37.33	43.50	-6.17	peak	
2		167.7400	51.18	-14.47	36.71	43.50	-6.79	peak	
3		233.7000	54.94	-15.99	38.95	46.00	-7.05	peak	
4		456.7998	50.07	-9.73	40.34	46.00	-5.66	peak	
5		625.5800	47.49	-6.83	40.66	46.00	-5.34	peak	
6	*	912.7000	44.36	-3.36	41.00	46.00	-5.00	peak	



EUT	Mini PCI Radio Module, 2x2 IEEE 802.11 b/g/n ,2.4 GHz	Model Name	RJ-1301
Temperature	26°C	Relative Humidity	60%
Test Voltage	AC 120V/60Hz		
Test Mode	IEEE 802.11b/2437 MHz		

Polarization: Horizontal



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1	*	200.7200	56.94	-16.90	40.04	43.50	-3.46	peak	
2		402.4800	51.13	-11.12	40.01	46.00	-5.99	peak	
3		697.3600	48.94	-6.49	42.45	46.00	-3.55	peak	
4		738.1000	46.32	-5.62	40.70	46.00	-5.30	peak	
5		769.1400	45.82	-5.15	40.67	46.00	-5.33	peak	
6		854.5000	44.31	-4.00	40.31	46.00	-5.69	peak	



9 RADIATED SPURIOUS EMISSION (ABOVE 1 GHz)

9.1 LIMIT

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequency Range: 9 kHz to 1 GHz		
FREQUENCY (MHz)	Field Strength (micровolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(kHz)	300
0.490~1.705	24000/F(kHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

Frequency Range: above 1 GHz				
FREQUENCY (MHz)	Class A (dBuV/m) (at 3m)		Class B (dBuV/m) (at 3m)	
	PEAK	AVERAGE	PEAK	AVERAGE
above 1 GHz	80	60	74	54

NOTE:

- (1) The limit for radiated test was performed according to FCC PART 15B.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).
- (4) The test result calculated as following:
 Measurement Value = Reading Level + Correct Factor
 Correct Factor = Antenna Factor + Cable Loss – Amplifier Gain(if use)
 Margin Level = Measurement Value – Limit Value



9.2 MEASUREMENT INSTRUMENTS LIST

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Spectrum Analyzer	R&S	FSP-30	100854	Sep. 08, 2014
2	Horn Antenna	Schwarzbeck	BBHA 9120	D-325	Apr. 15, 2014
3	Microwave Pre_amplifier	Agilent	8449B	3008A01714	Apr. 16, 2014
4	Microflex Cable	Harbour industries	27478LL142	1m	May. 13, 2014
5	Microflex Cable	EMC	S104-SMA	8m	May. 13, 2014
6	Microflex Cable	Harbour industries	27478LL142	3m	May. 13, 2014
7	Test Cable	LMR	LMR-400	12m	May. 14, 2014
8	Test Cable	LMR	LMR-400	3m	May. 14, 2014
9	Pre-Amplifier	Anritsu	MH648A	M92649	Jun. 18, 2014
10	Log-Bicon Antenna	Schwarzbeck	VULB9168-352	9168-352	Jun. 11, 2014
11	Preamplifier With Adaptor	EMC	EMC2654045	980030	Feb. 18, 2014
12	Horn Antenna	Schwarzbeck	BBHA 9170	187	Dec. 23, 2014

Remark: "N/A" denotes No Model Name, No Serial No. or No Calibration specified.

9.3 MEASURING INSTRUMENTS SETTING

Spectrum Analyzer	Parameter Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RB / VB (emission in restricted band)	1MHz / 1MHz for Peak, 1 MHz / 10Hz for Average
RB / VB (other emission)	1MHz / 1MHz for Peak, 1 MHz / 10Hz for Average

9.4 TEST PROCEDURES

- The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3m Semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- The height of the equipment or of the substitution antenna shall be 0.8 m; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
- For the actual test configuration, please refer to the related Item –EUT Test Photos.
- The testing follows the guidelines in ANSI C63.4 and FCC Public Notice DA 00-705 Measurement Guidelines. In case the emission is fail due to the used RBW/VBW is too wide, marker-delta method of FCC Public Notice DA 00-705 will be followed.


NOTE:

- Reading in which marked as Peak means measurements by using are Peak Mode with instrument setting in RBW= 1 MHz, VBW= 1 MHz, Swp. Time = Auto.
Reading in which marked as AV means measurements by using are Average Mode with instrument setting in RBW= 1 MHz, VBW= 10 Hz, Swp. Time = Auto.
- All readings are Peak Mode value unless otherwise stated AVG in column of Note. If the Peak Mode Measured value compliance with the Peak Limits and lower than AVG Limits, the EUT shall be deemed to meet both Peak & AVG Limits and then only Peak Mode was measured, but AVG Mode didn't perform.

9.5 DEVIATION FROM TEST STANDARD

No deviation

9.6 TEST SETUP LAYOUT






9.7 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 5.6 Unless otherwise a special operating condition is specified in the follows during the testing.



9.8 TEST RESULTS

EUT	Mini PCI Radio Module, 2x2 IEEE 802.11 b/g/n ,2.4 GHz	Model Name	RJ-1301
Temperature	26°C	Relative Humidity	60%
Test Voltage	AC 120V/60Hz		
Test Mode	IEEE 802.11b/2412 MHz		




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		2390.000	30.85	31.81	62.66	74.00	-11.34	peak	
2		2390.000	18.26	31.81	50.07	54.00	-3.93	AVG	
3	X	2414.750	80.27	31.91	112.18	74.00	38.18	peak	
4	*	2414.750	77.21	31.91	109.12	54.00	55.12	AVG	



EUT	Mini PCI Radio Module, 2x2 IEEE 802.11 b/g/n ,2.4 GHz	Model Name	RJ-1301
Temperature	26°C	Relative Humidity	60%
Test Voltage	AC 120V/60Hz		
Test Mode	IEEE 802.11b/2412 MHz		

Polarization: Vertical




No. Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1	4923.980	49.65	6.34	55.99	74.00	-18.01	peak	
2 *	4923.980	46.06	6.34	52.40	54.00	-1.60	AVG	
3	7385.940	42.64	13.05	55.69	74.00	-18.31	peak	
4	7385.940	31.36	13.05	44.41	54.00	-9.59	AVG	



EUT	Mini PCI Radio Module, 2x2 IEEE 802.11 b/g/n ,2.4 GHz	Model Name	RJ-1301
Temperature	26°C	Relative Humidity	60%
Test Voltage	AC 120V/60Hz		
Test Mode	IEEE 802.11b/2412 MHz		

Polarization: Horizontal




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		2390.000	25.88	31.81	57.69	74.00	-16.31	peak	
2		2390.000	11.94	31.81	43.75	54.00	-10.25	AVG	
3	X	2414.750	70.92	31.91	102.83	74.00	28.83	peak	
4	*	2414.750	68.56	31.91	100.47	54.00	46.47	AVG	



EUT	Mini PCI Radio Module, 2x2 IEEE 802.11 b/g/n ,2.4 GHz	Model Name	RJ-1301
Temperature	26°C	Relative Humidity	60%
Test Voltage	AC 120V/60Hz		
Test Mode	IEEE 802.11b/2412 MHz		

Polarization: Horizontal




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		4824.025	48.82	6.21	55.03	74.00	-18.97	peak	
2	*	4824.025	45.31	6.21	51.52	54.00	-2.48	AVG	
3		7236.000	43.57	12.49	56.06	74.00	-17.94	peak	
4		7236.000	33.11	12.49	45.60	54.00	-8.40	AVG	



EUT	Mini PCI Radio Module, 2x2 IEEE 802.11 b/g/n ,2.4 GHz	Model Name	RJ-1301
Temperature	26°C	Relative Humidity	60%
Test Voltage	AC 120V/60Hz		
Test Mode	IEEE 802.11b/2437 MHz		

Polarization: Vertical




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	X	2435.250	80.65	32.00	112.65	74.00	38.65	peak	
2	*	2435.250	78.40	32.00	110.40	54.00	56.40	AVG	



EUT	Mini PCI Radio Module, 2x2 IEEE 802.11 b/g/n ,2.4 GHz	Model Name	RJ-1301
Temperature	26°C	Relative Humidity	60%
Test Voltage	AC 120V/60Hz		
Test Mode	IEEE 802.11b/2437 MHz		

Polarization: Vertical




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		4874.050	46.69	6.28	52.97	74.00	-21.03	peak	
2	*	4874.050	44.37	6.28	50.65	54.00	-3.35	AVG	
3		7310.925	37.45	12.77	50.22	74.00	-23.78	peak	
4		7310.925	31.26	12.77	44.03	54.00	-9.97	AVG	



EUT	Mini PCI Radio Module, 2x2 IEEE 802.11 b/g/n ,2.4 GHz	Model Name	RJ-1301
Temperature	26°C	Relative Humidity	60%
Test Voltage	AC 120V/60Hz		
Test Mode	IEEE 802.11b/2437 MHz		

Polarization: Horizontal




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	X	2434.250	70.28	31.99	102.27	74.00	28.27	peak	
2	*	2434.250	68.09	31.99	100.08	54.00	46.08	AVG	



EUT	Mini PCI Radio Module, 2x2 IEEE 802.11 b/g/n ,2.4 GHz	Model Name	RJ-1301
Temperature	26°C	Relative Humidity	60%
Test Voltage	AC 120V/60Hz		
Test Mode	IEEE 802.11b/2437 MHz		

Polarization: Horizontal




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		4874.000	45.31	6.28	51.59	74.00	-22.41	peak	
2	*	4874.000	40.32	6.28	46.60	54.00	-7.40	AVG	
3		7311.050	37.81	12.77	50.58	74.00	-23.42	peak	
4		7311.050	31.23	12.77	44.00	54.00	-10.00	AVG	



EUT	Mini PCI Radio Module, 2x2 IEEE 802.11 b/g/n ,2.4 GHz	Model Name	RJ-1301
Temperature	26°C	Relative Humidity	60%
Test Voltage	AC 120V/60Hz		
Test Mode	IEEE 802.11b/2462 MHz		

Polarization: Vertical




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1	X	2463.750	76.07	32.11	108.18	74.00	34.18	peak	
2	*	2463.750	74.64	32.11	106.75	54.00	52.75	AVG	
3		2487.750	24.79	32.21	57.00	74.00	-17.00	peak	
4		2487.750	13.78	32.21	45.99	54.00	-8.01	AVG	



EUT	Mini PCI Radio Module, 2x2 IEEE 802.11 b/g/n ,2.4 GHz	Model Name	RJ-1301
Temperature	26°C	Relative Humidity	60%
Test Voltage	AC 120V/60Hz		
Test Mode	IEEE 802.11b/2462 MHz		

Polarization: Vertical




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		4924.000	47.59	6.34	53.93	74.00	-20.07	peak	
2	*	4924.000	45.51	6.34	51.85	54.00	-2.15	AVG	
3		7386.075	38.29	13.05	51.34	74.00	-22.66	peak	
4		7386.075	31.55	13.05	44.60	54.00	-9.40	AVG	



EUT	Mini PCI Radio Module, 2x2 IEEE 802.11 b/g/n ,2.4 GHz	Model Name	RJ-1301
Temperature	26°C	Relative Humidity	60%
Test Voltage	AC 120V/60Hz		
Test Mode	IEEE 802.11b/2462 MHz		


Polarization: Horizontal



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1	X	2463.750	63.95	32.11	96.06	74.00	22.06	peak	
2	*	2463.750	62.13	32.11	94.24	54.00	40.24	AVG	
3		2483.500	22.81	32.19	55.00	74.00	-19.00	peak	
4		2483.500	13.03	32.19	45.22	54.00	-8.78	AVG	



EUT	Mini PCI Radio Module, 2x2 IEEE 802.11 b/g/n ,2.4 GHz	Model Name	RJ-1301
Temperature	26°C	Relative Humidity	60%
Test Voltage	AC 120V/60Hz		
Test Mode	IEEE 802.11b/2462 MHz		




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		4924.025	44.99	6.34	51.33	74.00	-22.67	peak	
2	*	4924.025	41.92	6.34	48.26	54.00	-5.74	AVG	
3		7386.050	38.15	13.05	51.20	74.00	-22.80	peak	
4		7386.050	31.49	13.05	44.54	54.00	-9.46	AVG	



EUT	Mini PCI Radio Module, 2x2 IEEE 802.11 b/g/n ,2.4 GHz	Model Name	RJ-1301
Temperature	26°C	Relative Humidity	60%
Test Voltage	AC 120V/60Hz		
Test Mode	IEEE 802.11g/2412 MHz		


Polarization: Vertical



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		2390.000	36.74	31.81	68.55	74.00	-5.45	peak	
2		2390.000	20.94	31.81	52.75	54.00	-1.25	AVG	
3	X	2418.750	76.17	31.93	108.10	74.00	34.10	peak	
4	*	2418.750	69.20	31.93	101.13	54.00	47.13	AVG	



EUT	Mini PCI Radio Module, 2x2 IEEE 802.11 b/g/n ,2.4 GHz	Model Name	RJ-1301
Temperature	26°C	Relative Humidity	60%
Test Voltage	AC 120V/60Hz		
Test Mode	IEEE 802.11g/2412 MHz		




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		4824.000	41.17	6.21	47.38	74.00	-26.62	peak	
2		4824.000	33.74	6.21	39.95	54.00	-14.05	AVG	
3		7236.250	39.36	12.49	51.85	74.00	-22.15	peak	
4	*	7236.250	32.26	12.49	44.75	54.00	-9.25	AVG	



EUT	Mini PCI Radio Module, 2x2 IEEE 802.11 b/g/n ,2.4 GHz	Model Name	RJ-1301
Temperature	26°C	Relative Humidity	60%
Test Voltage	AC 120V/60Hz		
Test Mode	IEEE 802.11g/2412 MHz		

Polarization: Horizontal




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		2390.000	24.23	31.81	56.04	74.00	-17.96	peak	
2		2390.000	13.85	31.81	45.66	54.00	-8.34	AVG	
3	X	2419.500	63.78	31.93	95.71	74.00	21.71	peak	
4	*	2419.500	56.89	31.93	88.82	54.00	34.82	AVG	



EUT	Mini PCI Radio Module, 2x2 IEEE 802.11 b/g/n ,2.4 GHz	Model Name	RJ-1301
Temperature	26°C	Relative Humidity	60%
Test Voltage	AC 120V/60Hz		
Test Mode	IEEE 802.11g/2412 MHz		

Polarization: Horizontal




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		4823.850	41.34	6.21	47.55	74.00	-26.45	peak	
2		4823.850	33.03	6.21	39.24	54.00	-14.76	AVG	
3		7235.900	38.95	12.49	51.44	74.00	-22.56	peak	
4	*	7235.900	31.71	12.49	44.20	54.00	-9.80	AVG	



EUT	Mini PCI Radio Module, 2x2 IEEE 802.11 b/g/n ,2.4 GHz	Model Name	RJ-1301
Temperature	26°C	Relative Humidity	60%
Test Voltage	AC 120V/60Hz		
Test Mode	IEEE 802.11g/2437 MHz		

Polarization: Vertical




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1	X	2430.250	80.21	31.97	112.18	74.00	38.18	peak	
2	*	2430.250	71.79	31.97	103.76	54.00	49.76	AVG	



EUT	Mini PCI Radio Module, 2x2 IEEE 802.11 b/g/n ,2.4 GHz	Model Name	RJ-1301
Temperature	26°C	Relative Humidity	60%
Test Voltage	AC 120V/60Hz		
Test Mode	IEEE 802.11g/2437 MHz		

Polarization: Vertical




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		4873.750	38.22	6.28	44.50	74.00	-29.50	peak	
2		4873.750	31.15	6.28	37.43	54.00	-16.57	AVG	
3		7310.925	37.96	12.77	50.73	74.00	-23.27	peak	
4	*	7310.925	31.48	12.77	44.25	54.00	-9.75	AVG	



EUT	Mini PCI Radio Module, 2x2 IEEE 802.11 b/g/n ,2.4 GHz	Model Name	RJ-1301
Temperature	26°C	Relative Humidity	60%
Test Voltage	AC 120V/60Hz		
Test Mode	IEEE 802.11g/2437 MHz		

Polarization: Horizontal




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1	X	2430.250	69.87	31.97	101.84	74.00	27.84	peak	
2	*	2430.250	62.63	31.97	94.60	54.00	40.60	AVG	



EUT	Mini PCI Radio Module, 2x2 IEEE 802.11 b/g/n ,2.4 GHz	Model Name	RJ-1301
Temperature	26°C	Relative Humidity	60%
Test Voltage	AC 120V/60Hz		
Test Mode	IEEE 802.11g/2437 MHz		

Polarization: Horizontal




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		4874.250	37.51	6.28	43.79	74.00	-30.21	peak	
2		4874.250	31.07	6.28	37.35	54.00	-16.65	AVG	
3		7311.050	38.94	12.77	51.71	74.00	-22.29	peak	
4	*	7311.050	31.46	12.77	44.23	54.00	-9.77	AVG	



EUT	Mini PCI Radio Module, 2x2 IEEE 802.11 b/g/n ,2.4 GHz	Model Name	RJ-1301
Temperature	26°C	Relative Humidity	60%
Test Voltage	AC 120V/60Hz		
Test Mode	IEEE 802.11g/2462 MHz		

Polarization: Vertical




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1	X	2464.000	80.99	32.11	113.10	74.00	39.10	peak	
2	*	2464.000	72.59	32.11	104.70	54.00	50.70	AVG	
3		2483.500	32.12	32.19	64.31	74.00	-9.69	peak	
4		2483.500	17.51	32.19	49.70	54.00	-4.30	AVG	



EUT	Mini PCI Radio Module, 2x2 IEEE 802.11 b/g/n ,2.4 GHz	Model Name	RJ-1301
Temperature	26°C	Relative Humidity	60%
Test Voltage	AC 120V/60Hz		
Test Mode	IEEE 802.11g/2462 MHz		

Polarization: Vertical




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		4925.125	43.82	6.35	50.17	74.00	-23.83	peak	
2		4925.125	35.87	6.35	42.22	54.00	-11.78	AVG	
3		7385.750	42.25	13.05	55.30	74.00	-18.70	peak	
4	*	7385.750	31.78	13.05	44.83	54.00	-9.17	AVG	



EUT	Mini PCI Radio Module, 2x2 IEEE 802.11 b/g/n ,2.4 GHz	Model Name	RJ-1301
Temperature	26°C	Relative Humidity	60%
Test Voltage	AC 120V/60Hz		
Test Mode	IEEE 802.11g/2462 MHz		

Polarization: Horizontal




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1	X	2464.250	67.44	32.11	99.55	74.00	25.55	peak	
2	*	2464.250	60.24	32.11	92.35	54.00	38.35	AVG	
3		2483.500	24.42	32.19	56.61	74.00	-17.39	peak	
4		2483.500	13.61	32.19	45.80	54.00	-8.20	AVG	



EUT	Mini PCI Radio Module, 2x2 IEEE 802.11 b/g/n ,2.4 GHz	Model Name	RJ-1301
Temperature	26°C	Relative Humidity	60%
Test Voltage	AC 120V/60Hz		
Test Mode	IEEE 802.11g/2462 MHz		

Polarization: Horizontal




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		4925.000	42.45	6.35	48.80	74.00	-25.20	peak	
2		4925.000	35.50	6.35	41.85	54.00	-12.15	AVG	
3		7385.875	39.88	13.05	52.93	74.00	-21.07	peak	
4	*	7385.875	31.79	13.05	44.84	54.00	-9.16	AVG	



EUT	Mini PCI Radio Module, 2x2 IEEE 802.11 b/g/n ,2.4 GHz	Model Name	RJ-1301
Temperature	26°C	Relative Humidity	60%
Test Voltage	AC 120V/60Hz		
Test Mode	IEEE 802.11n (20 MHz)/2412 MHz-1TX		

Polarization: Vertical




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		2390.000	32.88	31.81	64.69	74.00	-9.31	peak	
2		2390.000	20.22	31.81	52.03	54.00	-1.97	AVG	
3	X	2418.500	74.48	31.93	106.41	74.00	32.41	peak	
4	*	2418.500	67.44	31.93	99.37	54.00	45.37	AVG	



EUT	Mini PCI Radio Module, 2x2 IEEE 802.11 b/g/n ,2.4 GHz	Model Name	RJ-1301
Temperature	26°C	Relative Humidity	60%
Test Voltage	AC 120V/60Hz		
Test Mode	IEEE 802.11n (20 MHz)/2412 MHz-1TX		

Polarization: Vertical




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		4824.000	43.61	6.21	49.82	74.00	-24.18	peak	
2		4824.000	33.32	6.21	39.53	54.00	-14.47	AVG	
3		7236.000	41.03	12.49	53.52	74.00	-20.48	peak	
4	*	7236.000	33.87	12.49	46.36	54.00	-7.64	AVG	



EUT	Mini PCI Radio Module, 2x2 IEEE 802.11 b/g/n ,2.4 GHz	Model Name	RJ-1301
Temperature	26°C	Relative Humidity	60%
Test Voltage	AC 120V/60Hz		
Test Mode	IEEE 802.11n (20 MHz)/2412 MHz-1TX		

Polarization: Horizontal




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		2390.000	24.25	31.81	56.06	74.00	-17.94	peak	
2		2390.000	15.46	31.81	47.27	54.00	-6.73	AVG	
3	X	2419.750	63.53	31.93	95.46	74.00	21.46	peak	
4	*	2419.750	56.44	31.93	88.37	54.00	34.37	AVG	



EUT	Mini PCI Radio Module, 2x2 IEEE 802.11 b/g/n ,2.4 GHz	Model Name	RJ-1301
Temperature	26°C	Relative Humidity	60%
Test Voltage	AC 120V/60Hz		
Test Mode	IEEE 802.11n (20 MHz)/2412 MHz-1TX		

Polarization: Horizontal




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		4824.000	41.57	6.21	47.78	74.00	-26.22	peak	
2		4824.000	33.08	6.21	39.29	54.00	-14.71	AVG	
3		7236.000	42.39	12.49	54.88	74.00	-19.12	peak	
4	*	7236.000	33.87	12.49	46.36	54.00	-7.64	AVG	



EUT	Mini PCI Radio Module, 2x2 IEEE 802.11 b/g/n ,2.4 GHz	Model Name	RJ-1301
Temperature	26°C	Relative Humidity	60%
Test Voltage	AC 120V/60Hz		
Test Mode	IEEE 802.11n (20 MHz)/2437 MHz-1TX		


Polarization: Vertical



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		2390.000	16.02	31.81	47.83	54.00	-6.17	AVG	
2	X	2429.500	82.86	31.97	114.83	74.00	40.83	peak	
3	*	2429.500	74.38	31.97	106.35	54.00	52.35	AVG	
4		2483.500	14.85	32.19	47.04	54.00	-6.96	AVG	



EUT	Mini PCI Radio Module, 2x2 IEEE 802.11 b/g/n ,2.4 GHz	Model Name	RJ-1301
Temperature	26°C	Relative Humidity	60%
Test Voltage	AC 120V/60Hz		
Test Mode	IEEE 802.11n (20 MHz)/2437 MHz-1TX		




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		4874.000	43.42	6.28	49.70	74.00	-24.30	peak	
2		4874.000	33.13	6.28	39.41	54.00	-14.59	AVG	
3		7311.250	41.69	12.77	54.46	74.00	-19.54	peak	
4	*	7311.250	33.02	12.77	45.79	54.00	-8.21	AVG	



EUT	Mini PCI Radio Module, 2x2 IEEE 802.11 b/g/n ,2.4 GHz	Model Name	RJ-1301
Temperature	26°C	Relative Humidity	60%
Test Voltage	AC 120V/60Hz		
Test Mode	IEEE 802.11n (20 MHz)/2437 MHz-1TX		

Polarization: Horizontal




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1	X	2430.750	70.31	31.98	102.29	74.00	28.29	peak	
2	*	2430.750	63.70	31.98	95.68	54.00	41.68	AVG	



EUT	Mini PCI Radio Module, 2x2 IEEE 802.11 b/g/n ,2.4 GHz	Model Name	RJ-1301
Temperature	26°C	Relative Humidity	60%
Test Voltage	AC 120V/60Hz		
Test Mode	IEEE 802.11n (20 MHz)/2437 MHz-1TX		


Polarization: Horizontal



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		4873.750	41.56	6.28	47.84	74.00	-26.16	peak	
2		4873.750	32.93	6.28	39.21	54.00	-14.79	AVG	
3		7310.250	42.15	12.76	54.91	74.00	-19.09	peak	
4	*	7310.250	33.04	12.76	45.80	54.00	-8.20	AVG	



EUT	Mini PCI Radio Module, 2x2 IEEE 802.11 b/g/n ,2.4 GHz	Model Name	RJ-1301
Temperature	26°C	Relative Humidity	60%
Test Voltage	AC 120V/60Hz		
Test Mode	IEEE 802.11n (20 MHz)/2462 MHz-1TX		




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1	X	2463.250	79.84	32.11	111.95	74.00	37.95	peak	
2	*	2463.250	72.17	32.11	104.28	54.00	50.28	AVG	
3		2483.500	29.86	32.19	62.05	74.00	-11.95	peak	
4		2483.500	18.42	32.19	50.61	54.00	-3.39	AVG	



EUT	Mini PCI Radio Module, 2x2 IEEE 802.11 b/g/n ,2.4 GHz	Model Name	RJ-1301
Temperature	26°C	Relative Humidity	60%
Test Voltage	AC 120V/60Hz		
Test Mode	IEEE 802.11n (20 MHz)/2462 MHz-1TX		

Polarization: Vertical




No. Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1	4925.000	42.78	6.35	49.13	74.00	-24.87	peak	
2	4925.000	35.46	6.35	41.81	54.00	-12.19	AVG	
3	7385.500	41.95	13.05	55.00	74.00	-19.00	peak	
4 *	7385.500	33.81	13.05	46.86	54.00	-7.14	AVG	



EUT	Mini PCI Radio Module, 2x2 IEEE 802.11 b/g/n ,2.4 GHz	Model Name	RJ-1301
Temperature	26°C	Relative Humidity	60%
Test Voltage	AC 120V/60Hz		
Test Mode	IEEE 802.11n (20 MHz)/2462 MHz-1TX		

Polarization: Horizontal




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1	X	2463.250	69.88	32.11	101.99	74.00	27.99	peak	
2	*	2463.250	62.19	32.11	94.30	54.00	40.30	AVG	
3		2483.500	24.62	32.19	56.81	74.00	-17.19	peak	
4		2483.500	15.32	32.19	47.51	54.00	-6.49	AVG	



EUT	Mini PCI Radio Module, 2x2 IEEE 802.11 b/g/n ,2.4 GHz	Model Name	RJ-1301
Temperature	26°C	Relative Humidity	60%
Test Voltage	AC 120V/60Hz		
Test Mode	IEEE 802.11n (20 MHz)/2462 MHz-1TX		

Polarization: Horizontal




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		4923.500	42.33	6.34	48.67	74.00	-25.33	peak	
2		4923.500	34.10	6.34	40.44	54.00	-13.56	AVG	
3		7385.500	41.14	13.05	54.19	74.00	-19.81	peak	
4	*	7385.500	33.88	13.05	46.93	54.00	-7.07	AVG	



EUT	Mini PCI Radio Module, 2x2 IEEE 802.11 b/g/n ,2.4 GHz	Model Name	RJ-1301
Temperature	26°C	Relative Humidity	60%
Test Voltage	AC 120V/60Hz		
Test Mode	IEEE 802.11n (40 MHz)/2422 MHz-1TX		

Polarization: Vertical




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		2390.000	32.85	31.81	64.66	74.00	-9.34	peak	
2		2390.000	20.06	31.81	51.87	54.00	-2.13	AVG	
3	X	2427.000	70.42	31.96	102.38	74.00	28.38	peak	
4	*	2427.000	63.38	31.96	95.34	54.00	41.34	AVG	



EUT	Mini PCI Radio Module, 2x2 IEEE 802.11 b/g/n ,2.4 GHz	Model Name	RJ-1301
Temperature	26°C	Relative Humidity	60%
Test Voltage	AC 120V/60Hz		
Test Mode	IEEE 802.11n (40 MHz)/2422 MHz-1TX		

Polarization: Vertical




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		4844.000	39.56	6.24	45.80	74.00	-28.20	peak	
2		4844.000	33.35	6.24	39.59	54.00	-14.41	AVG	
3		7266.000	41.13	12.61	53.74	74.00	-20.26	peak	
4	*	7266.000	34.51	12.61	47.12	54.00	-6.88	AVG	



EUT	Mini PCI Radio Module, 2x2 IEEE 802.11 b/g/n ,2.4 GHz	Model Name	RJ-1301
Temperature	26°C	Relative Humidity	60%
Test Voltage	AC 120V/60Hz		
Test Mode	IEEE 802.11n (40 MHz)/2422 MHz-1TX		

Polarization: Horizontal




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		2390.000	25.48	31.81	57.29	74.00	-16.71	peak	
2		2390.000	15.46	31.81	47.27	54.00	-6.73	AVG	
3	X	2427.000	60.55	31.96	92.51	74.00	18.51	peak	
4	*	2427.000	52.84	31.96	84.80	54.00	30.80	AVG	



EUT	Mini PCI Radio Module, 2x2 IEEE 802.11 b/g/n ,2.4 GHz	Model Name	RJ-1301
Temperature	26°C	Relative Humidity	60%
Test Voltage	AC 120V/60Hz		
Test Mode	IEEE 802.11n (40 MHz)/2422 MHz-1TX		

Polarization: Horizontal




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		4844.000	38.84	6.24	45.08	74.00	-28.92	peak	
2		4844.000	33.29	6.24	39.53	54.00	-14.47	AVG	
3		7266.000	43.41	12.61	56.02	74.00	-17.98	peak	
4	*	7266.000	34.16	12.61	46.77	54.00	-7.23	AVG	



EUT	Mini PCI Radio Module, 2x2 IEEE 802.11 b/g/n ,2.4 GHz	Model Name	RJ-1301
Temperature	26°C	Relative Humidity	60%
Test Voltage	AC 120V/60Hz		
Test Mode	IEEE 802.11n (40 MHz)/2437 MHz-1TX		

Polarization: Vertical




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		2390.000	31.90	31.81	63.71	74.00	-10.29	peak	
2		2390.000	19.11	31.81	50.92	54.00	-3.08	AVG	
3	X	2428.000	75.96	31.96	107.92	74.00	33.92	peak	
4	*	2428.000	68.23	31.96	100.19	54.00	46.19	AVG	



EUT	Mini PCI Radio Module, 2x2 IEEE 802.11 b/g/n ,2.4 GHz	Model Name	RJ-1301
Temperature	26°C	Relative Humidity	60%
Test Voltage	AC 120V/60Hz		
Test Mode	IEEE 802.11n (40 MHz)/2437 MHz-1TX		

Polarization: Vertical




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		4874.000	39.85	6.28	46.13	74.00	-27.87	peak	
2		4874.000	33.28	6.28	39.56	54.00	-14.44	AVG	
3		7311.000	40.64	12.77	53.41	74.00	-20.59	peak	
4	*	7311.000	34.29	12.77	47.06	54.00	-6.94	AVG	



EUT	Mini PCI Radio Module, 2x2 IEEE 802.11 b/g/n ,2.4 GHz	Model Name	RJ-1301
Temperature	26°C	Relative Humidity	60%
Test Voltage	AC 120V/60Hz		
Test Mode	IEEE 802.11n (40 MHz)/2437 MHz-1TX		

Polarization: Horizontal




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1	X	2428.000	64.24	31.96	96.20	74.00	22.20	peak	
2	*	2428.000	57.22	31.96	89.18	54.00	35.18	AVG	



EUT	Mini PCI Radio Module, 2x2 IEEE 802.11 b/g/n ,2.4 GHz	Model Name	RJ-1301
Temperature	26°C	Relative Humidity	60%
Test Voltage	AC 120V/60Hz		
Test Mode	IEEE 802.11n (40 MHz)/2437 MHz-1TX		

Polarization: Horizontal




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		4874.000	38.76	6.28	45.04	74.00	-28.96	peak	
2		4874.000	33.39	6.28	39.67	54.00	-14.33	AVG	
3		7311.000	43.52	12.77	56.29	74.00	-17.71	peak	
4	*	7311.000	34.64	12.77	47.41	54.00	-6.59	AVG	



EUT	Mini PCI Radio Module, 2x2 IEEE 802.11 b/g/n ,2.4 GHz	Model Name	RJ-1301
Temperature	26°C	Relative Humidity	60%
Test Voltage	AC 120V/60Hz		
Test Mode	IEEE 802.11n (40 MHz)/2452 MHz-1TX		

Polarization: Vertical




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1	X	2434.500	74.98	31.99	106.97	74.00	32.97	peak	
2	*	2434.500	67.84	31.99	99.83	54.00	45.83	AVG	
3		2483.500	39.68	32.19	71.87	74.00	-2.13	peak	
4		2483.500	20.15	32.19	52.34	54.00	-1.66	AVG	



EUT	Mini PCI Radio Module, 2x2 IEEE 802.11 b/g/n ,2.4 GHz	Model Name	RJ-1301
Temperature	26°C	Relative Humidity	60%
Test Voltage	AC 120V/60Hz		
Test Mode	IEEE 802.11n (40 MHz)/2452 MHz-1TX		

Polarization: Vertical




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		4904.000	39.28	6.32	45.60	74.00	-28.40	peak	
2		4904.000	33.39	6.32	39.71	54.00	-14.29	AVG	
3		7356.000	40.87	12.93	53.80	74.00	-20.20	peak	
4	*	7356.000	34.64	12.93	47.57	54.00	-6.43	AVG	



EUT	Mini PCI Radio Module, 2x2 IEEE 802.11 b/g/n ,2.4 GHz	Model Name	RJ-1301
Temperature	26°C	Relative Humidity	60%
Test Voltage	AC 120V/60Hz		
Test Mode	IEEE 802.11n (40 MHz)/2452 MHz-1TX		

Polarization: Horizontal




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1	X	2434.500	66.50	31.99	98.49	74.00	24.49	peak	
2	*	2434.500	57.34	31.99	89.33	54.00	35.33	AVG	
3		2483.500	30.20	32.19	62.39	74.00	-11.61	peak	
4		2483.500	15.61	32.19	47.80	54.00	-6.20	AVG	



EUT	Mini PCI Radio Module, 2x2 IEEE 802.11 b/g/n ,2.4 GHz	Model Name	RJ-1301
Temperature	26°C	Relative Humidity	60%
Test Voltage	AC 120V/60Hz		
Test Mode	IEEE 802.11n (40 MHz)/2452 MHz-1TX		

Polarization: Horizontal




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		4904.000	38.36	6.32	44.68	74.00	-29.32	peak	
2		4904.000	33.27	6.32	39.59	54.00	-14.41	AVG	
3		7356.000	43.42	12.93	56.35	74.00	-17.65	peak	
4	*	7356.000	34.83	12.93	47.76	54.00	-6.24	AVG	



EUT	Mini PCI Radio Module, 2x2 IEEE 802.11 b/g/n ,2.4 GHz	Model Name	RJ-1301
Temperature	26°C	Relative Humidity	60%
Test Voltage	AC 120V/60Hz		
Test Mode	IEEE 802.11n (20 MHz)/2412 MHz-2TX		

Polarization: Vertical




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		2390.000	31.83	31.81	63.64	74.00	-10.36	peak	
2		2390.000	20.60	31.81	52.41	54.00	-1.59	AVG	
3	X	2419.500	79.07	31.93	111.00	74.00	37.00	peak	
4	*	2419.500	69.44	31.93	101.37	54.00	47.37	AVG	



EUT	Mini PCI Radio Module, 2x2 IEEE 802.11 b/g/n ,2.4 GHz	Model Name	RJ-1301
Temperature	26°C	Relative Humidity	60%
Test Voltage	AC 120V/60Hz		
Test Mode	IEEE 802.11n (20 MHz)/2412 MHz-2TX		

Polarization: Vertical




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		4824.000	36.25	6.21	42.46	74.00	-31.54	peak	
2		4824.000	27.63	6.21	33.84	54.00	-20.16	AVG	
3		7236.000	34.18	12.49	46.67	74.00	-27.33	peak	
4	*	7236.000	24.66	12.49	37.15	54.00	-16.85	AVG	



EUT	Mini PCI Radio Module, 2x2 IEEE 802.11 b/g/n ,2.4 GHz	Model Name	RJ-1301
Temperature	26°C	Relative Humidity	60%
Test Voltage	AC 120V/60Hz		
Test Mode	IEEE 802.11n (20 MHz)/2412 MHz-2TX		

Polarization: Horizontal




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		2390.000	23.59	31.81	55.40	74.00	-18.60	peak	
2		2390.000	13.95	31.81	45.76	54.00	-8.24	AVG	
3	X	2417.750	66.23	31.92	98.15	74.00	24.15	peak	
4	*	2417.750	56.60	31.92	88.52	54.00	34.52	AVG	



EUT	Mini PCI Radio Module, 2x2 IEEE 802.11 b/g/n ,2.4 GHz	Model Name	RJ-1301
Temperature	26°C	Relative Humidity	60%
Test Voltage	AC 120V/60Hz		
Test Mode	IEEE 802.11n (20 MHz)/2412 MHz-2TX		

Polarization: Horizontal




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		4824.125	37.34	6.21	43.55	74.00	-30.45	peak	
2		4824.125	31.19	6.21	37.40	54.00	-16.60	AVG	
3		7236.250	39.68	12.49	52.17	74.00	-21.83	peak	
4	*	7236.250	31.53	12.49	44.02	54.00	-9.98	AVG	



EUT	Mini PCI Radio Module, 2x2 IEEE 802.11 b/g/n ,2.4 GHz	Model Name	RJ-1301
Temperature	26°C	Relative Humidity	60%
Test Voltage	AC 120V/60Hz		
Test Mode	IEEE 802.11n (20 MHz)/2437 MHz-2TX		

Polarization: Vertical




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1	X	2431.750	81.82	31.99	113.81	74.00	39.81	peak	
2	*	2431.750	72.06	31.99	104.05	54.00	50.05	AVG	



EUT	Mini PCI Radio Module, 2x2 IEEE 802.11 b/g/n ,2.4 GHz	Model Name	RJ-1301
Temperature	26°C	Relative Humidity	60%
Test Voltage	AC 120V/60Hz		
Test Mode	IEEE 802.11n (20 MHz)/2437 MHz-2TX		

Polarization: Vertical




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		4874.000	36.23	6.28	42.51	74.00	-31.49	peak	
2		4874.000	27.18	6.28	33.46	54.00	-20.54	AVG	
3		7311.000	33.52	12.77	46.29	74.00	-27.71	peak	
4	*	7311.000	24.16	12.77	36.93	54.00	-17.07	AVG	



EUT	Mini PCI Radio Module, 2x2 IEEE 802.11 b/g/n ,2.4 GHz	Model Name	RJ-1301
Temperature	26°C	Relative Humidity	60%
Test Voltage	AC 120V/60Hz		
Test Mode	IEEE 802.11n (20 MHz)/2437 MHz-2TX		

Polarization: Horizontal




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1	X	2432.500	68.02	31.99	100.01	74.00	26.01	peak	
2	*	2432.500	59.05	31.99	91.04	54.00	37.04	AVG	



EUT	Mini PCI Radio Module, 2x2 IEEE 802.11 b/g/n ,2.4 GHz	Model Name	RJ-1301
Temperature	26°C	Relative Humidity	60%
Test Voltage	AC 120V/60Hz		
Test Mode	IEEE 802.11n (20 MHz)/2437 MHz-2TX		

Polarization: Horizontal




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		4874.000	37.23	6.28	43.51	74.00	-30.49	peak	
2		4874.000	31.18	6.28	37.46	54.00	-16.54	AVG	
3		7311.000	39.39	12.77	52.16	74.00	-21.84	peak	
4	*	7311.000	31.20	12.77	43.97	54.00	-10.03	AVG	



EUT	Mini PCI Radio Module, 2x2 IEEE 802.11 b/g/n ,2.4 GHz	Model Name	RJ-1301
Temperature	26°C	Relative Humidity	60%
Test Voltage	AC 120V/60Hz		
Test Mode	IEEE 802.11n (20 MHz)/2462 MHz-2TX		

Polarization: Vertical




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1	X	2460.750	80.81	32.10	112.91	74.00	38.91	peak	
2	*	2460.750	71.53	32.10	103.63	54.00	49.63	AVG	
3		2483.500	25.69	32.19	57.88	74.00	-16.12	peak	
4		2483.500	15.52	32.19	47.71	54.00	-6.29	AVG	



EUT	Mini PCI Radio Module, 2x2 IEEE 802.11 b/g/n ,2.4 GHz	Model Name	RJ-1301
Temperature	26°C	Relative Humidity	60%
Test Voltage	AC 120V/60Hz		
Test Mode	IEEE 802.11n (20 MHz)/2462 MHz-2TX		

Polarization: Vertical




No. Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure-ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1	4924.000	36.13	6.34	42.47	74.00	-31.53	peak	
2	4924.000	27.25	6.34	33.59	54.00	-20.41	AVG	
3	7386.000	33.39	13.05	46.44	74.00	-27.56	peak	
4 *	7386.000	23.16	13.05	36.21	54.00	-17.79	AVG	



EUT	Mini PCI Radio Module, 2x2 IEEE 802.11 b/g/n ,2.4 GHz	Model Name	RJ-1301
Temperature	26°C	Relative Humidity	60%
Test Voltage	AC 120V/60Hz		
Test Mode	IEEE 802.11n (20 MHz)/2462 MHz-2TX		

Polarization: Horizontal




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1	X	2460.750	68.26	32.10	100.36	74.00	26.36	peak	
2	*	2460.750	59.26	32.10	91.36	54.00	37.36	AVG	
3		2483.500	23.54	32.19	55.73	74.00	-18.27	peak	
4		2483.500	13.10	32.19	45.29	54.00	-8.71	AVG	



EUT	Mini PCI Radio Module, 2x2 IEEE 802.11 b/g/n ,2.4 GHz	Model Name	RJ-1301
Temperature	26°C	Relative Humidity	60%
Test Voltage	AC 120V/60Hz		
Test Mode	IEEE 802.11n (20 MHz)/2462 MHz-2TX		


Polarization: Horizontal



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		4924.000	37.23	6.34	43.57	74.00	-30.43	peak	
2		4924.000	31.64	6.34	37.98	54.00	-16.02	AVG	
3		7386.000	39.52	13.05	52.57	74.00	-21.43	peak	
4	*	7386.000	30.18	13.05	43.23	54.00	-10.77	AVG	



EUT	Mini PCI Radio Module, 2x2 IEEE 802.11 b/g/n ,2.4 GHz	Model Name	RJ-1301
Temperature	26°C	Relative Humidity	60%
Test Voltage	AC 120V/60Hz		
Test Mode	IEEE 802.11n (40 MHz)/2422 MHz-2TX		




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		2390.000	32.29	31.81	64.10	74.00	-9.90	peak	
2		2390.000	20.44	31.81	52.25	54.00	-1.75	AVG	
3	X	2428.000	72.47	31.96	104.43	74.00	30.43	peak	
4	*	2428.000	63.80	31.96	95.76	54.00	41.76	AVG	



EUT	Mini PCI Radio Module, 2x2 IEEE 802.11 b/g/n ,2.4 GHz	Model Name	RJ-1301
Temperature	26°C	Relative Humidity	60%
Test Voltage	AC 120V/60Hz		
Test Mode	IEEE 802.11n (40 MHz)/2422 MHz-2TX		

Polarization: Vertical




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		4844.000	41.72	6.24	47.96	74.00	-26.04	peak	
2		4844.000	31.36	6.24	37.60	54.00	-16.40	AVG	
3		7265.500	38.80	12.61	51.41	74.00	-22.59	peak	
4	*	7265.500	30.86	12.61	43.47	54.00	-10.53	AVG	



EUT	Mini PCI Radio Module, 2x2 IEEE 802.11 b/g/n ,2.4 GHz	Model Name	RJ-1301
Temperature	26°C	Relative Humidity	60%
Test Voltage	AC 120V/60Hz		
Test Mode	IEEE 802.11n (40 MHz)/2422 MHz-2TX		

Polarization: Horizontal




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		2390.000	24.15	31.81	55.96	74.00	-18.04	peak	
2		2390.000	15.33	31.81	47.14	54.00	-6.86	AVG	
3	X	2427.000	61.08	31.96	93.04	74.00	19.04	peak	
4	*	2427.000	51.55	31.96	83.51	54.00	29.51	AVG	



EUT	Mini PCI Radio Module, 2x2 IEEE 802.11 b/g/n ,2.4 GHz	Model Name	RJ-1301
Temperature	26°C	Relative Humidity	60%
Test Voltage	AC 120V/60Hz		
Test Mode	IEEE 802.11n (40 MHz)/2422 MHz-2TX		

Polarization: Horizontal




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		4845.000	43.70	6.24	49.94	74.00	-24.06	peak	
2		4845.000	31.20	6.24	37.44	54.00	-16.56	AVG	
3		7267.000	38.99	12.61	51.60	74.00	-22.40	peak	
4	*	7267.000	30.77	12.61	43.38	54.00	-10.62	AVG	



EUT	Mini PCI Radio Module, 2x2 IEEE 802.11 b/g/n ,2.4 GHz	Model Name	RJ-1301
Temperature	26°C	Relative Humidity	60%
Test Voltage	AC 120V/60Hz		
Test Mode	IEEE 802.11n (40 MHz)/2437 MHz-2TX		

Polarization: Vertical




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	X	2428.500	79.96	31.97	111.93	74.00	37.93	peak	
2	*	2428.500	67.05	31.97	99.02	54.00	45.02	AVG	



EUT	Mini PCI Radio Module, 2x2 IEEE 802.11 b/g/n ,2.4 GHz	Model Name	RJ-1301
Temperature	26°C	Relative Humidity	60%
Test Voltage	AC 120V/60Hz		
Test Mode	IEEE 802.11n (40 MHz)/2437 MHz-2TX		

Polarization: Vertical




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		4874.000	41.52	6.28	47.80	74.00	-26.20	peak	
2		4874.000	31.13	6.28	37.41	54.00	-16.59	AVG	
3		7311.000	38.57	12.77	51.34	74.00	-22.66	peak	
4	*	7311.000	30.51	12.77	43.28	54.00	-10.72	AVG	



EUT	Mini PCI Radio Module, 2x2 IEEE 802.11 b/g/n ,2.4 GHz	Model Name	RJ-1301
Temperature	26°C	Relative Humidity	60%
Test Voltage	AC 120V/60Hz		
Test Mode	IEEE 802.11n (40 MHz)/2437 MHz-2TX		

Polarization: Horizontal




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1	X	2428.000	65.75	31.96	97.71	74.00	23.71	peak	
2	*	2428.000	54.25	31.96	86.21	54.00	32.21	AVG	



EUT	Mini PCI Radio Module, 2x2 IEEE 802.11 b/g/n ,2.4 GHz	Model Name	RJ-1301
Temperature	26°C	Relative Humidity	60%
Test Voltage	AC 120V/60Hz		
Test Mode	IEEE 802.11n (40 MHz)/2437 MHz-2TX		

Polarization: Horizontal




No. Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1	4874.000	43.66	6.28	49.94	74.00	-24.06	peak	
2	4874.000	31.16	6.28	37.44	54.00	-16.56	AVG	
3	7311.000	38.83	12.77	51.60	74.00	-22.40	peak	
4 *	7311.000	30.61	12.77	43.38	54.00	-10.62	AVG	



EUT	Mini PCI Radio Module, 2x2 IEEE 802.11 b/g/n ,2.4 GHz	Model Name	RJ-1301
Temperature	26°C	Relative Humidity	60%
Test Voltage	AC 120V/60Hz		
Test Mode	IEEE 802.11n (40 MHz)/2452 MHz-2TX		

Polarization: Vertical




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1	X	2434.500	76.20	31.99	108.19	74.00	34.19	peak	
2	*	2434.500	66.01	31.99	98.00	54.00	44.00	AVG	
3		2483.500	29.78	32.19	61.97	74.00	-12.03	peak	
4		2483.500	17.76	32.19	49.95	54.00	-4.05	AVG	



EUT	Mini PCI Radio Module, 2x2 IEEE 802.11 b/g/n ,2.4 GHz	Model Name	RJ-1301
Temperature	26°C	Relative Humidity	60%
Test Voltage	AC 120V/60Hz		
Test Mode	IEEE 802.11n (40 MHz)/2452 MHz-2TX		

Polarization: Vertical




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		4904.000	39.76	6.32	46.08	74.00	-27.92	peak	
2		4904.000	33.17	6.32	39.49	54.00	-14.51	AVG	
3		7357.000	40.92	12.94	53.86	74.00	-20.14	peak	
4	*	7357.000	33.58	12.94	46.52	54.00	-7.48	AVG	



EUT	Mini PCI Radio Module, 2x2 IEEE 802.11 b/g/n ,2.4 GHz	Model Name	RJ-1301
Temperature	26°C	Relative Humidity	60%
Test Voltage	AC 120V/60Hz		
Test Mode	IEEE 802.11n (40 MHz)/2452 MHz-2TX		

Polarization: Horizontal




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1	X	2434.500	62.55	31.99	94.54	74.00	20.54	peak	
2	*	2434.500	52.03	31.99	84.02	54.00	30.02	AVG	
3		2483.500	23.91	32.19	56.10	74.00	-17.90	peak	
4		2483.500	13.61	32.19	45.80	54.00	-8.20	AVG	



EUT	Mini PCI Radio Module, 2x2 IEEE 802.11 b/g/n ,2.4 GHz	Model Name	RJ-1301
Temperature	26°C	Relative Humidity	60%
Test Voltage	AC 120V/60Hz		
Test Mode	IEEE 802.11n (40 MHz)/2452 MHz-2TX		

Polarization: Horizontal




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		4902.500	38.82	6.31	45.13	74.00	-28.87	peak	
2		4902.500	33.06	6.31	39.37	54.00	-14.63	AVG	
3		7355.000	43.32	12.93	56.25	74.00	-17.75	peak	
4	*	7355.000	33.63	12.93	46.56	54.00	-7.44	AVG	



9.9 TEST RESULTS (RESTRICTED BANDS)

EUT	Mini PCI Radio Module, 2x2 IEEE 802.11 b/g/n ,2.4 GHz	Model Name	RJ-1301
Temperature	24°C	Relative Humidity	46%
Test Voltage	AC 120V/60Hz		
Test Mode	IEEE 802.11b		
NOTE	The transmitter was setup to transmit at the lowest channel and the field strength was measured at 2310-2390 MHz.		

Polarization: Vertical




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		2390.000	30.85	31.81	62.66	74.00	-11.34	peak	
2	*	2390.000	18.26	31.81	50.07	54.00	-3.93	AVG	



EUT	Mini PCI Radio Module, 2x2 IEEE 802.11 b/g/n ,2.4 GHz	Model Name	RJ-1301
Temperature	24°C	Relative Humidity	46%
Test Voltage	AC 120V/60Hz		
Test Mode	IEEE 802.11b		
NOTE	The transmitter was setup to transmit at the lowest channel and the field strength was measured at 2310-2390 MHz.		

Polarization: Horizontal




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		2390.000	25.88	31.81	57.69	74.00	-16.31	peak	
2	*	2390.000	11.94	31.81	43.75	54.00	-10.25	AVG	



EUT	Mini PCI Radio Module, 2x2 IEEE 802.11 b/g/n ,2.4 GHz	Model Name	RJ-1301
Temperature	24°C	Relative Humidity	46%
Test Voltage	AC 120V/60Hz		
Test Mode	IEEE 802.11b		
NOTE	The transmitter was setup to transmit at the highest channel and the field strength was measured at 2483.5-2500 MHz.		

Polarization: Vertical




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		2487.750	24.79	32.21	57.00	74.00	-17.00	peak	
2	*	2487.750	13.78	32.21	45.99	54.00	-8.01	AVG	



EUT	Mini PCI Radio Module, 2x2 IEEE 802.11 b/g/n ,2.4 GHz	Model Name	RJ-1301
Temperature	24°C	Relative Humidity	46%
Test Voltage	AC 120V/60Hz		
Test Mode	IEEE 802.11b		
NOTE	The transmitter was setup to transmit at the highest channel and the field strength was measured at 2483.5-2500 MHz.		

Polarization: Horizontal




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		2483.500	22.81	32.19	55.00	74.00	-19.00	peak	
2	*	2483.500	13.03	32.19	45.22	54.00	-8.78	AVG	



EUT	Mini PCI Radio Module, 2x2 IEEE 802.11 b/g/n ,2.4 GHz	Model Name	RJ-1301
Temperature	24°C	Relative Humidity	46%
Test Voltage	AC 120V/60Hz		
Test Mode	IEEE 802.11g		
NOTE	The transmitter was setup to transmit at the lowest channel and the field strength was measured at 2310-2390 MHz.		

Polarization: Vertical




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		2390.000	36.74	31.81	68.55	74.00	-5.45	peak	
2	*	2390.000	20.94	31.81	52.75	54.00	-1.25	AVG	



EUT	Mini PCI Radio Module, 2x2 IEEE 802.11 b/g/n ,2.4 GHz	Model Name	RJ-1301
Temperature	24°C	Relative Humidity	46%
Test Voltage	AC 120V/60Hz		
Test Mode	IEEE 802.11g		
NOTE	The transmitter was setup to transmit at the lowest channel and the field strength was measured at 2310-2390 MHz.		

Polarization: Horizontal




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		2390.000	24.23	31.81	56.04	74.00	-17.96	peak	
2	*	2390.000	13.85	31.81	45.66	54.00	-8.34	AVG	



EUT	Mini PCI Radio Module, 2x2 IEEE 802.11 b/g/n ,2.4 GHz	Model Name	RJ-1301
Temperature	24°C	Relative Humidity	46%
Test Voltage	AC 120V/60Hz		
Test Mode	IEEE 802.11g		
NOTE	The transmitter was setup to transmit at the highest channel and the field strength was measured at 2483.5-2500 MHz.		

Polarization: Vertical




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		2483.500	32.12	32.19	64.31	74.00	-9.69	peak	
2	*	2483.500	17.51	32.19	49.70	54.00	-4.30	AVG	



EUT	Mini PCI Radio Module, 2x2 IEEE 802.11 b/g/n ,2.4 GHz	Model Name	RJ-1301
Temperature	24°C	Relative Humidity	46%
Test Voltage	AC 120V/60Hz		
Test Mode	IEEE 802.11g		
NOTE	The transmitter was setup to transmit at the highest channel and the field strength was measured at 2483.5-2500 MHz.		

Polarization: Horizontal




No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		2483.500	24.42	32.19	56.61	74.00	-17.39	peak	
2	*	2483.500	13.61	32.19	45.80	54.00	-8.20	AVG	



EUT	Mini PCI Radio Module, 2x2 IEEE 802.11 b/g/n ,2.4 GHz	Model Name	RJ-1301
Temperature	24°C	Relative Humidity	46%
Test Voltage	AC 120V/60Hz		
Test Mode	IEEE 802.11n (20 MHz)-1TX		
NOTE	The transmitter was setup to transmit at the lowest channel and the field strength was measured at 2310-2390 MHz.		

Polarization: Vertical




No. Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1	2390.000	32.88	31.81	64.69	74.00	-9.31	peak	
2 *	2390.000	20.22	31.81	52.03	54.00	-1.97	AVG	



EUT	Mini PCI Radio Module, 2x2 IEEE 802.11 b/g/n ,2.4 GHz	Model Name	RJ-1301
Temperature	24°C	Relative Humidity	46%
Test Voltage	AC 120V/60Hz		
Test Mode	IEEE 802.11n (20 MHz)-1TX		
NOTE	The transmitter was setup to transmit at the lowest channel and the field strength was measured at 2310-2390 MHz.		

Polarization: Horizontal




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		2390.000	24.25	31.81	56.06	74.00	-17.94	peak	
2	*	2390.000	15.46	31.81	47.27	54.00	-6.73	AVG	



EUT	Mini PCI Radio Module, 2x2 IEEE 802.11 b/g/n ,2.4 GHz	Model Name	RJ-1301
Temperature	24°C	Relative Humidity	46%
Test Voltage	AC 120V/60Hz		
Test Mode	IEEE 802.11n (20 MHz)-1TX		
NOTE	The transmitter was setup to transmit at the highest channel and the field strength was measured at 2483.5-2500 MHz.		

Polarization: Vertical




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		2483.500	29.86	32.19	62.05	74.00	-11.95	peak	
2	*	2483.500	18.42	32.19	50.61	54.00	-3.39	AVG	



EUT	Mini PCI Radio Module, 2x2 IEEE 802.11 b/g/n ,2.4 GHz	Model Name	RJ-1301
Temperature	24°C	Relative Humidity	46%
Test Voltage	AC 120V/60Hz		
Test Mode	IEEE 802.11n (20 MHz)-1TX		
NOTE	The transmitter was setup to transmit at the highest channel and the field strength was measured at 2483.5-2500 MHz.		

Polarization: Horizontal




No. Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1	2483.500	24.62	32.19	56.81	74.00	-17.19	peak	
2 *	2483.500	15.32	32.19	47.51	54.00	-6.49	AVG	



EUT	Mini PCI Radio Module, 2x2 IEEE 802.11 b/g/n ,2.4 GHz	Model Name	RJ-1301
Temperature	24°C	Relative Humidity	46%
Test Voltage	AC 120V/60Hz		
Test Mode	IEEE 802.11n (40 MHz)-1TX		
NOTE	The transmitter was setup to transmit at the lowest channel and the field strength was measured at 2310-2390 MHz.		

Polarization: Vertical




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		2390.000	32.85	31.81	64.66	74.00	-9.34	peak	
2	*	2390.000	20.06	31.81	51.87	54.00	-2.13	AVG	



EUT	Mini PCI Radio Module, 2x2 IEEE 802.11 b/g/n ,2.4 GHz	Model Name	RJ-1301
Temperature	24°C	Relative Humidity	46%
Test Voltage	AC 120V/60Hz		
Test Mode	IEEE 802.11n (40 MHz)-1TX		
NOTE	The transmitter was setup to transmit at the lowest channel and the field strength was measured at 2310-2390 MHz.		

Polarization: Horizontal




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		2390.000	25.48	31.81	57.29	74.00	-16.71	peak	
2	*	2390.000	15.46	31.81	47.27	54.00	-6.73	AVG	



EUT	Mini PCI Radio Module, 2x2 IEEE 802.11 b/g/n ,2.4 GHz	Model Name	RJ-1301
Temperature	24°C	Relative Humidity	46%
Test Voltage	AC 120V/60Hz		
Test Mode	IEEE 802.11n (40 MHz)-1TX		
NOTE	The transmitter was setup to transmit at the highest channel and the field strength was measured at 2483.5-2500 MHz.		

Polarization: Vertical




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		2483.500	39.68	32.19	71.87	74.00	-2.13	peak	
2	*	2483.500	20.15	32.19	52.34	54.00	-1.66	AVG	



EUT	Mini PCI Radio Module, 2x2 IEEE 802.11 b/g/n ,2.4 GHz	Model Name	RJ-1301
Temperature	24°C	Relative Humidity	46%
Test Voltage	AC 120V/60Hz		
Test Mode	IEEE 802.11n (40 MHz)-1TX		
NOTE	The transmitter was setup to transmit at the highest channel and the field strength was measured at 2483.5-2500 MHz.		

Polarization: Horizontal




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		2483.500	30.20	32.19	62.39	74.00	-11.61	peak	
2	*	2483.500	15.61	32.19	47.80	54.00	-6.20	AVG	



EUT	Mini PCI Radio Module, 2x2 IEEE 802.11 b/g/n ,2.4 GHz	Model Name	RJ-1301
Temperature	24°C	Relative Humidity	46%
Test Voltage	AC 120V/60Hz		
Test Mode	IEEE 802.11n (20 MHz)-2TX		
NOTE	The transmitter was setup to transmit at the lowest channel and the field strength was measured at 2310-2390 MHz.		

Polarization: Vertical




No. Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1	2390.000	31.83	31.81	63.64	74.00	-10.36	peak	
2 *	2390.000	20.60	31.81	52.41	54.00	-1.59	AVG	



EUT	Mini PCI Radio Module, 2x2 IEEE 802.11 b/g/n ,2.4 GHz	Model Name	RJ-1301
Temperature	24°C	Relative Humidity	46%
Test Voltage	AC 120V/60Hz		
Test Mode	IEEE 802.11n (20 MHz)-2TX		
NOTE	The transmitter was setup to transmit at the lowest channel and the field strength was measured at 2310-2390 MHz.		

Polarization: Horizontal




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		2390.000	23.59	31.81	55.40	74.00	-18.60	peak	
2	*	2390.000	13.95	31.81	45.76	54.00	-8.24	AVG	



EUT	Mini PCI Radio Module, 2x2 IEEE 802.11 b/g/n ,2.4 GHz	Model Name	RJ-1301
Temperature	24°C	Relative Humidity	46%
Test Voltage	AC 120V/60Hz		
Test Mode	IEEE 802.11n (20 MHz)-2TX		
NOTE	The transmitter was setup to transmit at the highest channel and the field strength was measured at 2483.5-2500 MHz.		

Polarization: Vertical




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		2483.500	25.69	32.19	57.88	74.00	-16.12	peak	
2	*	2483.500	15.52	32.19	47.71	54.00	-6.29	AVG	



EUT	Mini PCI Radio Module, 2x2 IEEE 802.11 b/g/n ,2.4 GHz	Model Name	RJ-1301
Temperature	24°C	Relative Humidity	46%
Test Voltage	AC 120V/60Hz		
Test Mode	IEEE 802.11n (20 MHz)-2TX		
NOTE	The transmitter was setup to transmit at the highest channel and the field strength was measured at 2483.5-2500 MHz.		

Polarization: Horizontal




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		2483.500	23.54	32.19	55.73	74.00	-18.27	peak	
2	*	2483.500	13.10	32.19	45.29	54.00	-8.71	AVG	



EUT	Mini PCI Radio Module, 2x2 IEEE 802.11 b/g/n ,2.4 GHz	Model Name	RJ-1301
Temperature	24°C	Relative Humidity	46%
Test Voltage	AC 120V/60Hz		
Test Mode	IEEE 802.11n (40 MHz)-2TX		
NOTE	The transmitter was setup to transmit at the lowest channel and the field strength was measured at 2310-2390 MHz.		

Polarization: Vertical




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		2390.000	32.29	31.81	64.10	74.00	-9.90	peak	
2	*	2390.000	20.44	31.81	52.25	54.00	-1.75	AVG	



EUT	Mini PCI Radio Module, 2x2 IEEE 802.11 b/g/n ,2.4 GHz	Model Name	RJ-1301
Temperature	24°C	Relative Humidity	46%
Test Voltage	AC 120V/60Hz		
Test Mode	IEEE 802.11n (40 MHz)-2TX		
NOTE	The transmitter was setup to transmit at the lowest channel and the field strength was measured at 2310-2390 MHz.		

Polarization: Horizontal




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		2390.000	24.15	31.81	55.96	74.00	-18.04	peak	
2	*	2390.000	15.33	31.81	47.14	54.00	-6.86	AVG	



EUT	Mini PCI Radio Module, 2x2 IEEE 802.11 b/g/n ,2.4 GHz	Model Name	RJ-1301
Temperature	24°C	Relative Humidity	46%
Test Voltage	AC 120V/60Hz		
Test Mode	IEEE 802.11n (40 MHz)-2TX		
NOTE	The transmitter was setup to transmit at the highest channel and the field strength was measured at 2483.5-2500 MHz.		

Polarization: Vertical




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		2483.500	29.78	32.19	61.97	74.00	-12.03	peak	
2	*	2483.500	17.76	32.19	49.95	54.00	-4.05	AVG	



EUT	Mini PCI Radio Module, 2x2 IEEE 802.11 b/g/n ,2.4 GHz	Model Name	RJ-1301
Temperature	24°C	Relative Humidity	46%
Test Voltage	AC 120V/60Hz		
Test Mode	IEEE 802.11n (40 MHz)-2TX		
NOTE	The transmitter was setup to transmit at the highest channel and the field strength was measured at 2483.5-2500 MHz.		

Polarization: Horizontal



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		2483.500	23.91	32.19	56.10	74.00	-17.90	peak	
2	*	2483.500	13.61	32.19	45.80	54.00	-8.20	AVG	

**10 POWER SPECTRAL DENSITY****10.1 LIMIT**

Test Item	Frequency Range (MHz)	Limit
Power Spectral Density	2400-2483.5	8 dBm (in any 3 kHz)

10.2 MEASUREMENT INSTRUMENTS LIST

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Spectrum Analyzer	R&S	FSP-30	100854	Sep. 08, 2014

NOTE: **N/A**: denotes No Model Name, No Serial No. or No Calibration specified.

10.3 TEST PROCEDURES

- The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below.
- Spectrum Setting: RBW=3 kHz, VBW=30 kHz, Sweep time = 500s.

10.4 TEST SETUP LAYOUT**10.5 DEVIATION FROM TEST STANDARD**

No deviation

10.6 EUT OPERATING CONDITIONS


The EUT tested system was configured as the statements of 5.6 Unless otherwise a special operating condition is specified in the follows during the testing.



10.7 TEST RESULTS

EUT	Mini PCI Radio Module, 2x2 IEEE 802.11 b/g/n ,2.4 GHz	Model Name	RJ-1301
Temperature	26°C	Relative Humidity	60%
Test Voltage	AC 120V/60Hz		
Test Mode	IEEE 802.11b/2412 MHz, 2437 MHz, 2462 MHz		


Frequency	Power Density (dBm)	Limit (dBm)	Result
2412 MHz	-4.38	8	PASS
2437 MHz	-0.69	8	PASS
2462 MHz	-3.78	8	PASS



Date: 14.FEB.2014 17:37:49




IEEE 802.11b/2437 MHz/Power Sepctral Density



Date: 14.FEB.2014 17:45:48

IEEE 802.11b/2462 MHz/Power Sepctral Density




Date: 14.FEB.2014 21:10:50



EUT	Mini PCI Radio Module, 2x2 IEEE 802.11 b/g/n ,2.4 GHz	Model Name	RJ-1301
Temperature	26°C	Relative Humidity	60%
Test Voltage	AC 120V/60Hz		
Test Mode	IEEE 802.11g/2412 MHz, 2437 MHz, 2462 MHz		


Frequency	Power Density (dBm)	Limit (dBm)	Result
2412 MHz	-8.14	8	PASS
2437 MHz	-4.67	8	PASS
2462 MHz	-5.39	8	PASS



Date: 14.FEB.2014 21:19:59




IEEE 802.11g/2437 MHz/Power Sepctral Density



Date: 14.FEB.2014 21:26:37

IEEE 802.11g/2462 MHz/Power Sepctral Density




Date: 14.FEB.2014 21:34:29



EUT	Mini PCI Radio Module, 2x2 IEEE 802.11 b/g/n ,2.4 GHz	Model Name	RJ-1301
Temperature	26°C	Relative Humidity	60%
Test Voltage	AC 120V/60Hz		
Test Mode	IEEE 802.11n (20 MHz)/2412 MHz, 2437 MHz, 2462 MHz-1TX		


Frequency	Power Density (dBm)	Limit (dBm)	Result
2412 MHz	-7.98	8	PASS
2437 MHz	-4.59	8	PASS
2462 MHz	-5.60	8	PASS



Date: 14.FEB.2014 21:46:49




IEEE 802.11n (20 MHz)/2437 MHz/Power Sepctral Density



Date: 14.FEB.2014 22:04:33

IEEE 802.11n (20 MHz)/2462 MHz/Power Sepctral Density




Date: 14.FEB.2014 22:11:52



EUT	Mini PCI Radio Module, 2x2 IEEE 802.11 b/g/n ,2.4 GHz	Model Name	RJ-1301
Temperature	26°C	Relative Humidity	60%
Test Voltage	AC 120V/60Hz		
Test Mode	IEEE 802.11n (40 MHz)/2422 MHz, 2437 MHz, 2452 MHz-1TX		


Frequency	Power Density (dBm)	Limit (dBm)	Result
2422 MHz	-15.69	8	PASS
2437 MHz	-11.17	8	PASS
2452 MHz	-9.54	8	PASS



Date: 14.FEB.2014 22:18:33




IEEE 802.11n (40 MHz)/2437 MHz/Power Sepctral Density



Date: 14.FEB.2014 22:26:56

IEEE 802.11n (40 MHz)/2452 MHz/Power Sepctral Density




Date: 14.FEB.2014 22:39:20



EUT	Mini PCI Radio Module, 2x2 IEEE 802.11 b/g/n ,2.4 GHz	Model Name	RJ-1301
Temperature	26°C	Relative Humidity	60%
Test Voltage	AC 120V/60Hz		
Test Mode	IEEE 802.11n (20 MHz)/2412 MHz, 2437 MHz, 2462 MHz-2TX-ANT 1		


Frequency	Power Density (dBm)	Limit (dBm)	Result
2412 MHz	-11.53	8	PASS
2437 MHz	-7.53	8	PASS
2462 MHz	-8.99	8	PASS



Date: 14.FEB.2014 22:58:27




IEEE 802.11n (20 MHz)/2437 MHz/Power Sepctral Density



Date: 14.FEB.2014 23:19:41

IEEE 802.11n (20 MHz)/2462 MHz/Power Sepctral Density




Date: 14.FEB.2014 23:24:27



EUT	Mini PCI Radio Module, 2x2 IEEE 802.11 b/g/n ,2.4 GHz	Model Name	RJ-1301
Temperature	26°C	Relative Humidity	60%
Test Voltage	AC 120V/60Hz		
Test Mode	IEEE 802.11n (20 MHz)/2412 MHz, 2437 MHz, 2462 MHz-2TX-ANT 2		


Frequency	Power Density (dBm)	Limit (dBm)	Result
2412 MHz	-11.32	8	PASS
2437 MHz	-7.14	8	PASS
2462 MHz	-9.77	8	PASS



Date: 14.FEB.2014 23:31:57




IEEE 802.11n (20 MHz)/2437 MHz/Power Sepctral Density



Date: 14.FEB.2014 23:37:59

IEEE 802.11n (20 MHz)/2462 MHz/Power Sepctral Density



Date: 14.FEB.2014 23:42:29




EUT	Mini PCI Radio Module, 2x2 IEEE 802.11 b/g/n ,2.4 GHz	Model Name	RJ-1301
Temperature	26°C	Relative Humidity	60%
Test Voltage	AC 120V/60Hz		
Test Mode	IEEE 802.11n (20 MHz)/2412 MHz, 2437 MHz, 2462 MHz-2TX-Total		

Frequency	Power Density (dBm)	Limit (dBm)	Result
2412 MHz	-8.41	8	PASS
2437 MHz	-4.32	8	PASS
2462 MHz	-6.35	8	PASS



EUT	Mini PCI Radio Module, 2x2 IEEE 802.11 b/g/n ,2.4 GHz	Model Name	RJ-1301
Temperature	26°C	Relative Humidity	60%
Test Voltage	AC 120V/60Hz		
Test Mode	IEEE 802.11n (40 MHz)/2422 MHz, 2437 MHz, 2452 MHz-2TX-ANT 1		


Frequency	Power Density (dBm)	Limit (dBm)	Result
2422 MHz	-15.32	8	PASS
2437 MHz	-11.07	8	PASS
2452 MHz	-11.70	8	PASS



Date: 15.FEB.2014 00:16:40




IEEE 802.11n (40 MHz)/2437 MHz/Power Sepctral Density



Date: 15.FEB.2014 00:27:18

IEEE 802.11n (40 MHz)/2452 MHz/Power Sepctral Density




Date: 15.FEB.2014 00:34:24



EUT	Mini PCI Radio Module, 2x2 IEEE 802.11 b/g/n ,2.4 GHz	Model Name	RJ-1301
Temperature	26°C	Relative Humidity	60%
Test Voltage	AC 120V/60Hz		
Test Mode	IEEE 802.11n (40 MHz)/2422 MHz, 2437 MHz, 2452 MHz-2TX-ANT 2		


Frequency	Power Density (dBm)	Limit (dBm)	Result
2422 MHz	-17.39	8	PASS
2437 MHz	-12.20	8	PASS
2452 MHz	-13.59	8	PASS



Date: 14.FEB.2014 23:56:37




IEEE 802.11n (40 MHz)/2437 MHz/Power Sepctral Density



Date: 15.FEB.2014 00:01:26

IEEE 802.11n (40 MHz)/2452 MHz/Power Sepctral Density



Date: 15.FEB.2014 00:06:53



EUT	Mini PCI Radio Module, 2x2 IEEE 802.11 b/g/n ,2.4 GHz	Model Name	RJ-1301
Temperature	26°C	Relative Humidity	60%
Test Voltage	AC 120V/60Hz		
Test Mode	IEEE 802.11n (40 MHz)/2422 MHz, 2437 MHz, 2452 MHz-2TX-Total		

Frequency	Power Density (dBm)	Limit (dBm)	Result
2422 MHz	-13.22	8	PASS
2437 MHz	-8.59	8	PASS
2452 MHz	-9.53	8	PASS



11 RF EXPOSURE COMPLIANCE

11.1 LIMIT

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 0.2 m normally can be maintained between the user and the device.

(A) Limits for Occupational / Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842 / f	4.89 / f	(900 / f)*	6
30-300	61.4	0.163	1.0	6
300-1500			F/300	6
1500-100,000			5	6

(B) Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-100,000			1.0	30

NOTE: f = frequency in MHz ; *Plane-wave equivalent power density.

11.2 MEASUREMENT INSTRUMENTS LIST

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Power Meter	Anritsu	ML2495A	1128008	Feb,08,2015
2	Power Meter Sensor	Anritsu	MA2411B	1126001	Feb,18,2015

NOTE: **N/A**: denotes No Model Name, No Serial No. or No Calibration specified.

11.3 MPE CALCULATION METHOD

$$E \text{ (V/m)} = \frac{\sqrt{30 \times P \times G}}{d}$$

$$\text{Power Density: } Pd \text{ (W/m}^2\text{)} = \frac{E^2}{377}$$

E = Electric field (V/m)

P = Peak RF output power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)


The formula can be changed to

$$Pd = \frac{30 \times P \times G}{377 \times d^2}$$

From the peak EUT RF output power, the minimum mobile separation distance, d=0.2m, as well as the gain of the used antenna, the RF power density can be obtained



11.4 TEST SETUP LAYOUT



11.5 DEVIATION FROM TEST STANDARD

No deviation

11.6 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 5.6 Unless otherwise a special operating condition is specified in the follows during the testing.

**11.7 TEST RESULTS**

EUT	Mini PCI Radio Module, 2x2 IEEE 802.11 b/g/n ,2.4 GHz	Model Name	RJ-1301
Temperature	26°C	Relative Humidity	60%
Test Voltage	AC 120V/60Hz		
Test Mode	IEEE 802.11b/2412 MHz, 2437 MHz, 2462 MHz		

Frequency	Antenna Gain (dBi)	Antenna Gain (numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Power Density (S) (mW/cm ²)	Limit of Power Density (S) (mW/cm ²)	Result
2412 MHz	5	3.1623	23.3400	215.7744	0.13581582	1	PASS
2437 MHz	5	3.1623	25.1000	323.5937	0.20368093	1	PASS
2462 MHz	5	3.1623	22.0200	159.2209	0.10021907	1	PASS

**Neutron Engineering Inc.**

EUT	Mini PCI Radio Module, 2x2 IEEE 802.11 b/g/n ,2.4 GHz	Model Name	RJ-1301
Temperature	26°C	Relative Humidity	60%
Test Voltage	AC 120V/60Hz		
Test Mode	IEEE 802.11g/2412 MHz, 2437 MHz, 2462 MHz		

Frequency	Antenna Gain (dBi)	Antenna Gain (numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Power Density (S) (mW/cm ²)	Limit of Power Density (S) (mW/cm ²)	Result
2412 MHz	5	3.1623	24.8900	308.3188	0.19406641	1	PASS
2437 MHz	5	3.1623	26.6200	459.1980	0.28903496	1	PASS
2462 MHz	5	3.1623	26.0800	405.5085	0.25524096	1	PASS

**Neutron Engineering Inc.**

EUT	Mini PCI Radio Module, 2x2 IEEE 802.11 b/g/n ,2.4 GHz	Model Name	RJ-1301
Temperature	26°C	Relative Humidity	60%
Test Voltage	AC 120V/60Hz		
Test Mode	IEEE 802.11n (20 MHz)/2412 MHz, 2437 MHz, 2462 MHz-1TX		

Frequency	Antenna Gain (dBi)	Antenna Gain (numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Power Density (S) (mW/cm ²)	Limit of Power Density (S) (mW/cm ²)	Result
2412 MHz	5	3.1623	22.5200	178.6488	0.11244765	1	PASS
2437 MHz	5	3.1623	26.7200	469.8941	0.29576744	1	PASS
2462 MHz	5	3.1623	25.7800	378.4426	0.23820472	1	PASS

**Neutron Engineering Inc.**

EUT	Mini PCI Radio Module, 2x2 IEEE 802.11 b/g/n ,2.4 GHz	Model Name	RJ-1301
Temperature	26°C	Relative Humidity	60%
Test Voltage	AC 120V/60Hz		
Test Mode	IEEE 802.11n (40 MHz)/2422 MHz, 2437 MHz, 2452 MHz-1TX		

Frequency	Antenna Gain (dBi)	Antenna Gain (numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Power Density (S) (mW/cm ²)	Limit of Power Density (S) (mW/cm ²)	Result
2412 MHz	5	3.1623	22.2900	169.4338	0.10664742	1	PASS
2437 MHz	5	3.1623	25.1000	323.5937	0.20368093	1	PASS
2462 MHz	5	3.1623	25.5200	356.4511	0.22436255	1	PASS

**Neutron Engineering Inc.**

EUT	Mini PCI Radio Module, 2x2 IEEE 802.11 b/g/n ,2.4 GHz	Model Name	RJ-1301
Temperature	26°C	Relative Humidity	60%
Test Voltage	AC 120V/60Hz		
Test Mode	IEEE 802.11n (20 MHz)/2412 MHz, 2437 MHz, 2462 MHz-2TX-Total		

Frequency	Antenna Gain (dBi)	Antenna Gain (numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Power Density (S) (mW/cm ²)	Limit of Power Density (S) (mW/cm ²)	Result
2412 MHz	5	3.1623	25.5200	356.4511	0.22436255	1	PASS
2437 MHz	5	3.1623	27.8900	615.1769	0.38721339	1	PASS
2462 MHz	5	3.1623	27.4600	557.1857	0.35071179	1	PASS

**Neutron Engineering Inc.**

EUT	Mini PCI Radio Module, 2x2 IEEE 802.11 b/g/n ,2.4 GHz	Model Name	RJ-1301
Temperature	26°C	Relative Humidity	60%
Test Voltage	AC 120V/60Hz		
Test Mode	IEEE 802.11n (40 MHz)/2422 MHz, 2437 MHz, 2452 MHz-2TX-Total		

Frequency	Antenna Gain (dBi)	Antenna Gain (numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Power Density (S) (mW/cm ²)	Limit of Power Density (S) (mW/cm ²)	Result
2412 MHz	5	3.1623	22.7700	189.2344	0.11911059	1	PASS
2437 MHz	5	3.1623	27.1200	515.2286	0.32430255	1	PASS
2462 MHz	5	3.1623	26.8500	484.1724	0.30475467	1	PASS