



[www.nemko.com](http://www.nemko.com)



**Test Report:** 88791-1R2TRFWL

**Applicant:** Verint Systems Canada Inc.  
1800 Berlier  
LAVAL, QC  
H7L 4S4

**Apparatus:** S3100-24VAC, S3100-RP-24, S3100-POE, S3100-RP-5x, S3100-5x, S3100-24, S3100-BR-5x, S3100-BR-24

**FCC ID:** VKHCM9S3100

**In Accordance With:** FCC Part 15 Subpart E, 15.407  
Unlicensed National Information Infrastructure  
Devices

**Tested By:** Nemko Canada Inc.  
303 River Road  
Ottawa, Ontario  
K1V 1H2

**Authorized By:**   
Xu Jin, Wireless Specialist

**Date:** October 22, 2007

**Total Number of Pages:** 62

## Report Summary

These tests were conducted on a sample of the equipment for the purpose of demonstrating compliance with Part 15, Subpart E, 15.407. Radiated tests were conducted in accordance with ANSI C63.4-2003. Radiated emissions are made on an open area test site. A description of the test facility is on file with the FCC.

The assessment summary is as follows:

<b>Apparatus Assessed:</b>	S3100-24VAC, S3100-RP-24, S3100-POE, S3100-RP-5x, S3100-5x, S3100-24, S3100-BR-5x, S3100-BR-24
<b>Specification:</b>	FCC Part 15 Subpart E, 15.407
<b>Compliance Status:</b>	Complies
<b>Exclusions:</b>	None
<b>Non-compliances:</b>	None
<b>Report Release History:</b>	Original Release

Author: Roman Kuleba, EMC/Wireless Specialist

Note that the results contained in this report relate only to the items tested and were obtained in the period between the date of initial receipt of samples and the date of issue of the report.

This test report has been completed in accordance with the requirements of ISO/IEC 17025.

Nemko Canada Inc. authorizes the applicant to reproduce this report provided it is reproduced in its entirety and for use by the company's employees only.

Any use which a third party makes of this report, or any reliance on or decisions to be made based on it, are the responsibility of such third parties. Nemko Canada Inc. accepts no responsibility for damages, if any, suffered by any third party as a result of decisions made or actions based on this report.

## TABLE OF CONTENTS

<b>Report Summary</b> .....	<b>2</b>
<b>Section 1: Equipment Under Test</b> .....	<b>4</b>
1.1 Product Identification .....	4
1.2 Samples Submitted for Assessment.....	4
1.3 Theory of Operation .....	4
1.4 Technical Specifications of the EUT .....	5
<b>Section 2: Test Conditions</b> .....	<b>6</b>
2.1 Specifications .....	6
2.2 Deviations From Laboratory Test Procedures .....	6
2.3 Test Environment .....	6
2.4 Test Equipment.....	6
2.5 Measurement Uncertainty.....	7
<b>Section 3: Observations</b> .....	<b>8</b>
3.1 Modifications Performed During Assessment .....	8
3.2 Record Of Technical Judgements.....	8
3.3 EUT Parameters Affecting Compliance .....	8
3.4 Test Deleted.....	8
3.5 Additional Observations.....	8
<b>Section 4: Results Summary</b> .....	<b>9</b>
4.1 FCC Part 15 Subpart E, 15.407: Test Results.....	10
<b>Appendix A: Test Results</b> .....	<b>11</b>
§15.403(i) 26dB Emission Bandwidth.....	11
§15.407(a) Power Limits and Maximum Conducted Output Power.....	15
§15.407(a) Peak Power Spectral Density.....	23
§15.407(a)(6) Peak Excursion Measurement.....	31
§15.407(b) Undesirable Emissions.....	35
§15.407(b)(6) Unwanted emissions below 1 GHz.....	45
§15.407 (b)(7) Spurious emissions within restricted bands (radiated).....	51
§15.407(g) Frequency Stability .....	57
§15.31(e) Supply Voltage Variation.....	58
<b>Appendix B: Setup Photographs</b> .....	<b>59</b>
<b>Appendix C: Block Diagram of Test Setups</b> .....	<b>60</b>
Test Site For Radiated Emissions .....	60
Conducted Emissions.....	60
RF Conducted Measurements .....	61
TIA/EIA 603, Signal Substitution Method .....	61
EIRP of Radiated Emissions.....	62

## **Section 1: Equipment Under Test**

### **1.1 Product Identification**

The Equipment Under Test was identified as follows:

S3100-24VAC and S3100 POE

### **1.2 Samples Submitted for Assessment**

The following samples of the apparatus have been submitted for type assessment:

<b>Sample No.</b>	<b>Description</b>	<b>Serial No.</b>
6	S3100-24VAC	S/N: 00079A10154A
7	S3100 POE	S/N: 00079A101676
8	"A Qualities" 120VAC / 60Hz to 12VDC Power Adaptor	Model: MD481210
9	"A Qualities" 120VAC / 60Hz to 24VAC Power Adaptor / Transformer	Model: MA572416
10	Ault Inc I.T.E Power Supply (P.O.E.)	Model: PW130
11 & 12	Antenna 13 dBi / 5.150-5.875 GHz, Huber & Suhner AG, SPA 5600/40/14/0/V	Batch Nr: 713095 & 713101
13 & 14	Antenna 19 dBi / 5.15-5.875 GHz, Wireless Edge, MT-485001	01060 & 01071

The first samples were received on: June 26, 2007

### **1.3 Theory of Operation**

The S3100 is an 802.11a (OFDM) W-LAN wireless device designed for operation in band 5.725 – 5.825 GHz (U-NII-3).

## **1.4 Technical Specifications of the EUT**

<b>Operating Frequency:</b>	5745 – 5805 MHz
<b>Peak Output Power:</b>	5.725 – 5.825 GHz Band: 16.88 dBm Conducted
<b>Emission Designator:</b>	W7D
<b>Rated Power:</b>	5.725 – 5.825 GHz Band: 36 dBm EIRP
<b>Modulation:</b>	802.11a (OFDM)
<b>Antenna Data:</b>	13 dBi / 5.150-5.875 GHz, Huber & Suhner AG, SPA 5600/40/14/0/V 19 dBi / 5.15-5.875 GHz, Wireless Edge, MT-485001
<b>Antenna Connector:</b>	F-SMA
<b>Power Source:</b>	120 VAC

## Section 2: Test Conditions

### 2.1 Specifications

The apparatus was assessed against the following specifications:

FCC Part 15 Subpart E, 15.407

Unlicensed National Information Infrastructure Devices

### 2.2 Deviations From Laboratory Test Procedures

No deviations were made from laboratory test procedures.

### 2.3 Test Environment

All tests were performed under the following environmental conditions:

Temperature range : 15 – 30 °C  
 Humidity range : 20 - 75 %  
 Pressure range : 86 - 106 kPa  
 Power supply range : +/- 5% of rated voltages

### 2.4 Test Equipment

Equipment	Manufacturer	Model No.	Asset/Serial No.	Next Cal.
Spectrum Analyzer	Rhode & Schwarz	FSP40	FA001920	Mar. 19/08
Spectrum Analyzer	Rhode & Schwarz	FSU	FA001877	Jan. 16/08
Spectrum Analyzer/EMI Receiver	Rhode & Schwarz	ESU	FA002043	Oct. 24/07
Signal Generator	Rohde & Schwarz	SMR40	FA001879	Jul. 27/07
Power Meter	Agilent	N1911A	FA001946	Jan. 23/08
Power Sensor	Agilent	N1922A	FA001947	Jan. 23/08
RF AMP	JCA	1 – 2 GHz	FA001498	Aug. 2/07
RF AMP	JCA	2 – 4 GHz	FA001496	Aug. 2/07
RF AMP	JCA	4 – 8 GHz	FA001497	Aug. 2/07
RF AMP	Narda	5 – 18 GHz	FA001409	COU
RF AMP	Narda	18.0 – 26.0 GHz	FA001550	COU
Bi-Conical Antenna #2	EMCO	3109	FA000904	Sep. 12/07
Log Periodic Antenna #1	EMCO	3148	FA001355	Sep. 12/07
Horn Antenna #2	EMCO	3115	FA000825	Jan. 30/08
Horn 18 – 26.5 GHz	Electro-Metrics	SH-50/60-1	FA000479	COU

\* COU (Calibrate on Use)

\*\* NCR (No Calibration Required)2.5 Measurement Uncertainty

## **2.5 Measurement Uncertainty**

Nemko Canada measurement uncertainty has been calculated using guidance of UKAS LAB 34:2003 and TIA-603-B Nov 7, 2002. All calculations have been performed to provide a confidence level of 95% and can be found in Nemko Canada document MU-003.

## **Section 3: Observations**

### **3.1 Modifications Performed During Assessment**

No modifications were performed during assessment.

### **3.2 Record Of Technical Judgements**

No technical judgements were made during the assessment.

### **3.3 EUT Parameters Affecting Compliance**

The user of the apparatus could not alter parameters that would affect compliance.

### **3.4 Test Deleted**

No Tests were deleted from this assessment.

### **3.5 Additional Observations**

There were no additional observations made during this assessment.



## **Section 4: Results Summary**

This section contains the following:

FCC Part 15 Subpart E: Test Results

The column headed 'Required' indicates whether the associated clauses were invoked for the apparatus under test. The following abbreviations are used:

- N No: not applicable / not relevant.
- Y Yes: Mandatory i.e. the apparatus shall conform to these tests.
- N/T Not Tested, mandatory but not assessed. (See section 3.4 Test deleted)

The results contained in this section are representative of the operation of the apparatus as originally submitted.

**4.1 FCC Part 15 Subpart E, 15.407: Test Results**

Part 15	Test Description	Required	Result
§15.403(i)	26dB Emission Bandwidth	Y	PASS
§15.407(a)(3)&(4)	Power Limits and Maximum Conducted Output Power (for the band 5.725–5.825 GHz)	Y	PASS
§15.407(a)(3)&(5)	Peak Power Spectral Density (for the band 5.725–5.825 GHz)	Y	PASS
§15.407(a)(6)	Peak Excursion Measurement	Y	PASS
§15.407(b)(4)	Undesirable Emissions (5.725–5.825 GHz band)	Y	PASS
§15.407(b)(6)	Unwanted emissions below 1 GHz	–	–
§15.207	AC Power Line Conducted Emissions	Y	PASS
§15.209	Radiated Emission Limits (general requirements)	Y	PASS
§15.407(7)	Restricted Bands of Operation (see §15.205)	Y	PASS
§15.407(g)	Frequency Stability	Y	PASS

## Appendix A: Test Results

### §15.403(i) 26dB Emission Bandwidth

The emission bandwidth shall be determined by measuring the width of the signal between two points, one below the carrier centre frequency and one above the carrier centre frequency, that are 26 dB down relative to the maximum level of the modulated carrier. Determination of the emissions bandwidth is based on the use of measurement instrumentation employing a peak detector function with an instrument resolution bandwidth approximately equal to 1.0 percent of the emission bandwidth of the device under measurement.

#### Test Conditions:

<b>Sample Number:</b>	1	<b>Temperature (°C):</b>	23°C
<b>Date:</b>	July 4, 2007	<b>Humidity (%):</b>	36 %
<b>Modification State:</b>	0	<b>Tester:</b>	Roman Kuleba
		<b>Laboratory:</b>	Ottawa


**Test Results:** See plots.

26dB Emission Bandwidth, continued

Operating Band: 5.725–5.825 GHz

TX Frequency: 5.745 GHz

Measured Bandwidth: 29.8 MHz




Date: 4.JUL.2007 19:20:11

26dB Emission Bandwidth, continued

Operating Band: 5.725–5.825 GHz

TX Frequency: 5.785 GHz

Measured Bandwidth: 30.0 MHz




Date: 4.JUL.2007 19:15:55

26dB Emission Bandwidth, continued

Operating Band: 5.725–5.825 GHz

TX Frequency: 5.805 GHz

Measured Bandwidth: 28.2 MHz



Date: 4.JUL.2007 19:11:09

**§15.407(a) Power Limits and Maximum Conducted Output Power**

§15.407(a)(2) For the 5.25–5.35 GHz and 5.47–5.725 GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250 mW or 11 dBm + 10 log B, where B is the 26 dB emission bandwidth in megahertz. In addition, the peak power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the peak power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

§15.407(a)(3) For the band 5.725–5.825 GHz, the maximum conducted output power over the frequency band of operation shall not exceed the lesser of 1 W or 17 dBm + 10 log B, where B is the 26-dB emission bandwidth in MHz. In addition, the peak power spectral density shall not exceed 17 dBm in any 1-MHz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the peak power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. However, fixed point-to-point U-NII devices operating in this band may employ transmitting antennas with directional gain up to 23 dBi without any corresponding reduction in the transmitter peak output power or peak power spectral density. For fixed, point-to-point U-NII transmitters that employ a directional antenna gain greater than 23 dBi, a 1 dB reduction in peak transmitter power and peak power spectral density for each 1 dB of antenna gain in excess of 23 dBi would be required. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.

§15.407(a)(4) The maximum conducted output power must be measured over any interval of continuous transmission using instrumentation calibrated in terms of an rms-equivalent voltage. The measurement results shall be properly adjusted for any instrument limitations, such as detector response times, limited resolution bandwidth capability when compared to the emission bandwidth, sensitivity, etc., so as to obtain a true peak measurement conforming to the above definitions for the emission in question.

**Test Conditions:**

<b>Sample Number:</b>	1	<b>Temperature (°C):</b>	23°C
<b>Date:</b>	July 4 – Oct. 9, 2007	<b>Humidity (%):</b>	36 %
<b>Modification State:</b>	0	<b>Tester:</b>	Roman Kuleba
		<b>Laboratory:</b>	Ottawa

**Test Method:** FCC Public Notice Ref: DA: 02-2138  
Measurement Procedure for Peak Transmit Power in UNII Bands


**Test Results:** Pass (see plots and tables).

Maximum Conducted Output Power, continued

Operating Band: 5.725 – 5.825 GHz

TX Frequency: 5.745 GHz

Antenna Gain: 13 dBi




Date: 4.JUL.2007 13:56:49



Maximum Conducted Output Power, continued

Operating Band: 5.725 – 5.825 GHz  
TX Frequency: 5.745 GHz  
Antenna Gain: 19 dBi




Date: 9.OCT.2007 17:49:28

Maximum Conducted Output Power, continued

Operating Band: 5.725 – 5.825 GHz

TX Frequency: 5.785 GHz

Antenna Gain: 13 dBi




Date: 4.JUL.2007 14:05:31

Maximum Conducted Output Power, continued

Operating Band: 5.725 – 5.825 GHz

TX Frequency: 5.785 GHz

Antenna Gain: 19 dBi




Date: 4.JUL.2007 14:18:38

Maximum Conducted Output Power, continued

Operating Band: 5.725 – 5.825 GHz

TX Frequency: 5.805 GHz

Antenna Gain: 13 dBi



Date: 4.JUL.2007 14:09:27



Maximum Conducted Output Power, continued
---

Operating Band: 5.725 – 5.825 GHz

Ch. #	Freq. MHz	P <sub>TX</sub> Cond. dBm	P <sub>TX</sub> Limit dBm	Margin dB	G <sub>ANT</sub> dBi	EIRP dBm	EIRP Limit dBm	Margin dB
149	5745	16.82	30.0	13.18	13.0	29.82	36.0	6.18
157	5785	16.80	30.0	13.20	13.0	29.80	36.0	6.20
161	5805	16.68	30.0	13.32	13.0	29.68	36.0	6.32
149	5745	16.74	30.0	13.26	19.0	35.74	36.0	0.26
157	5785	16.88	30.0	13.12	19.0	35.88	36.0	0.12
161	5805	16.87	30.0	13.13	19.0	35.87	36.0	0.13

**§15.407(a) Peak Power Spectral Density**

§15.407(a)(2) For the 5.25–5.35 GHz and 5.47–5.725 GHz bands, the peak power spectral density shall not exceed 11 dBm in any 1 MHz band. If transmitting antennas of directional gain greater than 6 dBi are used the peak power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

§15.407(a)(3) For the band 5.725–5.825 GHz, the peak power spectral density shall not exceed 17 dBm in any 1 MHz band. If transmitting antennas of directional gain greater than 6 dBi are used the peak power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. However, fixed point-to-point U-NII devices operating in this band may employ transmitting antennas with directional gain up to 23 dBi without any corresponding reduction in the transmitter peak output power or peak power spectral density. For fixed, point-to-point U-NII transmitters that employ a directional antenna gain greater than 23 dBi, a 1 dB reduction in peak transmitter power and peak power spectral density for each 1 dB of antenna gain in excess of 23 dBi would be required. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.

§15.407(a)(5) The peak power spectral density is measured as a conducted emission by direct connection of a calibrated test instrument to the equipment under test. If the device cannot be connected directly, alternative techniques acceptable to the Commission may be used. Measurements are made over a bandwidth of 1 MHz or the 26 dB emission bandwidth of the device, whichever is less. A resolution bandwidth less than the measurement bandwidth can be used, provided that the measured power is integrated to show total power over the measurement bandwidth. If the resolution bandwidth is approximately equal to the measurement bandwidth, and much less than the emission bandwidth of the equipment under test, the measured results shall be corrected to account for any difference between the resolution bandwidth of the test instrument and its actual noise bandwidth.

**Test Conditions:**

<b>Sample Number:</b>	1	<b>Temperature (°C):</b>	23°C
<b>Date:</b>	July 5 & 15, 2007	<b>Humidity (%):</b>	36 %
<b>Modification State:</b>	0	<b>Tester:</b>	Roman Kuleba
		<b>Laboratory:</b>	Ottawa

**Test Method:** FCC Public Notice Ref: DA: 02-2138  
 Measurement Procedure Updated for Peak Transmit Power in the  
 Unlicensed National Information Infrastructure (U-NII) Bands

**Test Results:** Pass (see tables and plots).

Peak Power Spectral Density, continued


Operating Band: 5.725 – 5.825 GHz

TX Frequency: 5.745 GHz

Antenna Gain: 13 dBi



\*RBW 1 MHz      Marker 1 [T1 ]  
VBW 3 MHz      3.22 dBm  
SWT 20 ms      5.749615385 GHz



Date: 5.JUL.2007 11:27:40



Peak Power Spectral Density, continued


Operating Band: 5.725 – 5.825 GHz

TX Frequency: 5.745 GHz

Antenna Gain: 19 dBi



\*RBW 1 MHz      Marker 1 [T1 ]  
VBW 3 MHz      3.47 dBm  
SWT 20 ms      5.741826923 GHz



Date: 5.JUL.2007 11:32:35

Peak Power Spectral Density, continued


Operating Band: 5.725 – 5.825 GHz

TX Frequency: 5.785 GHz

Antenna Gain: 13 dBi



\*RBW 1 MHz      Marker 1 [T1 ]  
VBW 3 MHz      3.15 dBm  
SWT 20 ms      5.782692308 GHz



Date: 5.JUL.2007 11:40:57

Peak Power Spectral Density, continued


Operating Band: 5.725 – 5.825 GHz

TX Frequency: 5.785 GHz

Antenna Gain: 19 dBi



\*RBW 1 MHz      Marker 1 [T1 ]  
VBW 3 MHz      2.83 dBm  
SWT 20 ms      5.782596154 GHz




Date: 5.JUL.2007 11:44:28

Peak Power Spectral Density, continued

Operating Band: 5.725 – 5.825 GHz

TX Frequency: 5.805 GHz

Antenna Gain: 13 dBi



Date: 5.JUL.2007 12:02:20

Peak Power Spectral Density, continued


Operating Band: 5.725 – 5.825 GHz

TX Frequency: 5.805 GHz

Antenna Gain: 19 dBi



\*RBW 1 MHz      Marker 1 [T1 ]  
VBW 3 MHz      2.36 dBm  
SWT 20 ms      5.806682692 GHz



Date: 5.JUL.2007 12:05:53

Peak Power Spectral Density, continued
--

Operating Band: 5.725 – 5.825 GHz

Ch. #	Freq. MHz	PPSD dBm/MHz	PPSD Limit dBm/MHz	Margin dB	G <sub>ANT</sub> dBi	EIRP dBm/MHz	EIRP Limit dBm/MHz	Margin dB
149	5745	3.22	17.0	13.78	13.0	16.22	23.0	6.78
157	5785	3.15	17.0	13.85	13.0	16.15	23.0	6.85
161	5805	3.11	17.0	13.89	13.0	16.11	23.0	6.89
149	5745	3.47	17.0	13.53	19.0	22.47	23.0	0.53
157	5785	2.83	17.0	14.17	19.0	21.83	23.0	1.17
161	5805	2.36	17.0	14.64	19.0	21.36	23.0	1.64

**§15.407(a)(6) Peak Excursion Measurement**

§15.407(a)(6) The ratio of the peak excursion of the modulation envelope (measured using a peak hold function) to the maximum conducted output power (measured as specified above) shall not exceed 13 dB across any 1 MHz bandwidth or the emission bandwidth whichever is less.

**Test Conditions:**

<b>Sample Number:</b>	1	<b>Temperature (°C):</b>	23°C
<b>Date:</b>	July 6, 2007	<b>Humidity (%):</b>	36 %
<b>Modification State:</b>	0	<b>Tester:</b>	Roman Kuleba
		<b>Laboratory:</b>	Ottawa

**Test Method:** FCC Public Notice Ref: DA: 02-2138  
Measurement Procedure Updated for Peak Transmit Power in the  
Unlicensed National Information Infrastructure (U-NII) Bands

**Test Results:** Pass (see plots).

Peak Excursion Measurement, continued

Operating Band: 5.725 – 5.825 GHz

TX Frequency: 5.745 GHz




\* RBW 1 MHz

VBW 3 MHz

SWT 20 ms

Ref 30 dBm

\* Att 20 dB




Date: 6.JUL.2007 14:34:54



Peak Excursion Measurement, continued

Operating Band: 5.725 – 5.825 GHz

TX Frequency: 5.785 GHz




Date: 6.JUL.2007 14:46:33

Peak Excursion Measurement, continued

Operating Band: 5.725 – 5.825 GHz

TX Frequency: 5.805 GHz



Date: 6.JUL.2007 14:46:33

**§15.407(b) Undesirable Emissions**

§15.407(b) Undesirable emission limits: Except as shown in paragraph (b)(6) of this section, the peak emissions outside of the frequency bands of operation shall be attenuated in accordance with the following limits:

§15.407(b)(2) For transmitters operating in the 5.25–5.35 GHz band: all emissions outside of the 5.15–5.35 GHz band shall not exceed an EIRP of –27 dBm/MHz. Devices operating in the 5.25–5.35 GHz band that generate emissions in the 5.15–5.25 GHz band must meet all applicable technical requirements for operation in the 5.15–5.25 GHz band (including indoor use) or alternatively meet an out-of-band emission EIRP limit of –27 dBm/MHz in the 5.15–5.25 GHz band.

§15.407(b)(4) For transmitters operating in the 5.725–5.825 GHz band: all emissions within the frequency range from the band edge to 10 MHz above or below the band edge shall not exceed an EIRP of –17 dBm/MHz; for frequencies 10 MHz or greater above or below the band edge, emissions shall not exceed an EIRP of –27 dBm/MHz.

§15.407(b)(5) The emission measurements shall be performed using a minimum resolution bandwidth of 1 MHz. A lower resolution bandwidth may be employed near the band edge, when necessary, provided the measured energy is integrated to show the total power over 1 MHz.

**Test Conditions:**

<b>Sample Number:</b>	1	<b>Temperature (°C):</b>	23°C
<b>Date:</b>	July 9 – 10, 2007	<b>Humidity (%):</b>	36 %
<b>Modification State:</b>	0	<b>Tester:</b>	Roman Kuleba
		<b>Laboratory:</b>	Ottawa

**Test Results:** Pass (See plots).


**Additional Observations:**

The Spectrum was searched from 1GHz to the 40 GHz.  
 No harmonics were found within 20dB below the limit.  
 Measurements were performed at a distance of 3 meters using a Sample Detector with 1 MHz RBW and VBW ≥ RBW.

Undesirable Emissions, continued

Operating Band: 5.725 – 5.825 GHz  
Band Edge: 10 MHz Below Lower Band Edge (5.715 GHz)

Antenna Gain: 13 dBi  
TX Frequency: 5.745 GHz




Date: 9.JUL.2007 19:16:18

Integration Interval: 5714 – 5715 MHz  
Measured Emission: -33.33 dBm/MHz  
Limit: -27 dBm/MHz  
Margin: 6.33 dB

Undesirable Emissions, continued

Operating Band: 5.725 – 5.825 GHz  
Band Edge: Lower (5.725 GHz)

Antenna Gain: 13 dBi  
TX Frequency: 5.745 GHz




Date: 9.JUL.2007 19:15:10

Integration Interval: 5724 – 5725 MHz  
Measured Emission: -22.55 dBm/MHz  
Limit: -17 dBm/MHz  
Margin: 5.55 dB

Undesirable Emissions, continued

Operating Band: 5.725 – 5.825 GHz  
 Band Edge: Upper (5.825 GHz)

Antenna Gain: 13 dBi  
 TX Frequency: 5.805 GHz




Date: 9.JUL.2007 19:23:56

Integration Interval: 5825 – 5826 MHz  
 Measured Emission: -24.91 dBm/MHz  
 Limit: -17 dBm/MHz  
 Margin: 7.91 dB

Undesirable Emissions, continued

Operating Band: 5.725 – 5.825 GHz  
Band Edge: 10 MHz Above Upper Band Edge (5.835 GHz)

Antenna Gain: 13 dBi  
TX Frequency: 5.805 GHz




Date: 9.JUL.2007 19:26:29

Integration Interval: 5835 – 5836 MHz  
Measured Emission: -37.39 dBm/MHz  
Limit: -27 dBm/MHz  
Margin: 10.39 dB

Undesirable Emissions, continued

Operating Band: 5.725 – 5.825 GHz  
Band Edge: 10 MHz Below Lower Band Edge (5.715 GHz)

Antenna Gain: 19 dBi  
TX Frequency: 5.745 GHz



Date: 9.JUL.2007 19:44:17


Integration Interval: 5714 – 5715 MHz  
Measured Emission: -28.52 dBm/MHz  
Limit: -27 dBm/MHz  
Margin: 1.52 dB



Undesirable Emissions, continued

Operating Band: 5.725 – 5.825 GHz  
Band Edge: Lower (5.725 GHz)

Antenna Gain: 19 dBi  
TX Frequency: 5.745 GHz




Date: 9.JUL.2007 19:42:00

Integration Interval: 5724 – 5725 MHz  
Measured Emission: -18.79 dBm/MHz  
Limit: -17 dBm/MHz  
Margin: 1.79 dB

Undesirable Emissions, continued

Operating Band: 5.725 – 5.825 GHz  
Band Edge: Upper (5.825 GHz)

Antenna Gain: 19 dBi  
TX Frequency: 5.805 GHz




Date: 9.JUL.2007 19:37:08

Integration Interval: 5825 – 5826 MHz  
Measured Emission: -20.25 dBm/MHz  
Limit: -17 dBm/MHz  
Margin: 3.25 dB

Undesirable Emissions, continued

Operating Band: 5.725 – 5.825 GHz  
Band Edge: 10 MHz Above Upper Band Edge (5.835 GHz)

Antenna Gain: 19 dBi  
TX Frequency: 5.805 GHz



Date: 9.JUL.2007 19:35:40

Integration Interval: 5835 – 5836 MHz  
Measured Emission: -33.18 dBm/MHz  
Limit: -27 dBm/MHz  
Margin: 6.18 dB

Undesirable Emissions, continued

Frequency (MHz)	Antenna	Polarity	RCVD Signal (dBµV)	Sig. Sub. Factor	Emission Level (dBm)	Limit (dBm)	Margin (dB)	Reading	Amp.
1 1077.10	Horn2	V	30.6	-72.4	-41.8	-27.0	14.8	Average	-
2 7067.00	Horn2	V	65.7	-106.6	-40.9	-27.0	13.9	Average	4-8GHz

Note 1: Antenna Legend: BC = Biconical, BL = Bilog, LP = Log-Periodic, Horn = Horn, ED = EMCO Dipole  
 Note 2: nf – noise floor  
 Note 3: Measurements were performed using Peak Detector and 1MHz RBW / 10Hz VBW

Harmonics:

Frequency (MHz)	Antenna	Polarity	RCVD Signal (dBµV)	Sig. Sub. Factor	Emission Level (dBm)	Limit (dBm)	Margin (dB)	Reading	Amp.
1 11490	Horn2	V	35.8	N/A	-60.0	-27.0	33.0	Average	5-13GHz
2 11570	Horn2	V	32.8	N/A	-62.9 nf	-27.0	35.9	Average	5-13GHz
3 11610	Horn2	V	32.5	N/A	-63.2 nf	-27.0	36.2	Average	5-13GHz
4 11490	Horn2	H	36.7	N/A	-59.1	-27.0	32.1	Average	5-13GHz
5 11570	Horn2	H	33.6	N/A	-62.1 nf	-27.0	35.1	Average	5-13GHz
6 11610	Horn2	H	35.2	N/A	-60.5	-27.0	33.5	Average	5-13GHz

Note 1: Antenna Legend: BC = Biconical, BL = Bilog, LP = Log-Periodic, Horn = Horn, ED = EMCO Dipole  
 Note 2: nf – noise floor  
 Note 3: Measurements were performed using Peak Detector and 1MHz RBW / 10Hz VBW

The Spectrum was searched from 1GHz to the 40 GHz.  
 Tested with the highest gain antenna connected to the EUT.

**§15.407(b)(6) Unwanted emissions below 1 GHz**

§15.407 (b)(6) Unwanted emissions below 1 GHz  
 Unwanted emissions below 1 GHz must comply with the general field strength limits set forth in §15.209. Further, any U-NII devices using an AC power line are required to comply also with the conducted limits set forth in §15.207.

§15.207 Conducted limits.

a) Except as shown in paragraphs (b) and (c) of this section, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50µH/50 ohms line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the boundary between the frequency ranges.

Frequency of Emission (MHz)	Conducted limit (dBµV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

\* Decreases with the logarithm of the frequency.

§ 15.209 (a) Radiated emission limits; general requirements

Except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009-0.490	2400/F (kHz)	300
0.490-1.705	24000/F (kHz)	30
1.705-30.0	30	30
30-88	100 <sup>(1)</sup>	3
88-216	150 <sup>(2)</sup>	3
216-960	200 <sup>(3)</sup>	3
Above 960	500	3

**Test Conditions:**

<b>Sample Number:</b>	1	<b>Temperature (°C):</b>	23°C
<b>Date:</b>	July 2 – 13, 2007	<b>Humidity (%):</b>	36 %
<b>Modification State:</b>	0	<b>Tester:</b>	Roman Kuleba
		<b>Laboratory:</b>	Ottawa

**Test Results:** Pass (see attached plots and table).

**Additional Observations:**

The spectrum was searched for radiated emissions from 30MHz to 1GHz. All radiated measurements were performed at a distance of 3 meters using a test receiver in Peak Detector mode with 120 kHz RBW and VBW > RBW.

Unwanted emissions below 1 GHz, continued

§15.207 AC Power-line Conducted Emissions

S3100-24VAC with 120VAC/24VAC Adapter/Transformer

Line: LIVE




Unwanted emissions below 1 GHz, continued

§15.207 AC Power-line Conducted Emissions

S3100-24VAC with 120VAC/24VAC Adapter/Transformer

Line: NEUTRAL



— CISRP 22 Voltage on Mains QP Class B      - - - CISPR 22 Voltage on Mains AV Class B  
— Preview Measurement Peak Detector      — Preview Measurement Average Detector

Unwanted emissions below 1 GHz, continued

§15.207 AC Power-line Conducted Emissions

S3100 POE with Power Over Ethernet (-48VDC)

Line: LIVE






Unwanted emissions below 1 GHz, continued

§15.207 AC Power-line Conducted Emissions

S3100 POE with Power Over Ethernet (-48VDC)

Line: NEUTRAL



Unwanted emissions below 1 GHz, continued

15.209(a) Radiated Emissions – General Requirements  
 Tested with the highest gain antenna connected to the EUT.

Frequency (MHz)	Antenna	Polarity	RCVD Signal (dBµV)	Ant. Factor (dB)	Cable Loss (dB)	Emission Level (dBµV/m)	Limit (dBµV/m)	Margin (dB)	
1	55.00	BC2	V	14.1	8.9	0.8	23.8	40.0	16.2
2	67.30	BC2	V	14.2	8.9	0.9	24.0	40.0	16.0
3	83.30	BC2	V	12.3	7.6	0.9	20.8	40.0	19.2
4	103.30	BC2	V	12.8	10.6	1.1	24.5	43.5	19.0
5	165.10	BC2	V	9.2	13.9	1.3	24.4	43.5	19.2
6	220.10	BC2	V	10.7	16.0	1.6	28.3	46.0	17.7
7	250.10	BC2	V	8.0	17.0	1.7	26.7	46.0	19.3
8	330.00	LP1	V	12.2	14.6	1.8	28.6	46.0	17.4
9	375.10	LP1	V	9.6	15.4	1.9	26.9	46.0	19.1
10	495.10	LP1	V	15.2	17.6	2.1	34.9	46.0	11.1
11	536.50	LP1	V	18.1	18.1	2.4	38.6	46.0	7.4
12	589.70	LP1	V	14.5	18.8	2.5	35.8	46.0	10.2
13	619.90	LP1	V	15.4	19.3	2.5	37.3	46.0	8.7
14	660.50	LP1	V	13.5	20.6	2.6	36.7	46.0	9.3
15	953.20	LP1	V	14.9	23.8	3.2	41.9	46.0	4.1
16	989.90	LP1	V	16.2	24.0	3.3	43.5	54.0	10.5
17	67.30	BC2	H	10.4	9.2	0.9	20.4	40.0	19.6
18	83.30	BC2	H	10.4	7.6	0.9	18.9	40.0	21.1
19	103.30	BC2	H	21.4	9.7	1.1	32.2	43.5	11.3
20	165.10	BC2	H	14.9	12.4	1.3	28.6	43.5	14.9
21	171.60	BC2	H	13.9	12.5	1.3	27.7	43.5	15.8
22	220.10	BC2	H	11.3	15.7	1.6	28.6	46.0	17.5
23	250.10	BC2	H	8.5	16.9	1.7	27.1	46.0	19.0
24	330.00	LP1	H	13.8	15.2	1.8	30.8	46.0	15.2
25	440.00	LP1	H	11.0	16.8	2.0	29.8	46.0	16.2
26	495.10	LP1	H	14.9	18.5	2.1	35.5	46.0	10.5
27	543.60	LP1	H	15.5	18.6	2.4	36.5	46.0	9.5
28	617.20	LP1	H	13.7	20.1	2.5	36.3	46.0	9.7
29	668.30	LP1	H	14.3	21.4	2.6	38.3	46.0	7.7
30	741.40	LP1	H	12.0	21.5	2.8	36.3	46.0	9.7
31	956.70	LP1	H	12.0	24.7	3.2	39.9	46.0	6.2
32	987.10	LP1	H	13.9	25.0	3.3	42.1	54.0	11.8

Note 1: Antenna Legend: BC = Biconical, BL = Bilog, LP = Log-Periodic, Horn = Horn, ED = EMCO Dipole  
 Note 2: Peak detector used

**§15.407 (b)(7) Spurious emissions within restricted bands (radiated)**

§15.407 (b)(7) The provisions of §15.205 apply to intentional radiators operating under this section.

§15.205 (b) Except as provided in paragraphs (d) and (e) of this section, the field strength of emissions appearing within these frequency bands (restricted bands of operation) shall not exceed the limits shown in §15.209. At frequencies equal to or less than 1000 MHz, compliance with the limits in §15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1000 MHz, compliance with the emission limits in §15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in §15.35 apply to these measurements.

**Test Conditions:**

<b>Sample Number:</b>	1	<b>Temperature (°C):</b>	23°C
<b>Date:</b>	July 10, 2007	<b>Humidity (%):</b>	36 %
<b>Modification State:</b>	0	<b>Tester:</b>	Roman Kuleba
		<b>Laboratory:</b>	Ottawa

**Test Results:** See attached plots.

**Additional Observations:**


These results apply to emissions found in the Restricted Bands defined in FCC Part 15 Subpart C, 15.205.

The Spectrum was searched from 30MHz to 40 GHz.

Measurements were performed as radiated at 3 meter distance. On frequencies below 1GHz peak detector and 120kHz RBW was used to obtain readings. On frequencies above 1GHz Peak Detector mode with RBW = 1MHz / VBW = 1MHz was used to obtain peak readings and RBW = 1MHz / VBW = 10Hz was used to obtain average readings.

Spurious Emissions Within Restricted Bands, continued

Antenna: 13 dBi  
TX Frequency: 5.745 GHz  
Restricted Band: 5.35 – 5.46 GHz




Date: 10.JUL.2007 15:02:01

Spurious Emissions Within Restricted Bands, continued

Antenna: 13 dBi  
TX Frequency: 5.745 GHz  
Restricted Band: 5.35 – 5.46 GHz




\*RBW 1 MHz      Marker 1 [T1 ]  
\*VBW 1 MHz      65.67 dBμV/m  
SWT 20 ms      5.355112179 GHz



Date: 10.JUL.2007 15:00:44

Spurious Emissions Within Restricted Bands, continued

Antenna: 19 dBi  
TX Frequency: 5.745 GHz  
Restricted Band: 5.35 – 5.46 GHz




Date: 10.JUL.2007 15:41:17

Spurious Emissions Within Restricted Bands, continued

Antenna: 19 dBi  
TX Frequency: 5.745 GHz  
Restricted Band: 5.35 – 5.46 GHz



\*RBW 1 MHz      Marker 1 [T1 ]  
\*VBW 1 MHz      68.33 dBμV/m  
SWT 20 ms      5.360576923 GHz



Date: 10.JUL.2007 15:43:02

Spurious Emissions Within Restricted Bands, continued

Frequency (MHz)	Antenna	Polarity	RCVD Signal (dBµV)	Ant. Factor (dB)	Amp. Gain (dB)	Cable Loss (dB)	Emission Level (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Reading	
1	165.10	BC2	V	9.2	13.9	-	1.3	24.4	43.5	19.2	Peak
2	250.10	BC2	V	8.0	17.0	-	1.7	26.7	46.0	19.3	Peak
3	330.00	LP1	V	12.2	14.6	-	1.8	28.6	46.0	17.4	Peak
4	989.90	LP1	V	16.2	24.0	-	3.3	43.5	54.0	10.5	Peak
5	165.10	BC2	H	14.9	12.4	-	1.3	28.6	43.5	14.9	Peak
6	171.60	BC2	H	13.9	12.5	-	1.3	27.7	43.5	15.8	Peak
7	250.10	BC2	H	8.5	16.9	-	1.7	27.1	46.0	19.0	Peak
8	330.00	LP1	H	13.8	15.2	-	1.8	30.8	46.0	15.2	Peak
9	987.10	LP1	H	13.9	25.0	-	3.3	42.1	54.0	11.8	Peak
10	1077.10	Horn2	V	25.2	25.0	-	3.4	53.6	74.0	20.4	Peak
11	1077.10	Horn2	V	25.0	25.0	-	3.4	53.4	54.0	0.6	Average
12	11490	Horn2	V	31.1	38.6	41.2	8.4	36.9	54.0	17.1	Average
13	11570	Horn2	V	27.6	39.2	41.1	8.4	34.1	54.0	19.9	Average
14	11610	Horn2	V	27.6	39.2	41.1	8.4	34.1	54.0	19.9	Average
15	11490	Horn2	H	31.4	38.6	41.2	8.4	37.2	54.0	16.8	Average
16	11570	Horn2	H	28.1	39.1	41.1	8.4	34.5	54.0	19.5	Average
17	11610	Horn2	H	29.3	39.1	41.1	8.4	35.7	54.0	18.3	Average

Antenna Legend: BC = Biconical, BL = Bilog, LP = Log-Periodic, Horn = Horn, ED = EMCO Dipole

The Spectrum was searched from 30 MHz to the 40 GHz.  
 Tested with the highest gain antenna connected to the EUT.



**§15.407(g) Frequency Stability**

§15.407(g) Manufacturers of U-NII devices are responsible for ensuring frequency stability such that an emission is maintained within the band of operation under all conditions of normal operation as specified in the users manual.

**Test Conditions:**

<b>Sample Number:</b>	1	<b>Temperature (°C):</b>	23°C
<b>Date:</b>	July 12, 2007	<b>Humidity (%):</b>	36 %
<b>Modification State:</b>	0	<b>Tester:</b>	Roman Kuleba
		<b>Laboratory:</b>	Ottawa

**Test Results:** See tables.

Frequency Band: 5.725 - 5.825 GHz

T ( °C)	Nominal Freq. (GHz)	Measured Freq. (GHz)	Deviation (ppm)
-30	5.785	5.784992430	1.600
-20	5.785	5.784990578	1.280
-10	5.785	5.784988727	0.960
0	5.785	5.784986876	0.640
10	5.785	5.784985025	0.320
<b>20</b>	<b>5.785</b>	<b>5.784983174</b>	<b>0.000</b>
30	5.785	5.784995994	2.216
40	5.785	5.785008815	4.432
50	5.785	5.785021635	6.649

**§15.31(e) Supply Voltage Variation**

§15.31(e) For intentional radiators, measurements of the variation of the input power or the radiated signal level of the fundamental frequency component of the emission, as appropriate, shall be performed with the supply voltage varied between 85% and 115% of the nominal rated supply voltage. For battery operated equipment, the equipment tests shall be performed using a new battery.

**Test Conditions:**

<b>Sample Number:</b>	1	<b>Temperature (°C):</b>	23°C
<b>Date:</b>	July 4, 2007	<b>Humidity (%):</b>	36 %
<b>Modification State:</b>	0	<b>Tester:</b>	Roman Kuleba
		<b>Laboratory:</b>	Ottawa

**Test Results:** Pass.  
 Transmit output power was measured while supply voltage was varied from 102 VAC to 138 VAC (85% to 115% of the nominal rated supply voltage).  
 No measurable change in transmit output power was observed.


## Appendix B: Setup Photographs

**Spurious Emissions Setup:**




### Appendix C: Block Diagram of Test Setups


#### Test Site For Radiated Emissions




#### Conducted Emissions




### RF Conducted Measurements



### TIA/EIA 603, Signal Substitution Method



**EIRP of Radiated Emissions**



Determining Off-set Correction Factor (in dB) needed to read EIRP of measured radiated emissions (in dBm) directly on a Spectrum Analyzer:

$$E(V/m) = \frac{\sqrt{30 \cdot EIRP(W)}}{d(m)} \Rightarrow E(dB\mu V/m) = 90 + 10 \cdot \log_{10} 30 + EIRP(dBm) - 20 \cdot \log_{10} d(m)$$

$$E(dB\mu V/m) = V(dB\mu V/m) + L(dB) + AF(dB) = P_{Read}(dBm) + 106.99 + L(dB) + AF(dB)$$

$$EIRP(dBm) = P_{Read}(dBm) + 2.22 + L(dB) + AF(dB) + 20 \cdot \log_{10} d(m)$$

$$EIRP(dBm) = P_{Read}(dBm) + \text{Off-set (dB)}$$

$$\text{Off-set (dB)} = 2.22 + L(dB) + AF(dB) + 20 \cdot \log_{10} d(m)$$

- EIRP: Equivalent Isotropically Radiated Power transmitted from EUT
- E: Electric Field Strength measured at a distance 'd' from EUT
- d: Distance (m)
- V: Voltage at Spectrum Analyzer Input (dBμV/m)
- P<sub>Read</sub>(dBm): Reading on Spectrum Analyzer (dBm)
- L: Cable Loss (dB)
- AF: Antenna Factor (dB)
- Off-set: Off-set Correction Factor (in dB) needed to read EIRP of radiated emissions (in dBm) directly on Spectrum Analyzer