

RF EXPOSURE REPORT

Applicant	Asian Express Holdings Limited	
Address	RM1702, Sino Centre, 582-592 Nathan Road, Mongkok, Kowloon, Hong Kong.	

Manufacturer or Supplier	Asian Express Holdings Limited
Address	RM1702, Sino Centre, 582-592 Nathan Road, Mongkok, Kowloon, Hong Kong.
Product	Sky Rider with camera/air pressure sensor/Wifi
Additional Name	Cloud Rider 2.0 /Graviton+Streaming
Brand Name	PROPEL
Model	PL-1710
Additional Model & Model Difference	PL-1711, PL-1712, PL-1713, PL-1714, PL-1715, PL-1716, PL-1717, PL-1718, PL-1719, PL-1720, PL-1721, PL-1722, PL-1723, PL-1724, PL-1725, PL-1726, PL-1727, PL-1728, PL-1729, KH-2142
Date of tests	May 26, 2017 ~ Jul. 10, 2017

- **☐** IEEE C95.1

CONCLUSION: The submitted sample was found to COMPLY with the test requirement

Tested by Breeze Jiang	Approved by Glyn He
Project Engineer / EMC Department	Supervisor / EMC Department
Breeze	Date: Jul 11, 2017

This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification



TABLE OF CONTENTS

RELE	EASE CONTROL RECORD	3
1.	CERTIFICATION	4
	RF EXPOSURE LIMIT	
3.	MPE CALCULATION FORMULA	5
4.	CLASSIFICATION	5
5.	ANTENNA GAIN	6
6	CALCULATION RESULT OF MAXIMUM CONDUCTED POWER	6

Tel: +86 769 8593 5656 Fax: +86 769 8593 1080

Email: customerservice.dg@cn.bureauveritas.com



RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
FS170525N025-4	N/A	Jul. 11, 2017

Tel: +86 769 8593 5656 Fax: +86 769 8593 1080

Email: customerservice.dg@cn.bureauveritas.com

Page 3 of 6

Report Version 1



1. CERTIFICATION

FCC ID:	VLEPL-1710H	
PRODUCT:	Sky Rider with camera/air pressure sensor/Wifi	
ADDITIONAL NAME:	Cloud Rider 2.0 /Graviton+Streaming	
BRAND NAME:	PROPEL	
MODEL NO.:	PL-1710	
ADDITIONAL NO.:	PL-1711, PL-1712, PL-1713, PL-1714, PL-1715, PL-1716, PL-1717, PL-1718, PL-1719, PL-1720, PL-1721, PL-1722, PL-1723, PL-1724, PL-1725, PL-1726, PL-1727, PL-1728, PL-1729, KH-2142	
TEST SAMPLE:	Engineering Sample	
APPLICANT:	Asian Express Holdings Limited	
STANDARDS:	FCC Part 2 (Section 2.1091)	
	KDB 447498 D01	
	IEEE C95.1	

Note:

Additional models (see above table) are identical with the test model PL-1710 except the color of the model number for trading purpose.

In this report that EUT is 720P WiFi camera, the camera power supply by the plane's battery, that battery charging mode was tested in FCC Part 15B(VOC) report(report no.:FV170525N025.)

Tel: +86 769 8593 5656 Fax: +86 769 8593 1080

Email: customerservice.dg@cn.bureauveritas.com



2. RF EXPOSURE LIMIT

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

FREQUENCY RANGE (MHz)	AVERAGE TIME (minutes)					
LIMITS FOR GENERAL POPULATION / UNCONTROLLED EXPOSURE						
300-1500 F/1500 30						
1500-100,000			1.0	30		

F = Frequency in MHz

3. MPE CALCULATION FORMULA

 $Pd = (Pout*G) / (4*pi*r^2)$

where

Pd = power density in mW/cm²

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

R = distance between observation point and center of the radiator in cm

4. CLASSIFICATION

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. So, this device is classified as **Mobile Device**.

Tel: +86 769 8593 5656 Fax: +86 769 8593 1080

Email: customerservice.dg@cn.bureauveritas.com



5. ANTENNA GAIN

The antennas provided to the EUT, please refer to the following table:

Transmitter Circuit	Peak Gain (dBi)	Antenna Type
Chain 0	2.0	Integral Antenna

6. CALCULATION RESULT OF MAXIMUM CONDUCTED POWER

The tuned conducted Average Power (declared by client)

Mode	Target Power (dBm)	Tolerance (dBm)	Lower Tolerance (dBm)	Upper Tolerance (dBm)
802.11b	10	+-2	8	12
802.11g	5	+-2	3	7
802.11n(HT20)	5	+-2	3	7

The measured conducted Average Power

Mode	Frequency (MHz)	Averaged Power (dBm)
802.11b	2462	11.49
802.11g	2462	6.54
802.11n(HT20)	2462	6.56

FREQUENCY BAND (MHz)	MAX AVERAGE POWER (dBm)	ANTENNA GAIN (dBi)	DISTANCE (cm)	POWER DENSITY (mW/cm²)	LIMIT (mW/cm²)
2412-2462	12	2.0	20	0.005	1.0

--- END ---

Tel: +86 769 8593 5656 Fax: +86 769 8593 1080

Email: customerservice.dg@cn.bureauveritas.com