

RF EXPOSURE REPORT

Applicant	Asian Express Holdings Limited
Address	RM1702, Sino Centre, 582-592 Nathan Road, Mongkok, Kowloon, Hong Kong.

Manufacturer or Supplier	Asian Express Holdings Limited
Address	RM1702, Sino Centre, 582-592 Nathan Road, Mongkok, Kowloon, Hong Kong.
Product	HD Video Drone/Quantum HD/Quantum HD+wifi streaming
Brand Name	PROPEL
Model	PL-1750
Additional Model & Model Difference	PL-1741, PL-1742, PL-1743, PL-1744, PL-1745, PL-1746, PL-1747, PL-1748, PL-1749, PL-1750, PL-1751, PL-1752, PL-1753, PL-1754, PL-1755, PL-1756, PL-1757, PL-1758, PL-1759; See item 1
Date of tests	May 26, 2017 ~ Jul. 06, 2017

FCC Part 2 (Section 2.1091)

KDB 447498 D01

IEEE C95.1

CONCLUSION: The submitted sample was found to <u>COMPLY</u> with the test requirement

Tested by Breeze Jiang Project Engineer / EMC Department	Approved by Glyn He Supervisor / EMC Department
prene	Au
This report is for your exclusive use. Any copying or replication of this report to	Date: Jul. 12, 2017 o or for any other person or entity, or use of our name or trademark, is
permitted only with our prior written permission. This report sets forth our findin set forth in this report are not indicative or representative of the quality or chara	gs solely with respect to the test samples identified herein. The results cteristics of the lot from which a test sample was taken or any similar or
identical product unless specifically and expressly noted. Our report includes a information that you provided to us. You have 60 days from date of issuance of	
negligence, provided, however, that such notice shall be in writing and shall spe	cifically address the issue you wish to raise. A failure to raise such issue
within the prescribed time shall constitute your unqualified acceptance of the cor report contents. Unless specific mention, the uncertainty of measurement h	

Bureau Veritas Shenzhen Co., Ltd. Dongguan Branch

non-compliance to the specification

No. 34, Chenwulu Section, Guantai Rd., Houjie Town, Dongguan City, Guangdong 523942, China

Tel: +86 769 8593 5656 Fax: +86 769 8593 1080 Email: <u>customerservice.dg@cn.bureauveritas.com</u>



TABLE OF CONTENTS

RELE	ASE CONTROL RECORD	3
	CERTIFICATION RF EXPOSURE LIMIT	
3.	MPE CALCULATION FORMULA	5
5.	CLASSIFICATION	6
6.	CALCULATION RESULT OF MAXIMUM CONDUCTED POWER	6

Report Version 1



RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
FS170622N049	Original release	Jul. 12, 2017

Bureau Veritas Shenzhen Co., Ltd. Dongguan Branch No. 34, Chenwulu Section, Guantai Rd., Houjie Town, Dongguan City, Guangdong 523942, China

Tel: +86 769 8593 5656 Fax: +86 769 8593 1080 Email: <u>customerservice.dg@cn.bureauveritas.com</u>



1. CERTIFICATION

FCC ID:	VLEPL-1750R		
PRODUCT:	HD Video Drone/Quantum HD/Quantum HD+wifi streaming		
BRAND NAME:	PROPEL		
MODEL NO.:	PL-1750		
ADDITIONAL NO.:	PL-1740, PL-1741, PL-1742, PL-1743, PL-1744, PL-1745, PL-1746, PL-1747, PL-1748, PL-1749, PL-1751, PL-1752, PL-1753, PL-1754, PL-1755, PL-1756, PL-1757, PL-1758, PL-1759		
TEST SAMPLE:	Engineering Sample		
APPLICANT:	Asian Express Holdings Limited		
STANDARDS:	FCC Part 2 (Section 2.1091)		
	KDB 447498 D01		
	IEEE C95.1		

Note:

Additional models (see above table) are identical with the test model PL-1750 except the color of the model number for trading purpose.



2. RF EXPOSURE LIMIT

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

FREQUENCY RANGE (MHz)	ELECTRIC FIELD MAGNETIC FIELD POWER DENSI STRENGTH (V/m) STRENGTH (A/m) (mW/cm²)			AVERAGE TIME (minutes)		
LIMITS FOR GENERAL POPULATION / UNCONTROLLED EXPOSURE						
300-1500 F/1500 30						
1500-100,000			1.0	30		

F = Frequency in MHz

3. MPE CALCULATION FORMULA

 $Pd = (Pout^*G) / (4^*pi^*r^2)$

where

 $Pd = power density in mW/cm^2$

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

R = distance between observation point and center of the radiator in cm

4. CLASSIFICATION

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. So, this device is classified as **Mobile Device**.



5. ANTENNA GAIN

The antennas provided to the EUT, please refer to the following table:

Transmitter Circuit	Peak Gain (dBi)	Antenna Type
Chain 0	2.5	Integral Wire Antenna

6. CALCULATION RESULT OF MAXIMUM CONDUCTED POWER

The tuned conducted Average Power (declared by client)

Mode	Target Power (dBm)	Tolerance (dBm)	Lower Tolerance (dBm)	Upper Tolerance (dBm)
802.11b	13	+-2	11	15
802.11g	13	+-2	11	15

The measured conducted Average Power

Mode	Frequency (MHz)	Averaged Power (dBm)
802.11b	2412	13.71
802.11g	2412	14.15

FREQUENCY BAND (MHz)	MAX AVERAGE POWER (dBm)	ANTENNA GAIN (dBi)	DISTANCE (cm)	POWER DENSITY (mW/cm ²)	LIMIT (mW/cm²)
2412-2462	15	2.5	20	0.01119	1.0

--- END ----