

# TEST REPORT

**Applicant:** Binatone Electronics International Ltd.  
**Address of Applicant:** Floor 23A, 9 Des Voeux Road West, Sheung Wan, Hong Kong

**Equipment Under Test (EUT)**

**Product Name:** Baby Unit(2.8" HD Wi-Fi® Video Baby and Home Monitor; 5" HD Wi-Fi® Video Baby and Home Monitor)  
**Model Name.:** CN28BU, COMFORT40BU, CN50BU, COMFORT60BU  
**Trade mark:** motorola

**FCC ID:** VLJ-CN28BU  
**Canada IC:** 4522A-CN28BU  
**HVIN:** CN28BU

**Applicable standards:** CFR47 FCC Part 15: Subpart C Section 15.247  
CFR47 FCC Part 15: Subpart C Section 15.207  
CFR47 FCC Part 15: Subpart C Section 15.209  
RSS-Gen Issue 5, April 2018  
RSS-247 Issue 2, February 2017

**Date of sample receipt:** 20 Nov. 2018  
**Date of Test:** 20 Nov. 2018 to 15 Jun. 2019  
**Date of report issued:** 08 Jul. 2019  
**Test Result:** PASS\*

\* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:



Bruce Zhang  
Laboratory Manager

This report details the results of the testing carried out on one sample. The results contained in this test report do not relate to other samples of the same product and does not permit the use of the CCIS product certification mark. The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report.

This report may only be reproduced and distributed in full. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards.

This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.



Table of Contents		Page
<b>1</b>	<b>SUMMARY OF TEST RESULTS</b> .....	<b>5</b>
1.1	TEST FACTORY.....	6
1.2	MEASUREMENT UNCERTAINTY .....	6
<b>2</b>	<b>GENERAL INFORMATION</b> .....	<b>7</b>
2.1	GENERAL DESCRIPTION OF EUT .....	7
2.2	DESCRIPTION OF TEST MODES .....	9
2.3	BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED.....	10
2.4	DESCRIPTION OF NECESSARY ACCESSORIES AND SUPPORT UNITS .....	10
2.5	EQUIPMENTS LIST .....	11
<b>3</b>	<b>EMC EMISSION TEST</b> .....	<b>12</b>
3.1	CONDUCTED EMISSION MEASUREMENT .....	12
3.2	RADIATED SPURIOUS EMISSION MEASUREMENT .....	16
<b>4</b>	<b>CONDUCTED SPURIOUS &amp; BAND EDGE EMISSION</b> .....	<b>30</b>
4.1	APPLIED PROCEDURES / LIMIT .....	30
4.2	TEST PROCEDURE .....	30
4.3	DEVIATION FROM STANDARD .....	30
4.4	TEST SETUP.....	30
4.5	EUT OPERATION CONDITIONS.....	30
4.6	TEST RESULTS.....	31
<b>5</b>	<b>NUMBER OF HOPPING CHANNEL</b> .....	<b>35</b>
5.1	APPLIED PROCEDURES / LIMIT .....	35
5.2	TEST PROCEDURE .....	35
5.3	DEVIATION FROM STANDARD .....	35
5.4	TEST SETUP.....	35
5.5	EUT OPERATION CONDITIONS.....	35
5.6	TEST RESULTS.....	36
<b>6</b>	<b>AVERAGE TIME OF OCCUPANCY</b> .....	<b>37</b>
6.1	APPLIED PROCEDURES / LIMIT .....	37
6.2	TEST PROCEDURE .....	37
6.3	DEVIATION FROM STANDARD .....	37
6.4	TEST SETUP.....	37
6.5	EUT OPERATION CONDITIONS.....	37
6.6	TEST RESULTS.....	38

- 7 HOPPING CHANNEL SEPARATION MEASUREMENTS .....40**
  - 7.1 APPLIED PROCEDURES / LIMIT .....40
  - 7.2 TEST PROCEDURE .....40
  - 7.3 DEVIATION FROM STANDARD .....40
  - 7.4 TEST SETUP.....40
  - 7.5 EUT OPERATION CONDITIONS.....40
  - 7.6 TEST RESULTS.....41
- 8 BANDWIDTH TEST .....43**
  - 8.1 APPLIED PROCEDURES / LIMIT .....43
  - 8.2 TEST PROCEDURE .....43
  - 8.3 DEVIATION FROM STANDARD .....43
  - 8.4 TEST SETUP.....43
  - 8.5 EUT OPERATION CONDITIONS.....43
  - 8.6 TEST RESULTS.....44
- 9 PEAK OUTPUT POWER TEST .....46**
  - 9.1 APPLIED PROCEDURES / LIMIT .....46
  - 9.2 TEST PROCEDURE .....46
  - 9.3 DEVIATION FROM STANDARD .....46
  - 9.4 TEST SETUP.....46
  - 9.5 EUT OPERATION CONDITIONS.....46
  - 9.6 TEST RESULTS.....47
- 10 ANTENNA REQUIREMENT .....48**
  - 10.1 STANDARD REQUIREMENT .....48
  - 10.2 EUT ANTENNA .....48
- 11 APPENDIX - PHOTOS OF TEST SETUP .....49**

## 1 SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:

KDB 558074 D01 DTS Meas Guidance v05

FCC Part 15, Subpart C RSS-247 Issue 2			
Standard Section	Test Item	Judgment	Remark
FCC Part 15.207(a) RSS-Gen Clause 8.8	Conducted Emission	PASS	
FCC Part 15.247(a)(1) RSS-247 Clause 5.1(a)	20dB Bandwidth	PASS	
RSS-Gen Clause 6.7	99% Bandwidth	PASS	
FCC Part 15.247(a)(1) RSS-247 Clause 5.4(b)	Output Power	PASS	
FCC Part 15.247(d) RSS-247 Clause 3.3	Radiated Spurious Emission	PASS	
FCC Part 15.247(d) RSS-247 Clause 5.5	Conducted Spurious & Band Edge Emission	PASS	
FCC Part 15.247(a)(1) RSS-247 Clause 5.1(b)	Hopping Channel Separation	PASS	
FCC Part 15.247(a)(1) RSS-247 Clause 5.1(d)	Number of Hopping Frequency	PASS	
FCC Part 15.247(a)(1) RSS-247 Clause 5.1(d)	Dwell Time	PASS	
FCC Part 15.205	Restricted Band Edge Emission	PASS	
FCC Part 15.247(d) & 15.209(a) RSS-247 Clause 5.5	Band Edge Emission	PASS	
FCC Part 15.247(b)(4) & 15.203	Antenna Requirement	PASS	

NOTE:

- 1) 'N/A' denotes test is not applicable in this test report
- 2) All tests were performed according to the procedures in ANSI C63.10: 2013.

## 1.1 TEST FACTORY

Shenzhen Zhongjian Nanfang Testing Co., Ltd.  
 Address: No. B-C, 1/F., Building 2, Laodong No.2 Industrial Park, Xixiang Road,  
 Bao'an District, Shenzhen, Guangdong, China  
 Tel: +86-755-23118282, Fax: +86-755-23116366  
 Email: info@ccis-cb.com, Website: http://www.ccis-cb.com

The test facility is recognized, certified, or accredited by the following organizations:

- FCC - Designation No.: CN1211

Shenzhen Zhongjian Nanfang Testing Co., Ltd. has been accredited as a testing laboratory by FCC(Federal Communications Commission). The test firm Registration No. is 727551.

- ISED - CAB identifier.: CN0021

The 3m Semi-anechoic chamber of Shenzhen Zhongjian Nanfang Testing Co., Ltd. has been Registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 10106A-1.

- CNAS - Registration No.: CNAS L6048

Shenzhen Zhongjian Nanfang Testing Co., Ltd. is accredited to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration laboratories for the competence of testing. The Registration No. is CNAS L6048.

- A2LA - Registration No.: 4346.01

This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2005 General requirements for the competence of testing and calibration laboratories.

The test scope can be found as below link: <https://portal.a2la.org/scopepdf/4346-01.pdf>

## 1.2 MEASUREMENT UNCERTAINTY

Parameters	Expanded Uncertainty
Conducted Emission (9kHz ~ 30MHz)	±2.22 dB (k=2)
Radiated Emission (9kHz ~ 30MHz)	±2.76 dB (k=2)
Radiated Emission (30MHz ~ 1000MHz)	±4.28 dB (k=2)
Radiated Emission (1GHz ~ 18GHz)	±5.72 dB (k=2)
Radiated Emission (18GHz ~ 40GHz)	±2.88 dB (k=2)

## 2 GENERAL INFORMATION

### 2.1 GENERAL DESCRIPTION OF EUT

Product Name	<b>Baby Unit</b> (2.8" HD Wi-Fi® Video Baby and Home Monitor; 5" HD Wi-Fi® Video Baby and Home Monitor)	
Trade Name	motorola	
Model Name	CN28BU	
Series Model	COMFORT40BU, CN50BU, COMFORT60BU	
Model Difference	All models are fully identical except model name.	
Product Description	The EUT is a Baby Unit(2.8" HD Wi-Fi® Video Baby and Home Monitor; 5" HD Wi-Fi® Video Baby and Home Monitor) of one of the Video Baby Monitor With Wi-Fi® which supports 2.4GHz FHSS and Wi-Fi 802.11b/g/n wireless technologies. This report for 2.4GHz FHSS operation only.	
	Operation Frequency:	2402 - 2477 MHz
	Modulation Type:	GFSK
	Bit Rate of Transmitter:	1 Mbps
	Number Of Channel:	22 channels
	Antenna Designation:	Please see Note 4
	Antenna Gain (dBi):	0dBi
Channel List	Please refer to the Note 2.	
Adapter 1#	Model: S005BNU0500100 (Tenpao) Input: AC 100-240V, 0.15mA, 50/60Hz Output: DC 5.0V, 1000mA	
Adapter 2#	Model: CS6F050100FUF (Csec) Input: AC 100-240V, 0.20mA, 50/60Hz Output: DC 5.0V, 1000mA	
Battery	N/A	
Hardware version	N/A	
Software version	N/A	
Radio Hardware version	N/A	
Radio Software version	N/A	
Test Software	SecureCRT	
RF Power Setting TEST Software (power class)	1	
Connecting I/O Port(s)	Please refer to the User's Manual	

Note:

- 1 For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.

2

RF Channel and Frequency			
RF Channel	Freq.(MHz)	RF Channel	Freq.(MHz)
<b>01</b>	<b>2402</b>	12	2445
02	2404	13	2450
03	2406	14	2455
04	2408	15	2460
05	2410	16	2465
06	2415	17	2467
07	2420	18	2469
08	2425	19	2471
09	2430	20	2473
10	2435	21	2475
<b>11</b>	<b>2440</b>	<b>22</b>	<b>2477</b>

3 Note:

- 1) In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test;
- 2) Test frequencies are lowest channel: 2402 MHz, middle channel: 2440 MHz and highest channel: 2477 MHz

4

Ant	Brand	Model Name	Antenna Type	Connector	Gain (dBi)	NOTE
1	N/A	CN28BU	Integral Antenna	N/A	0	2.4G Antenna



## 2.2 DESCRIPTION OF TEST MODES

Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.


Worst Mode	Description	Data Rate
Mode 1	TX GFSK CH01	/
Mode 2	TX GFSK CH11	/
Mode 3	TX GFSK CH22	/
Mode 4	Transmitting mode	/

Note:


- 1) The measurements are performed at all Bit Rate of Transmitter, the worst data was reported
- 2) We have be tested for all avaiable U.S. voltage and frequencies(For 120V,50/60Hz and 240V, 50/60Hz) for which the device is capable of operation , and the worst case of 120V/60Hz is shown in the report
- 3) Controlled using a bespoke application on the laptop PC supplied by the customer. The application was used to enable a continuous transmission mode and to select the test channels, data rates and modulation schemes as required.

## 2.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED

Radiation Test Set



Conduction Test Set



## 2.4 DESCRIPTION OF NECESSARY ACCESSORIES AND SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	Serial No.	Note
E-2	Adapter	Tenpao	S005BNU0500100	N/A	Accessories Equipment
E-2	Adapter	Csec	CS6F050100FUF	N/A	
E-3	Personal computer	HP	500-320cx	4CV428DQYN	Auxiliary Equipment

Item	Shielded Type	Ferrite Core	Length	Note
C-1	Adapter DC Cable	NO	200cm	N/A

Note:

- 1) The support equipment was authorized by Declaration of Confirmation.
- 2) For detachable type I/O cable should be specified the length in cm in 『Length』 column.
- 3) “YES” is means “shielded” “with core”; “NO” is means “unshielded” “without core”.

## 2.5 EQUIPMENTS LIST

<b>Radio Spectrum Testing</b>				
<b>Equipment</b>	<b>Manufacturer</b>	<b>Model No.</b>	<b>Serial No.</b>	<b>Cal. Until</b>
USB RF power sensor	DARE	RPR3006W	15I00041SNO09	05.03.2020
Spectrum analyzer	Agilent	N9020A	MY51110123	01.03.2020
<b>Spurious Emission</b>				
<b>Equipment</b>	<b>Manufacturer</b>	<b>Model No.</b>	<b>Serial No.</b>	<b>Cal. Until</b>
Loop Antenna	Schwarzbeck	FMZB1519B	00044	14.03.2020
Bilog Antenna	Schwarzbeck	VULB9163	497	14.03.2020
Horn Antenna	Schwarzbeck	BBHA 9120D	1805	21.06.2020
SHF-EHF Horn Antenna	Schwarzbeck	BBHA 9170	BBHA9170582	20.11.2019
Pre-amplifier	HP	8447D	2944A09358	05.03.2020
Pre-amplifier	CD	PAP-1G18	11804	05.03.2020
EMI Test Receiver	R&S	ESRP7	101070	05.03.2020
Spectrum analyzer	R&S	FSP30	101454	05.03.2020
Spectrum analyzer	R&S	FSP40	100363	05.03.2020
Cable	ZDECL	Z108-NJ-NJ-81	1608458	05.03.2020
Cable	MICRO-COAX	MFR64639	K10742-5	05.03.2020
Cable	SUHNER	SUCOFLEX100	58193/4PE	05.03.2020
<b>Conducted Emission on AC Mains</b>				
<b>Equipment</b>	<b>Manufacturer</b>	<b>Model No.</b>	<b>Serial No.</b>	<b>Cal. Until</b>
EMI Test Receiver	R&S	ESCI	101189	05.03.2020
Pulse Limiter	Schwarzbeck	OSRAM 2306	9731	05.03.2020
LISN	CHASE	MN2050D	1447	17.03.2020
LISN	R&S	ESH3-Z5	8438621/010	20.07.2019

## 3 EMC EMISSION TEST

### 3.1 CONDUCTED EMISSION MEASUREMENT

#### 3.1.1 POWER LINE CONDUCTED EMISSION LIMITS

operating frequency band. In case the emission fall within the restricted band specified on Part 15. 207(a), 107(a), RSS-Gen Table3 limit in the table below has to be followed.

This item was performed according to the procedures in ANSI C63.10: 2013.

FREQUENCY (MHz)	Conducted Emission limit (dBuV)	
	Quasi-peak	Average
0.15 -0.5	66 - 56 *	56 - 46 *
0.50 -5.0	56.00	46.00
5.0 -30.0	60.00	50.00

Note:

- 1) The tighter limit applies at the band edges.
- 2) The limit of " \* " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.


The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz

### 3.1.2 TEST PROCEDURE

- a. The EUT was 0.8 meters from the horizontal ground plane and 0.4 meters from the vertical ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- c. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- d. LISN at least 80 cm from nearest part of EUT chassis.
- e. For the actual test configuration, please refer to the related Item –EUT Test Photos.

### 3.1.3 TEST SETUP



- Note: 1.Support units were connected to second LISN.**  
**2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes**

### 3.1.4 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.


### 3.1.5 TEST RESULT

Temperature:	22 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60Hz	Phase:	L
Test Mode:	Mode 4	Test Date:	2019-06-15
Note:	Adapter(Tenpao)		

Frequency (MHz)	Reading (dBuV)	Correct Factor(dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
0.3980	23.53	20.49	44.02	57.90	-13.88	QP
0.3980	15.73	20.49	36.22	47.90	-11.68	AVG
0.7820	20.17	20.23	40.40	56.00	-15.60	QP
0.7820	4.96	20.23	25.19	46.00	-20.81	AVG
1.2540	17.39	20.13	37.52	56.00	-18.48	QP
1.2540	5.64	20.13	25.77	46.00	-20.23	AVG
2.0820	17.16	20.05	37.21	56.00	-18.79	QP
2.0820	3.22	20.05	23.27	46.00	-22.73	AVG
4.2500	15.28	19.95	35.23	56.00	-20.77	QP
4.2500	3.36	19.95	23.31	46.00	-22.69	AVG
16.8260	14.56	19.97	34.53	60.00	-25.47	QP
16.8260	1.60	19.97	21.57	50.00	-28.43	AVG

Remark:

1. All readings are Quasi-Peak and Average values.
2. Margin = Result (Result =Reading + Factor )–Limit




Temperature:	22 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60Hz	Phase:	N
Test Mode:	Mode 4	Test Date:	2019-06-15
Note:	Adapter(Tenpao)		

Frequency (MHz)	Reading (dBuV)	Correct Factor(dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
0.3820	30.78	20.54	51.32	58.24	-6.92	QP
0.3820	21.67	20.54	42.21	48.24	-6.03	AVG
0.8220	23.76	20.22	43.98	56.00	-12.02	QP
0.8220	10.33	20.22	30.55	46.00	-15.45	AVG
1.5060	22.17	20.11	42.28	56.00	-13.72	QP
1.5060	8.91	20.11	29.02	46.00	-16.98	AVG
2.1460	20.72	20.05	40.77	56.00	-15.23	QP
2.1460	6.81	20.05	26.86	46.00	-19.14	AVG
3.4620	18.49	19.97	38.46	56.00	-17.54	QP
3.4620	6.21	19.97	26.18	46.00	-19.82	AVG
9.6540	14.09	20.10	34.19	60.00	-25.81	QP
9.6540	0.72	20.10	20.82	50.00	-29.18	AVG

Remark:

1. All readings are Quasi-Peak and Average values.
2. Margin = Result (Result =Reading + Factor )–Limit



## 3.2 RADIATED SPURIOUS EMISSION MEASUREMENT

### 3.2.1 RADIATED EMISSION LIMITS

in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the Restricted band specified on Part15.205(a)&209(a) and RSS-247 Issue 2 limit in the table and according to ANSI C63.10-2013 below has to be followed.

LIMITS OF RADIATED EMISSION MEASUREMENT (0.009MHz - 1000MHz)

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

LIMITS OF RADIATED EMISSION MEASUREMENT (1000MHz-25GHz)

FREQUENCY (MHz)	(dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

For Radiated Emission

Spectrum Parameter	Setting
Attenuation	Auto
Detector	Peak/AV
Start Frequency	1000 MHz(Peak/AV)
Stop Frequency	10th carrier hamonic(Peak/AV)
RB / VB (emission in restricted	1 MHz /3MHz

For Band edge

Spectrum Parameter	Setting
Detector	Peak/AV
Start/Stop Frequency	Lower Band Edge: 2300 to 2422 MHz Upper Band Edge: 2452 to 2500 MHz
RB / VB (emission in restricted band)	1 MHz /3MHz



Receiver Parameter	Setting
Start ~ Stop Frequency	9kHz~90kHz / RB 200Hz for PK & AV
Start ~ Stop Frequency	90kHz~110kHz / RB 200Hz for QP
Start ~ Stop Frequency	110kHz~490kHz / RB 200Hz for PK & AV
Start ~ Stop Frequency	490kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

### 3.2.2 TEST PROCEDURE


- a) The measuring distance of at 3 m shall be used for measurements at frequency 0.009MHz up to 1GHz. For frequencies above 1GHz, any suitable measuring distance may be used.
- b) The EUT was placed on the top of a rotating table 0.8 meters (above 1GHz is 1.5 m) above the ground at a 3 meter anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- c) The height of the equipment shall be 0.8 m (above 1GHz is 1.5 m); the height of the test antenna shall vary between 1 m to 4 m. Horizontal and vertical polarizations of the antenna are set to make the measurement
- d) The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- e) If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
- f) For the actual test configuration, please refer to the related Item –EUT Test Photos.

**Note:**


*Both horizontal and vertical antenna polarities were tested and performed test to three orthogonal axis. The worst case emissions were reported*

## 3.2.3 TEST SETUP


### a) Radiated Emission Test-Up Frequency Below 30MHz



### b) Radiated Emission Test-Up Frequency 30MHz~1GHz



### c) Radiated Emission Test-Up Frequency Above 1GHz



## 3.2.4 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.

### 3.2.5 FIELD STRENGTH CALCULATION

The field strength is calculated by adding the Antenna Factor and Cable Factor and subtracting the Amplifier Gain and Duty Cycle Correction Factor (if any) from the measured reading. The basic equation with a sample calculation is as follows:

$$FS = RA + AF + CL - AG$$

Where

FS = Field Strength

CL = Cable Attenuation Factor (Cable Loss)

RA = Reading Amplitude

AG = Amplifier Gain

AF = Antenna Factor

For example

Frequency (MHz)	FS (dB $\mu$ V/m)	RA (dB $\mu$ V/m)	AF (dB)	CL (dB)	AG (dB)	Factor (dB)
300	40	58.1	12.2	1.6	31.9	-18.1

$$\text{Factor} = \text{AF} + \text{CL} - \text{AG}$$

### 3.2.6 TEST RESULT

9KHz-30MHz

Temperature:	25.4 °C	Relative Humidity:	56%
Test Voltage:	AC 120V/60Hz	Polarization:	--
Test Mode:	TX Mode		

Freq. (MHz)	Reading (dBuV/m)	Limit (dBuV/m)	Margin (dB)	State P/F	Test Result
--	--	--	--	--	PASS
--	--	--	--	--	PASS

Note:

The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

Distance extrapolation factor = 40 log (specific distance/test distance)(dB);

Limit line = specific limits(dBuV) + distance extrapolation factor.

(30MHz - 1000MHz)


Temperature:	25.4 °C	Relative Humidity:	56%
Test Voltage:	AC 120V/60Hz	Polarization:	Horizontal
Test Mode:	Mode 1/2/3 (Mode 3 worst mode)	Test Date:	2019-06-15
Note:	Adapter(Tenpao)		

Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
30.8535	27.35	-11.62	15.73	40.00	-24.27	QP
68.3906	33.27	-24.14	9.13	40.00	-30.87	QP
191.0738	35.23	-20.24	14.99	43.50	-28.51	QP
325.5957	47.16	-14.12	33.04	46.00	-12.96	QP
625.0780	47.27	-6.43	40.84	46.00	-5.16	QP
776.8777	44.19	-3.18	41.01	46.00	-4.99	QP

Remark:

1. Margin = Result (Result =Reading + Factor )-Limit

80.0 dBuV/m




Temperature:	25.4 °C	Relative Humidity:	56%
Test Voltage:	AC 120V/60Hz	Polarization:	Vertical
Test Mode:	Mode 1/2/3 (Mode 3 worst mode)	Test Date:	2019-06-15
Note:	Adapter(Tenpao)		

Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
61.9951	49.23	-24.30	24.93	40.00	-15.07	QP
108.6470	42.26	-18.46	23.80	43.50	-19.70	QP
325.5957	55.13	-14.12	41.01	46.00	-4.99	QP
475.4990	50.69	-9.57	41.12	46.00	-4.88	QP
625.0780	48.12	-6.43	41.69	46.00	-4.31	QP
975.7527	43.31	-0.14	43.17	54.00	-10.83	QP

Remark:.

1. Margin = Result (Result =Reading + Factor )–Limit


80.0 dBuV/m



(1000MHz-25GHz) Restricted band and Spurious emission Requirements

**Low  
vertical**


RSE\_FCC Test Case\_FCC 15C 1GHz-25GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	OverLimit (dB)	Detector	ANT	Verdict
1**	1864.000	27.17	-1.06	54.0	-26.83	AV	V	Pass
1	1864.000	36.51	-1.06	74.0	-37.49	Peak	V	Pass
2**	7500.000	23.34	10.47	54.0	-30.66	AV	V	Pass
2	7500.000	33.85	10.47	74.0	-40.15	Peak	V	Pass
3**	11330.000	29.14	15.79	54.0	-24.86	AV	V	Pass
3	11330.000	40.19	15.79	74.0	-33.81	Peak	V	Pass
4**	14428.000	41.04	25.10	54.0	-12.96	AV	V	Pass
4	14428.000	50.17	25.10	74.0	-23.83	Peak	V	Pass
5**	21976.001	44.03	23.89	54.0	-9.97	AV	V	Pass
5	21976.001	55.36	23.89	74.0	-18.64	Peak	V	Pass
6**	24196.000	45.91	23.24	54.0	-8.09	AV	V	Pass
6	24196.000	55.81	23.24	74.0	-18.19	Peak	V	Pass

## Horizontal


RSE\_FCC Test Case\_FCC 15C 1GHz-25GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	OverLimit (dB)	Detector	ANT	Verdict
1**	1314.000	25.52	-4.64	54.0	-28.48	AV	H	Pass
1	1314.000	35.69	-4.64	74.0	-38.31	Peak	H	Pass
2**	1860.000	26.64	-1.10	54.0	-27.36	AV	H	Pass
2	1860.000	36.90	-1.10	74.0	-37.10	Peak	H	Pass
3**	8000.000	24.54	10.93	54.0	-29.46	AV	H	Pass
3	8000.000	33.71	10.93	74.0	-40.29	Peak	H	Pass
4**	14404.000	40.52	24.76	54.0	-13.48	AV	H	Pass
4	14404.000	50.50	24.76	74.0	-23.50	Peak	H	Pass
5**	21268.001	44.38	24.07	54.0	-9.62	AV	H	Pass
5	21268.001	54.40	24.07	74.0	-19.60	Peak	H	Pass
6**	23704.001	45.91	23.40	54.0	-8.09	AV	H	Pass
6	23704.001	56.87	23.40	74.0	-17.13	Peak	H	Pass

**Middle  
vertical**

RSE\_FCC Test Case\_FCC 15C 1GHz-25GHz




No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	OverLimit (dB)	Detector	ANT	Verdict
1**	24952.001	45.82	23.01	54.0	-8.18	AV	V	Pass
1	24952.001	57.34	23.01	74.0	-16.66	Peak	V	Pass
2**	21748.001	45.44	23.95	54.0	-8.56	AV	V	Pass
2	21748.001	56.62	23.95	74.0	-17.38	Peak	V	Pass
3**	14368.000	42.73	24.92	54.0	-11.27	AV	V	Pass
3	14368.000	52.44	24.92	74.0	-21.56	Peak	V	Pass
4**	2494.000	29.13	1.27	54.0	-24.87	AV	V	Pass
4	2494.000	38.87	1.27	74.0	-35.13	Peak	V	Pass
5**	1014.000	24.14	-5.41	54.0	-29.86	AV	V	Pass
5	1014.000	31.91	-5.41	74.0	-42.09	Peak	V	Pass
6**	1400.000	24.39	-4.30	54.0	-29.61	AV	V	Pass
6	1400.000	35.40	-4.30	74.0	-38.60	Peak	V	Pass



## Horizontal


RSE\_FCC Test Case\_FCC 15C 1GHz-25GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	OverLimit (dB)	Detector	ANT	Verdict
1**	24231.999	46.48	23.23	54.0	-7.52	AV	H	Pass
1	24231.999	56.50	23.23	74.0	-17.50	Peak	H	Pass
2**	14644.000	40.47	23.10	54.0	-13.53	AV	H	Pass
2	14644.000	51.70	23.10	74.0	-22.30	Peak	H	Pass
3**	5800.000	19.06	3.53	54.0	-34.94	AV	H	Pass
3	5800.000	38.30	3.53	74.0	-35.70	Peak	H	Pass
4**	2444.000	29.12	1.19	54.0	-24.88	AV	H	Pass
4	2444.000	38.34	1.19	74.0	-35.66	Peak	H	Pass
5**	1968.000	26.04	-2.51	54.0	-27.96	AV	H	Pass
5	1968.000	36.56	-2.51	74.0	-37.44	Peak	H	Pass
6**	1526.000	24.55	-4.13	54.0	-29.45	AV	H	Pass
6	1526.000	34.60	-4.13	74.0	-39.40	Peak	H	Pass

## High vertical


RSE\_FCC Test Case\_FCC 15C 1GHz-25GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	OverLimit (dB)	Detector	ANT	Verdict
1**	1902.000	27.85	-0.68	54.0	-26.15	AV	V	Pass
1	1902.000	37.44	-0.68	74.0	-36.56	Peak	V	Pass
2**	2504.000	27.99	-0.42	54.0	-26.01	AV	V	Pass
2	2504.000	37.50	-0.42	74.0	-36.50	Peak	V	Pass
3**	8040.000	23.63	10.41	54.0	-30.37	AV	V	Pass
3	8040.000	34.40	10.41	74.0	-39.60	Peak	V	Pass
4**	14416.000	41.34	25.52	54.0	-12.66	AV	V	Pass
4	14416.000	50.25	25.52	74.0	-23.75	Peak	V	Pass
5**	21327.999	43.46	24.05	54.0	-10.54	AV	V	Pass
5	21327.999	55.03	24.05	74.0	-18.97	Peak	V	Pass
6**	24184.001	45.82	23.25	54.0	-8.18	AV	V	Pass
6	24184.001	56.41	23.25	74.0	-17.59	Peak	V	Pass

## Horizontal


RSE\_FCC Test Case\_FCC 15C 1GHz-25GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	OverLimit (dB)	Detector	ANT	Verdict
1**	1868.000	26.82	-1.01	54.0	-27.18	AV	H	Pass
1	1868.000	36.93	-1.01	74.0	-37.07	Peak	H	Pass
2**	7840.000	23.55	9.75	54.0	-30.45	AV	H	Pass
2	7840.000	34.00	9.75	74.0	-40.00	Peak	H	Pass
3**	11340.000	30.58	16.89	54.0	-23.42	AV	H	Pass
3	11340.000	40.15	16.89	74.0	-33.85	Peak	H	Pass
4**	14404.000	40.44	24.76	54.0	-13.56	AV	H	Pass
4	14404.000	50.45	24.76	74.0	-23.55	Peak	H	Pass
5**	21700.000	45.08	23.96	54.0	-8.92	AV	H	Pass
5	21700.000	56.37	23.96	74.0	-17.63	Peak	H	Pass
6**	24256.000	45.79	23.22	54.0	-8.21	AV	H	Pass
6	24256.000	56.57	23.22	74.0	-17.43	Peak	H	Pass


## 3.2.7 TEST RESULTS (RESTRICTED BAND)

### Low Horizontal




No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2334.216	58.77	-11.12	47.65	74.00	-26.35	peak
2	2390.000	58.31	-10.75	47.56	74.00	-26.44	peak

### Vertical




No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2366.456	58.62	-10.90	47.72	74.00	-26.28	peak
2	2390.000	55.31	-10.75	44.56	74.00	-29.44	peak

## High Horizontal



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	56.96	-10.29	46.67	74.00	-27.33	peak
2	2521.425	57.89	-10.15	47.74	74.00	-26.26	peak

## Vertical



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	57.59	-10.29	47.30	74.00	-26.70	peak
2	2515.875	59.32	-10.17	49.15	74.00	-24.85	peak

## 4 CONDUCTED SPURIOUS & BAND EDGE EMISSION

### 4.1 APPLIED PROCEDURES / LIMIT

According to FCC Part 15.247(d) and RSS-247 Clause 5.5, in any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

### 4.2 TEST PROCEDURE

Spectrum Parameter	Setting
Detector	Peak
Start/Stop Frequency	30 MHz to 10th carrier harmonic
RB / VB (emission in restricted band)	100 KHz/300 KHz
Trace-Mode:	Max hold


For Band edge

Spectrum Parameter	Setting
Detector	Peak
Start/Stop Frequency	Lower Band Edge: 2300 to 2422 MHz Upper Band Edge: 2452 to 2500 MHz
RB / VB (emission in restricted band)	100 KHz/300 KHz
Trace-Mode:	Max hold

### 4.3 DEVIATION FROM STANDARD

No deviation.

### 4.4 TEST SETUP



The EUT which is powered by the Adapter, is coupled to the Spectrum Analyzer; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading.

Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. In order to make an accurate measurement, set the span greater than RBW.


### 4.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.


## 4.6 TEST RESULTS

Temperature :	25 °C	Relative Humidity :	60%
Test Voltage :	AC 120V/60Hz	Test Mode :	TX Mode /CH01, CH11, CH22


### CH 01



### CH 11




## CH 22







## CH 01




## CH 22



## CH 01



## CH 22



## 5 NUMBER OF HOPPING CHANNEL

### 5.1 APPLIED PROCEDURES / LIMIT

FCC Part 15.247, Subpart C RSS-247 Issue 2				
Section	Test Item	Limit	Frequency Range (MHz)	Result
FCC Part 15.247(a)(1) RSS-247 Clause 5.1(d)	Number of Hopping Channel	≥15	2400-2483.5	PASS

Spectrum Parameters	Setting
Attenuation	Auto
Span Frequency	> Operating FrequencyRange
RB	1MHz
VB	1MHz
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

### 5.2 TEST PROCEDURE

- 1) The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below
- 2) Spectrum Setting : RBW= 1MHz, VBW=1MHz, Sweep time = Auto.

### 5.3 DEVIATION FROM STANDARD

No deviation.

### 5.4 TEST SETUP



### 5.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.


## 5.6 TEST RESULTS

Temperature:	25 °C	Relative Humidity:	60%
Test Voltage:	AC 120V/60Hz	Test Mode:	Hopping mode

Number of Hopping Channel

22

### Hopping channel



## 6 AVERAGE TIME OF OCCUPANCY

### 6.1 APPLIED PROCEDURES / LIMIT

FCC Part 15.247, Subpart C RSS-247 Issue 2				
Section	Test Item	Limit	Frequency Range (MHz)	Result
FCC Part 15.247(a)(1) RSS-247 Clause 5.1(d)	Average Time of Occupancy	0.4sec	2400-2483.5	PASS


### 6.2 TEST PROCEDURE

- 1) The transmitter output (antenna port) was connected to the spectrum analyzer
- 2) Set RBW =1MHz/VBW =3MHz.
- 3) Use a video trigger with the trigger level set to enable triggering only on full pulses.
- 4) Sweep Time is more than once pulse time.
- 5) Set the center frequency on any frequency would be measure and set the frequency span to zero span.
- 6) Measure the maximum time duration of one single pulse.
- 7) Measure the maximum burst number of one hopping period.
- 8) A Period Time =  $22 \times 0.4 = 8.8$  S

### 6.3 DEVIATION FROM STANDARD

No deviation.

### 6.4 TEST SETUP



### 6.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.


## 6.6 TEST RESULTS

Temperature:	25 °C	Relative Humidity:	60%
Test Voltage:	AC 120V/60Hz	Test Mode:	Hopping mode


Frequency (MHz)	Pulse Duration(ms)	Pulse number	Dwell Time(s)	Limits(s)
2402MHz	2.483	109	0.271	0.4
2477MHz	1.192	72	0.086	0.4

### CH01

#### Pulse Duration




#### Pulse number




## CH22

### Pulse Duration



### Pulse number



## 7 HOPPING CHANNEL SEPARATION MEASUREMENT

### 7.1 APPLIED PROCEDURES / LIMIT

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	> 20 dB Bandwidth or Channel Separation
RB	30 kHz (20dB Bandwidth) / 30 kHz (Channel Separation)
VB	100 kHz (20dB Bandwidth) / 100 kHz (Channel Separation)
Detector	Peak
Trace	Max Hold
Sweep Time	Auto


### 7.2 TEST PROCEDURE

- 1) The transmitter output (antenna port) was connected to the spectrum analyser in peak hold mode.
- 2) The resolution bandwidth of 30 kHz and the video bandwidth of 100 kHz were utilised for 20 dB bandwidth measurement.
- 3) The resolution bandwidth of 30 kHz and the video bandwidth of 100 kHz were utilised for channel separation measurement.

### 7.3 DEVIATION FROM STANDARD

No deviation.

### 7.4 TEST SETUP



### 7.5 EUT OPERATION CONDITIONS

The EUT was programmed to be in continuously transmitting mode.




## 7.6 TEST RESULTS

Temperature:	25 °C	Relative Humidity:	60%
Test Voltage:	AC 120V/60Hz	Test Mode:	Hopping mode


Test Mode	Frequency	Ch. Separation (MHz)	Limit	Result
TX	2402 MHz	1.996	1.387	Complies
	2440 MHz	5.330	1.643	Complies
	2477 MHz	2.012	1.603	Complies

Ch. Separation Limits: > two-thirds 20dB bandwidth


### CH01



## CH11



## CH22



## 8 BANDWIDTH TEST

### 8.1 APPLIED PROCEDURES / LIMIT

FCC Part 15.247, Subpart C RSS-247 Issue 2 & RSS-Gen Issue 5				
Section	Test Item	Limit	Frequency Range (MHz)	Result
FCC Part 15.247(a)(1) RSS-247 Clause 5.1(a)	Bandwidth	(20dB Bandwidth)	2400-2483.5	PASS
RSS-Gen Clause 6.7	99% Bandwidth	-	2400-2483.5	PASS


### 8.2 TEST PROCEDURE

The automatic bandwidth measurement capability of an instrument may be employed using the X dB bandwidth mode with X set to 6 dB, if the functionality described above (i.e., RBW = 1% - 5% OBW, VBW ≥ 3RBW, peak detector with maximum hold) is implemented by the instrumentation function. When using this capability, care shall be taken so that the bandwidth measurement is not influenced by any intermediate power nulls in the fundamental emission that might be ≥ 6 dB.

### 8.3 DEVIATION FROM STANDARD

No deviation.

### 8.4 TEST SETUP



### 8.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.


## 8.6 TEST RESULTS

Temperature:	25 °C	Relative Humidity:	60%
Test Voltage:	AC 120V/60Hz	Test Mode:	TX b Mode /CH01, CH11, CH22


Remark: PEAK DETECTOR IS USED

Test Mode	Frequency (MHz)	20dB Bandwidth (MHz)	99% Bandwidth (MHz)	Limit of 20dB Bandwidth (MHz)	Result
TX	2402.00	2.081	2.1089	N/A	PASS
	2440.00	2.465	2.6454	N/A	PASS
	2477.00	2.404	2.4070	N/A	PASS


### TX CH 01



## TX CH 11



## TX CH 22



## 9 PEAK OUTPUT POWER TEST

### 9.1 APPLIED PROCEDURES / LIMIT

FCC Part 15.247, Subpart C RSS-247 Issue 2				
Section	Test Item	Limit	Frequency Range (MHz)	Result
FCC Part 15.247(a)(1) RSS-247 Clause 5.4(b)	Output Power	1 W or 0.125W if channel separation > 2/3 bandwidth provided the systems operate with an output power no greater than 125 mW (20.97dBm)	2400-2483.5	PASS


### 9.2 TEST PROCEDURE

- a. The EUT was directly connected to the Power Sensor & PC

### 9.3 DEVIATION FROM STANDARD

No deviation.

### 9.4 TEST SETUP



### 9.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.

## 9.6 TEST RESULTS

Temperature :	25 °C	Relative Humidity :	60%
Test Voltage :	AC 120V/60Hz		

Test Channel	Frequency (MHz)	Conducted Output Power		Limit (dBm)
		Peak(dBm)	AVG(dBm)	
CH01	2402.00	19.17	14.61	20.97
CH11	2440.00	19.50	15.03	20.97
CH22	2477.00	19.62	15.18	20.97

Note:

1. The cable loss and antenna gain are taken into account in results.
2. Antenna gain(G): 0 dBi
3. The max. e.i.r.p = conducted power + antenna gain = 19.62 dBm

## 10 ANTENNA REQUIREMENT

### 10.1 STANDARD REQUIREMENT

15.203 and RSS-Gen Issue 5 requirement: For intentional device, according to 15.203 and RSS-Gen Issue 5: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

### 10.2 EUT ANTENNA

The EUT antenna is Integral Antenna. It comply with the standard requirement.



