


Shenzhen EMTEK Co., Ltd.
Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China
www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282



Radiated Emission Measurement



Site 3m Chamber #2 Polarization: **Vertical** Temperature: 24 C
 Limit: (RE)FCC PART 15C Power: AC 120V/60Hz Humidity: 53 %
 EUT: ID Camera
 M/N: Focus 72
 Mode: 11b 2462
 Note:

| No. | Mk. | Freq. | Reading Level | Correct Factor | Measurement | Limit | Over | Antenna Height | Table Degree | Comment |
|-----|-----|----------|---------------|----------------|-------------|--------|--------|----------------|--------------|---------|
| | | MHz | dBuV | dB | dBuV/m | dBuV/m | dB | cm | degree | |
| 1 | | 15433.00 | 62.75 | -10.96 | 51.79 | 74.00 | -22.21 | peak | | |
| 2 | * | 15433.00 | 46.26 | -10.96 | 35.30 | 54.00 | -18.70 | AVG | | |

*:Maximum data x:Over limit !:over margin


Operator: KK

Wi-Fi 802.11 g mode, 54 Mbps
30MHz - 1GHz

Shenzhen EMTEK Co., Ltd.
Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China
www.emtek.com.cn Tel:+86-755-2695 4280 Fax:+86-755-2695 4282



Radiated Emission Measurement



Site 3m Chamber #2 Polarization: **Horizontal** Temperature: 22 C
Limit: (RE)FCC PART 15C Power: AC 120V/60Hz Humidity: 55 %
EUT: ID Camera
M/N: Focus 72
Mode:TX 11g Low
Note:

| No. | Mk. | Freq. MHz | Reading Level dBuV | Correct Factor dB | Measure- ment dBuV/m | Limit dBuV/m | Over dB | Antenna Height cm | Table Degree degree | Comment |
|-----|-----|--------------|--------------------------|-------------------------|----------------------------|-----------------|------------|-------------------------|---------------------------|---------|
| 1 | | 199.7500 | 45.49 | -14.19 | 31.30 | 43.50 | -12.20 | QP | | |
| 2 | * | 272.5000 | 46.64 | -12.21 | 34.43 | 46.00 | -11.57 | QP | | |
| 3 | | 400.5400 | 42.32 | -8.66 | 33.66 | 46.00 | -12.34 | QP | | |
| 4 | | 475.2300 | 34.34 | -7.03 | 27.31 | 46.00 | -18.69 | QP | | |
| 5 | | 780.7800 | 32.15 | -1.03 | 31.12 | 46.00 | -14.88 | QP | | |
| 6 | | 818.6100 | 33.90 | -0.39 | 33.51 | 46.00 | -12.49 | QP | | |


*:Maximum data x:Over limit !:over margin

Operator: KK

Shenzhen EMTEK Co., Ltd.
Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China
www.emtek.com.cn Tel:+86-755-2695 4280 Fax:+86-755-2695 4282



Radiated Emission Measurement



Site 3m Chamber #2 Polarization: **Vertical** Temperature: 22 C
Limit: (RE)FCC PART 15C Power: AC 120V/60Hz Humidity: 55 %
EUT: ID Camera
M/N: Focus 72
Mode:TX 11g Low
Note:

| No. | Mk. | Freq. MHz | Reading Level dBuV | Correct Factor dB | Measure- ment dBuV/m | Limit dBuV/m | Over dB | Antenna Height cm | Table Degree | Comment |
|-----|-----|--------------|--------------------------|-------------------------|----------------------------|-----------------|------------|-------------------------|-----------------|---------|
| 1 | | 115.3600 | 36.76 | -15.75 | 21.01 | 43.50 | -22.49 | QP | | |
| 2 | | 199.7500 | 38.76 | -14.19 | 24.57 | 43.50 | -18.93 | QP | | |
| 3 | * | 400.5400 | 39.90 | -8.66 | 31.24 | 46.00 | -14.76 | QP | | |
| 4 | | 490.7500 | 36.76 | -6.67 | 30.09 | 46.00 | -15.91 | QP | | |
| 5 | | 525.6700 | 33.14 | -5.78 | 27.36 | 46.00 | -18.64 | QP | | |
| 6 | | 600.3600 | 31.10 | -3.78 | 27.32 | 46.00 | -18.68 | QP | | |


*:Maximum data x:Over limit !:over margin

Operator: KK

Shenzhen EMTEK Co., Ltd.
Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China
www.emtek.com.cn Tel:+86-755-2695 4280 Fax:+86-755-2695 4282



Radiated Emission Measurement



Site 3m Chamber #2 Polarization: **Horizontal** Temperature: 22 C
Limit: (RE)FCC PART 15C Power: AC 120V/60Hz Humidity: 55 %
EUT: ID Camera
M/N: Focus 72
Mode:TX 11g Mid
Note:

| No. | Mk. | Freq. MHz | Reading Level dBuV | Correct Factor dB | Measure- ment dBuV/m | Limit dBuV/m | Over dB | Detector | Antenna Height cm | Table Degree | Comment |
|-----|-----|--------------|--------------------------|-------------------------|----------------------------|-----------------|------------|----------|-------------------------|-----------------|---------|
| 1 | | 149.3100 | 40.04 | -18.32 | 21.72 | 43.50 | -21.78 | QP | | | |
| 2 | | 199.7500 | 43.59 | -14.19 | 29.40 | 43.50 | -14.10 | QP | | | |
| 3 | | 250.1900 | 43.21 | -12.79 | 30.42 | 46.00 | -15.58 | QP | | | |
| 4 | | 272.5000 | 46.33 | -12.21 | 34.12 | 46.00 | -11.88 | QP | | | |
| 5 | | 400.5400 | 39.52 | -8.66 | 30.86 | 46.00 | -15.14 | QP | | | |
| 6 | * | 818.6100 | 34.71 | -0.39 | 34.32 | 46.00 | -11.68 | QP | | | |


*:Maximum data x:Over limit l:over margin

Operator: KK

Shenzhen EMTEK Co., Ltd.
Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China
www.emtek.com.cn Tel:+86-755-2695 4280 Fax:+86-755-2695 4282



Radiated Emission Measurement



Site 3m Chamber #2 Polarization: **Vertical** Temperature: 22 C
Limit: (RE)FCC PART 15C Power: AC 120V/60Hz Humidity: 55 %
EUT: ID Camera
M/N: Focus 72
Mode:TX 11g Mid
Note:

| No. | Mk. | Freq. MHz | Reading Level dBuV | Correct Factor dB | Measure- ment dBuV/m | Limit dBuV/m | Over dB | Antenna Height cm | Table Degree | Comment |
|-----|-----|--------------|--------------------------|-------------------------|----------------------------|-----------------|------------|-------------------------|-----------------|---------|
| 1 | | 120.2100 | 38.39 | -16.63 | 21.76 | 43.50 | -21.74 | QP | | |
| 2 | | 199.7500 | 39.54 | -14.19 | 25.35 | 43.50 | -18.15 | QP | | |
| 3 | | 400.5400 | 36.88 | -8.66 | 28.22 | 46.00 | -17.78 | QP | | |
| 4 | * | 490.7500 | 34.97 | -6.67 | 28.30 | 46.00 | -17.70 | QP | | |
| 5 | | 600.3600 | 30.91 | -3.78 | 27.13 | 46.00 | -18.87 | QP | | |
| 6 | | 828.3100 | 27.63 | -0.19 | 27.44 | 46.00 | -18.56 | QP | | |


*:Maximum data x:Over limit !:over margin

Operator: KK

Shenzhen EMTEK Co., Ltd.
Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China
www.emtek.com.cn Tel:+86-755-2695 4280 Fax:+86-755-2695 4282



Radiated Emission Measurement



Site 3m Chamber #2 Polarization: **Horizontal** Temperature: 22 C
Limit: (RE)FCC PART 15C Power: AC 120V/60Hz Humidity: 55 %
EUT: ID Camera
M/N: Focus 72
Mode:TX 11g High
Note:

| No. | Mk. | Freq. MHz | Reading Level dBuV | Correct Factor dB | Measure- ment dBuV/m | Limit dBuV/m | Over dB | Detector | Antenna Height cm | Table Degree | Comment |
|-----|-----|--------------|--------------------------|-------------------------|----------------------------|-----------------|------------|----------|-------------------------|-----------------|---------|
| 1 | | 62.0100 | 34.15 | -15.07 | 19.08 | 40.00 | -20.92 | QP | | | |
| 2 | | 199.7500 | 44.59 | -14.19 | 30.40 | 43.50 | -13.10 | QP | | | |
| 3 | | 250.1900 | 43.61 | -12.79 | 30.82 | 46.00 | -15.18 | QP | | | |
| 4 | | 272.5000 | 44.51 | -12.21 | 32.30 | 46.00 | -13.70 | QP | | | |
| 5 | | 400.5400 | 41.78 | -8.66 | 33.12 | 46.00 | -12.88 | QP | | | |
| 6 | * | 818.6100 | 34.62 | -0.39 | 34.23 | 46.00 | -11.77 | QP | | | |


*:Maximum data x:Over limit l:over margin

Operator: KK

Shenzhen EMTEK Co., Ltd.
Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China
www.emtek.com.cn Tel:+86-755-2695 4280 Fax:+86-755-2695 4282



Radiated Emission Measurement



Site 3m Chamber #2 Polarization: **Vertical** Temperature: 22 C
Limit: (RE)FCC PART 15C Power: AC 120V/60Hz Humidity: 55 %
EUT: ID Camera
M/N: Focus 72
Mode:TX 11g High
Note:

| No. | Mk. | Freq. MHz | Reading Level dBuV | Correct Factor dB | Measure- ment dBuV/m | Limit dBuV/m | Over dB | Antenna Height cm | Table Degree | Comment |
|-----|-----|--------------|--------------------------|-------------------------|----------------------------|-----------------|------------|-------------------------|-----------------|---------|
| 1 | | 120.2100 | 37.71 | -16.63 | 21.08 | 43.50 | -22.42 | QP | | |
| 2 | | 199.7500 | 36.96 | -14.19 | 22.77 | 43.50 | -20.73 | QP | | |
| 3 | | 400.5400 | 37.57 | -8.66 | 28.91 | 46.00 | -17.09 | QP | | |
| 4 | * | 475.2300 | 37.10 | -7.03 | 30.07 | 46.00 | -15.93 | QP | | |
| 5 | | 525.6700 | 33.18 | -5.78 | 27.40 | 46.00 | -18.60 | QP | | |
| 6 | | 589.6900 | 30.84 | -4.07 | 26.77 | 46.00 | -19.23 | QP | | |

*:Maximum data x:Over limit !:over margin


Operator: KK

1GHz - 18GHz

Shenzhen EMTEK Co., Ltd.
Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China
www.emtek.com.cn Tel:+86-755-2695 4280 Fax:+86-755-2695 4282



Radiated Emission Measurement



Site 3m Chamber #2 Polarization: **Horizontal** Temperature: 24 C
Limit: (RE)FCC PART 15C Power: AC 120V/60Hz Humidity: 53 %
EUT: ID Camera
M/N: Focus 72
Mode:11g 2412
Note:

| No. | Mk. | Freq. | Reading Level | Correct Factor | Measurement | Limit | Over | Antenna Height | Table Degree | Comment |
|-----|-----|----------|---------------|----------------|-------------|--------|--------|----------------|--------------|---------|
| | | MHz | dBuV | dB | dBuV/m | dBuV/m | dB | cm | degree | |
| 1 | | 14974.00 | 61.46 | -9.55 | 51.91 | 74.00 | -22.09 | peak | | |
| 2 | * | 14974.00 | 45.65 | -9.55 | 36.10 | 54.00 | -17.90 | AVG | | |


*:Maximum data x:Over limit !:over margin

Operator: KK

Shenzhen EMTEK Co., Ltd.
Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China
www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282



Radiated Emission Measurement



Site 3m Chamber #2 Polarization: **Vertical** Temperature: 24 C
Limit: (RE)FCC PART 15C Power: AC 120V/60Hz Humidity: 53 %
EUT: ID Camera
M/N: Focus 72
Mode:11g 2412
Note:

| No. | Mk. | Freq. | Reading Level | Correct Factor | Measurement | Limit | Over | Antenna Height | Table Degree | |
|-----|-----|----------|---------------|----------------|-------------|--------|--------|----------------|--------------|---------|
| | | MHz | dBuV | dB | dBuV/m | dBuV/m | dB | cm | degree | Comment |
| 1 | | 15773.00 | 65.98 | -12.04 | 53.94 | 74.00 | -20.06 | peak | | |
| 2 | * | 15773.00 | 50.14 | -12.04 | 38.10 | 54.00 | -15.90 | AVG | | |


*:Maximum data x:Over limit !:over margin

Operator: KK

Shenzhen EMTEK Co., Ltd.
Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China
www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282



Radiated Emission Measurement



Site 3m Chamber #2 Polarization: **Horizontal** Temperature: 24 C
 Limit: (RE)FCC PART 15C Power: AC 120V/60Hz Humidity: 53 %
 EUT: ID Camera
 M/N: Focus 72
 Mode:11g 2437
 Note:

| No. | Mk. | Freq. | Reading Level | Correct Factor | Measurement | Limit | Over | Antenna Height | Table Degree | Comment |
|-----|-----|----------|---------------|----------------|-------------|--------|--------|----------------|--------------|---------|
| | | MHz | dBuV | dB | dBuV/m | dBuV/m | dB | cm | degree | |
| 1 | | 15773.00 | 64.03 | -12.04 | 51.99 | 74.00 | -22.01 | peak | | |
| 2 | * | 15773.00 | 45.94 | -12.04 | 33.90 | 54.00 | -20.10 | AVG | | |


*:Maximum data x:Over limit !:over margin

Operator: KK

Shenzhen EMTEK Co., Ltd.
Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China
www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282



Radiated Emission Measurement



Site 3m Chamber #2 Polarization: **Vertical** Temperature: 24 C
 Limit: (RE)FCC PART 15C Power: AC 120V/60Hz Humidity: 53 %
 EUT: ID Camera
 M/N: Focus 72
 Mode:11g 2437
 Note:

| No. | Mk. | Freq. | Reading Level | Correct Factor | Measurement | Limit | Over | Antenna Height | Table Degree | Comment |
|-----|-----|----------|---------------|----------------|-------------|--------|--------|----------------|--------------|---------|
| | | MHz | dBuV | dB | dBuV/m | dBuV/m | dB | cm | degree | |
| 1 | | 17218.00 | 59.02 | -6.61 | 52.41 | 74.00 | -21.59 | peak | | |
| 2 | * | 17218.00 | 43.81 | -6.61 | 37.20 | 54.00 | -16.80 | AVG | | |


*:Maximum data x:Over limit !:over margin

Operator: KK

Shenzhen EMTEK Co., Ltd.
Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China
www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282



Radiated Emission Measurement



Site 3m Chamber #2 Polarization: **Horizontal** Temperature: 24 C
 Limit: (RE)FCC PART 15C Power: AC 120V/60Hz Humidity: 53 %
 EUT: ID Camera
 M/N: Focus 72
 Mode: 11g 2462
 Note:

| No. | Mk. | Freq. | Reading Level | Correct Factor | Measurement | Limit | Over | Antenna Height | Table Degree | |
|-----|-----|----------|---------------|----------------|-------------|--------|--------|----------------|--------------|---------|
| | | MHz | dBuV | dB | dBuV/m | dBuV/m | dB | cm | degree | Comment |
| 1 | | 14260.00 | 60.67 | -8.28 | 52.39 | 74.00 | -21.61 | peak | | |
| 2 | * | 14260.00 | 44.58 | -8.28 | 36.30 | 54.00 | -17.70 | AVG | | |


*:Maximum data x:Over limit !:over margin

Operator: KK

Shenzhen EMTEK Co., Ltd.
Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China
www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282



Radiated Emission Measurement



Site 3m Chamber #2 Polarization: **Vertical** Temperature: 24 C
 Limit: (RE)FCC PART 15C Power: AC 120V/60Hz Humidity: 53 %
 EUT: ID Camera
 M/N: Focus 72
 Mode: 11g 2462
 Note:

| No. | Mk. | Freq. | Reading Level | Correct Factor | Measurement | Limit | Over | Antenna Height | Table Degree | |
|-----|-----|----------|---------------|----------------|-------------|--------|--------|----------------|--------------|---------|
| | | MHz | dBuV | dB | dBuV/m | dBuV/m | dB | cm | degree | Comment |
| 1 | | 14328.00 | 60.33 | -8.40 | 51.93 | 74.00 | -22.07 | | | peak |
| 2 | * | 14328.00 | 42.90 | -8.40 | 34.50 | 54.00 | -19.50 | | | AVG |

*:Maximum data x:Over limit !:over margin


Operator: KK

**Wi-Fi 802.11 n(HT20) mode, MCS0
30MHz - 1GHz**

Shenzhen EMTEK Co., Ltd.
Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China
www.emtek.com.cn Tel:+86-755-2695 4280 Fax:+86-755-2695 4282



Radiated Emission Measurement



Site 3m Chamber #2 Polarization: **Horizontal** Temperature: 22 C
Limit: (RE)FCC PART 15C Power: AC 120V/60Hz Humidity: 55 %
EUT: ID Camera
M/N: Focus 72
Mode:TX 11n20 Low
Note:

| No. | Mk. | Freq. MHz | Reading Level dBuV | Correct Factor dB | Measure- ment dBuV/m | Limit dBuV/m | Over dB | Antenna Height cm | Table Degree | Comment |
|-----|-----|--------------|--------------------------|-------------------------|----------------------------|-----------------|------------|-------------------------|-----------------|---------|
| 1 | | 62.0100 | 34.74 | -15.07 | 19.67 | 40.00 | -20.33 | QP | | |
| 2 | | 199.7500 | 45.73 | -14.19 | 31.54 | 43.50 | -11.96 | QP | | |
| 3 | | 272.5000 | 46.69 | -12.21 | 34.48 | 46.00 | -11.52 | QP | | |
| 4 | | 400.5400 | 41.02 | -8.66 | 32.36 | 46.00 | -13.64 | QP | | |
| 5 | | 475.2300 | 35.77 | -7.03 | 28.74 | 46.00 | -17.26 | QP | | |
| 6 | * | 818.6100 | 35.46 | -0.39 | 35.07 | 46.00 | -10.93 | QP | | |


*:Maximum data x:Over limit !:over margin

Operator: KK

Shenzhen EMTEK Co., Ltd.
Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China
www.emtek.com.cn Tel:+86-755-2695 4280 Fax:+86-755-2695 4282



Radiated Emission Measurement



Site 3m Chamber #2 Polarization: **Vertical** Temperature: 22 C
Limit: (RE)FCC PART 15C Power: AC 120V/60Hz Humidity: 55 %
EUT: ID Camera
M/N: Focus 72
Mode:TX 11n20 Low
Note:

| No. | Mk. | Freq. MHz | Reading Level dBuV | Correct Factor dB | Measure- ment dBuV/m | Limit dBuV/m | Over dB | Antenna Height cm | Table Degree | Comment |
|-----|-----|--------------|--------------------------|-------------------------|----------------------------|-----------------|------------|-------------------------|-----------------|---------|
| 1 | | 120.2100 | 36.57 | -16.63 | 19.94 | 43.50 | -23.56 | QP | | |
| 2 | | 199.7500 | 39.80 | -14.19 | 25.61 | 43.50 | -17.89 | QP | | |
| 3 | * | 400.5400 | 38.65 | -8.66 | 29.99 | 46.00 | -16.01 | QP | | |
| 4 | | 475.2300 | 35.97 | -7.03 | 28.94 | 46.00 | -17.06 | QP | | |
| 5 | | 525.6700 | 32.86 | -5.78 | 27.08 | 46.00 | -18.92 | QP | | |
| 6 | | 600.3600 | 30.76 | -3.78 | 26.98 | 46.00 | -19.02 | QP | | |


*:Maximum data x:Over limit !:over margin

Operator: KK

Shenzhen EMTEK Co., Ltd.
Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China
www.emtek.com.cn Tel:+86-755-2695 4280 Fax:+86-755-2695 4282



Radiated Emission Measurement



Site 3m Chamber #2 Polarization: **Horizontal** Temperature: 22 C
Limit: (RE)FCC PART 15C Power: AC 120V/60Hz Humidity: 55 %
EUT: ID Camera
M/N: Focus 72
Mode:TX 11n20 Mid
Note:

| No. | Mk. | Freq. | Reading Level | Correct Factor | Measurement | Limit | Over | Antenna Height | Table Degree | Detector | Comment |
|-----|-----|----------|---------------|----------------|-------------|--------|--------|----------------|--------------|----------|---------|
| | | MHz | dBuV | dB | dBuV/m | dBuV/m | dB | cm | degree | | |
| 1 | * | 199.7500 | 43.77 | -14.19 | 29.58 | 43.50 | -13.92 | QP | | | |
| 2 | | 224.9700 | 41.27 | -13.77 | 27.50 | 46.00 | -18.50 | QP | | | |
| 3 | | 272.5000 | 43.57 | -12.21 | 31.36 | 46.00 | -14.64 | QP | | | |
| 4 | | 400.5400 | 34.27 | -8.66 | 25.61 | 46.00 | -20.39 | QP | | | |
| 5 | | 475.2300 | 33.81 | -7.03 | 26.78 | 46.00 | -19.22 | QP | | | |
| 6 | | 850.6200 | 28.83 | 0.26 | 29.09 | 46.00 | -16.91 | QP | | | |


*:Maximum data x:Over limit l:over margin

Operator: KK

Shenzhen EMTEK Co., Ltd.
Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China
www.emtek.com.cn Tel:+86-755-2695 4280 Fax:+86-755-2695 4282



Radiated Emission Measurement



Site 3m Chamber #2 Polarization: **Vertical** Temperature: 22 C
 Limit: (RE)FCC PART 15C Power: AC 120V/60Hz Humidity: 55 %
 EUT: ID Camera
 M/N: Focus 72
 Mode:TX 11n20 Mid
 Note:

| No. | Mk. | Freq. MHz | Reading Level dBuV | Correct Factor dB | Measure- ment dBuV/m | Limit dBuV/m | Over dB | Antenna Height cm | Table Degree | Comment |
|-----|-----|--------------|--------------------------|-------------------------|----------------------------|-----------------|------------|-------------------------|-----------------|---------|
| 1 | | 97.9000 | 34.78 | -15.44 | 19.34 | 43.50 | -24.16 | QP | | |
| 2 | | 199.7500 | 35.10 | -14.19 | 20.91 | 43.50 | -22.59 | QP | | |
| 3 | | 400.5400 | 37.85 | -8.66 | 29.19 | 46.00 | -16.81 | QP | | |
| 4 | * | 475.2300 | 38.89 | -7.03 | 31.86 | 46.00 | -14.14 | QP | | |
| 5 | | 525.6700 | 35.24 | -5.78 | 29.46 | 46.00 | -16.54 | QP | | |
| 6 | | 595.5100 | 30.20 | -3.90 | 26.30 | 46.00 | -19.70 | QP | | |


*:Maximum data x:Over limit !:over margin

Operator: KK

Shenzhen EMTEK Co., Ltd.
Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China
www.emtek.com.cn Tel:+86-755-2695 4280 Fax:+86-755-2695 4282



Radiated Emission Measurement



Site 3m Chamber #2 Polarization: **Horizontal** Temperature: 22 C
 Limit: (RE)FCC PART 15C Power: AC 120V/60Hz Humidity: 55 %
 EUT: ID Camera
 M/N: Focus 72
 Mode:TX 11n20 High
 Note:

| No. | Mk. | Freq. MHz | Reading Level dBuV | Correct Factor dB | Measure- ment dBuV/m | Limit dBuV/m | Over dB | Antenna Height cm | Table Degree | Comment |
|-----|-----|--------------|--------------------------|-------------------------|----------------------------|-----------------|------------|-------------------------|-----------------|---------|
| 1 | | 199.7500 | 40.36 | -14.19 | 26.17 | 43.50 | -17.33 | QP | | |
| 2 | | 224.9700 | 41.04 | -13.77 | 27.27 | 46.00 | -18.73 | QP | | |
| 3 | | 272.5000 | 44.57 | -12.21 | 32.36 | 46.00 | -13.64 | QP | | |
| 4 | | 400.5400 | 36.08 | -8.66 | 27.42 | 46.00 | -18.58 | QP | | |
| 5 | | 475.2300 | 33.24 | -7.03 | 26.21 | 46.00 | -19.79 | QP | | |
| 6 | * | 818.6100 | 33.45 | -0.39 | 33.06 | 46.00 | -12.94 | QP | | |


*:Maximum data x:Over limit !:over margin

Operator: KK

Shenzhen EMTEK Co., Ltd.
Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China
www.emtek.com.cn Tel:+86-755-2695 4280 Fax:+86-755-2695 4282



Radiated Emission Measurement



Site 3m Chamber #2 Polarization: **Vertical** Temperature: 22 C
 Limit: (RE)FCC PART 15C Power: AC 120V/60Hz Humidity: 55 %
 EUT: ID Camera
 M/N: Focus 72
 Mode:TX 11n20 High
 Note:

| No. | Mk. | Freq. MHz | Reading Level dBuV | Correct Factor dB | Measure- ment dBuV/m | Limit dBuV/m | Over dB | Antenna Height cm | Table Degree | Comment |
|-----|-----|--------------|--------------------------|-------------------------|----------------------------|-----------------|------------|-------------------------|-----------------|---------|
| 1 | | 199.7500 | 38.16 | -14.19 | 23.97 | 43.50 | -19.53 | QP | | |
| 2 | | 272.5000 | 33.02 | -12.21 | 20.81 | 46.00 | -25.19 | QP | | |
| 3 | | 400.5400 | 39.44 | -8.66 | 30.78 | 46.00 | -15.22 | QP | | |
| 4 | * | 475.2300 | 38.09 | -7.03 | 31.06 | 46.00 | -14.94 | QP | | |
| 5 | | 518.8800 | 31.33 | -5.96 | 25.37 | 46.00 | -20.63 | QP | | |
| 6 | | 600.3600 | 30.46 | -3.78 | 26.68 | 46.00 | -19.32 | QP | | |

*:Maximum data x:Over limit !:over margin


Operator: KK

1GHz - 18GHz

Shenzhen EMTEK Co., Ltd.
Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China
www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282



Radiated Emission Measurement



Site 3m Chamber #2 Polarization: *Horizontal* Temperature: 24 C
Limit: (RE)FCC PART 15C Power: AC 120V/60Hz Humidity: 53 %
EUT: ID Camera
M/N: Focus 72
Mode:11n20 2412
Note:

| No. | Mk. | Freq. | Reading Level | Correct Factor | Measurement | Limit | Over | Antenna Height | Table Degree | Comment |
|-----|-----|----------|---------------|----------------|-------------|--------|--------|----------------|--------------|---------|
| | | MHz | dBuV | dB | dBuV/m | dBuV/m | dB | cm | degree | |
| 1 | | 16470.00 | 64.28 | -11.11 | 53.17 | 74.00 | -20.83 | peak | | |
| 2 | * | 16470.00 | 48.11 | -11.11 | 37.00 | 54.00 | -17.00 | AVG | | |


*:Maximum data x:Over limit !:over margin

Operator: KK

Shenzhen EMTEK Co., Ltd.
Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China
www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282



Radiated Emission Measurement



Site 3m Chamber #2 Polarization: **Vertical** Temperature: 24 C
 Limit: (RE)FCC PART 15C Power: AC 120V/60Hz Humidity: 53 %
 EUT: ID Camera
 M/N: Focus 72
 Mode:11n20 2412
 Note:

| No. | Mk. | Freq. | Reading Level | Correct Factor | Measurement | Limit | Over | Antenna Height | Table Degree | Comment |
|-----|-----|----------|---------------|----------------|-------------|--------|--------|----------------|--------------|---------|
| | | MHz | dBuV | dB | dBuV/m | dBuV/m | dB | cm | degree | |
| 1 | | 16946.00 | 62.02 | -9.45 | 52.57 | 74.00 | -21.43 | peak | | |
| 2 | * | 16946.00 | 46.25 | -9.45 | 36.80 | 54.00 | -17.20 | AVG | | |


*:Maximum data x:Over limit !:over margin

Operator: KK

Shenzhen EMTEK Co., Ltd.
Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China
www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282



Radiated Emission Measurement



Site 3m Chamber #2 Polarization: **Horizontal** Temperature: 24 C
Limit: (RE)FCC PART 15C Power: AC 120V/60Hz Humidity: 53 %
EUT: ID Camera
M/N: Focus 72
Mode:11n20 2437
Note:

| No. | Mk. | Freq. | Reading Level | Correct Factor | Measurement | Limit | Over | Antenna Height | Table Degree | Comment |
|-----|-----|----------|---------------|----------------|-------------|--------|--------|----------------|--------------|---------|
| | | MHz | dBuV | dB | dBuV/m | dBuV/m | dB | cm | degree | |
| 1 | | 14872.00 | 61.55 | -9.36 | 52.19 | 74.00 | -21.81 | peak | | |
| 2 | * | 14872.00 | 46.26 | -9.36 | 36.90 | 54.00 | -17.10 | AVG | | |


*:Maximum data x:Over limit !:over margin

Operator: KK

Shenzhen EMTEK Co., Ltd.
Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China
www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282



Radiated Emission Measurement



Site 3m Chamber #2 Polarization: **Vertical** Temperature: 24 C
 Limit: (RE)FCC PART 15C Power: AC 120V/60Hz Humidity: 53 %
 EUT: ID Camera
 M/N: Focus 72
 Mode:11n20 2437
 Note:

| No. | Mk. | Freq. | Reading Level | Correct Factor | Measurement | Limit | Over | Antenna Height | Table Degree | Comment |
|-----|-----|----------|---------------|----------------|-------------|--------|--------|----------------|--------------|---------|
| | | MHz | dBuV | dB | dBuV/m | dBuV/m | dB | cm | degree | |
| 1 | | 14957.00 | 61.83 | -9.51 | 52.32 | 74.00 | -21.68 | peak | | |
| 2 | * | 14957.00 | 46.41 | -9.51 | 36.90 | 54.00 | -17.10 | AVG | | |


*:Maximum data x:Over limit !:over margin

Operator: KK

Shenzhen EMTEK Co., Ltd.
Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China
www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282



Radiated Emission Measurement



Site 3m Chamber #2 Polarization: **Horizontal** Temperature: 24 C
 Limit: (RE)FCC PART 15C Power: AC 120V/60Hz Humidity: 53 %
 EUT: ID Camera
 M/N: Focus 72
 Mode:11n20 2462
 Note:

| No. | Mk. | Freq. | Reading Level | Correct Factor | Measurement | Limit | Over | Antenna Height | Table Degree | |
|-----|-----|----------|---------------|----------------|-------------|--------|--------|----------------|--------------|---------|
| | | MHz | dBuV | dB | dBuV/m | dBuV/m | dB | cm | degree | Comment |
| 1 | | 15399.00 | 62.61 | -10.85 | 51.76 | 74.00 | -22.24 | peak | | |
| 2 | * | 15399.00 | 46.05 | -10.85 | 35.20 | 54.00 | -18.80 | AVG | | |


*:Maximum data x:Over limit !:over margin

Operator: KK

Shenzhen EMTEK Co., Ltd.
Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China
www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282



Radiated Emission Measurement



Site 3m Chamber #2 Polarization: **Vertical** Temperature: 24 C
 Limit: (RE)FCC PART 15C Power: AC 120V/60Hz Humidity: 53 %
 EUT: ID Camera
 M/N: Focus 72
 Mode:11n20 2462
 Note:

| No. | Mk. | Freq. | Reading Level | Correct Factor | Measurement | Limit | Over | Antenna Height | Table Degree | Comment |
|-----|-----|----------|---------------|----------------|-------------|--------|--------|----------------|--------------|---------|
| | | MHz | dBuV | dB | dBuV/m | dBuV/m | dB | cm | degree | |
| 1 | | 17201.00 | 60.21 | -6.81 | 53.40 | 74.00 | -20.60 | peak | | |
| 2 | * | 17201.00 | 44.91 | -6.81 | 38.10 | 54.00 | -15.90 | AVG | | |

*:Maximum data x:Over limit !:over margin


Operator: KK

Wi-Fi 802.11 n(HT40) mode, MCS0
30MHz - 1GHz

Shenzhen EMTEK Co., Ltd.
Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China
www.emtek.com.cn Tel:+86-755-2695 4280 Fax:+86-755-2695 4282



Radiated Emission Measurement



Site 3m Chamber #2 Polarization: **Horizontal** Temperature: 22 C
Limit: (RE)FCC PART 15C Power: AC 120V/60Hz Humidity: 55 %
EUT: ID Camera
M/N: Focus 72
Mode:TX 11n40 Low
Note:

| No. | Mk. | Freq. MHz | Reading Level dBuV | Correct Factor dB | Measure- ment dBuV/m | Limit dBuV/m | Over dB | Antenna Height cm | Table Degree degree | Comment |
|-----|-----|--------------|--------------------------|-------------------------|----------------------------|-----------------|------------|-------------------------|---------------------------|---------|
| 1 | | 163.8600 | 38.87 | -17.41 | 21.46 | 43.50 | -22.04 | QP | | |
| 2 | * | 199.7500 | 42.27 | -14.19 | 28.08 | 43.50 | -15.42 | QP | | |
| 3 | | 245.3400 | 40.45 | -12.88 | 27.57 | 46.00 | -18.43 | QP | | |
| 4 | | 272.5000 | 40.29 | -12.21 | 28.08 | 46.00 | -17.92 | QP | | |
| 5 | | 400.5400 | 39.22 | -8.66 | 30.56 | 46.00 | -15.44 | QP | | |
| 6 | | 825.4000 | 30.45 | -0.25 | 30.20 | 46.00 | -15.80 | QP | | |


*:Maximum data x:Over limit !:over margin

Operator: KK

Shenzhen EMTEK Co., Ltd.
Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China
www.emtek.com.cn Tel:+86-755-2695 4280 Fax:+86-755-2695 4282



Radiated Emission Measurement



Site 3m Chamber #2 Polarization: **Vertical** Temperature: 22 C
 Limit: (RE)FCC PART 15C Power: AC 120V/60Hz Humidity: 55 %
 EUT: ID Camera
 M/N: Focus 72
 Mode:TX 11n40 Low
 Note:

| No. | Mk. | Freq. MHz | Reading Level dBuV | Correct Factor dB | Measure- ment dBuV/m | Limit dBuV/m | Over dB | Antenna Height cm | Table Degree | Comment |
|-----|-----|--------------|--------------------------|-------------------------|----------------------------|-----------------|------------|-------------------------|-----------------|---------|
| 1 | | 112.4500 | 36.37 | -15.24 | 21.13 | 43.50 | -22.37 | QP | | |
| 2 | | 199.7500 | 34.99 | -14.19 | 20.80 | 43.50 | -22.70 | QP | | |
| 3 | | 400.5400 | 36.43 | -8.66 | 27.77 | 46.00 | -18.23 | QP | | |
| 4 | * | 475.2300 | 38.34 | -7.03 | 31.31 | 46.00 | -14.69 | QP | | |
| 5 | | 525.6700 | 32.24 | -5.78 | 26.46 | 46.00 | -19.54 | QP | | |
| 6 | | 600.3600 | 31.67 | -3.78 | 27.89 | 46.00 | -18.11 | QP | | |


*:Maximum data x:Over limit !:over margin

Operator: KK

Shenzhen EMTEK Co., Ltd.
Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China
www.emtek.com.cn Tel:+86-755-2695 4280 Fax:+86-755-2695 4282



Radiated Emission Measurement



Site 3m Chamber #2 Polarization: **Horizontal** Temperature: 22 C
Limit: (RE)FCC PART 15C Power: AC 120V/60Hz Humidity: 55 %
EUT: ID Camera
M/N: Focus 72
Mode:TX 11n40 Mid
Note:

| No. | Mk. | Freq. MHz | Reading Level dBuV | Correct Factor dB | Measure- ment dBuV/m | Limit dBuV/m | Over dB | Antenna Height cm | Table Degree | Comment |
|-----|-----|--------------|--------------------------|-------------------------|----------------------------|-----------------|------------|-------------------------|-----------------|---------|
| 1 | | 199.7500 | 42.23 | -14.19 | 28.04 | 43.50 | -15.46 | QP | | |
| 2 | | 272.5000 | 45.05 | -12.21 | 32.84 | 46.00 | -13.16 | QP | | |
| 3 | | 400.5400 | 36.60 | -8.66 | 27.94 | 46.00 | -18.06 | QP | | |
| 4 | | 475.2300 | 34.42 | -7.03 | 27.39 | 46.00 | -18.61 | QP | | |
| 5 | | 774.9600 | 31.25 | -1.12 | 30.13 | 46.00 | -15.87 | QP | | |
| 6 | * | 818.6100 | 33.94 | -0.39 | 33.55 | 46.00 | -12.45 | QP | | |


*:Maximum data x:Over limit !:over margin

Operator: KK

Shenzhen EMTEK Co., Ltd.
Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China
www.emtek.com.cn Tel:+86-755-2695 4280 Fax:+86-755-2695 4282



Radiated Emission Measurement



Site 3m Chamber #2 Polarization: **Vertical** Temperature: 22 C
Limit: (RE)FCC PART 15C Power: AC 120V/60Hz Humidity: 55 %
EUT: ID Camera
M/N: Focus 72
Mode:TX 11n40 Mid
Note:

| No. | Mk. | Freq. MHz | Reading Level dBuV | Correct Factor dB | Measure- ment dBuV/m | Limit dBuV/m | Over dB | Antenna Height cm | Table Degree | Comment |
|-----|-----|--------------|--------------------------|-------------------------|----------------------------|-----------------|------------|-------------------------|-----------------|---------|
| 1 | | 120.2100 | 37.51 | -16.63 | 20.88 | 43.50 | -22.62 | QP | | |
| 2 | | 199.7500 | 38.23 | -14.19 | 24.04 | 43.50 | -19.46 | QP | | |
| 3 | * | 400.5400 | 42.98 | -8.66 | 34.32 | 46.00 | -11.68 | QP | | |
| 4 | | 475.2300 | 38.01 | -7.03 | 30.98 | 46.00 | -15.02 | QP | | |
| 5 | | 600.3600 | 33.83 | -3.78 | 30.05 | 46.00 | -15.95 | QP | | |
| 6 | | 654.6800 | 31.34 | -3.06 | 28.28 | 46.00 | -17.72 | QP | | |


*:Maximum data x:Over limit !:over margin

Operator: KK

Shenzhen EMTEK Co., Ltd.
Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China
www.emtek.com.cn Tel:+86-755-2695 4280 Fax:+86-755-2695 4282



Radiated Emission Measurement



Site 3m Chamber #2 Polarization: **Horizontal** Temperature: 22 C
Limit: (RE)FCC PART 15C Power: AC 120V/60Hz Humidity: 55 %
EUT: ID Camera
M/N: Focus 72
Mode:TX 11n40 High
Note:

| No. | Mk. | Freq. MHz | Reading Level dBuV | Correct Factor dB | Measure- ment dBuV/m | Limit dBuV/m | Over dB | Antenna Height cm | Table Degree | Comment |
|-----|-----|--------------|--------------------------|-------------------------|----------------------------|-----------------|------------|-------------------------|-----------------|---------|
| 1 | | 62.0100 | 34.24 | -15.07 | 19.17 | 40.00 | -20.83 | QP | | |
| 2 | * | 199.7500 | 46.67 | -14.19 | 32.48 | 43.50 | -11.02 | QP | | |
| 3 | | 272.5000 | 44.29 | -12.21 | 32.08 | 46.00 | -13.92 | QP | | |
| 4 | | 400.5400 | 34.92 | -8.66 | 26.26 | 46.00 | -19.74 | QP | | |
| 5 | | 475.2300 | 35.02 | -7.03 | 27.99 | 46.00 | -18.01 | QP | | |
| 6 | | 818.6100 | 30.88 | -0.39 | 30.49 | 46.00 | -15.51 | QP | | |


*:Maximum data x:Over limit !:over margin

Operator: KK

Shenzhen EMTEK Co., Ltd.
Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China
www.emtek.com.cn Tel:+86-755-2695 4280 Fax:+86-755-2695 4282



Radiated Emission Measurement



Site 3m Chamber #2 Polarization: **Vertical** Temperature: 22 C
Limit: (RE)FCC PART 15C Power: AC 120V/60Hz Humidity: 55 %
EUT: ID Camera
M/N: Focus 72
Mode:TX 11n40 High
Note:

| No. | Mk. | Freq. MHz | Reading Level dBuV | Correct Factor dB | Measure- ment dBuV/m | Limit dBuV/m | Over dB | Antenna Height cm | Table Degree | Comment |
|-----|-----|--------------|--------------------------|-------------------------|----------------------------|-----------------|------------|-------------------------|-----------------|---------|
| 1 | | 199.7500 | 35.56 | -14.19 | 21.37 | 43.50 | -22.13 | QP | | |
| 2 | | 400.5400 | 38.16 | -8.66 | 29.50 | 46.00 | -16.50 | QP | | |
| 3 | * | 475.2300 | 38.90 | -7.03 | 31.87 | 46.00 | -14.13 | QP | | |
| 4 | | 525.6700 | 34.09 | -5.78 | 28.31 | 46.00 | -17.69 | QP | | |
| 5 | | 592.6000 | 29.69 | -3.99 | 25.70 | 46.00 | -20.30 | QP | | |
| 6 | | 900.0900 | 28.19 | 1.20 | 29.39 | 46.00 | -16.61 | QP | | |

*:Maximum data x:Over limit !:over margin


Operator: KK

1GHz - 18GHz

Shenzhen EMTEK Co., Ltd.
Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China
www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282



Radiated Emission Measurement



Site 3m Chamber #2 Polarization: **Horizontal** Temperature: 24 C
 Limit: (RE)FCC PART 15C Power: AC 120V/60Hz Humidity: 53 %
 EUT: ID Camera
 M/N: Focus 72
 Mode:11n40 2422
 Note:

| No. | Mk. | Freq. | Reading Level | Correct Factor | Measurement | Limit | Over | Antenna Height | Table Degree | Comment |
|-----|-----|----------|---------------|----------------|-------------|--------|--------|----------------|--------------|---------|
| | | MHz | dBuV | dB | dBuV/m | dBuV/m | dB | cm | degree | |
| 1 | | 14396.00 | 60.58 | -8.52 | 52.06 | 74.00 | -21.94 | peak | | |
| 2 | * | 14396.00 | 44.72 | -8.52 | 36.20 | 54.00 | -17.80 | AVG | | |


*:Maximum data x:Over limit !:over margin

Operator: KK

Shenzhen EMTEK Co., Ltd.
Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China
www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282



Radiated Emission Measurement



Site 3m Chamber #2 Polarization: **Vertical** Temperature: 24 C
 Limit: (RE)FCC PART 15C Power: AC 120V/60Hz Humidity: 53 %
 EUT: ID Camera
 M/N: Focus 72
 Mode:11n40 2422
 Note:

| No. | Mk. | Freq. | Reading Level | Correct Factor | Measurement | Limit | Over | Antenna Height | Table Degree | Comment |
|-----|-----|----------|---------------|----------------|-------------|--------|--------|----------------|--------------|---------|
| | | MHz | dBuV | dB | dBuV/m | dBuV/m | dB | cm | degree | |
| 1 | | 15739.00 | 63.48 | -11.92 | 51.56 | 74.00 | -22.44 | peak | | |
| 2 | * | 15739.00 | 47.32 | -11.92 | 35.40 | 54.00 | -18.60 | AVG | | |


*:Maximum data x:Over limit !:over margin

Operator: KK

Shenzhen EMTEK Co., Ltd.
Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China
www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282



Radiated Emission Measurement



Site 3m Chamber #2 Polarization: **Horizontal** Temperature: 24 C
 Limit: (RE)FCC PART 15C Power: AC 120V/60Hz Humidity: 53 %
 EUT: ID Camera
 M/N: Focus 72
 Mode:11n40 2437
 Note:

| No. | Mk. | Freq. | Reading Level | Correct Factor | Measurement | Limit | Over | Antenna Height | Table Degree | Comment |
|-----|-----|----------|---------------|----------------|-------------|--------|--------|----------------|--------------|---------|
| | | MHz | dBuV | dB | dBuV/m | dBuV/m | dB | cm | degree | |
| 1 | | 15314.00 | 64.11 | -10.58 | 53.53 | 74.00 | -20.47 | peak | | |
| 2 | * | 15314.00 | 49.48 | -10.58 | 38.90 | 54.00 | -15.10 | AVG | | |


*:Maximum data x:Over limit !:over margin

Operator: KK

Shenzhen EMTEK Co., Ltd.
Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China
www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282



Radiated Emission Measurement



Site 3m Chamber #2 Polarization: **Vertical** Temperature: 24 C
 Limit: (RE)FCC PART 15C Power: AC 120V/60Hz Humidity: 53 %
 EUT: ID Camera
 M/N: Focus 72
 Mode:11n40 2437
 Note:

| No. | Mk. | Freq. | Reading Level | Correct Factor | Measurement | Limit | Over | Antenna Height | Table Degree | |
|-----|-----|----------|---------------|----------------|-------------|--------|--------|----------------|--------------|---------|
| | | MHz | dBuV | dB | dBuV/m | dBuV/m | dB | cm | degree | Comment |
| 1 | | 12849.00 | 63.76 | -12.85 | 50.91 | 74.00 | -23.09 | peak | | |
| 2 | * | 12849.00 | 48.65 | -12.85 | 35.80 | 54.00 | -18.20 | AVG | | |


*:Maximum data x:Over limit !:over margin

Operator: KK

Shenzhen EMTEK Co., Ltd.
Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China
www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282



Radiated Emission Measurement



Site 3m Chamber #2 Polarization: **Horizontal** Temperature: 24 C
 Limit: (RE)FCC PART 15C Power: AC 120V/60Hz Humidity: 53 %
 EUT: ID Camera
 M/N: Focus 72
 Mode:11n40 2452
 Note:

| No. | Mk. | Freq. | Reading Level | Correct Factor | Measurement | Limit | Over | Antenna Height | Table Degree | Comment |
|-----|-----|----------|---------------|----------------|-------------|--------|--------|----------------|--------------|---------|
| | | MHz | dBuV | dB | dBuV/m | dBuV/m | dB | cm | degree | |
| 1 | | 15382.00 | 63.09 | -10.79 | 52.30 | 74.00 | -21.70 | | | peak |
| 2 | * | 15382.00 | 47.49 | -10.79 | 36.70 | 54.00 | -17.30 | | | AVG |


*:Maximum data x:Over limit !:over margin

Operator: KK

Shenzhen EMTEK Co., Ltd.
Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China
www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282



Radiated Emission Measurement



Site 3m Chamber #2 Polarization: **Vertical** Temperature: 24 C
 Limit: (RE)FCC PART 15C Power: AC 120V/60Hz Humidity: 53 %
 EUT: ID Camera
 M/N: Focus 72
 Mode:11n40 2452
 Note:

| No. | Mk. | Freq. | Reading Level | Correct Factor | Measurement | Limit | Over | Antenna Height | Table Degree | Comment |
|-----|-----|----------|---------------|----------------|-------------|--------|--------|----------------|--------------|---------|
| | | MHz | dBuV | dB | dBuV/m | dBuV/m | dB | cm | degree | |
| 1 | | 15280.00 | 62.20 | -10.48 | 51.72 | 74.00 | -22.28 | peak | | |
| 2 | * | 15280.00 | 45.78 | -10.48 | 35.30 | 54.00 | -18.70 | AVG | | |

*:Maximum data x:Over limit !:over margin


Operator: KK

Appendix C.2: Test Results of Radiated Emissions in Restricted Bands
Wi-Fi 802.11 b mode, 11 Mbps
Low channel

Shenzhen EMTEK Co., Ltd.
 Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China
 www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282



Radiated Emission Measurement



Site 3m Chamber #2 Polarization: **Horizontal** Temperature: 24 C
 Limit: (RE)FCC PART 15 C Power: AC 120V/60Hz Humidity: 53 %
 EUT: ID Camera
 M/N: Focus 72
 Mode: 11b 2412
 Note:

| No. | Mk. | Freq. | Reading Level | Correct Factor | Measurement | Limit | Over | Antenna Height | Table Degree | |
|-----|-----|----------|---------------|----------------|-------------|--------|--------|----------------|--------------|---------|
| | | MHz | dBuV | dB | dBuV/m | dBuV/m | dB | cm | degree | Comment |
| 1 | | 2379.200 | 35.83 | 14.95 | 50.78 | 74.00 | -23.22 | peak | | |
| 2 | * | 2379.200 | 21.05 | 14.95 | 36.00 | 54.00 | -18.00 | AVG | | |


*:Maximum data x:Over limit !:over margin

Operator: KK

Shenzhen EMTEK Co., Ltd.
Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China
www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282



Radiated Emission Measurement



Site 3m Chamber #2 Polarization: **Vertical** Temperature: 24 C
 Limit: (RE)FCC PART 15 C Power: AC 120V/60Hz Humidity: 53 %
 EUT: ID Camera
 M/N: Focus 72
 Mode: 11b 2412
 Note:

| No. | Mk. | Freq. | Reading Level | Correct Factor | Measurement | Limit | Over | Antenna Height | Table Degree | Comment |
|-----|-----|----------|---------------|----------------|-------------|--------|--------|----------------|--------------|---------|
| | | MHz | dBuV | dB | dBuV/m | dBuV/m | dB | cm | degree | |
| 1 | | 2387.360 | 38.77 | 15.01 | 53.78 | 74.00 | -20.22 | | | peak |
| 2 | * | 2387.360 | 23.49 | 15.01 | 38.50 | 54.00 | -15.50 | | | AVG |

*:Maximum data x:Over limit !:over margin


Operator: KK

High channel

Shenzhen EMTEK Co., Ltd.
Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China
www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282



Radiated Emission Measurement



Site 3m Chamber #2 Polarization: **Horizontal** Temperature: 24 C
Limit: (RE)FCC PART 15 C Power: AC 120V/60Hz Humidity: 53 %
EUT: ID Camera
M/N: Focus 72
Mode: 11b 2462
Note:

| No. | Mk. | Freq. | Reading Level | Correct Factor | Measurement | Limit | Over | Antenna Height | Table Degree | Comment |
|-----|-----|----------|---------------|----------------|-------------|--------|--------|----------------|--------------|---------|
| | | MHz | dBuV | dB | dBuV/m | dBuV/m | dB | cm | degree | |
| 1 | | 2487.262 | 35.77 | 15.83 | 51.60 | 74.00 | -22.40 | peak | | |
| 2 | * | 2487.262 | 19.47 | 15.83 | 35.30 | 54.00 | -18.70 | AVG | | |


*:Maximum data x:Over limit !:over margin

Operator: KK

Shenzhen EMTEK Co., Ltd.
Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China
www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282



Radiated Emission Measurement



Site 3m Chamber #2 Polarization: **Vertical** Temperature: 24 C
 Limit: (RE)FCC PART 15 C Power: AC 120V/60Hz Humidity: 53 %
 EUT: ID Camera
 M/N: Focus 72
 Mode: 11b 2462
 Note:

| No. | Mk. | Freq. | Reading Level | Correct Factor | Measurement | Limit | Over | Antenna Height | Table Degree | |
|-----|-----|----------|---------------|----------------|-------------|--------|--------|----------------|--------------|---------|
| | | MHz | dBuV | dB | dBuV/m | dBuV/m | dB | cm | degree | Comment |
| 1 | | 2484.209 | 36.24 | 15.81 | 52.05 | 74.00 | -21.95 | peak | | |
| 2 | * | 2484.209 | 21.59 | 15.81 | 37.40 | 54.00 | -16.60 | AVG | | |

*:Maximum data x:Over limit !:over margin


Operator: KK

Wi-Fi 802.11 g mode, 54 Mbps
Low channel

Shenzhen EMTEK Co., Ltd.
Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China
www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282



Radiated Emission Measurement



Site 3m Chamber #2 Polarization: **Horizontal** Temperature: 24 C
Limit: (RE)FCC PART 15 C Power: AC 120V/60Hz Humidity: 53 %
EUT: ID Camera
M/N: Focus 72
Mode: 11g 2412
Note:

| No. | Mk. | Freq. | Reading Level | Correct Factor | Measurement | Limit | Over | Antenna Height | Table Degree | Comment |
|-----|-----|----------|---------------|----------------|-------------|--------|--------|----------------|--------------|---------|
| | | MHz | dBuV | dB | dBuV/m | dBuV/m | dB | cm | degree | |
| 1 | | 2388.960 | 38.38 | 15.03 | 53.41 | 74.00 | -20.59 | peak | | |
| 2 | * | 2388.960 | 23.57 | 15.03 | 38.60 | 54.00 | -15.40 | AVG | | |


*:Maximum data x:Over limit !:over margin

Operator: KK

Shenzhen EMTEK Co., Ltd.
Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China
www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282



Radiated Emission Measurement



Site 3m Chamber #2 Polarization: **Vertical** Temperature: 24 C
 Limit: (RE)FCC PART 15 C Power: AC 120V/60Hz Humidity: 53 %
 EUT: ID Camera
 M/N: Focus 72
 Mode:11g 2412
 Note:

| No. | Mk. | Freq. | Reading Level | Correct Factor | Measurement | Limit | Over | Antenna Height | Table Degree | Comment |
|-----|-----|----------|---------------|----------------|-------------|--------|--------|----------------|--------------|---------|
| | | MHz | dBuV | dB | dBuV/m | dBuV/m | dB | Detector | cm | degree |
| 1 | | 2389.680 | 39.85 | 15.03 | 54.88 | 74.00 | -19.12 | peak | | |
| 2 | * | 2389.680 | 24.17 | 15.03 | 39.20 | 54.00 | -14.80 | AVG | | |

*:Maximum data x:Over limit !:over margin


Operator: KK

High channel

Shenzhen EMTEK Co., Ltd.
Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China
www.emtek.com.cn Tel:+86-755-2695 4280 Fax:+86-755-2695 4282



Radiated Emission Measurement



Site 3m Chamber #2 Polarization: **Horizontal** Temperature: 24 C
 Limit: (RE)FCC PART 15 C Power: AC 120V/60Hz Humidity: 53 %
 EUT: ID Camera
 M/N: Focus 72
 Mode:11g 2462
 Note:

| No. | Mk. | Freq. | Reading Level | Correct Factor | Measurement | Limit | Over | Antenna Height | Table Degree | Comment |
|-----|-----|----------|---------------|----------------|-------------|--------|--------|----------------|--------------|---------|
| | | MHz | dBuV | dB | dBuV/m | dBuV/m | dB | cm | degree | |
| 1 | | 2483.550 | 38.55 | 15.80 | 54.35 | 74.00 | -19.65 | peak | | |
| 2 | * | 2483.550 | 22.60 | 15.80 | 38.40 | 54.00 | -15.60 | AVG | | |


*:Maximum data x:Over limit !:over margin

Operator: KK

Shenzhen EMTEK Co., Ltd.
Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China
www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282



Radiated Emission Measurement



Site 3m Chamber #2 Polarization: **Vertical** Temperature: 24 C
Limit: (RE)FCC PART 15 C Power: AC 120V/60Hz Humidity: 53 %
EUT: ID Camera
M/N: Focus 72
Mode: 11g 2462
Note:

| No. | Mk. | Freq. | Reading Level | Correct Factor | Measurement | Limit | Over | Antenna Height | Table Degree | |
|-----|-----|----------|---------------|----------------|-------------|--------|--------|----------------|--------------|---------|
| | | MHz | dBuV | dB | dBuV/m | dBuV/m | dB | cm | degree | Comment |
| 1 | | 2483.715 | 39.01 | 15.80 | 54.81 | 74.00 | -19.19 | peak | | |
| 2 | * | 2483.715 | 23.20 | 15.80 | 39.00 | 54.00 | -15.00 | AVG | | |

*:Maximum data x:Over limit !:over margin


Operator: KK

Wi-Fi 802.11 n(HT20) mode, MCS0
Low channel

Shenzhen EMTEK Co., Ltd.
Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China
www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282



Radiated Emission Measurement



Site 3m Chamber #2 Polarization: **Horizontal** Temperature: 24 C
Limit: (RE)FCC PART 15 C Power: AC 120V/60Hz Humidity: 53 %
EUT: ID Camera
M/N: Focus 72
Mode:11n20 2412
Note:

| No. | Mk. | Freq. | Reading Level | Correct Factor | Measurement | Limit | Over | Antenna Height | Table Degree | Comment |
|-----|-----|----------|---------------|----------------|-------------|--------|--------|----------------|--------------|---------|
| | | MHz | dBuV | dB | dBuV/m | dBuV/m | dB | cm | degree | |
| 1 | | 2380.480 | 37.76 | 14.96 | 52.72 | 74.00 | -21.28 | peak | | |
| 2 | * | 2380.480 | 22.54 | 14.96 | 37.50 | 54.00 | -16.50 | AVG | | |


*:Maximum data x:Over limit !:over margin

Operator: KK

Shenzhen EMTEK Co., Ltd.
Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China
www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282



Radiated Emission Measurement



Site 3m Chamber #2 Polarization: **Vertical** Temperature: 24 C
 Limit: (RE)FCC PART 15 C Power: AC 120V/60Hz Humidity: 53 %
 EUT: ID Camera
 M/N: Focus 72
 Mode:11n20 2412
 Note:

| No. | Mk. | Freq. | Reading Level | Correct Factor | Measurement | Limit | Over | Antenna Height | Table Degree | Comment |
|-----|-----|----------|---------------|----------------|-------------|--------|--------|----------------|--------------|---------|
| | | MHz | dBuV | dB | dBuV/m | dBuV/m | dB | cm | degree | |
| 1 | | 2381.520 | 35.10 | 14.96 | 50.06 | 74.00 | -23.94 | peak | | |
| 2 | * | 2381.520 | 20.74 | 14.96 | 35.70 | 54.00 | -18.30 | AVG | | |

*:Maximum data x:Over limit !:over margin


Operator: KK

High channel

Shenzhen EMTEK Co., Ltd.
Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China
www.emtek.com.cn Tel:+86-755-2695 4280 Fax:+86-755-2695 4282



Radiated Emission Measurement



Site 3m Chamber #2 Polarization: **Horizontal** Temperature: 24 C
 Limit: (RE)FCC PART 15 C Power: AC 120V/60Hz Humidity: 53 %
 EUT: ID Camera
 M/N: Focus 72
 Mode:11n20 2462
 Note:

| No. | Mk. | Freq. | Reading Level | Correct Factor | Measurement | Limit | Over | Antenna Height | Table Degree | Comment |
|-----|-----|----------|---------------|----------------|-------------|--------|--------|----------------|--------------|---------|
| | | MHz | dBuV | dB | dBuV/m | dBuV/m | dB | cm | degree | |
| 1 | | 2484.077 | 35.46 | 15.81 | 51.27 | 74.00 | -22.73 | peak | | |
| 2 | * | 2484.077 | 20.69 | 15.81 | 36.50 | 54.00 | -17.50 | AVG | | |


*:Maximum data x:Over limit !:over margin

Operator: KK

Shenzhen EMTEK Co., Ltd.
Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China
www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282



Radiated Emission Measurement



Site 3m Chamber #2 Polarization: **Vertical** Temperature: 24 C
Limit: (RE)FCC PART 15 C Power: AC 120V/60Hz Humidity: 53 %
EUT: ID Camera
M/N: Focus 72
Mode:11n20 2462
Note:

| No. | Mk. | Freq. | Reading Level | Correct Factor | Measurement | Limit | Over | Antenna Height | Table Degree | |
|-----|-----|----------|---------------|----------------|-------------|--------|--------|----------------|--------------|---------|
| | | MHz | dBuV | dB | dBuV/m | dBuV/m | dB | cm | degree | Comment |
| 1 | | 2484.110 | 37.35 | 15.81 | 53.16 | 74.00 | -20.84 | peak | | |
| 2 | * | 2484.110 | 22.59 | 15.81 | 38.40 | 54.00 | -15.60 | AVG | | |

*:Maximum data x:Over limit !:over margin


Operator: KK

Wi-Fi 802.11 n(HT40) mode, MCS0
Low channel

Shenzhen EMTEK Co., Ltd.
Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P.R. China
www.emtek.com.cn Tel:+86-755-2695 4280 Fax:+86-755-2695 4282



Radiated Emission Measurement



Site 3m Chamber #2 Polarization: **Horizontal** Temperature: 24 C
Limit: (RE)FCC PART 15 C Power: AC 120V/60Hz Humidity: 53 %
EUT: ID Camera
M/N: Focus 72
Mode:11n40 2422
Note:

| No. | Mk. | Freq. | Reading Level | Correct Factor | Measurement | Limit | Over | Antenna Height | Table Degree | Comment |
|-----|-----|----------|---------------|----------------|-------------|--------|--------|----------------|--------------|---------|
| | | MHz | dBuV | dB | dBuV/m | dBuV/m | dB | cm | degree | |
| 1 | | 2384.080 | 44.54 | 7.57 | 52.11 | 74.00 | -21.89 | peak | | |
| 2 | * | 2384.080 | 29.63 | 7.57 | 37.20 | 54.00 | -16.80 | AVG | | |


*:Maximum data x:Over limit !:over margin

Operator: KK

Shenzhen EMTEK Co., Ltd.
Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China
www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282



Radiated Emission Measurement



Site 3m Chamber #2 Polarization: **Vertical** Temperature: 24 C
 Limit: (RE)FCC PART 15 C Power: AC 120V/60Hz Humidity: 53 %
 EUT: ID Camera
 M/N: Focus 72
 Mode:11n40 2422
 Note:

| No. | Mk. | Freq. | Reading Level | Correct Factor | Measurement | Limit | Over | Antenna Height | Table Degree | Comment |
|-----|-----|----------|---------------|----------------|-------------|--------|--------|----------------|--------------|---------|
| | | MHz | dBuV | dB | dBuV/m | dBuV/m | dB | cm | degree | |
| 1 | | 2380.480 | 43.43 | 7.54 | 50.97 | 74.00 | -23.03 | | | peak |
| 2 | * | 2380.480 | 28.46 | 7.54 | 36.00 | 54.00 | -18.00 | | | AVG |

*:Maximum data x:Over limit !:over margin


Operator: KK

High channel

Shenzhen EMTEK Co., Ltd.
Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China
www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282



Radiated Emission Measurement



Site 3m Chamber #2 Polarization: **Horizontal** Temperature: 24 C
 Limit: (RE)FCC PART 15 C Power: AC 120V/60Hz Humidity: 53 %
 EUT: ID Camera
 M/N: Focus 72
 Mode:11n40 2452
 Note:

| No. | Mk. | Freq. | Reading Level | Correct Factor | Measurement | Limit | Over | Antenna Height | Table Degree | Comment |
|-----|-----|----------|---------------|----------------|-------------|--------|--------|----------------|--------------|---------|
| | | MHz | dBuV | dB | dBuV/m | dBuV/m | dB | cm | degree | |
| 1 | | 2486.371 | 42.88 | 8.31 | 51.19 | 74.00 | -22.81 | peak | | |
| 2 | * | 2486.371 | 28.19 | 8.31 | 36.50 | 54.00 | -17.50 | AVG | | |


*:Maximum data x:Over limit !:over margin

Operator: KK

Shenzhen EMTEK Co., Ltd.
Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China
www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282



Radiated Emission Measurement



Site 3m Chamber #2 Polarization: **Vertical** Temperature: 24 C
 Limit: (RE)FCC PART 15 C Power: AC 120V/60Hz Humidity: 53 %
 EUT: ID Camera
 M/N: Focus 72
 Mode:11n40 2452
 Note:

| No. | Mk. | Freq. | Reading Level | Correct Factor | Measurement | Limit | Over | Antenna Height | Table Degree | |
|-----|-----|----------|---------------|----------------|-------------|--------|--------|----------------|--------------|---------|
| | | MHz | dBuV | dB | dBuV/m | dBuV/m | dB | cm | degree | Comment |
| 1 | | 2486.421 | 46.76 | 8.31 | 55.07 | 74.00 | -18.93 | peak | | |
| 2 | * | 2486.421 | 31.39 | 8.31 | 39.70 | 54.00 | -14.30 | AVG | | |

*:Maximum data x:Over limit !:over margin

Operator: KK

Appendix C.3: Test Results of Conducted Emission on AC Mains B mode

Shenzhen EMTEK Co., Ltd.
Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China
www.emtek.com.cn Tel:+86-755-2695 4280 Fax:+86-755-2695 4282




Conducted Emission Measurement

File :TUV
80.0 dBuV

Data :#2770

Date: 17/06/28/



Site Conduction #1

Phase: **L1**

Temperature: 22

Limit: (CE)FCC PART 15 class B_QP

Power: AC 120V/60Hz

Humidity: 55 %

EUT: IP Camera

M/N: Focus 72

Mode: Lan Mode

Note:

| No. | Mk. | Freq. MHz | Reading Level dBuV | Correct Factor dB | Measure- ment dBuV | Limit dBuV | Over dB | Detector | Comment |
|-----|-----|--------------|--------------------------|-------------------------|--------------------------|---------------|------------|----------|---------|
| 1 | | 0.4450 | 39.76 | 0.00 | 39.76 | 56.97 | -17.21 | QP | |
| 2 | * | 0.4450 | 31.09 | 0.00 | 31.09 | 46.97 | -15.88 | AVG | |
| 3 | | 0.9350 | 28.95 | 0.00 | 28.95 | 56.00 | -27.05 | QP | |
| 4 | | 0.9350 | 19.56 | 0.00 | 19.56 | 46.00 | -26.44 | AVG | |
| 5 | | 3.3750 | 31.17 | 0.00 | 31.17 | 56.00 | -24.83 | QP | |
| 6 | | 3.3750 | 19.29 | 0.00 | 19.29 | 46.00 | -26.71 | AVG | |
| 7 | | 6.0400 | 38.26 | 0.00 | 38.26 | 60.00 | -21.74 | QP | |
| 8 | | 6.0400 | 32.60 | 0.00 | 32.60 | 50.00 | -17.40 | AVG | |
| 9 | | 17.8900 | 40.30 | 0.00 | 40.30 | 60.00 | -19.70 | QP | |
| 10 | | 17.8900 | 22.00 | 0.00 | 22.00 | 50.00 | -28.00 | AVG | |
| 11 | | 23.2600 | 38.36 | 0.00 | 38.36 | 60.00 | -21.64 | QP | |
| 12 | | 23.2600 | 21.61 | 0.00 | 21.61 | 50.00 | -28.39 | AVG | |

*:Maximum data x:Over limit !:over margin Comment: Factor build in receiver. Operator: Stan

File :TUVData :#2770

Page: 1

Shenzhen EMTEK Co., Ltd.
Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China
www.emtek.com.cn Tel:+86-755-2695 4280 Fax:+86-755-2695 4282




Conducted Emission Measurement

File :TUV
80.0 dBuV

Data :#2769

Date: 17/06/28/



Site Conduction #1

Phase: **N**

Temperature: 22

Limit: (CE)FCC PART 15 class B_QP

Power: AC 120V/60Hz

Humidity: 55 %

EUT: IP Camera

M/N: Focus 72

Mode: Lan Mode

Note:

| No. | Mk. | Freq. MHz | Reading Level dBuV | Correct Factor dB | Measure- ment dBuV | Limit dBuV | Over dB | Detector | Comment |
|-----|-----|--------------|--------------------------|-------------------------|--------------------------|---------------|------------|----------|---------|
| 1 | | 0.1600 | 34.71 | 0.00 | 34.71 | 65.46 | -30.75 | QP | |
| 2 | | 0.1600 | 17.71 | 0.00 | 17.71 | 55.46 | -37.75 | AVG | |
| 3 | | 0.4450 | 30.95 | 0.00 | 30.95 | 56.97 | -26.02 | QP | |
| 4 | | 0.4450 | 21.33 | 0.00 | 21.33 | 46.97 | -25.64 | AVG | |
| 5 | | 1.2800 | 26.70 | 0.00 | 26.70 | 56.00 | -29.30 | QP | |
| 6 | | 1.2800 | 11.68 | 0.00 | 11.68 | 46.00 | -34.32 | AVG | |
| 7 | | 6.0400 | 34.93 | 0.00 | 34.93 | 60.00 | -25.07 | QP | |
| 8 | | 6.0400 | 26.11 | 0.00 | 26.11 | 50.00 | -23.89 | AVG | |
| 9 | | 18.4400 | 37.95 | 0.00 | 37.95 | 60.00 | -22.05 | QP | |
| 10 | | 18.4400 | 20.66 | 0.00 | 20.66 | 50.00 | -29.34 | AVG | |
| 11 | * | 21.8600 | 38.06 | 0.00 | 38.06 | 60.00 | -21.94 | QP | |
| 12 | | 21.8600 | 18.68 | 0.00 | 18.68 | 50.00 | -31.32 | AVG | |

*:Maximum data x:Over limit !:over margin Comment: Factor build in receiver. Operator: Stan

File :TUV\Data :#2769

Page: 1


C mode

Shenzhen EMTEK Co., Ltd.
Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China
www.emtek.com.cn Tel:+86-755-2695 4280 Fax:+86-755-2695 4282



Conducted Emission Measurement

File :TUV Data :#1264 Date: 2017/06/19



Site Conduction #2 Phase: **L1** Temperature: 21
Limit: (CE)FCC PART 15 class B_QP Power: AC 120V/60Hz Humidity: 53 %
EUT: IP CAMERA
M/N: FOCUS 72
Mode: WIFI MODE
Note:

| No. | Mk. | Freq. | Reading Level | Correct Factor | Measurement | Limit | Over | Detector | Comment |
|-----|-----|---------|---------------|----------------|-------------|-------|--------|----------|---------|
| | | MHz | dBuV | dB | dBuV | dBuV | dB | | |
| 1 | | 0.1660 | 26.85 | 9.62 | 36.47 | 65.16 | -28.69 | QP | |
| 2 | | 0.1660 | 15.84 | 9.62 | 25.46 | 55.16 | -29.70 | AVG | |
| 3 | | 0.4460 | 31.90 | 9.70 | 41.60 | 56.95 | -15.35 | QP | |
| 4 | | 0.4460 | 24.03 | 9.70 | 33.73 | 46.95 | -13.22 | AVG | |
| 5 | | 1.2700 | 21.32 | 9.85 | 31.17 | 56.00 | -24.83 | QP | |
| 6 | | 1.2700 | 11.62 | 9.85 | 21.47 | 46.00 | -24.53 | AVG | |
| 7 | | 5.8420 | 30.15 | 9.87 | 40.02 | 60.00 | -19.98 | QP | |
| 8 | | 5.8420 | 20.86 | 9.87 | 30.73 | 50.00 | -19.27 | AVG | |
| 9 | | 13.4820 | 29.78 | 10.63 | 40.41 | 60.00 | -19.59 | QP | |
| 10 | | 13.4820 | 24.24 | 10.63 | 34.87 | 50.00 | -15.13 | AVG | |
| 11 | | 18.3060 | 39.99 | 10.47 | 50.46 | 60.00 | -9.54 | QP | |
| 12 | * | 18.3060 | 32.66 | 10.47 | 43.13 | 50.00 | -6.87 | AVG | |

*:Maximum data x:Over limit !:over margin Comment: Factor build in receiver. Operator: CSL

File :TUVData :#1264


Page: 1

Shenzhen EMTEK Co., Ltd.
Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China
www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282



Conducted Emission Measurement

File :TUV Data :#1265 Date: 2017/06/19




Site Conduction #2 Phase: **N** Temperature: 21
Limit: (CE)FCC PART 15 class B_QP Power: AC 120V/60Hz Humidity: 53 %
EUT: IP CAMERA
M/N: FOCUS 72
Mode: WIFI MODE
Note:

| No. | Mk. | Freq. | Reading Level | Correct Factor | Measurement | Limit | Over | Detector | Comment |
|-----|-----|---------|---------------|----------------|-------------|-------|--------|----------|---------|
| | | MHz | dBuV | dB | dBuV | dBuV | dB | | |
| 1 | | 0.1620 | 24.47 | 9.62 | 34.09 | 65.36 | -31.27 | QP | |
| 2 | | 0.1620 | 11.11 | 9.62 | 20.73 | 55.36 | -34.63 | AVG | |
| 3 | | 0.4140 | 26.44 | 9.69 | 36.13 | 57.57 | -21.44 | QP | |
| 4 | | 0.4140 | 14.17 | 9.69 | 23.86 | 47.57 | -23.71 | AVG | |
| 5 | | 0.9500 | 20.80 | 9.84 | 30.64 | 56.00 | -25.36 | QP | |
| 6 | | 0.9500 | 7.65 | 9.84 | 17.49 | 46.00 | -28.51 | AVG | |
| 7 | | 6.1180 | 29.68 | 9.88 | 39.56 | 60.00 | -20.44 | QP | |
| 8 | | 6.1180 | 18.57 | 9.88 | 28.45 | 50.00 | -21.55 | AVG | |
| 9 | | 13.4220 | 28.76 | 10.63 | 39.39 | 60.00 | -20.61 | QP | |
| 10 | | 13.4220 | 21.83 | 10.63 | 32.46 | 50.00 | -17.54 | AVG | |
| 11 | | 18.3060 | 38.33 | 10.47 | 48.80 | 60.00 | -11.20 | QP | |
| 12 | * | 18.3060 | 29.30 | 10.47 | 39.77 | 50.00 | -10.23 | AVG | |

*:Maximum data x:Over limit !:over margin Comment: Factor build in receiver. Operator: CSL

Appendix C.4: Test Results of Radiated Emission B mode

Shenzhen EMTEK Co., Ltd.
Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China
www.emtek.com.cn Tel:+86-755-2695 4280 Fax:+86-755-2695 4282



| No. | Mk. | Freq. MHz | Reading Level dBuV | Correct Factor dB | Measure- ment dBuV/m | Limit dBuV/m | Over dB | Antenna Height cm | Table Degree degree | Comment |
|-----|-----|--------------|--------------------------|-------------------------|----------------------------|-----------------|------------|-------------------------|---------------------------|---------|
| 1 | | 299.6600 | 44.57 | -11.27 | 33.30 | 46.00 | -12.70 | QP | | |
| 2 | | 382.1100 | 43.28 | -8.77 | 34.51 | 46.00 | -11.49 | QP | | |
| 3 | | 475.2300 | 42.54 | -7.43 | 35.11 | 46.00 | -10.89 | QP | | |
| 4 | | 600.3600 | 33.37 | -4.48 | 28.89 | 46.00 | -17.11 | QP | | |
| 5 | | 709.0000 | 38.88 | -2.80 | 36.08 | 46.00 | -9.92 | QP | | |
| 6 | * | 818.6100 | 37.04 | -0.88 | 36.16 | 46.00 | -9.84 | QP | | |


*:Maximum data x:Over limit !:over margin

Operator: KK

Shenzhen EMTEK Co., Ltd.
Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China
www.emtek.com.cn Tel:+86-755-2695 4280 Fax:+86-755-2695 4282



Radiated Emission Measurement



Site 3m Chamber #2 Polarization: **Vertical** Temperature: 22 C
 Limit: (RE)FCC PART 15 CLASS B Power: AC 120V/60Hz Humidity: 55 %
 EUT: IP Camera
 M/N: Focus 72
 Mode:Lan Mode
 Note:

| No. | Mk. | Freq. | Reading Level | Correct Factor | Measurement | Limit | Over | Antenna Height | Table Degree | Detector | Comment |
|-----|-----|----------|---------------|----------------|-------------|--------|--------|----------------|--------------|----------|---------|
| | | MHz | dBuV | dB | dBuV/m | dBuV/m | dB | cm | degree | | |
| 1 | | 218.1800 | 46.37 | -13.98 | 32.39 | 46.00 | -13.61 | | | QP | |
| 2 | | 272.5000 | 44.51 | -11.74 | 32.77 | 46.00 | -13.23 | | | QP | |
| 3 | | 490.7500 | 37.59 | -7.07 | 30.52 | 46.00 | -15.48 | | | QP | |
| 4 | | 600.3600 | 36.74 | -4.48 | 32.26 | 46.00 | -13.74 | | | QP | |
| 5 | * | 709.0000 | 38.42 | -2.80 | 35.62 | 46.00 | -10.38 | | | QP | |
| 6 | | 827.3400 | 34.26 | -0.74 | 33.52 | 46.00 | -12.48 | | | QP | |


*:Maximum data x:Over limit l:over margin

Operator: KK

Shenzhen EMTEK Co., Ltd.
Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China
www.emtek.com.cn Tel:+86-755-2695 4280 Fax:+86-755-2695 4282



Radiated Emission Measurement



Site 3m Chamber #2 Polarization: **Horizontal** Temperature: 22 C
 Limit: (RE)FCC PART 15 CLASS B Power: AC 120V/60Hz Humidity: 55 %
 EUT: IP Camera
 M/N: Focus 72
 Mode:LAN Mode
 Note:

| No. | Mk. | Freq. | Reading Level | Correct Factor | Measurement | Limit | Over | Antenna Height | Table Degree | Comment |
|-----|-----|----------|---------------|----------------|-------------|--------|--------|----------------|--------------|---------|
| | | MHz | dBuV | dB | dBuV/m | dBuV/m | dB | cm | degree | |
| 1 | | 1885.000 | 55.48 | -14.11 | 41.37 | 74.00 | -32.63 | peak | | |
| 2 | | 1885.000 | 39.71 | -14.11 | 25.60 | 54.00 | -28.40 | AVG | | |
| 3 | | 2435.000 | 54.07 | -12.71 | 41.36 | 74.00 | -32.64 | peak | | |
| 4 | | 2435.000 | 39.61 | -12.71 | 26.90 | 54.00 | -27.10 | AVG | | |
| 5 | | 4150.000 | 51.97 | -9.75 | 42.22 | 74.00 | -31.78 | peak | | |
| 6 | | 4150.000 | 37.05 | -9.75 | 27.30 | 54.00 | -26.70 | AVG | | |
| 7 | | 5055.000 | 52.64 | -8.02 | 44.62 | 74.00 | -29.38 | peak | | |
| 8 | * | 5055.000 | 38.22 | -8.02 | 30.20 | 54.00 | -23.80 | AVG | | |
| 9 | | 5500.000 | 51.54 | -7.42 | 44.12 | 74.00 | -29.88 | peak | | |
| 10 | | 5500.000 | 35.92 | -7.42 | 28.50 | 54.00 | -25.50 | AVG | | |
| 11 | | 5720.000 | 51.79 | -6.97 | 44.82 | 74.00 | -29.18 | peak | | |
| 12 | | 5720.000 | 36.07 | -6.97 | 29.10 | 54.00 | -24.90 | AVG | | |


*:Maximum data x:Over limit l:over margin

Operator: KK

Shenzhen EMTEK Co., Ltd.
Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China
www.emtek.com.cn Tel:+86-755-2695 4280 Fax:+86-755-2695 4282



Radiated Emission Measurement



Site 3m Chamber #2 Polarization: **Vertical** Temperature: 22 C
 Limit: (RE)FCC PART 15 CLASS B Power: AC 120V/60Hz Humidity: 55 %
 EUT: IP Camera
 M/N: Focus 72
 Mode:LAN Mode
 Note:

| No. | Mk. | Freq. MHz | Reading Level dBuV | Correct Factor dB | Measure- ment dBuV/m | Limit dBuV/m | Over dB | Detector | Antenna Height cm | Table Degree | Comment |
|-----|-----|--------------|--------------------------|-------------------------|----------------------------|-----------------|------------|----------|-------------------------|-----------------|---------|
| 1 | | 1885.000 | 54.77 | -14.11 | 40.66 | 74.00 | -33.34 | peak | | | |
| 2 | | 1885.000 | 39.51 | -14.11 | 25.40 | 54.00 | -28.60 | AVG | | | |
| 3 | | 2470.000 | 52.86 | -12.60 | 40.26 | 74.00 | -33.74 | peak | | | |
| 4 | | 2470.000 | 38.90 | -12.60 | 26.30 | 54.00 | -27.70 | AVG | | | |
| 5 | | 4145.000 | 51.64 | -9.76 | 41.88 | 74.00 | -32.12 | peak | | | |
| 6 | | 4145.000 | 36.86 | -9.76 | 27.10 | 54.00 | -26.90 | AVG | | | |
| 7 | | 4380.000 | 51.75 | -9.15 | 42.60 | 74.00 | -31.40 | peak | | | |
| 8 | | 4380.000 | 37.35 | -9.15 | 28.20 | 54.00 | -25.80 | AVG | | | |
| 9 | | 4660.000 | 52.35 | -8.60 | 43.75 | 74.00 | -30.25 | peak | | | |
| 10 | * | 4660.000 | 38.00 | -8.60 | 29.40 | 54.00 | -24.60 | AVG | | | |
| 11 | | 5280.000 | 51.02 | -7.72 | 43.30 | 74.00 | -30.70 | peak | | | |
| 12 | | 5280.000 | 35.22 | -7.72 | 27.50 | 54.00 | -26.50 | AVG | | | |

*:Maximum data x:Over limit !:over margin

Operator: KK