



Prüfbericht-Nr.: <i>Test report No.:</i>	50074440 001	Auftrags-Nr.: <i>Order No.:</i>	164084981	Seite 1 von 27 <i>Page 1 of 27</i>	
Kunden-Referenz-Nr.: <i>Client reference No.:</i>	N/A	Auftragsdatum: <i>Order date.:</i>	06.02.2017		
Auftraggeber: <i>Client:</i>	Binatone Electronics International Ltd. Floor 23A, 9 Des Voeux Road West, Sheung Wan, Hong Kong				
Prüfgegenstand: <i>Test item:</i>	Digital Video Baby Monitor (Parent Unit)				
Bezeichnung / Typ-Nr.: <i>Identification / Type No.:</i>	MBP33SPU, MBP35SPU (Trademark: motorola)				
Auftrags-Inhalt: <i>Order content:</i>	FCC and IC approval				
Prüfgrundlage: <i>Test specification:</i>	CFR47 FCC Part 15: Subpart C Section 15.247 CFR47 FCC Part 15: Subpart C Section 15.207 CFR47 FCC Part 15: Subpart C Section 15.209 CFR47 FCC Part 15: Subpart B Section 15.107 CFR47 FCC Part 15: Subpart B Section 15.109 CFR47 FCC Part 2: Section 2.1091				
Wareneingangsdatum: <i>Date of receipt:</i>	06.02.2017	Please refer to photo documents			
Prüfmuster-Nr.: <i>Test sample No.:</i>	A000491418-001 A000491418-002				
Prüfzeitraum: <i>Testing period:</i>	06.02.2017 - 13.03.2017				
Ort der Prüfung: <i>Place of testing:</i>	EMTEK(Shenzhen) Co., Ltd.				
Prüflaboratorium: <i>Testing laboratory:</i>	TÜV Rheinland (Shenzhen) Co., Ltd.				
Prüfergebnis*: <i>Test result*:</i>	Pass				
geprüft von / tested by:		kontrolliert von / reviewed by:			
 26.04.2017 Ryan Yang / Senior Project Engineer		 26.04.2017 Winnie Hou / Technical Certifier			
Datum <i>Date</i>	Name/Stellung <i>Name/Position</i>	Unterschrift <i>Signature</i>	Datum <i>Date</i>	Name/Stellung <i>Name/Position</i>	Unterschrift <i>Signature</i>
Sonstiges / Other:					
This report is for Parent Unit of digital video baby monitor system only. FCC ID: VLJ-MBP33SCPU IC: 4522A-MBP33SCPU HVIN: MBP33SPU, MBP35SPU					
Zustand des Prüfgegenstandes bei Anlieferung: <i>Condition of the test item at delivery:</i>			Prüfmuster vollständig und unbeschädigt <i>Test item complete and undamaged:</i>		
* Legende: 1 = sehr gut 2 = gut 3 = befriedigend 4 = ausreichend 5 = mangelhalt P(ass) = entspricht o.g. Prüfgrundlage(n) F(ail) = entspricht nicht o.g. Prüfgrundlage(n) N/A = nicht anwendbar N/T = nicht getestet Legend: 1 = very good 2 = good 3 = satisfactory 4 = sufficient 5 = poor P(ass) = passed a.m. test specifications(s) F(ail) = failed a.m. test specifications(s) N/A = not applicable N/T = not tested					
Dieser Prüfbericht bezieht sich nur auf das o.g. Prüfmuster und darf ohne Genehmigung der Prüfstelle nicht auszugsweise vervielfältigt werden. Dieser Bericht berechtigt nicht zur Verwendung eines Prüfzeichens.					
<i>This test report only relates to the a. m. test sample. Without permission of the test center this test report is not permitted to be duplicated in extracts. This test report does not entitle to carry any test mark.</i>					

Test Summary

5.1.1 ANTENNA REQUIREMENT*RESULT: Pass***5.1.2 MAXIMUM PEAK CONDUCTED OUTPUT POWER***RESULT: Pass***5.1.3 99% BANDWIDTH***RESULT: Pass***5.1.4 CONDUCTED SPURIOUS EMISSIONS MEASURED IN 100 KHZ BANDWIDTH***RESULT: Pass***5.1.5 RADIATED SPURIOUS EMISSION***RESULT: Pass***5.1.6 20dB BANDWIDTH***RESULT: Pass***5.1.7 CARRIER FREQUENCY SEPARATION***RESULT: Pass***5.1.8 NUMBER OF HOPPING FREQUENCY***RESULT: Pass***5.1.9 TIME OF OCCUPANCY***RESULT: Pass***5.1.10 CONDUCTED EMISSION ON AC MAINS***RESULT: Pass***5.1.11 RADIATED EMISSION***RESULT: Pass***6.1.1 ELECTROMAGNETIC FIELDS***RESULT: Pass*

Contents

1	GENERAL REMARKS	5
1.1	COMPLEMENTARY MATERIALS	5
2	TEST SITES	5
2.1	TEST FACILITIES	5
2.2	LIST OF TEST AND MEASUREMENT INSTRUMENTS.....	6
2.3	TRACEABILITY	7
2.4	CALIBRATION	7
2.5	MEASUREMENT UNCERTAINTY.....	7
2.6	LOCATION OF ORIGINAL DATA.....	7
2.7	STATUS OF FACILITY USED FOR TESTING.....	7
3	GENERAL PRODUCT INFORMATION	8
3.1	PRODUCT FUNCTION AND INTENDED USE.....	8
3.2	RATINGS AND SYSTEM DETAILS	8
3.3	INDEPENDENT OPERATION MODES	10
3.4	NOISE GENERATING AND NOISE SUPPRESSING PARTS.....	10
3.5	SUBMITTED DOCUMENTS.....	10
4	TEST SET-UP AND OPERATION MODES	11
4.1	PRINCIPLE OF CONFIGURATION SELECTION	11
4.2	TEST OPERATION AND TEST SOFTWARE.....	11
4.3	SPECIAL ACCESSORIES AND AUXILIARY EQUIPMENT.....	11
4.4	COUNTERMEASURES TO ACHIEVE EMC COMPLIANCE.....	11
4.5	TEST SETUP DIAGRAM.....	12
5	TEST RESULTS	14
5.1	TRANSMITTER REQUIREMENT & TEST SUITES	14
5.1.1	<i>Antenna Requirement</i>	<i>14</i>
5.1.2	<i>Maximum Peak Conducted Output Power.....</i>	<i>15</i>
5.1.3	<i>99% Bandwidth</i>	<i>16</i>
5.1.4	<i>Conducted Spurious Emissions Measured in 100 kHz Bandwidth</i>	<i>17</i>
5.1.5	<i>Radiated Spurious Emission</i>	<i>18</i>
5.1.6	<i>20dB Bandwidth</i>	<i>19</i>
5.1.7	<i>Carrier Frequency Separation.....</i>	<i>20</i>
5.1.8	<i>Number of Hopping Frequency.....</i>	<i>21</i>
5.1.9	<i>Time of Occupancy</i>	<i>22</i>
5.1.10	<i>Conducted Emission on AC Mains</i>	<i>23</i>
5.1.11	<i>Radiated Emission.....</i>	<i>24</i>
6	SAFETY HUMAN EXPOSURE	25
6.1	RADIO FREQUENCY EXPOSURE COMPLIANCE	25
6.1.1	<i>Electromagnetic Fields.....</i>	<i>25</i>
7	PHOTOGRAPHS OF THE TEST SET-UP	27

8	LIST OF TABLES.....	27
----------	----------------------------	-----------

1 General Remarks

1.1 Complementary Materials

All attachments are integral parts of this test report. This applies especially to the following appendix:

Appendix A: Photographs of the Test Set-up

Appendix B: Test Results of General 2.4GHz Wireless of Conducted Testing

Appendix C: Test Results of General 2.4GHz Wireless of Radiated Testing

2 Test Sites

2.1 Test Facilities

EMTEK(Shenzhen) Co., Ltd.

Building 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, China

FCC Registration No.: 406365

Test site Industry Canada No.: 4480A-2

The tests at the test sites have been conducted under the supervision of a TÜV engineer.

2.2 List of Test and Measurement Instruments

Table 1: List of Test and Measurement Equipment

EMTEK(Shenzhen) Co., Ltd.

Radio Spectrum Testing				
Equipment	Manufacturer	Model No.	Serial No.	Cal. Until
EMI Test Receiver	R&S	ESU	1302.6005.26	28.05.2017
Signal Analyzer	Agilent	N9010A	My53470879	28.05.2017
Power Analyzer	Agilent	PS-X10-200	N/A	28.05.2017
Test Accessories	Agilent	PS-X10-100	N/A	28.05.2017
Spurious Emission & Radiated Emission				
Equipment	Manufacturer	Model No.	Serial No.	Cal. Until
EMI Test Receiver	R&S	ESU	1302.6005.26	28.05.2017
Pre-Amplifier	HP	8447D	2944A07999	28.05.2017
Bilog Antenna	Schwarzbeck	VULB9163	142	28.05.2017
Horn Antenna	Schwarzbeck	BBHA 9170	BBHA9170399	28.05.2017
Horn Antenna	Schwarzbeck	BBHA 9120	D143	28.05.2017
Cable	Schwarzbeck	AK9513	ACRX1	28.05.2017
Cable	Rosenberger	N/A	FP2RX2	28.05.2017
Cable	Schwarzbeck	AK9513	CRPX1	28.05.2017
Cable	Schwarzbeck	AK9513	CRRX2	28.05.2017
Pre-Amplifier	LUNAR-EM	LNA30M3G-25	J10100000070	28.05.2017
Conducted Emission on AC Mains				
Equipment	Manufacturer	Model No.	Serial No.	Cal. Until
Test Receiver	R&S	ESCI	26115-010-0027	28.05.2017
L.I.S.N.	R&S	ENV216	101161	28.05.2017
50Ω Coaxial Switch	Anritsu	MP59B	6100175589	28.05.2017

2.3 Traceability

All measurement equipment calibrations are traceable to NIM (National Institute of Metrology) or where calibration is performed in other countries, to equivalent nationally recognized standards organizations.

2.4 Calibration

Equipment requiring calibration is calibrated periodically by the manufacturer or according to manufacturer's specifications. Additionally all equipment is verified for proper performance on a regular basis using in house standards or comparisons.

2.5 Measurement Uncertainty

The estimated combined standard uncertainty for radiated emissions and conducted emissions measurements as below table

Parameter	Uncertainty
RF Output Power	±1.0%
Accumulated Transmit Time, Frequency Occupation and Hopping Sequence	±1.3%
Occupied Channel Bandwidth	±2.3%
Transmitter Unwanted Emission in the Out-of Band	±1.2%
Transmitter Unwanted Emissions in the Spurious Domain	±2.7%
Conducted Emission, 9k~150kHz	3.16dB
Conducted Emission, 150k-30MHz	2.90dB
Radiated Emission, below 1GHz	4.27dB
Radiated Emission, above 1GHz	4.46dB

2.6 Location of Original Data

The original copies of all test data taken during actual testing were attached at Appendix A & B & C of this report and delivered to the applicant. A copy has been retained in the TÜV Rheinland (Shenzhen) file for certification follow-up purposes.

2.7 Status of Facility Used for Testing

The EMTEK(Shenzhen) Co., Ltd. Test facility located at Building 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, China is listed on the US Federal Communications Commission list of facilities approved to perform measurements.

3 General Product Information

3.1 Product Function and Intended Use

The EUT is a Digital Video Baby Monitor (Parent Unit) device, it supports general 2.4GHz wireless technology.

According to the declaration of the applicant, the electrical circuit design, PCB layout and components used are identical for all models, only the model number is different.

For details refer to the User Manual, Technical Description and Circuit Diagram.

3.2 Ratings and System Details

Table 2: Technical Specification of EUT

General Information of EUT	Value
Kind of Equipment	Digital Video Baby Monitor (Parent Unit)
Type Designation	MBP33SPU, MBP35SPU
Trademark	motorola
FCC ID	VLJ-MBP33SCPU
IC	4522A-MBP33SCPU
HVIN	MBP33SPU, MBP35SPU
Operating Temperature Range	5 °C ~ +45 °C
Operating Voltage	DC 6.0V 500mA input via AC/DC adapter DC 3.6V 800mA input via Ni-MH battery
Testing Voltage	AC 120V, 60Hz
AC/DC Adapter	Model: S003GU0600050 (TenPao) Input: AC 100-240V~50/60Hz, 150mA Output: DC 6.0V~500mA
Ni-MH Battery #1	Model: GP80AAAHC3BMXZ (GPI) DC 3.6V 800mAh, Ni-MH Battery
Ni-MH Battery #2	Model: JHAAA800P3H (JUSTHIGH) DC 3.6V 800mAh, Ni-MH Battery
Technical Specification of General 2.4GHz Wireless	
Operating Frequency	2405 - 2475 MHz
Type of Modulation	FSK
Channel Number	32 channels
Antenna Type	Integral Antenna
Antenna Gain	0 dBi

Table 3: RF Channel and Frequency of General 2.4GHz Wireless

RF Channel	Frequency (MHz)	RF Channel	Frequency (MHz)	RF Channel	Frequency (MHz)
01	2405	12	2428	23	2454
02	2407	13	2430	24	2456
03	2409	14	2433	25	2458.5
04	2411	15	2435	26	2460.5
05	2413	16	2437	27	2462.5
06	2415	17	2439	28	2467
07	2418	18	2441	29	2469
08	2420	19	2444	30	2471
09	2422	20	2446	31	2473
10	2424	21	2450	32	2475
11	2426	22	2452	/	/

Table 4: Frequency Hopping Information

Technical Specification	Description
Hopping Sequence	<p>Describe how the hopping sequence is generated. Provide an example of the hopping sequence channels, in order to demonstrate that the sequence meets the requirement specified in the definition of a frequency hopping spread spectrum system, found in Section 2.1. This system is controlled by microchip to generate Pseudorandom Frequency Hopping Sequence base on CCITT16 and distributed it over 32 hopping channels. The sequential hops are randomly distributed in both direction and magnitude of change in the hop set which meet the requirement specified in the definition of FCC part 2 section.1.</p> <p>Describe how each individual EUT meets the requirement that each of its hopping channels is used equally on average (e.g., that each new transmission event begins on the next channel in the hopping sequence after the final channel used in the previous transmission event). A single data frame is transmitted on each frequency location before skipping to the next hopping frequency in the list. So each hopping channels is used equally on average in long term.</p>
Receiver input bandwidth	<p>Describe how the associated receiver(s) complies with the requirement that its input bandwidth (either RF or IF) matches the bandwidth of the transmitted signal. Both receiver and transmitter are set to same bandwidth of 2MHz.</p> <p>Describe how the associated receiver(s) has the ability to shift frequencies in synchronization with the transmitted signals. Both transmitter and receiver will share the same device ID so the same sequence is generated for the communication. Moreover, the microchip has a clock recovery mechanism to synchronize the timing between the transmitter and receiver. With the same hopping sequence and timing, the receiver can shift frequencies in synchronization with the transmitted signals.</p>

3.3 Independent Operation Modes

The basic operation modes are:

- A. On, General 2.4GHz wireless transmitting (with adapter + battery #1)
 - 1. Low channel
 - 2. Middle channel
 - 3. High channel
- B. On, General 2.4GHz wireless on hopping channel (with adapter + battery #1)
- C. On, Normal operation with general 2.4GHz wireless transmitting (with adapter + battery #1)
- D. On, Charging mode (with adapter + battery #1, adapter + battery #2)
- E. Off

3.4 Noise Generating and Noise Suppressing Parts

Refer to Circuit Diagram for further details.

3.5 Submitted Documents

- Application Form
- Block Diagram
- FCC/IC Label and Location Info
- Operation Description
- Photo Document
- Schematics
- User Manual

4 Test Set-up and Operation Modes

4.1 Principle of Configuration Selection

Radio Spectrum: The equipment under test (EUT) was configured at its highest power output in order to measure its highest possible radiation and conducted level. The test modes were adapted accordingly in reference to the instructions for use.

Emission: The equipment under test (EUT) was configured to measure its highest possible radiation level. The test modes were adapted accordingly in reference to the instructions for use.

4.2 Test Operation and Test Software

Test operation refers to test setup in chapter 5. All testing were performed according to the procedures in ANSI C63.10: 2013 and ANSI C63.4: 2014.

According to clause 3.2, Radio Spectrum and Radiated Spurious Emission tests were performed on model MBP33SPU(with adapter + Battery #1), and Conducted Emission and Radiated Emission tests were performed on model MBP33SPU with all operation mode in this report.

4.3 Special Accessories and Auxiliary Equipment

Table 5: List of Accessories and Auxiliary Equipment

Description	Manufacturer	Model	S/N	Rating
Notebook	HP	Compaq 6515b	SS05538914	N/A
Digital Video Baby Monitor (Baby Unit)	VTech (Dongguan) Telecommunications Ltd.	MBP33SBU	N/A	N/A

4.4 Countermeasures to Achieve EMC Compliance

Additional countermeasures to the submitted test sample(s) for Radiated Spurious Emission were employed to achieve compliance.

4.5 Test Setup Diagram

Diagram of Measurement Configuration for Radiation Test (Below 1GHz)




Diagram of Measurement Configuration for Radiation Test (Above 1GHz)




Diagram of Measurement Configuration for Mains Conduction Measurement





Diagram of Measurement Configuration for Conducted Transmitter Measurement



5 Test Results

5.1 Transmitter Requirement & Test Suites

5.1.1 Antenna Requirement

RESULT:**Pass****Test Specification**

Test standard : FCC Part 15.247(b)(4) and Part 15.203

According to the manufacturer declared, the EUT has an internal antenna, the directional gain of antenna is 0 dBi, and the antenna connector is designed with permanent attachment and no consideration of replacement. Therefore the EUT is considered sufficient to comply with the provision.

Therefore the EUT is considered sufficient to comply with the provision.

Refer to EUT Photo for further details.

5.1.2 Maximum Peak Conducted Output Power

RESULT:
Pass
Test Specification

Test standard : FCC Part 15.247(b)(1)
 RSS-247 Clause 5.4(2)

Basic standard : ANSI C63.10: 2013

Limits : 0.125 Watts

Kind of test site : Shielded Room

Test Setup

Date of testing : 17.02.2017

Input voltage : AC 120V, 60Hz

Operation mode : A

Test channel : Low / Middle / High

Ambient temperature : 25 °C

Relative humidity : 56 %

Atmospheric pressure : 101 kPa

For details refer to following test result.

Table 6: Test Result of Maximum Peak Conducted Output Power

Test EUT	Frequency (MHz)	Measured Power		Limit (W)
		(dBm)	(W)	
Parent Unit	2405.0	17.704	0.05894	< 0.125
	2441.0	17.454	0.05564	
	2475.0	16.909	0.04908	
Maximum Measured Value		17.704	0.05894	

Note: The cable loss is taken into account in results.

For the measurement records, refer to the appendix B.

5.1.3 99% Bandwidth

RESULT:
Pass
Test Specification

Test standard : RSS-Gen Clause 6.6
 Basic standard : ANSI C63.10: 2013
 Kind of test site : Shielded Room

Test Setup

Date of testing : 17.02.2017
 Input voltage : AC 120V, 60Hz
 Operation mode : A
 Test channel : Low / Middle / High
 Ambient temperature : 25 °C
 Relative humidity : 56 %
 Atmospheric pressure : 101 kPa

For details refer to following test result.

Table 7: Test Result of 99% Bandwidth

Test EUT	Frequency (MHz)	99% Bandwidth (MHz)	Limit (kHz)
Parent Unit	2405.0	2.124	/
	2441.0	2.121	
	2475.0	2.114	
Maximum Measured Value		2.124	

For the measurement records, refer to the appendix B.

5.1.4 Conducted Spurious Emissions Measured in 100 kHz Bandwidth

RESULT: **Pass****Test Specification**

Test standard	: FCC Part 15.247(d) RSS-247 Clause 5.5
Basic standard	: ANSI C63.10: 2013
Limits	: 20dB (below that in the 100kHz bandwidth within the band that contains the highest level of the desired power); In addition, radiated emissions which fall in the restricted bands, must also comply with the radiated emission limits specified in 15.209(a)
Kind of test site	: Shielded Room

Test Setup

Date of testing	: 17.02.2017
Input voltage	: AC 120V, 60Hz
Operation mode	: A
Test channel	: Low / Middle / High
Ambient temperature	: 25 °C
Relative humidity	: 56 %
Atmospheric pressure	: 101 kPa

Test results of 100kHz Bandwidth of Frequency Band Edge by Conducted method refer to test plots, and compliance is achieved as well.

For the measurement records, refer to the appendix B.

5.1.5 Radiated Spurious Emission

RESULT:**Pass****Test Specification**

Test standard	: FCC Part 15.247(d) & FCC Part 15.205 RSS-247 Clause 3.3
Basic standard	: ANSI C63.10: 2013
Limits	: Refer to 15.209(a) of FCC part 15.247(d) RSS-Gen Issue 4 Table 4
Kind of test site	: 3m Semi-anechoic Chamber

Test Setup

Date of testing	: Refer to test result
Input voltage	: AC 120V, 60Hz
Operation mode	: A
Test channel	: Low / Middle / High
Ambient temperature	: 25 °C
Relative humidity	: 56 %
Atmospheric pressure	: 101 kPa

Remark:

Testing was carried out within frequency range 9kHz to the tenth harmonics. Only the worst case spurious emissions configuration of the each mode were reported.

For the measurement records, refer to the appendix C.

5.1.6 20dB Bandwidth

RESULT:
Pass
Test Specification

Test standard : FCC Part 15.247(a)(1)
RSS-247 Clause 5.1(1)

Basic standard : ANSI C63.10: 2013

Kind of test site : Shielded Room

Test Setup

Date of testing : 17.02.2017

Input voltage : AC 120V, 60Hz

Operation mode : A

Test channel : Low / Middle / High

Ambient temperature : 25 °C

Relative humidity : 56 %

Atmospheric pressure : 101 kPa

For details refer to following test result.

Table 8: Test Result of 20dB Bandwidth

Test EUT	Frequency (MHz)	20dB Bandwidth (kHz)	2/3 of 20dB Bandwidth (kHz)	Limit (MHz)
Parent Unit	2405.0	2093.0	1395.3	/
	2441.0	2093.0	1395.3	
	2475.0	2093.0	1395.3	
Maximum Measured Value		2093.0	1395.3	/

For the measurement records, refer to the appendix B.

5.1.7 Carrier Frequency Separation

RESULT:
Pass
Test Specification

Test standard	: FCC Part 15.247(a)(1) RSS-247 Clause 5.1(2)
Basic standard	: ANSI C63.10: 2013
Limits	: $\geq 25\text{kHz}$ or 2/3 of 20dB bandwidth, whichever is greater
Kind of test site	: Shielded Room

Test Setup

Date of testing	: 17.02.2017
Input voltage	: AC 120V, 60Hz
Operation mode	: B
Test channel	: Low / Middle / High
Ambient temperature	: 25 °C
Relative humidity	: 56 %
Atmospheric pressure	: 101 kPa

For details refer to following test result.

Table 9: Test Result of Carrier Frequency Separation

Test EUT	Test Channel	Frequency (MHz)	Measured Channel Separation (KHz)	Limit (kHz)
Parent Unit	Low Channel	2405.0	2000.0	$\geq 25\text{kHz}$ or 2/3 of 20dB bandwidth
	Adjacency Channel	2407.0		
	Middle Channel	2441.0	3000.0	
	Adjacency Channel	2444.0		
	High Channel	2475.0	2008.0	
	Adjacency Channel	2473.0		

Note: The limit is maximum 2/3 of the 20 dB bandwidth: 1395.3 KHz.

For the measurement records, refer to the appendix B.

5.1.8 Number of Hopping Frequency

RESULT:
Pass
Test Specification

Test standard : FCC part 15.247(a)(1)(iii)
RSS-247 Clause 5.1(4)

Basic standard : ANSI C63.10: 2013

Limits : ≥ 15 non-overlapping channels

Kind of test site : Shielded Room

Test Setup

Date of testing : 17.02.2017

Input voltage : AC 120V, 60Hz

Operation mode : B

Ambient temperature : 25 °C

Relative humidity : 56 %

Atmospheric pressure : 101 kPa

For details refer to following test result.

Table 10: Test Result of Number of Hopping Frequency

Test EUT	Frequency Range	Measured Quantity of Hopping Channel	Limit
Parent Unit	2405 - 2475 MHz	32	≥ 15

For the measurement records, refer to the appendix B.

5.1.9 Time of Occupancy

RESULT: **Pass****Test Specification**

Test standard : FCC part 15.247(a)(1)(iii)
RSS-247 Clause 5.1(4)

Basic standard : ANSI C63.10: 2013

Limits : < 0.4s

Kind of test site : Shielded Room

Test Setup

Date of testing : 17.02.2017

Input voltage : AC 120V, 60Hz

Operation mode : B

Test channel : Low / Middle / High

Ambient temperature : 25 °C

Relative humidity : 56 %

Atmospheric pressure : 101 kPa

For details refer to following test result.

Table 11: Test Result of Time of Occupancy

Test EUT	Frequency (MHz)	Pulse width (ms)	Number of Channels	Measured Dwell time (s)	Limit (s)
Parent Unit	2405.0	0.812	70	0.057	0.4s
	2441.0	0.812	70	0.057	
	2475.0	0.841	70	0.059	

Note:

Dwell time = Pulse width x Number of channels in Period

Period = 0.4 (seconds/ channel) x 32 (channel) = 12.8 seconds

For the measurement records, refer to the appendix B.

5.1.10 Conducted Emission on AC Mains**RESULT:****Pass****Test Specification**

Test standard	: FCC Part 15.207(a) & FCC Part 15.107(a) RSS-Gen Clause 8.8 & ICES-003
Basic standard	: ANSI C63.10: 2013 & ANSI C63.4: 2014
Frequency range	: 0.15 – 30MHz
Limits	: FCC Part 15.207(a) & FCC Part 15.107(a) RSS-Gen Table 3 & ICES-003 Table 2
Kind of test site	: Shielded Room

Test Setup

Date of testing	: 11.02.2017
Input voltage	: AC 120V, 60Hz
Operation mode	: C, D
Earthing	: Not connected
Ambient temperature	: 22 °C
Relative humidity	: 55 %
Atmospheric pressure	: 101 kPa

For the measurement records, refer to the appendix C.

5.1.11 Radiated Emission**RESULT:****Pass****Test Specification**

Test standard	: FCC Part 15.109(a) ICES-003
Basic standard	: ANSI C63.4: 2014
Frequency range	: 30 - 6000MHz
Classification	: Class B
Limits	: FCC Part 15.109(a) ICES-003 Table 5 & Table 7
Kind of test site	: 3m Semi-anechoic Chamber

Test Setup

Date of testing	: Refer to test result
Input voltage	: AC 120V, 60Hz
Operation mode	: C
Earthing	: Not connected
Ambient temperature	: 24 °C
Relative humidity	: 48 %
Atmospheric pressure	: 101 kPa

For the measurement records, refer to the appendix C.

6 Safety Human Exposure

6.1 Radio Frequency Exposure Compliance

6.1.1 Electromagnetic Fields

RESULT:

Pass

Test Specification

Test standard : CFR47 FCC Part 2: Section 2.1091
CFR47 FCC Part 1: Section 1.1310
FCC KDB Publication 447498 v06
FCC KDB Publication 865664 D02 v01r02
OET Bulletin 65 (Edition 97-01)
RSS-102 Issue 5 March 2015

➤ FCC requirements

FCC requirement: Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 20cm normally can be maintained between the user and the device.

MPE Calculation Method according to OET Bulletin 65

Power Density: $S_{(mW/cm^2)} = PG/4\pi R^2$ or $EIRP/4\pi R^2$

Where:

S = power density (mW/cm²)

P = power input to the antenna (mW)

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna (cm)

The nominal maximum conducted output power specified:

2.4GHz FHSS: 20.00 dBm

From the peak RF output power, the minimum mobile separation distance, d=20 cm, as well as the antenna gain (Max. 0.0 dBi for 2.4GHz FHSS), the RF power density can be calculated as below:

For 2.4GHz FHSS: $S_{(mW/cm^2)} = PG/4\pi R^2 = 0.020$ mW/cm²

Limits for Maximum Permissible Exposure (MPE) according to FCC Part 1.1310:

1.0 mW/cm²

➤ **IC requirements:** The EUT shall comply with the requirement of RSS-102 section 2.5.2.

Exemption from Routine Evaluation Limits – RF Exposure Evaluation

RF exposure evaluation is required if the separation distance between the user and/or bystander and the device's radiating element is greater than 20 cm, except when the device operates as follows:

at or above 300 MHz and below 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than $1.31 \times 10^{-2} f^{0.6834}$ W (adjusted for tune-up tolerance), where f is in MHz;

- RF exposure evaluation exempted power for 2.4GHz FHSS: 2.679 W

The nominal maximum conducted output power specified:

2.4GHz FHSS: 20.00 dBm

Antenna Gain: 0.0 dBi for 2.4GHz FHSS

The Max. e.i.r.p. for 2.4GHz FHSS = 20.00 dBm \approx 0.100 W is less than the RF exposure evaluation exempted power. So RF exposure evaluation is not required.

“RF Radiation Exposure Statement Caution: This Transmitter must be installed to provide a separation distance of at least 20 cm from all persons.”

7 Photographs of the Test Set-Up

For photographs of the test set-up, refer to the appendix A.



8 List of Tables


Table 1: List of Test and Measurement Equipment.....	6
Table 2: Technical Specification of EUT	8
Table 3: RF Channel and Frequency of General 2.4GHz Wireless	9
Table 4: Frequency Hopping Information.....	9
Table 5: List of Accessories and Auxiliary Equipment.....	11
Table 6: Test Result of Maximum Peak Conducted Output Power.....	15
Table 7: Test Result of 99% Bandwidth	16
Table 8: Test Result of 20dB Bandwidth.....	19
Table 9: Test Result of Carrier Frequency Separation	20
Table 10: Test Result of Number of Hopping Frequency	21
Table 11: Test Result of Time of Occupancy	22

Appendix B: Test Results of Conducted Testing


APPENDIX B: TEST RESULTS OF CONDUCTED TESTING	1
APPENDIX B.1: TEST RESULTS OF MAXIMUM PEAK CONDUCTED OUTPUT POWER	2
APPENDIX B.2: TEST RESULTS OF 99% BANDWIDTH AND 20dB BANDWIDTH	3
APPENDIX B.3: TEST RESULTS OF CONDUCTED SPURIOUS EMISSIONS MEASURED IN 100 KHz BANDWIDTH	5
<i>Low Channel.....</i>	<i>5</i>
<i>Middle Channel.....</i>	<i>5</i>
<i>High Channel.....</i>	<i>6</i>
<i>Band Edge, Low Channel.....</i>	<i>7</i>
<i>Band Edge, High Channel.....</i>	<i>7</i>
APPENDIX B.4: TEST RESULTS OF CARRIER FREQUENCY SEPARATION	8
APPENDIX B.5: TEST RESULTS OF NUMBER OF HOPPING FREQUENCY	9
APPENDIX B.6: TEST RESULTS OF TIME OF OCCUPANCY	10
<i>Low Channel.....</i>	<i>10</i>
<i>Middle Channel.....</i>	<i>11</i>
<i>High Channel.....</i>	<i>12</i>


Appendix B.1: Test Results of Maximum Peak Conducted Output Power





Appendix B.2: Test Results of 99% Bandwidth and 20dB Bandwidth





Appendix B.3: Test Results of Conducted Spurious Emissions Measured in 100 kHz Bandwidth

Low Channel




Middle Channel



High Channel





Band Edge, Low Channel




Band Edge, High Channel



Appendix B.4: Test Results of Carrier Frequency Separation






Appendix B.5: Test Results of Number of Hopping Frequency




Appendix B.6: Test Results of Time of Occupancy

Low Channel




Date: 14.MAR.2017 03:32:50




Date: 14.MAR.2017 03:34:16

Middle Channel




Date: 14.MAR.2017 03:37:48




Date: 14.MAR.2017 03:37:19

High Channel



Date: 14.MAR.2017 03:38:41



Date: 14.MAR.2017 03:39:19

Appendix C: Test Results of Radiated Testing


APPENDIX C: TEST RESULTS OF RADIATED TESTING	1
APPENDIX C.1: TEST RESULTS OF RADIATED SPURIOUS EMISSIONS.....	2
30MHz - 1GHz.....	2
1GHz - 18GHz.....	8
18GHz - 26.5GHz.....	14
APPENDIX C.2: TEST RESULTS OF RADIATED EMISSIONS IN RESTRICTED BANDS	20
Low Channel.....	20
High Channel.....	22
APPENDIX C.3: TEST RESULTS OF CONDUCTED EMISSION ON AC MAINS	24
C mode with adapter + battery #1.....	24
D mode with adapter + battery #1	26
D mode with adapter + battery #2	30
APPENDIX C.4: TEST RESULTS OF RADIATED EMISSION.....	32
Below 1GHz, D mode with adapter + battery #1	32
Below 1GHz, D mode with adapter + battery #2	34
Above 1GHz, D mode with adapter + battery #1	36
Above 1GHz, D mode with adapter + battery #2	38

Note: Testing was carried out within frequency range 9kHz to the tenth harmonics. The measurement results below 30MHz were greater than 20dB below the limit, so only the radiated spurious emissions from 30MHz to 26.5GHz were reported.

Appendix C.1: Test Results of Radiated Spurious Emissions

30MHz - 1GHz


Shenzhen EMTEK Co., Ltd.
Bldg. 69, Najialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China
www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282



Shenzhen EMTEK Co., Ltd.
Bldg. 69, Najialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China
www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282



Radiated Emission Measurement



Site 3m Chamber #2 Polarization: **Horizontal** Temperature: 22 C
 Limit: (RE)FCC PART 15 C Power: AC 120V/60Hz Humidity: 55 %
 EUT: Digital Video Baby Monitor
 M/N: MBP33SC
 Mode:TX(LOW CHANNEL)
 Note: PU(Tenpao Adapter)

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	Detector	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree		
1	*	161.9200	53.05	-17.49	35.56	43.50	-7.94			QP	
2		189.0800	51.07	-15.98	35.09	43.50	-8.41			QP	
3		296.7500	45.25	-11.35	33.90	46.00	-12.10			QP	
4		384.0500	45.51	-8.74	36.77	46.00	-9.23			QP	
5		720.6400	38.56	-2.53	36.03	46.00	-9.97			QP	
6		810.8500	33.86	-0.95	32.91	46.00	-13.09			QP	


*:Maximum data x:Over limit !:over margin

Operator: CSL

Shenzhen EMTEK Co., Ltd.
Bldg. 69, Najialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China
www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282



Radiated Emission Measurement



Site 3m Chamber #2 Polarization: **Horizontal** Temperature: 22 C
Limit: (RE)FCC PART 15 C Power: AC 120V/60Hz Humidity: 55 %
EUT: Digital Video Baby Monitor
M/N: MBP33SC
Mode:TX(MID CHANNEL)
Note: PU(Tenpao Adapter)

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	Detector	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree		
1		134.7600	46.75	-18.10	28.65	43.50	-14.85			QP	
2	*	161.9200	52.40	-17.49	34.91	43.50	-8.59			QP	
3		189.0800	50.42	-15.98	34.44	43.50	-9.06			QP	
4		296.7500	46.73	-11.35	35.38	46.00	-10.62			QP	
5		384.0500	43.32	-8.74	34.58	46.00	-11.42			QP	
6		810.8500	35.41	-0.95	34.46	46.00	-11.54			QP	

*:Maximum data x:Over limit !:over margin

Operator: CSL


File :TUV\Data :#1403

Page: 1

Shenzhen EMTEK Co., Ltd.
Bldg. 69, Najialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China
www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282



Radiated Emission Measurement



Site 3m Chamber #2 Polarization: **Vertical** Temperature: 22 C
 Limit: (RE)FCC PART 15 C Power: AC 120V/60Hz Humidity: 55 %
 EUT: Digital Video Baby Monitor
 M/N: MBP33SC
 Mode:TX(MID CHANNEL)
 Note: PU(Tenpao Adapter)

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	Detector	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree		
1		80.4400	43.87	-19.40	24.47	40.00	-15.53			QP	
2		107.6000	42.18	-14.90	27.28	43.50	-16.22			QP	
3		134.7600	51.60	-18.10	33.50	43.50	-10.00			QP	
4	*	161.9200	53.87	-17.49	36.38	43.50	-7.12			QP	
5		335.5500	40.64	-9.90	30.74	46.00	-15.26			QP	
6		384.0500	46.92	-8.74	38.18	46.00	-7.82			QP	


*:Maximum data x:Over limit !:over margin

Operator: CSL

Shenzhen EMTEK Co., Ltd.
Bldg. 69, Najialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China
www.emtek.com.cn Tel:+86-755-2695 4280 Fax:+86-755-2695 4282



Radiated Emission Measurement



Site 3m Chamber #2 Polarization: **Vertical** Temperature: 22 C
 Limit: (RE)FCC PART 15 C Power: AC 120V/60Hz Humidity: 55 %
 EUT: Digital Video Baby Monitor
 M/N: MBP33SC
 Mode:TX(HIGH CHANNEL)
 Note: PU(Tenpao Adapter)

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	Detector	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree		
1		35.8200	35.93	-16.45	19.48	40.00	-20.52			QP	
2		107.6000	41.04	-14.90	26.14	43.50	-17.36			QP	
3		134.7600	49.26	-18.10	31.16	43.50	-12.34			QP	
4		161.9200	48.73	-17.49	31.24	43.50	-12.26			QP	
5		336.5200	40.12	-9.87	30.25	46.00	-15.75			QP	
6	*	384.0500	46.08	-8.74	37.34	46.00	-8.66			QP	


*:Maximum data x:Over limit !:over margin

Operator: CSL

Shenzhen EMTEK Co., Ltd.
Bldg. 69, Najialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China
www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282



Radiated Emission Measurement



Site 3m Chamber #2 Polarization: **Horizontal** Temperature: 22 C
 Limit: (RE)FCC PART 15 C Power: AC 120V/60Hz Humidity: 55 %
 EUT: Digital Video Baby Monitor
 M/N: MBP33SC
 Mode:TX(HIGH CHANNEL)
 Note: PU(Tenpao Adapter)

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	Detector	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree		
1		161.9200	51.44	-17.49	33.95	43.50	-9.55			QP	
2		189.0800	49.10	-15.98	33.12	43.50	-10.38			QP	
3		296.7500	47.73	-11.35	36.38	46.00	-9.62			QP	
4	*	384.0500	47.02	-8.74	38.28	46.00	-7.72			QP	
5		720.6400	37.42	-2.53	34.89	46.00	-11.11			QP	
6		810.8500	36.58	-0.95	35.63	46.00	-10.37			QP	

*:Maximum data x:Over limit !:over margin


Operator: CSL

1GHz - 18GHz

Shenzhen EMTEK Co., Ltd.
Bldg. 69, Najialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China
www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282



Radiated Emission Measurement



File :TUV Data :#1445 Date: 2017-2-14
Site 3m Chamber #2 Polarization: **Horizontal** Temperature: 22 C
Limit: (RE)FCC PART 15 C Power: AC 120V/60Hz Humidity: 55 %
EUT: Digital Video Baby Monitor
M/N: MBP33SC
Mode:TX(LOW CHANNEL)
Note: PU(Tenpao Adapter)

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	Detector	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree		
1		1714.000	53.32	-14.27	39.05	74.00	-34.95			peak	
2		1714.000	42.92	-14.27	28.65	54.00	-25.35			AVG	
3		2870.000	48.75	-9.49	39.26	74.00	-34.74			peak	
4		2870.000	38.14	-9.49	28.65	54.00	-25.35			AVG	
5		3278.000	47.57	-8.19	39.38	74.00	-34.62			peak	
6		3278.000	37.43	-8.19	29.24	54.00	-24.76			AVG	
7		10401.00	39.48	9.49	48.97	74.00	-25.03			peak	
8		10401.00	28.98	9.49	38.47	54.00	-15.53			AVG	
9		15076.00	39.44	12.29	51.73	74.00	-22.27			peak	
10	*	15076.00	29.34	12.29	41.63	54.00	-12.37			AVG	
11		16402.00	39.02	12.82	51.84	74.00	-22.16			peak	
12		16402.00	27.80	12.82	40.62	54.00	-13.38			AVG	


*:Maximum data x:Over limit !:over margin

Operator: CSL

Shenzhen EMTEK Co., Ltd.
Bldg. 69, Najialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China
www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282



Radiated Emission Measurement



File :TUV Data :#1446 Date: 2017-2-14
Site 3m Chamber #2 Polarization: **Vertical** Temperature: 22 C
Limit: (RE)FCC PART 15 C Power: AC 120V/60Hz Humidity: 55 %
EUT: Digital Video Baby Monitor
M/N: MBP33SC
Mode:TX(LOW CHANNEL)
Note: PU(Tenpao Adapter)

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		1612.000	51.91	-14.32	37.59	74.00	-36.41			peak
2		1612.000	40.90	-14.32	26.58	54.00	-27.42			AVG
3		2887.000	49.46	-9.40	40.06	74.00	-33.94			peak
4		2887.000	39.54	-9.40	30.14	54.00	-23.86			AVG
5		5913.000	45.70	-0.55	45.15	74.00	-28.85			peak
6		5913.000	35.78	-0.55	35.23	54.00	-18.77			AVG
7		9857.000	40.57	8.36	48.93	74.00	-25.07			peak
8		9857.000	30.05	8.36	38.41	54.00	-15.59			AVG
9		15280.00	41.70	11.78	53.48	74.00	-20.52			peak
10		15280.00	30.74	11.78	42.52	54.00	-11.48			AVG
11		16640.00	37.68	14.48	52.16	74.00	-21.84			peak
12	*	16640.00	28.27	14.48	42.75	54.00	-11.25			AVG


*:Maximum data x:Over limit !:over margin

Operator: CSL

Shenzhen EMTEK Co., Ltd.
Bldg. 69, Najialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China
www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282



Radiated Emission Measurement



File :TUV Data :#1447 Date: 2017-2-14
Site 3m Chamber #2 Polarization: **Vertical** Temperature: 22 C
Limit: (RE)FCC PART 15 C Power: AC 120V/60Hz Humidity: 55 %
EUT: Digital Video Baby Monitor
M/N: MBP33SC
Mode:TX(MID CHANNEL)
Note: PU(Tenpao Adapter)

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	Detector	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree		
1		1731.000	52.21	-14.27	37.94	74.00	-36.06			peak	
2		1731.000	40.85	-14.27	26.58	54.00	-27.42			AVG	
3		2904.000	48.93	-9.31	39.62	74.00	-34.38			peak	
4		2904.000	37.95	-9.31	28.64	54.00	-25.36			AVG	
5		9194.000	42.53	7.09	49.62	74.00	-24.38			peak	
6		9194.000	32.38	7.09	39.47	54.00	-14.53			AVG	
7		10877.00	40.23	10.53	50.76	74.00	-23.24			peak	
8		10877.00	30.09	10.53	40.62	54.00	-13.38			AVG	
9		13886.00	37.49	13.85	51.34	74.00	-22.66			peak	
10		13886.00	27.47	13.85	41.32	54.00	-12.68			AVG	
11		17966.00	34.66	18.34	53.00	74.00	-21.00			peak	
12	*	17966.00	24.24	18.34	42.58	54.00	-11.42			AVG	


*:Maximum data x:Over limit !:over margin

Operator: CSL

Shenzhen EMTEK Co., Ltd.
Bldg. 69, Najialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China
www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282



Radiated Emission Measurement



Site 3m Chamber #2 Polarization: **Horizontal** Temperature: 22 C
 Limit: (RE)FCC PART 15 C Power: AC 120V/60Hz Humidity: 55 %
 EUT: Digital Video Baby Monitor
 M/N: MBP33SC
 Mode:TX(MID CHANNEL)
 Note: PU(Tenpao Adapter)

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	Detector	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree		
1		1697.000	51.99	-14.28	37.71	74.00	-36.29			peak	
2		1697.000	40.86	-14.28	26.58	54.00	-27.42			AVG	
3		2853.000	48.99	-9.59	39.40	74.00	-34.60			peak	
4		2853.000	37.95	-9.59	28.36	54.00	-25.64			AVG	
5		5454.000	46.47	-2.25	44.22	74.00	-29.78			peak	
6		5454.000	36.97	-2.25	34.72	54.00	-19.28			AVG	
7		10911.000	40.32	10.60	50.92	74.00	-23.08			peak	
8		10911.000	29.63	10.60	40.23	54.00	-13.77			AVG	
9		13988.000	37.05	14.16	51.21	74.00	-22.79			peak	
10		13988.000	26.52	14.16	40.68	54.00	-13.32			AVG	
11		17949.000	34.64	18.32	52.96	74.00	-21.04			peak	
12	*	17949.000	24.04	18.32	42.36	54.00	-11.64			AVG	


*:Maximum data x:Over limit !:over margin

Operator: CSL

Shenzhen EMTEK Co., Ltd.
Bldg. 69, Najialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China
www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282



Radiated Emission Measurement



File :TUV Data :#1449 Date: 2017-2-14
Site 3m Chamber #2 Polarization: **Horizontal** Temperature: 22 C
Limit: (RE)FCC PART 15 C Power: AC 120V/60Hz Humidity: 55 %
EUT: Digital Video Baby Monitor
M/N: MBP33SC
Mode:TX(HIGH CHANNEL)
Note: PU(Tenpao Adapter)

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	
1		1782.000	53.90	-14.25	39.65	74.00	-34.35			peak
2		1782.000	43.50	-14.25	29.25	54.00	-24.75			AVG
3		2853.000	50.16	-9.59	40.57	74.00	-33.43			peak
4		2853.000	40.06	-9.59	30.47	54.00	-23.53			AVG
5		7562.000	43.49	3.81	47.30	74.00	-26.70			peak
6		7562.000	32.44	3.81	36.25	54.00	-17.75			AVG
7		9925.000	40.68	8.48	49.16	74.00	-24.84			peak
8		9925.000	29.99	8.48	38.47	54.00	-15.53			AVG
9		14073.000	37.35	14.07	51.42	74.00	-22.58			peak
10		14073.000	26.28	14.07	40.35	54.00	-13.65			AVG
11		16300.000	40.09	12.11	52.20	74.00	-21.80			peak
12	*	16300.000	29.52	12.11	41.63	54.00	-12.37			AVG


*:Maximum data x:Over limit !:over margin

Operator: CSL

Shenzhen EMTEK Co., Ltd.
Bldg. 69, Najialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China
www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282



Radiated Emission Measurement



File :TUV Data :#1450 Date: 2017-2-14
Site 3m Chamber #2 Polarization: **Vertical** Temperature: 22 C
Limit: (RE)FCC PART 15 C Power: AC 120V/60Hz Humidity: 55 %
EUT: Digital Video Baby Monitor
M/N: MBP33SC
Mode:TX(HIGH CHANNEL)
Note: PU(Tenpao Adapter)

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		1799.000	52.59	-14.25	38.34	74.00	-35.66			peak
2		1799.000	42.90	-14.25	28.65	54.00	-25.35			AVG
3		3329.000	49.71	-8.09	41.62	74.00	-32.38			peak
4		3329.000	39.34	-8.09	31.25	54.00	-22.75			AVG
5		8191.000	42.37	5.45	47.82	74.00	-26.18			peak
6		8191.000	30.97	5.45	36.42	54.00	-17.58			AVG
7		12237.00	39.80	11.40	51.20	74.00	-22.80			peak
8		12237.00	28.86	11.40	40.26	54.00	-13.74			AVG
9		15076.00	39.85	12.29	52.14	74.00	-21.86			peak
10		15076.00	29.33	12.29	41.62	54.00	-12.38			AVG
11		16776.00	36.64	15.42	52.06	74.00	-21.94			peak
12	*	16776.00	27.16	15.42	42.58	54.00	-11.42			AVG

*:Maximum data x:Over limit !:over margin


Operator: CSL

18GHz - 26.5GHz

Shenzhen EMTEK Co., Ltd.
Bldg. 69, Najialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China
www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282



Radiated Emission Measurement



Site 3m Chamber #3 Polarization: **Horizontal** Temperature: 24 C
 Limit: (RE)FCC Part 15 C Power: AC 120V/60Hz Humidity: 53 %
 EUT: Digital Video Baby Monitor
 M/N: MBP33SC
 Mode:TX(LOW Channel)
 Note:PU(Tenpao Adapter)

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	
1		16589.00	49.12	2.67	51.79	74.00	-22.21	peak		
2	*	16589.00	32.53	2.67	35.20	54.00	-18.80	AVG		


*:Maximum data x:Over limit !:over margin

Operator: KK

Shenzhen EMTEK Co., Ltd.
Bldg. 69, Najialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China
www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282



Radiated Emission Measurement



Site 3m Chamber #3 Polarization: **Vertical** Temperature: 24 C
 Limit: (RE)FCC Part 15 C Power: AC 120V/60Hz Humidity: 53 %
 EUT: Digital Video Baby Monitor
 M/N: MBP33SC
 Mode:TX(LOW Channel)
 Note:PU(Tenpao Adapter)

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		14736.00	48.08	4.09	52.17	74.00	-21.83	peak		
2	*	14736.00	32.11	4.09	36.20	54.00	-17.80	AVG		


*:Maximum data x:Over limit !:over margin

Operator: KK

Shenzhen EMTEK Co., Ltd.
Bldg. 69, Najialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China
www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282



Radiated Emission Measurement



Site 3m Chamber #3 Polarization: **Horizontal** Temperature: 24 C
Limit: (RE)FCC Part 15 C Power: AC 120V/60Hz Humidity: 53 %
EUT: Digital Video Baby Monitor
M/N: MBP33SC
Mode:TX(MID Channel)
Note:PU(Tenpao Adapter)

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	Detector	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree		
1		16232.00	51.06	1.13	52.19	74.00	-21.81			peak	
2	*	16232.00	35.27	1.13	36.40	54.00	-17.60			AVG	

*:Maximum data x:Over limit !:over margin

Operator: KK


File :TUV\Data :#143

Page: 1

Shenzhen EMTEK Co., Ltd.
Bldg. 69, Najialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China
www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282



Radiated Emission Measurement



Site 3m Chamber #3 Polarization: **Vertical** Temperature: 24 C
Limit: (RE)FCC Part 15 C Power: AC 120V/60Hz Humidity: 53 %
EUT: Digital Video Baby Monitor
M/N: MBP33SC
Mode:TX(MID Channel)
Note:PU(Tenpao Adapter)

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	Detector	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree		
1		16776.00	48.58	3.46	52.04	74.00	-21.96			peak	
2	*	16776.00	33.24	3.46	36.70	54.00	-17.30			AVG	

*:Maximum data x:Over limit !:over margin

Operator: KK


File :TUV\Data :#144

Page: 1

Shenzhen EMTEK Co., Ltd.
Bldg. 69, Najialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China
www.emtek.com.cn Tel:+86-755-2695 4280 Fax:+86-755-2695 4282



Radiated Emission Measurement



Site 3m Chamber #3 Polarization: **Vertical** Temperature: 24 C
Limit: (RE)FCC Part 15 C Power: AC 120V/60Hz Humidity: 53 %
EUT: Digital Video Baby Monitor
M/N: MBP33SC
Mode:TX(HIGH Channel)
Note:PU(Tenpao Adapter)

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1		14328.00	47.78	3.40	51.18	74.00	-22.82	peak			
2	*	14328.00	32.80	3.40	36.20	54.00	-17.80	AVG			

*:Maximum data x:Over limit !:over margin

Operator: KK


File :TUV\Data :#145

Page: 1

Shenzhen EMTEK Co., Ltd.
Bldg. 69, Najialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China
www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282



Radiated Emission Measurement



Site 3m Chamber #3 Polarization: **Horizontal** Temperature: 24 C
 Limit: (RE)FCC Part 15 C Power: AC 120V/60Hz Humidity: 53 %
 EUT: Digital Video Baby Monitor
 M/N: MBP33SC
 Mode:TX(HIGH Channel)
 Note:PU(Tenpao Adapter)

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	Detector	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree		
1		15671.00	53.06	-0.07	52.99	74.00	-21.01			peak	
2	*	15671.00	36.77	-0.07	36.70	54.00	-17.30			AVG	

*:Maximum data x:Over limit !:over margin

Operator: KK

File :TUV\Data :#146

Page: 1


Appendix C.2: Test Results of Radiated Emissions in Restricted Bands

Low Channel

Shenzhen EMTEK Co., Ltd.
Bldg. 69, Najialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China
www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282



Radiated Emission Measurement



Site 3m Chamber #2 Polarization: **Vertical** Temperature: 22 C
 Limit: (RE)FCC PART 15 C Power: AC 120V/60Hz Humidity: 55 %
 EUT: Digital Video Baby Monitor
 M/N: MBP33SC
 Mode:TX (LOW Channel)
 Note: PU(Tenpao Adapter)

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1	*	2347.520	59.20	-12.30	46.90	74.00	-27.10	peak		
2		2347.520	39.16	-12.30	26.86	54.00	-27.14	AVG		

*:Maximum data x:Over limit !:over margin

Operator: CSL


File :tuv\Data :#160

Page: 1

Shenzhen EMTEK Co., Ltd.
Bldg. 69, Najialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China
www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282



Radiated Emission Measurement



Site 3m Chamber #2 Polarization: **Horizontal** Temperature: 22 C
 Limit: (RE)FCC PART 15 C Power: AC 120V/60Hz Humidity: 55 %
 EUT: Digital Video Baby Monitor
 M/N: MBP33SC
 Mode:TX (LOW Channel)
 Note: PU(Tenpao Adapter)

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	Detector	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree		
1	*	2346.560	57.02	-12.31	44.71	74.00	-29.29			peak	
2		2346.560	36.67	-12.31	24.36	54.00	-29.64			AVG	

*:Maximum data x:Over limit !:over margin

Operator: CSL

File :tuv\Data :#161


Page: 1

High Channel

Shenzhen EMTEK Co., Ltd.
Bldg. 69, Najialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China
www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282



Radiated Emission Measurement



Site 3m Chamber #2 Polarization: **Vertical** Temperature: 22 C
Limit: (RE)FCC PART 15 C Power: AC 120V/60Hz Humidity: 55 %
EUT: Digital Video Baby Monitor
M/N: MBP33SC
Mode:TX (HIGH Channel)
Note: PU(Tenpao Adapter)

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1	*	2484.012	67.33	-11.56	55.77	74.00	-18.23			peak
2		2484.012	47.28	-11.56	35.72	54.00	-18.28			AVG

*:Maximum data x:Over limit !:over margin

Operator: CSL


File :tuv\Data :#162

Page: 1

Shenzhen EMTEK Co., Ltd.
Bldg. 69, Najialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China
www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282



Radiated Emission Measurement



Site 3m Chamber #2 Polarization: **Horizontal** Temperature: 22 C
 Limit: (RE)FCC PART 15 C Power: AC 120V/60Hz Humidity: 55 %
 EUT: Digital Video Baby Monitor
 M/N: MBP33SC
 Mode:TX (HIGH Channel)
 Note: PU(Tenpao Adapter)

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	Detector	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree		
1	*	2485.166	57.54	-11.56	45.98	74.00	-28.02			peak	
2		2485.166	36.99	-11.56	25.43	54.00	-28.57			AVG	

*:Maximum data x:Over limit !:over margin

Operator: CSL


Appendix C.3: Test Results of Conducted Emission on AC Mains

C mode with adapter + battery #1

Shenzhen EMTEK Co., Ltd.
Bldg. 69, Majialong Industry Zone, Manshan District, Shenzhen, Guangdong, 518052 P. R. China
www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282



Conducted Emission Measurement



Site Conduction #1 Phase: **N** Temperature: 22 C
Limit: (CE)FCC PART 15 C Power: AC 120V/60Hz Humidity: 55 %
EUT: Digital Video Baby Monitor
M/N: MBP33SC
Mode: Charging + 2.4G Wireless connecting
Note: PU(TenPao Adapter+GP)

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector	Comment
		MHz	dBuV	dB	dBuV	dBuV	dB		
1		0.6250	37.57	0.00	37.57	56.00	-18.43	QP	
2		0.6250	20.55	0.00	20.55	46.00	-25.45	AVG	
3		0.8500	36.78	0.00	36.78	56.00	-19.22	QP	
4		0.8500	23.04	0.00	23.04	46.00	-22.96	AVG	
5	*	1.7850	40.18	0.00	40.18	56.00	-15.82	QP	
6		1.7850	28.03	0.00	28.03	46.00	-17.97	AVG	
7		4.3600	39.55	0.00	39.55	56.00	-16.45	QP	
8		4.3600	24.14	0.00	24.14	46.00	-21.86	AVG	
9		9.7200	43.11	0.00	43.11	60.00	-16.89	QP	
10		9.7200	29.77	0.00	29.77	50.00	-20.23	AVG	
11		17.8250	40.26	0.00	40.26	60.00	-19.74	QP	
12		17.8250	26.72	0.00	26.72	50.00	-23.28	AVG	

*:Maximum data x:Over limit !:over margin Comment: Factor build in receiver. Operator: Jason

Shenzhen EMTEK Co., Ltd.
Bldg. 69, Najialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P.R. China
www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282




Conducted Emission Measurement

File :TUV-RH
80.0 dBuV

Data :#333

Date: 17/02/11/



Site Conduction #1

Phase: L1

Temperature: 22 C

Limit: (CE)FCC PART 15 C

Power: AC 120V/60Hz

Humidity: 55 %

EUT: Digital Video Baby Monitor

M/N: MBP33SC

Mode: Charging + 2.4G Wireless connecting

Note: PU(TenPao Adapter+GP)

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector	Comment
		MHz	dBuV	dB	dBuV	dBuV	dB		
1		0.3950	42.71	0.00	42.71	57.96	-15.25	QP	
2		0.3950	31.32	0.00	31.32	47.96	-16.64	AVG	
3		0.5700	41.43	0.00	41.43	56.00	-14.57	QP	
4		0.5700	28.51	0.00	28.51	46.00	-17.49	AVG	
5		0.8550	41.20	0.00	41.20	56.00	-14.80	QP	
6		0.8550	27.44	0.00	27.44	46.00	-18.56	AVG	
7		1.4750	40.13	0.00	40.13	56.00	-15.87	QP	
8		1.4750	27.96	0.00	27.96	46.00	-18.04	AVG	
9	*	4.0850	42.43	0.00	42.43	56.00	-13.57	QP	
10		4.0850	27.53	0.00	27.53	46.00	-18.47	AVG	
11		7.7600	43.90	0.00	43.90	60.00	-16.10	QP	
12		7.7600	29.49	0.00	29.49	50.00	-20.51	AVG	

*:Maximum data x:Over limit !:over margin Comment: Factor build in receiver. Operator: Jason

File :TUV-RHData :#333


Page: 1

D mode with adapter + battery #1

Shenzhen EMTEK Co., Ltd.
Bldg. 69, Majialong Industry Zone, Manshan District, Shenzhen, Guangdong, 518052 P. R. China
www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282



Conducted Emission Measurement



Site Conduction #1 Phase: **N** Temperature: 22 C
 Limit: (CE)FCC PART 15 class B_QP Power: AC 120V/60Hz Humidity: 55 %
 EUT: Digital Video Baby Monitor
 M/N: MBP33SC
 Mode: Charging + 2.4G Wireless connecting
 Note: PU(TenPao Adapter+GP)

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector	Comment
		MHz	dBuV	dB	dBuV	dBuV	dB		
1		0.6250	37.57	0.00	37.57	56.00	-18.43	QP	
2		0.6250	20.55	0.00	20.55	46.00	-25.45	AVG	
3		0.8500	36.78	0.00	36.78	56.00	-19.22	QP	
4		0.8500	23.04	0.00	23.04	46.00	-22.96	AVG	
5	*	1.7850	40.18	0.00	40.18	56.00	-15.82	QP	
6		1.7850	28.03	0.00	28.03	46.00	-17.97	AVG	
7		4.3600	39.55	0.00	39.55	56.00	-16.45	QP	
8		4.3600	24.14	0.00	24.14	46.00	-21.86	AVG	
9		9.7200	43.11	0.00	43.11	60.00	-16.89	QP	
10		9.7200	29.77	0.00	29.77	50.00	-20.23	AVG	
11		17.8250	40.26	0.00	40.26	60.00	-19.74	QP	
12		17.8250	26.72	0.00	26.72	50.00	-23.28	AVG	

*:Maximum data x:Over limit !:over margin Comment: Factor build in receiver. Operator: Jason

Shenzhen EMTEK Co., Ltd.
Bldg. 69, Najialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P.R. China
www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282




Conducted Emission Measurement

File :TUV-RH
80.0 dBuV

Data :#333

Date: 17/02/11/



Site Conduction #1 Phase: L1 Temperature: 22 C
Limit: (CE)FCC PART 15 class B_QP Power: AC 120V/60Hz Humidity: 55 %
EUT: Digital Video Baby Monitor
M/N: MBP33SC
Mode: Charging + 2.4G Wireless connecting
Note: PU(TenPao Adapter+GP)

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector	Comment
		MHz	dBuV	dB	dBuV	dBuV	dB		
1		0.3950	42.71	0.00	42.71	57.96	-15.25	QP	
2		0.3950	31.32	0.00	31.32	47.96	-16.64	AVG	
3		0.5700	41.43	0.00	41.43	56.00	-14.57	QP	
4		0.5700	28.51	0.00	28.51	46.00	-17.49	AVG	
5		0.8550	41.20	0.00	41.20	56.00	-14.80	QP	
6		0.8550	27.44	0.00	27.44	46.00	-18.56	AVG	
7		1.4750	40.13	0.00	40.13	56.00	-15.87	QP	
8		1.4750	27.96	0.00	27.96	46.00	-18.04	AVG	
9	*	4.0850	42.43	0.00	42.43	56.00	-13.57	QP	
10		4.0850	27.53	0.00	27.53	46.00	-18.47	AVG	
11		7.7600	43.90	0.00	43.90	60.00	-16.10	QP	
12		7.7600	29.49	0.00	29.49	50.00	-20.51	AVG	

*:Maximum data x:Over limit !:over margin Comment: Factor build in receiver. Operator: Jason

File :TUV-RHData :#333

Page: 1

Shenzhen EMTEK Co., Ltd.
Bldg. 69, Najialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P.R. China
www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282




Conducted Emission Measurement

File :TUV-RH
80.0 dBuV

Data :#332

Date: 17/02/11/



Site Conduction #1

Phase: N

Temperature: 22 C

Limit: (CE)FCC PART 15 class B_QP

Power: AC 120V/60Hz

Humidity: 55 %

EUT: Digital Video Baby Monitor

M/N: MBP33SC

Mode: Charging + 2.4G Wireless connecting

Note: PU(TenPao Adapter+GP)

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector	Comment
		MHz	dBuV	dB	dBuV	dBuV	dB		
1		0.6250	37.57	0.00	37.57	56.00	-18.43	QP	
2		0.6250	20.55	0.00	20.55	46.00	-25.45	AVG	
3		0.8500	36.78	0.00	36.78	56.00	-19.22	QP	
4		0.8500	23.04	0.00	23.04	46.00	-22.96	AVG	
5	*	1.7850	40.18	0.00	40.18	56.00	-15.82	QP	
6		1.7850	28.03	0.00	28.03	46.00	-17.97	AVG	
7		4.3600	39.55	0.00	39.55	56.00	-16.45	QP	
8		4.3600	24.14	0.00	24.14	46.00	-21.86	AVG	
9		9.7200	43.11	0.00	43.11	60.00	-16.89	QP	
10		9.7200	29.77	0.00	29.77	50.00	-20.23	AVG	
11		17.8250	40.26	0.00	40.26	60.00	-19.74	QP	
12		17.8250	26.72	0.00	26.72	50.00	-23.28	AVG	

*:Maximum data x:Over limit !:over margin Comment: Factor build in receiver. Operator: Jason


File :TUV-RHData :#332

Page: 1

Shenzhen EMTEK Co., Ltd.
Bldg. 69, Najialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P.R. China
www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282



Conducted Emission Measurement



Site Conduction #1 Phase: **L1** Temperature: 22 C
Limit: (CE)FCC PART 15 class B_QP Power: AC 120V/60Hz Humidity: 55 %
EUT: Digital Video Baby Monitor
M/N: MBP33SC
Mode: Charging + 2.4G Wireless connecting
Note: PU(TenPao Adapter+GP)

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector	Comment
		MHz	dBuV	dB	dBuV	dBuV	dB		
1		0.3950	42.71	0.00	42.71	57.96	-15.25	QP	
2		0.3950	31.32	0.00	31.32	47.96	-16.64	AVG	
3		0.5700	41.43	0.00	41.43	56.00	-14.57	QP	
4		0.5700	28.51	0.00	28.51	46.00	-17.49	AVG	
5		0.8550	41.20	0.00	41.20	56.00	-14.80	QP	
6		0.8550	27.44	0.00	27.44	46.00	-18.56	AVG	
7		1.4750	40.13	0.00	40.13	56.00	-15.87	QP	
8		1.4750	27.96	0.00	27.96	46.00	-18.04	AVG	
9	*	4.0850	42.43	0.00	42.43	56.00	-13.57	QP	
10		4.0850	27.53	0.00	27.53	46.00	-18.47	AVG	
11		7.7600	43.90	0.00	43.90	60.00	-16.10	QP	
12		7.7600	29.49	0.00	29.49	50.00	-20.51	AVG	


*:Maximum data x:Over limit !:over margin Comment: Factor build in receiver. Operator: Jason

D mode with adapter + battery #2

Shenzhen EMTEK Co., Ltd.
Bldg. 69, Majialong Industry Zone, Manshan District, Shenzhen, Guangdong, 518052 P. R. China
www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282



Conducted Emission Measurement



Site Conduction #1 Phase: **N** Temperature: 22
 Limit: (CE)FCC PART 15 class B_QP Power: AC 120V/60Hz Humidity: 55 %
 EUT: Digital Video Baby Monitor
 M/N: MBP33SC
 Mode: Charging mode
 Note: PU(TenPao Adapter+JUST Battery)

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector	Comment
		MHz	dBuV	dB	dBuV	dBuV	dB		
1		0.1850	41.80	0.00	41.80	64.26	-22.46	QP	
2		0.1850	17.12	0.00	17.12	54.26	-37.14	AVG	
3		0.3300	38.56	0.00	38.56	59.45	-20.89	QP	
4		0.3300	17.31	0.00	17.31	49.45	-32.14	AVG	
5		0.3955	38.03	0.00	38.03	57.95	-19.92	QP	
6		0.3955	19.60	0.00	19.60	47.95	-28.35	AVG	
7		1.7850	39.18	0.00	39.18	56.00	-16.82	QP	
8		1.7850	24.53	0.00	24.53	46.00	-21.47	AVG	
9	*	4.3837	39.42	0.00	39.42	56.00	-16.58	QP	
10		4.3837	24.09	0.00	24.09	46.00	-21.91	AVG	
11		9.7200	41.61	0.00	41.61	60.00	-18.39	QP	
12		9.7200	27.69	0.00	27.69	50.00	-22.31	AVG	

*:Maximum data x:Over limit !:over margin Comment: Factor build in receiver. Operator: Jason

Shenzhen EMTEK Co., Ltd.
Bldg. 69, Najialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P.R. China
www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282




Conducted Emission Measurement

File :TUV-RH
80.0 dBuV

Data :#374

Date: 17/02/11/



Site Conduction #1 Phase: L1 Temperature: 22
Limit: (CE)FCC PART 15 class B_QP Power: AC 120V/60Hz Humidity: 55 %
EUT: Digital Video Baby Monitor
M/N: MBP33SC
Mode: Charging mode
Note: PU(TenPao Adapter+JUST Battery)

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector	Comment
		MHz	dBuV	dB	dBuV	dBuV	dB		
1		0.3976	43.68	0.00	43.68	57.90	-14.22	QP	
2		0.3976	27.65	0.00	27.65	47.90	-20.25	AVG	
3		0.6250	41.02	0.00	41.02	56.00	-14.98	QP	
4		0.6250	27.46	0.00	27.46	46.00	-18.54	AVG	
5		0.6800	41.47	0.00	41.47	56.00	-14.53	QP	
6		0.6800	24.60	0.00	24.60	46.00	-21.40	AVG	
7		3.4450	40.43	0.00	40.43	56.00	-15.57	QP	
8		3.4450	25.88	0.00	25.88	46.00	-20.12	AVG	
9	*	4.0920	41.85	0.00	41.85	56.00	-14.15	QP	
10		4.0920	27.14	0.00	27.14	46.00	-18.86	AVG	
11		12.2250	42.41	0.00	42.41	60.00	-17.59	QP	
12		12.2250	27.61	0.00	27.61	50.00	-22.39	AVG	

*:Maximum data x:Over limit !:over margin Comment: Factor build in receiver. Operator: Jason

File :TUV-RHData :#374

Page: 1


Appendix C.4: Test Results of Radiated Emission

Below 1GHz, D mode with adapter + battery #1

Shenzhen EMTEK Co., Ltd.
Bldg. 69, Najialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China
www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282



Radiated Emission Measurement



File :TUV Data :#1741 Date: 17/03/08/
Site 3m Chamber #2 Polarization: **Horizontal** Temperature: 22 C
Limit: (RE)FCC PART 15 CLASS B Power: AC 120V/60Hz Humidity: 55 %
EUT: Digital Video Baby Monitor
M/N: MBP33SC
Mode:Charging+2.4G wireless connecting
Note: PU(Tenpao Adapter+GP Battery)

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		95.9600	51.28	-15.45	35.83	43.50	-7.67	QP		
2		143.4900	54.72	-18.24	36.48	43.50	-7.02	QP		
3		239.5200	50.37	-13.32	37.05	46.00	-8.95	QP		
4		504.3300	42.06	-6.64	35.42	46.00	-10.58	QP		
5		696.3900	41.08	-2.97	38.11	46.00	-7.89	QP		
6	*	744.8900	44.40	-2.09	42.31	46.00	-3.69	QP		


*:Maximum data x:Over limit !:over margin

Operator: CSL

Shenzhen EMTEK Co., Ltd.
Bldg. 69, Najialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China
www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282



Radiated Emission Measurement



Site 3m Chamber #2 Polarization: **Vertical** Temperature: 22 C
Limit: (RE)FCC PART 15 CLASS B Power: AC 120V/60Hz Humidity: 55 %
EUT: Digital Video Baby Monitor
M/N: MBP33SC
Mode:Charging+2.4G wireless connecting
Note: PU(Tenpao Adapter+GP Battery)

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	Detector	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree		
1		95.9600	51.48	-15.45	36.03	43.50	-7.47			QP	
2		167.7400	53.16	-16.75	36.41	43.50	-7.09			QP	
3		191.9900	51.39	-15.79	35.60	43.50	-7.90			QP	
4		239.5200	48.22	-13.32	34.90	46.00	-11.10			QP	
5		455.8300	42.73	-7.81	34.92	46.00	-11.08			QP	
6	*	504.3300	46.09	-6.64	39.45	46.00	-6.55			QP	

*:Maximum data x:Over limit !:over margin

Operator: CSL

File :TUV\Data :#1742


Page: 1

Below 1GHz, D mode with adapter + battery #2

Shenzhen EMTEK Co., Ltd.
Bldg. 69, Najialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China
www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282



Radiated Emission Measurement



Site 3m Chamber #2 Polarization: **Horizontal** Temperature: 22 C
Limit: (RE)FCC PART 15 CLASS B Power: AC 120V/60Hz Humidity: 55 %
EUT: Digital Video Baby Monitor
M/N: MBP33SC
Mode: Charging mdoe
Note: PU(Tenpao Adapter+JUST Battery)

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		95.9600	50.78	-15.45	35.33	43.50	-8.17	QP		
2		143.4900	54.72	-18.24	36.48	43.50	-7.02	QP		
3		191.9900	51.36	-15.79	35.57	43.50	-7.93	QP		
4		239.5200	49.37	-13.32	36.05	46.00	-9.95	QP		
5	*	744.8900	41.40	-2.09	39.31	46.00	-6.69	QP		
6		792.4200	39.87	-1.23	38.64	46.00	-7.36	QP		


*:Maximum data x:Over limit !:over margin

Operator: CSL

Shenzhen EMTEK Co., Ltd.
Bldg. 69, Najialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China
www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282



Radiated Emission Measurement



Site 3m Chamber #2 Polarization: **Vertical** Temperature: 22 C
 Limit: (RE)FCC PART 15 CLASS B Power: AC 120V/60Hz Humidity: 55 %
 EUT: Digital Video Baby Monitor
 M/N: MBP33SC
 Mode:Charging mode
 Note: PU(Tenpao Adapter+JUST Battery)


No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	Detector	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree		
1		95.9600	49.48	-15.45	34.03	43.50	-9.47			QP	
2		143.4900	53.96	-18.24	35.72	43.50	-7.78			QP	
3	*	167.7400	54.66	-16.75	37.91	43.50	-5.59			QP	
4		191.9900	52.89	-15.79	37.10	43.50	-6.40			QP	
5		504.3300	46.59	-6.64	39.95	46.00	-6.05			QP	
6		984.4800	40.18	1.08	41.26	54.00	-12.74			QP	

*:Maximum data x:Over limit !:over margin

Operator: CSL

Above 1GHz, D mode with adapter + battery #1

Shenzhen EMTEK Co., Ltd.
Bldg. 69, Najialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China
www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282



Site 3m Chamber #2 Polarization: **Horizontal** Temperature: 22 C
Limit: (RE)FCC PART 15 CLASS B Power: AC 230V/50Hz Humidity: 55 %
EUT: Digital Video Baby Monitor
M/N: MBP33SC
Mode:Charging + 2.4G Wireless connecting
Note: PU(Tenpao Adapter+GP Battery)

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		1810.000	69.80	-14.25	55.55	74.00	-18.45			peak
2		1810.000	41.11	-14.25	26.86	54.00	-27.14			AVG
3	*	2185.000	76.79	-13.19	63.60	74.00	-10.40			peak
4		2185.000	56.33	-13.19	43.14	54.00	-10.86			AVG
5		2700.000	73.50	-10.41	63.09	74.00	-10.91			peak
6		2700.000	42.88	-10.41	32.47	54.00	-21.53			AVG
7		3035.000	66.85	-8.71	58.14	74.00	-15.86			peak
8		3035.000	37.39	-8.71	28.68	54.00	-25.32			AVG
9		4655.000	60.08	-4.88	55.20	74.00	-18.80			peak
10		4655.000	32.23	-4.88	27.35	54.00	-26.65			AVG
11		5095.000	60.02	-3.59	56.43	74.00	-17.57			peak
12		5095.000	32.11	-3.59	28.52	54.00	-25.48			AVG


*:Maximum data x:Over limit !:over margin

Operator: CSL

Shenzhen EMTEK Co., Ltd.
Bldg. 69, Najialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China
www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282



Radiated Emission Measurement



Site 3m Chamber #2 Polarization: **Vertical** Temperature: 22 C
 Limit: (RE)FCC PART 15 CLASS B Power: AC 230V/50Hz Humidity: 55 %
 EUT: Digital Video Baby Monitor
 M/N: MBP33SC
 Mode:Charging + 2.4G Wireless connecting
 Note: PU(Tenpao Adapter+GP Battery)


No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		1870.000	75.31	-14.23	61.08	74.00	-12.92			peak
2		1870.000	44.70	-14.23	30.47	54.00	-23.53			AVG
3		2115.000	76.37	-13.56	62.81	74.00	-11.19			peak
4		2115.000	45.25	-13.56	31.69	54.00	-22.31			AVG
5		2665.000	78.18	-10.60	67.58	74.00	-6.42			peak
6		2665.000	43.17	-10.60	32.57	54.00	-21.43			AVG
7	*	3020.000	77.84	-8.75	69.09	74.00	-4.91			peak
8		3020.000	43.43	-8.75	34.68	54.00	-19.32			AVG
9		4210.000	69.95	-6.08	63.87	74.00	-10.13			peak
10		4210.000	37.68	-6.08	31.60	54.00	-22.40			AVG
11		4655.000	64.90	-4.88	60.02	74.00	-13.98			peak
12		4655.000	35.73	-4.88	30.85	54.00	-23.15			AVG

*:Maximum data x:Over limit !:over margin

Operator: CSL

Above 1GHz, D mode with adapter + battery #2

Shenzhen EMTEK Co., Ltd.
Bldg. 69, Najialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China
www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		1815.000	70.20	-14.24	55.96	74.00	-18.04			peak
2		1815.000	41.92	-14.24	27.68	54.00	-26.32			AVG
3		2180.000	74.62	-13.20	61.42	74.00	-12.58			peak
4		2180.000	56.78	-13.20	43.58	54.00	-10.42			AVG
5	*	2700.000	74.50	-10.41	64.09	74.00	-9.91			peak
6		2700.000	42.99	-10.41	32.58	54.00	-21.42			AVG
7		3010.000	70.73	-8.77	61.96	74.00	-12.04			peak
8		3010.000	38.91	-8.77	30.14	54.00	-23.86			AVG
9		4175.000	69.07	-6.19	62.88	74.00	-11.12			peak
10		4175.000	37.88	-6.19	31.69	54.00	-22.31			AVG
11		5405.000	63.63	-2.43	61.20	74.00	-12.80			peak
12		5405.000	34.19	-2.43	31.76	54.00	-22.24			AVG


*:Maximum data x:Over limit !:over margin

Operator: CSL

Shenzhen EMTEK Co., Ltd.
Bldg. 69, Najialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China
www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282



Radiated Emission Measurement



Site 3m Chamber #2 Polarization: **Vertical** Temperature: 22 C
Limit: (RE)FCC PART 15 CLASS B Power: AC 120V/60Hz Humidity: 55 %
EUT: Digital Video Baby Monitor
M/N: MBP33SC
Mode:Charging mode
Note: PU(Tenpao Adapter+Justin Battery)

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		1845.000	76.59	-14.24	62.35	74.00	-11.65			peak
2		1845.000	44.38	-14.24	30.14	54.00	-23.86			AVG
3		2130.000	74.71	-13.48	61.23	74.00	-12.77			peak
4		2130.000	43.70	-13.48	30.22	54.00	-23.78			AVG
5		2575.000	77.03	-11.08	65.95	74.00	-8.05			peak
6		2575.000	43.62	-11.08	32.54	54.00	-21.46			AVG
7		2745.000	74.86	-10.16	64.70	74.00	-9.30			peak
8		2745.000	41.72	-10.16	31.56	54.00	-22.44			AVG
9	*	3010.000	79.60	-8.77	70.83	74.00	-3.17			peak
10		3010.000	44.24	-8.77	35.47	54.00	-18.53			AVG
11		4235.000	69.71	-6.02	63.69	74.00	-10.31			peak
12		4235.000	37.58	-6.02	31.56	54.00	-22.44			AVG

*:Maximum data x:Over limit !:over margin

Operator: CSL

File :TUV\Data :#1332

Page: 1