

TEST REPORT

Application No.: HKEM2108000856AT
Applicant: BINATONE ELECTRONICS INTERNATIONAL LIMITED
Address of Applicant: 25/F, Guangdong Investment Tower, 148 Connaught Road Central, Sheung Wan, Hong Kong

Equipment Under Test (EUT):
EUT Name: Video Baby Monitor
Model No.: Nursery View Pro(BU)
Additional Model: Please refer to section 2 of this report which indicates which item was actually tested and which were electrically identical.

Trademark: Hubble
FCC ID: VLJ-NV532BU
IC: 4522A-NV532BU
HVIN: NV532BU
Standard(s) : 47 CFR Part 1.1307; 47 CFR Part 2.1091
KDB447498D01 General RF Exposure Guidance v06
RSS102 Issue 5 March 2015

Date of Receipt: 2021-10-30
Date of Test: 2021-10-31 to 2021-11-10
Date of Issue: 2021-11-11

Test Result:**Pass***

* In the configuration tested, the EUT complied with the standards specified above.





Law Man Kit
EMC Manager

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request and accessible at <http://www.sgs.com/en/Terms-and-conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-conditions.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. The document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

| Revision Record | | | | |
|------------------------|----------------|-------------|-----------------|---------------|
| Version | Chapter | Date | Modifier | Remark |
| 01 | | 2021-11-11 | | Original |
| | | | | |
| | | | | |

| | | | |
|---------------------------------|--|---|------------------|
| Authorized for issue by: | | | |
| | |  | |
| | | <hr/> Leo Xu /Project Engineer | Date: 2021-11-11 |
| | |  | |
| | | <hr/> Law Man Kit /Reviewer | Date: 2021-11-11 |

2 Test Summary

| Radio Spectrum Technical Requirement | | | | |
|--------------------------------------|--|--------------------------|----------------|--------|
| Item | Standard | Method | Requirement | Result |
| RF Exposure | 47 CFR Part 1.1307, 47 CFR Part 2.1091, KDB 447498 D01 | KDB447498D01 | KDB447498D01 | PASS |
| RF Exposure | RSS102 Issue 5 | RSS-102 Section 2.5.1 | RSS102 Issue 5 | PASS |

Declaration of EUT Family Grouping:

None.

Abbreviation:

- Tx: In this whole report Tx (or tx) means Transmitter.
 Rx: In this whole report Rx (or rx) means Receiver.
 RF: In this whole report RF means Radiated Frequency.
 CH: In this whole report CH means channel.
 Volt: In this whole report Volt means Voltage.
 Temp: In this whole report Temp means Temperature.
 Humid: In this whole report Humid means humidity.
 Press: In this whole report Press means Pressure.
 N/A: In this whole report not application.

3 Contents

| | Page |
|---|-----------|
| 1 COVER PAGE | 1 |
| 2 TEST SUMMARY | 3 |
| 3 CONTENTS | 4 |
| 4 GENERAL INFORMATION | 5 |
| 4.1 DETAILS OF E.U.T. | 5 |
| 4.2 DESCRIPTION OF SUPPORT UNITS | 6 |
| 4.3 TEST LOCATION..... | 7 |
| 4.4 TEST FACILITY..... | 7 |
| 4.5 DEVIATION FROM STANDARDS | 7 |
| 4.6 ABNORMALITIES FROM STANDARD CONDITIONS | 7 |
| 5 RADIO SPECTRUM TECHNICAL REQUIREMENT | 8 |
| 5.1 RF EXPOSURE | 8 |
| 5.1.1 <i>Test Requirement:</i> | 8 |
| 5.1.1 <i>IC Radiofrequency radiation</i> | 9 |
| 5.1.2 <i>EUT RF Exposure Evaluation</i> | 10 |
| 6 PHOTOGRAPHS | 11 |

4 General Information

4.1 Details of E.U.T.

| | |
|----------------------|---|
| Power supply: | Model: YWK-AD050100-U Input: AC 100-240V, 50/60Hz, Max 0.3A Output: DC 5V, 1000mA |
| Test voltage: | AC 120V |
| Cable: | Power Cable: 180cm unshielded 2 wires DC cable |
| Antenna Gain: | 0 dBi |
| Antenna Type: | Integral antenna |
| Modulation Type: | GFSK |
| Number of Channels: | 22 |
| Operation Frequency: | 2402MHz to 2477MHz |
| Series number: | A1 |
| Hardware Version: | V1.0 |
| Software Version: | 0.11 |
| | Remark: Power level setting was not adjustable and fixed default through SW Version. |

Frequency List

FHSS:

| Channel Number | TX Freq (MHz) | Channel Number | TX Freq (MHz) |
|----------------|---------------|----------------|---------------|
| 1 | 2402 | 12 | 2445 |
| 2 | 2404 | 13 | 2450 |
| 3 | 2406 | 14 | 2455 |
| 4 | 2408 | 15 | 2460 |
| 5 | 2410 | 16 | 2465 |
| 6 | 2415 | 17 | 2467 |
| 7 | 2420 | 18 | 2469 |
| 8 | 2425 | 19 | 2471 |
| 9 | 2430 | 20 | 2473 |
| 10 | 2435 | 21 | 2475 |
| 11 | 2440 | 22 | 2477 |

- Remark: 1. Operation channel is total 22.
2. Testing Channels are highlighted in **bold**.

4.2 Description of Support Units

The EUT has been tested with corresponding accessories as below:

Supplied by client

| Description | Manufacturer | Model No. | SN/Certificate NO |
|-----------------|--------------|-----------|-------------------|
| UART Test board | N/A | N/A | N/A |

Supplied by SGS:

| Description | Manufacturer | Model No. | SN/Certificate NO |
|-----------------|--------------|-----------|-------------------|
| NoteBook (EMC4) | Dell | P75F | N/A |

4.3 Test Location

All tests were performed at:

SGS Hong Kong Limited
Unit 2 and 3, G/F, Block A, Po Lung Centre,
11 Wang Chiu Road, Kowloon Bay, Kowloon, Hong Kong
Tel: +852 2305 2570 Fax: +852 2756 4480

No tests were sub-contracted.

4.4 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

• **IAS Accreditation (Lab Code: TL-817)**

SGS Hong Kong Limited has met the requirements of AC89, IAS Accreditation Criteria for Testing Laboratories, and has demonstrated compliance with ISO/IEC Standard 17025:2017, General requirements for the competence of testing and calibration laboratories. This organization is accredited to provide the services specified in the scope of accreditation maintained on the IAS website (www.iasonline.org).

The report must not be used by the client to claim product certification, approval, or endorsement by IAS, NIST, or any agency of the Federal Government.

• **FCC Recognized Accredited Test Firm(CAB Registration No.: 514599)**

SGS Hong Kong Limited has been accredited and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Designation Number: HK0015, Test Firm Registration Number: 514599.

• **Industry Canada (Site Registration No.: 26103; CAB Identifier No.: HK0015)**

SGS Hong Kong Limited has been recognized by Department of Innovation, Science and Economic Development (ISED) Canada as a wireless testing laboratory. The acceptance letter from the ISED is maintained in our files. CAB Identifier No: HK0015, Site Registration Number: 26103.

4.5 Deviation from Standards

None

4.6 Abnormalities from Standard Conditions

None

5 Radio Spectrum Technical Requirement

5.1 RF Exposure

5.1.1 Test Requirement:

CFR 47 Part 1.1310

Limit:

According to FCC Part1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in Part1.1307(b)

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

| Frequency range (MHz) | Electric field strength (V/m) | Magnetic field strength (A/m) | Power density (mW/cm ²) | Averaging time (minutes) |
|--|-------------------------------|-------------------------------|-------------------------------------|--------------------------|
| (A) Limits for Occupational/Controlled Exposure | | | | |
| 0.3-3.0 | 614 | 1.63 | *100 | 6 |
| 3.0-30 | 1842/f | 4.89/f | *900/f ² | 6 |
| 30-300 | 61.4 | 0.163 | 1.0 | 6 |
| 300-1,500 | | | f/300 | 6 |
| 1,500-100,000 | | | 5 | 6 |
| (B) Limits for General Population/Uncontrolled Exposure | | | | |
| 0.3-1.34 | 614 | 1.63 | *100 | 30 |
| 1.34-30 | 824/f | 2.19/f | *180/f ² | 30 |
| 30-300 | 27.5 | 0.073 | 0.2 | 30 |
| 300-1,500 | | | f/1500 | 30 |
| 1,500-100,000 | | | 1.0 | 30 |

f = frequency in MHz

* = Plane-wave equivalent power density

According to IEEE C95.3:2002 section 5.5.1.1, The power density S at a point on the axis at a distance d from a transmitting antenna is given by the Friis free-space transmission formula

$$S = \frac{PG}{4\pi d^2}$$

S = power density (mW/cm²)
P = the net power delivered to the antenna (mW)
G = gain of the antenna in linear scale
d = distance between observation point and center of the radiator (cm)

5.1.1 IC Radiofrequency radiation

According to RSS-102 Issue 5, section 2.5.2 Exemption.

RF exposure evaluation is required if the separation distance between the user and the device's radiating element is greater than 20 cm, except when the device operates as follows:

below 20 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 1 W (adjusted for tune-up tolerance);

at or above 20 MHz and below 48 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than $22.48/f^{0.5}$ W (adjusted for tune-up tolerance), where f is in MHz;

at or above 48 MHz and below 300 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 0.6 W (adjusted for tune-up tolerance);

at or above 300 MHz and below 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than $1.31 \times 10^{-2} f^{0.6834}$ W (adjusted for tune-up tolerance), where f is in MHz;

at or above 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 5 W (adjusted for tune-up tolerance).

5.1.2 EUT RF Exposure Evaluation

Antenna Gain: 0 dBi

The maximum Gain measured in fully anechoic chamber is 1.0 in linear scale.

Output Power Into Antenna & RF Exposure Evaluation Distance:

For FCC;

FHSS:

| Channel | Frequency (MHz) | Conduct power (including Tune-up tolerance) (dBm) | Conduct power (mW) | Power Density at R = 20 cm (mW/cm ²) | Limit | MPE Ratios | Result |
|---------|-----------------|---|--------------------|--|-------|------------|--------|
| Low | 2402 | 14.8 | 30.200 | 0.00601 | 1 | 0.00601 | PASS |
| Middle | 2440 | 15.2 | 33.113 | 0.00659 | 1 | 0.00659 | PASS |
| High | 2477 | 14.2 | 26.303 | 0.00523 | 1 | 0.00523 | PASS |

For IC:

FHSS:

| Channel | Frequency (MHz) | Conduct power (including Tune-up tolerance) (dBm) | E.I.R.P (dBm) | E.I.R.P (W) | Limit (W) | Result |
|---------|-----------------|---|---------------|-------------|-----------|--------|
| Low | 2402 | 14.8 | 14.8 | 0.0302 | 2.7 | PASS |
| Middle | 2440 | 15.2 | 15.2 | 0.0331 | 2.7 | PASS |
| High | 2477 | 14.2 | 14.2 | 0.0263 | 2.7 | PASS |

Note: 1. Refer to report No. HKEM211000108602 for EUT test conducted power value. requirement.



6 Photographs

Remark: Photos refer to Appendix of HKEM2110001086AT.

- End of the Report -
