

TEST REPORT

Report Number: HK09120779-2

Application
for
Original Grant of 47 CFR Part 15 Certification
New Family of RSS-210 Issue 7 Equipment Certification

1.9GHz Digital Modulation Cordless Phone with Caller ID, Speakerphone,
Digital Answering Machine and Bluetooth - Base Unit (Bluetooth Portion)

FCC ID: VLJ80-7472-02

IC: 4522A-80747202

Prepared and Checked by:



Koo Wai Ip
Engineer
January 08, 2010

Approved by:



Nip Ming Fung, Melvin
Supervisor
January 08, 2010

- The test report only allows to be revised within the retention period unless further standard or the requirement was noticed.
- This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

INTERTEK TESTING SERVICES

GENERAL INFORMATION

Applicant Name:	Binatone Electronics International Limited
Applicant Address:	Floor 23A, 9 Des Voeux Road West, Sheung Wan, Hong Kong.
FCC Specification Standard:	FCC Part 15: 2008
FCC ID:	VLJ80-7472-02
FCC Model(s):	L512BT, L511BT, L513BT, L514BT, L515BT, L51XBT
IC Specification Standard:	RSS-210 Issue 7, June 2007 RSS-Gen Issue 2, June 2007 RSS-102 Issue 3, June 2009
IC:	4522A-80747202
IC Model(s):	L512BT, L511BT, L513BT, L514BT, L515BT
Type of EUT:	Transceiver
Description of EUT:	1.9GHz Digital Modulation Cordless Phone with Caller ID, Speakerphone, Digital Answering Machine and Bluetooth - Base Unit (Bluetooth Portion)
Serial Number:	N/A
Sample Receipt Date:	December 18, 2009
Date of Test:	December 23-30, 2009
Report Date:	January 08, 2010
Environmental Conditions:	Temperature: +10 to 40°C Humidity: 10 to 90%

INTERTEK TESTING SERVICES

Table of Contents

1.0 Summary of Test Results	3
2.0 General Description	5
2.1 Product Description	5
2.2 Test Methodology	6
2.3 Test Facility	6
3.0 System Test Configuration	8
3.1 Justification	8
3.2 EUT Exercising Software	9
3.3 Details of EUT and Description of Peripherals	10
3.4 Measurement Uncertainty	10
3.5 Equipment Modification	10
4.0 Test Results	12
4.1 Field Strength Calculation	12
4.2 Radiated Emissions from Transmitter	13
4.2.1 Radiated Emission Configuration Photograph	13
4.2.2 Radiated Emission Data	13
4.2.3 Transmitter Duty Cycle Calculation and Measurements	14
4.3 Radiated Emissions from Receiver	19
4.3.1 Radiated Emission Configuration Photograph	19
4.3.2 Radiated Emission Data	19
4.4 Radiated Emission on the Bandedge	21
4.5 AC Power Line Conducted Emission	22
4.5.1 AC Power Line Conducted Emission Configuration Photograph	22
4.5.2 AC Power Line Conducted Emission Data	22
4.6 Radio Frequency Exposure Compliance	23
5.0 Equipment List	24
Appendix – Exhibits for Application of Certification	

INTERTEK TESTING SERVICES

1.0 Summary of Test Results

Test Items	FCC Part 15 Section	RSS-210/ RSS-Gen [#] / RSS-310 [^] Section	Results	Details see section
Antenna Requirement	15.203	7.1.4 [#]	Pass	2.1
Radiated Emission Radiated Emission on the Bandedge	15.249(a), 209, & 109 15.249(d)	A2.9(a) A2.9(b)	Pass Pass	4.2 4.4
Radiated Emission in Restricted Bands	15.205	2.2	Pass	4.2
Radiated Emission from Receiver	N/A	2.3	Pass	4.3
AC Power Line Conducted Emission	15.207 & 15.107	7.2.2 [#]	Pass	4.5
Radio Frequency Exposure Compliance	N/A	RSS-102	Pass	4.6

Note: Pursuant to FCC Part 15 Section 15.215(c), the 20dB bandwidth of the emission was contained within the frequency band designated (mentioned as above) which the EUT operated. The effects, if any, from frequency sweeping, frequency hopping, other modulation techniques and frequency stability over expected variations in temperature and supply voltage were considered.

INTERTEK TESTING SERVICES

**EXHIBIT 2
GENERAL DESCRIPTION**

INTERTEK TESTING SERVICES

2.0 General Description

2.1 Product Description

The L512BT is a 1.9GHz Digital Modulation Cordless Phone with Caller ID, Speakerphone, Digital Answering Machine and Bluetooth. Only base unit has Bluetooth feature, and it operates at frequency range of 2402MHz to 2480MHz with 79 channels. It is powered by an adaptor 100-120VAC to 6.0VDC 400mA. With Bluetooth and 1.9GHz wireless communications enabled, the base unit allows users to use a cordless handset to dial out or receive Bluetooth- equipped cellular phone calls via the cellular network, or use a corresponding Bluetooth-equipped headset instead of the cordless headset. Only one cellular phone or headset can be on a call at a time.

The antenna used in base unit is integral, and the tested sample is a prototype.

For FCC, the Model(s): L511BT, L513BT, L514BT, L515BT and L51XBT are the same as the Model: L512BT in hardware aspect. Suffix (X) indicates different number of handset and charger.

For IC, the Model(s): L511BT, L513BT, L514BT and L515BT are the same as the Model: L512BT in hardware aspect. The difference in model number represents different number of handset and charger.

The circuit description is attached in the Appendix and saved with filename: descri.pdf.

Connection between the device and the telephone network is accomplished through the use of USOC RJ11C in the 2-wire loop calling central office line.

INTERTEK TESTING SERVICES

2.2 Test Methodology

Both AC power line-conducted and radiated emission measurements were performed according to the procedures in ANSI C63.4 (2003). Preliminary radiated scans and all radiated measurements were performed in Open Area Test Sites. All Radiated tests were performed at an antenna to EUT distance of 3 meters, unless stated otherwise in the "**Justification Section**" of this Application.

2.3 Test Facility

The open area test site and conducted measurement facility used to collect the radiated data and conducted data are located at Roof Top and 2nd Floor respectively of Garment Centre, 576 Castle Peak Road, Kowloon, Hong Kong. This test facility and site measurement data have been fully placed on file with the FCC and the Industry Canada.

INTERTEK TESTING SERVICES

**EXHIBIT 3
SYSTEM TEST CONFIGURATION**

INTERTEK TESTING SERVICES

3.0 System Test Configuration

3.1 Justification

For radiated emissions testing, the equipment under test (EUT) was setup to transmit / receive continuously to simplify the measurement methodology. Care was taken to ensure proper power supply voltages during testing. During testing, all cables (if any) were manipulated to produce worst case emissions.

The Base Unit was powered by a 100-120VAC to 6.0VDC 400mA adaptor.

The handset was powered by a fully charged battery.

For the measurements, the EUT is attached to a plastic stand if necessary and placed on the wooden turntable. If the base unit attaches to peripherals, they are connected and operational to simulate typical use.

The signal is maximized through rotation and placement in the three orthogonal axes. The antenna height and polarization are varied during the search for maximum signal level. The antenna height is varied from 1 to 4 meters. Radiated emissions are taken at three meters unless the signal level is too low for measurement at that distance. If necessary, a pre-amplifier is used and/or the test is conducted at a closer distance.

Measurements of the radiated signal level of the fundamental frequency component of the emission was performed with the supply voltage varied between 85% and 115% of the nominal rated supply voltage.

For transmitter radiated measurement, the spectrum analyzer resolution bandwidth was 100 kHz for frequencies below 1000 MHz. The resolution bandwidth was 1 MHz for frequencies above 1000 MHz.

For receiver radiated measurement, the spectrum analyzer resolution bandwidth was 1MHz for measurement above 1GHz while 100kHz for measurement from 30MHz to 1GHz.

Radiated emission measurement for transmitter were performed from the lowest radio frequency signal generated in the device which is greater than 9 kHz to the tenth harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower. Receiver was performed from 30MHz to the fifth harmonic of the highest frequency or 40GHz, whichever is lower.

Emission that are directly caused by digital circuits in the transmit path and transmitter portion are measured, and the limit are according to FCC Part 15 Section 15.109.

INTERTEK TESTING SERVICES

3.1 Justification - Cont'd

Detector function for radiated emissions is in peak mode. Average readings, when required, are taken by measuring the duty cycle of the equipment under test and subtracting the corresponding amount in dB from the measured peak readings. A detailed description for the calculation of the average factor can be found in Exhibit 4.2.3.

Determination of pulse desensitization was made according to *Hewlett Packard Application Note 150-2, Spectrum Analysis... Pulsed RF*. The effective period (T_{eff}) was 625 μ s. With the resolution bandwidth 1MHz and spectrum analyzer IF bandwidth 3dB, the pulse desensitization factor was 0dB.

For AC line conducted emission test, the EUT along with its peripherals were placed on a 1.0m(W)x1.5m(L) and 0.8m in height wooden table and the EUT was adjusted to maintain a 0.4 meter space from a vertical reference plane. The EUT was connected to power mains through a line impedance stabilization network (LISN), which provided 50ohm coupling impedance for measuring instrument. The LISN housing, measuring instrument case, reference ground plane, and vertical ground plane were bounded together. The excess power cable between the EUT and the LISN was bundled.

All connecting cables of EUT and peripherals were manipulated to find the maximum emission.

All relevant operation modes have been tested, and the worst case data is included in this report.

3.2 EUT Exercising Software

The EUT exercise program used during radiated and conducted testing was designed to exercise the various system components in a manner similar to a typical use.

INTERTEK TESTING SERVICES

3.3 Details of EUT and Description of Peripherals

Details of EUT:

An AC adaptor and/or a battery (provided with the unit) were used to power the device. Their description are listed below.

- (1) Base Unit: An AC adaptor (100-120VAC to 6.0VDC 400mA, Model: S005IU0600040) (Supplied by Client)

Description of Peripherals:

- (1) Handset: A "Ni-MH" type rechargeable battery (2.4V, 550mAh) (Supplied by Client)
- (2) Handset, Model: L512BT, FCC ID: VLJ80-7472-01 (Supplied by Client)
- (3) Nokia Mobile Phone, Model: 5300, FCC ID: PPIRM-146 (Supplied by Intertek)
- (4) 1m Telephone Line with Termination (Supplied by Intertek)
- (5) 3m Telephone Line (Supplied by Intertek)
- (6) Telephone Line Simulator, Model: TLS-5D-01, S/N: 119319 (Supplied by Intertek)

3.4 Measurement Uncertainty

When determining of the test conclusion, the Measurement Uncertainty of test has been considered.

3.5 Equipment Modification

Any modifications installed previous to testing by Binatone Electronics International Limited will be incorporated in each production model sold/leased in the United States and Canada.

No modifications were installed by Commercial & Electrical Division, Intertek Testing Services Hong Kong Ltd.

INTERTEK TESTING SERVICES

**EXHIBIT 4
TEST RESULTS**

INTERTEK TESTING SERVICES

4.0 Test Results

Data is included of the worst case configuration (the configuration which resulted in the highest emission levels). A sample calculation, configuration photographs and data tables of the emissions are included.

4.1 Field Strength Calculation

The field strength is calculated by adding the Antenna Factor and Cable Factor, and subtracting the Amplifier Gain (if any) from the measured reading. The basic equation with a sample calculation is as follows:

$$FS = RA + AF + CF - AG$$

where FS = Field Strength in dB μ V/m
 RA = Receiver Amplitude (including preamplifier) in dB μ V
 CF = Cable Attenuation Factor in dB
 AF = Antenna Factor in dB
 AG = Amplifier Gain in dB

In the following table(s), the reading shown on the data table reflects the preamplifier gain. An example for the calculations in the following table is as follows:-

$$FS = RR + LF$$

where FS = Field Strength in dB μ V/m
 RR = RA - AG in dB μ V
 LF = CF + AF in dB

Assume a receiver reading of 52.0 dB μ V is obtained. The antenna factor of 7.4 dB and cable factor of 1.6 dB is added. The amplifier gain of 29 dB is subtracted, giving a field strength of 32 dB μ V/m. This value in dB μ V/m was converted to its corresponding level in μ V/m.

RA = 52.0 dB μ V	
AF = 7.4 dB	RR = 23.0 dB μ V
CF = 1.6 dB	LF = 9.0 dB
AG = 29.0 dB	
FS = RR + LF	
FS = 23 + 9 = 32 dB μ V/m	

$$\text{Level in } \mu\text{V/m} = \text{Common Antilogarithm} [(32 \text{ dB}\mu\text{V/m})/20] = 39.8 \mu\text{V/m}$$

INTERTEK TESTING SERVICES

4.2 Radiated Emissions

4.2.1 Radiated Emission Configuration Photograph

Worst Case Radiated Emission
at
55.300 MHz

The worst case radiated emission configuration photographs are attached in the Appendix and saved with filename: config photos.pdf

4.2.2 Radiated Emission Data

The data in tables 1-4 list the significant emission frequencies, the limit and the margin of compliance.

Judgement -
Passed by 6.1 dB margin

INTERTEK TESTING SERVICES

4.2.3 Transmitter Duty Cycle Calculation

Based on the Bluetooth Specification Version 2.1 + EDR, the transmitter ON time for each timeslot of Bluetooth is 625 μ s. DH5 has the maximum duty cycle, which consists of 5 continuous Tx slots and 1 Rx slot. Therefore one hopset take (5+1) x 625 μ s = 3.75ms. For one period for a pseudo-random hopping through all 79 RF channels, it take: 79 x 3.75ms = 296.25ms.

The dwell time for DH5 is 5 x 625 μ s = 3.125ms.

Therefore,

$$\begin{aligned}\text{Duty Cycle (DC)} &= \text{Maximum On time in 100ms/100ms} \\ &= 3.125\text{ms}/100\text{ms} \\ &= 0.03125\end{aligned}$$

$$\begin{aligned}\text{Average Factor (AF) of Bluetooth in dB} &= 20 \log_{10} (0.03125) \\ &= -30.1\text{dB}\end{aligned}$$

INTERTEK TESTING SERVICES

Mode: TX-Channel 00

Table 1

Radiated Emission Data

Polarization	Frequency (MHz)	Reading (dB μ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Average Factor (dB)	Calculated at 3m (dB μ V/m)	Average Limit at 3m (dB μ V/m)	Margin (dB)
H	2402.000	92.5	33	29.4	30.1	58.8	94.0	-35.2
H	4804.000	59.0	33	34.9	30.1	30.8	54.0	-23.2
H	7206.000	52.7	33	37.9	30.1	27.5	54.0	-26.5
H	9608.000	51.2	33	40.4	30.1	28.5	54.0	-25.5
H	12010.000	52.1	33	40.5	30.1	29.5	54.0	-24.5
H	14412.000	53.0	33	40.0	30.1	29.9	54.0	-24.1

Polarization	Frequency (MHz)	Reading (dB μ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Peak (dB μ V/m)	Peak Limit at 3m (dB μ V/m)	Margin (dB)
H	2402.000	92.5	33	29.4	88.9	114.0	-25.1
H	4804.000	59.0	33	34.9	60.9	74.0	-13.1
H	7206.000	52.7	33	37.9	57.6	74.0	-16.4
H	9608.000	51.2	33	40.4	58.6	74.0	-15.4
H	12010.000	52.1	33	40.5	59.6	74.0	-14.4
H	14412.000	53.0	33	40.0	60.0	74.0	-14.0

- NOTES:
1. Peak detector is used for the emission measurement.
 2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.
 3. Negative value in the margin column shows emission below limit.
 4. Horn antenna is used for the emission over 1000MHz.
 5. Emission (the row indicated by **bold italic**) within the restricted band meets the requirement of FCC Part 15 Section 15.205 / RSS-210 Section 2.2.

INTERTEK TESTING SERVICES

Mode: TX-Channel 39

Table 2

Radiated Emission Data

Polarization	Frequency (MHz)	Reading (dB μ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Average Factor (dB)	Calculated at 3m (dB μ V/m)	Average Limit at 3m (dB μ V/m)	Margin (dB)
H	2441.000	93.3	33	29.4	30.1	59.6	94.0	-34.4
H	4882.000	59.2	33	34.9	30.1	31.0	54.0	-23.0
H	7323.000	52.4	33	37.9	30.1	27.2	54.0	-26.8
H	9764.000	50.8	33	40.4	30.1	28.1	54.0	-25.9
H	12205.000	51.6	33	40.5	30.1	29.0	54.0	-25.0
H	14646.000	54.6	33	38.4	30.1	29.9	54.0	-24.1

Polarization	Frequency (MHz)	Reading (dB μ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Peak (dB μ V/m)	Peak Limit at 3m (dB μ V/m)	Margin (dB)
H	2441.000	93.3	33	29.4	89.7	114.0	-24.3
H	4882.000	59.2	33	34.9	61.1	74.0	-12.9
H	7323.000	52.4	33	37.9	57.3	74.0	-16.7
H	9764.000	50.8	33	40.4	58.2	74.0	-15.8
H	12205.000	51.6	33	40.5	59.1	74.0	-14.9
H	14646.000	54.6	33	38.4	60.0	74.0	-14.0

- NOTES:
1. Peak detector is used for the emission measurement.
 2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.
 3. Negative value in the margin column shows emission below limit.
 4. Horn antenna is used for the emission over 1000MHz.
 5. Emission (the row indicated by **bold italic**) within the restricted band meets the requirement of FCC Part 15 Section 15.205 / RSS-210 Section 2.2.

INTERTEK TESTING SERVICES

Mode: TX-Channel 78

Table 3

Radiated Emission Data

Polarization	Frequency (MHz)	Reading (dB μ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Average Factor (dB)	Calculated at 3m (dB μ V/m)	Average Limit at 3m (dB μ V/m)	Margin (dB)
H	2480.000	93.2	33	29.4	30.1	59.5	94.0	-34.5
H	4960.000	58.9	33	34.9	30.1	30.7	54.0	-23.3
H	7440.000	52.7	33	37.9	30.1	27.5	54.0	-26.5
H	9920.000	51.1	33	40.4	30.1	28.4	54.0	-25.6
H	12400.000	52.1	33	40.5	30.1	29.5	54.0	-24.5
H	14880.000	55.2	33	38.4	30.1	30.5	54.0	-23.5

Polarization	Frequency (MHz)	Reading (dB μ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Peak (dB μ V/m)	Peak Limit at 3m (dB μ V/m)	Margin (dB)
H	2480.000	93.2	33	29.4	89.6	114.0	-24.4
H	4960.000	58.9	33	34.9	60.8	74.0	-13.2
H	7440.000	52.7	33	37.9	57.6	74.0	-16.4
H	9920.000	51.1	33	40.4	58.5	74.0	-15.5
H	12400.000	52.1	33	40.5	59.6	74.0	-14.4
H	14880.000	55.2	33	38.4	60.6	74.0	-13.4

- NOTES:
1. Peak detector is used for the emission measurement.
 2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.
 3. Negative value in the margin column shows emission below limit.
 4. Horn antenna is used for the emission over 1000MHz.
 5. Emission (the row indicated by **bold italic**) within the restricted band meets the requirement of FCC Part 15 Section 15.205 / RSS-210 Section 2.2.

INTERTEK TESTING SERVICES

Mode: Talk

Table 4

Radiated Emission Data

Polarization	Frequency (MHz)	Reading (dB μ V)	Pre-amp (dB)	Antenna Factor (dB)	Net at 3m (dB μ V/m)	Limit at 3m (dB μ V/m)	Margin (dB)
V	55.300	38.9	16	11.0	33.9	40.0	-6.1
V	110.600	36.1	16	14.0	34.1	43.5	-9.4
V	165.900	33.2	16	17.0	34.2	43.5	-9.3
H	221.200	32.5	16	17.0	33.5	46.0	-12.5
H	276.500	27.2	16	22.0	33.2	46.0	-12.8
H	331.800	24.6	16	24.0	32.6	46.0	-13.4

- NOTES:
1. Peak detector is used for the emission measurement.
 2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.
 3. Negative value in the margin column shows emission below limit.
 4. Emission (the row indicated by **bold italic**) within the restricted band meets the requirement of FCC Part 15 Section 15.205 / RSS-210 Section 2.2.

INTERTEK TESTING SERVICES

4.3 Radiated Emissions from Receiver

4.3.1 Radiated Emission Configuration Photograph

Worst Case Radiated Emission
at

2439.513 MHz

The worst case radiated emission configuration photographs are attached in the Appendix and saved with filename: config photos.pdf

4.3.2 Radiated Emission Data

The data in tables 5 list the significant emission frequencies, the limit and the margin of compliance.

Judgement -

Base Unit: Passed by 5.4 dB margin

INTERTEK TESTING SERVICES

Mode: Receiving

Table 5

Radiated Emissions Data

Middle Channel

Polarization	Frequency (MHz)	Reading (dB μ V)	Pre-amp (dB)	Antenna Factor (dB)	Net at 3m (dB μ V/m)	Limit at 3m (dB μ V/m)	Margin (dB)
V	2439.513	52.2	33	29.4	48.6	54.0	-5.4
V	4879.026	45.0	33	34.9	46.9	54.0	-7.1
H	7318.539	41.3	33	37.9	46.2	54.0	-7.8
H	9758.052	37.2	33	40.4	44.6	54.0	-9.4
H	12197.565	36.7	33	40.5	44.2	54.0	-9.8

NOTES:

1. Peak detector is used for the emission measurement.
2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.
3. Negative value in the margin column shows emission below limit.
4. Horn antenna is used for the emission over 1000MHz.

INTERTEK TESTING SERVICES

4.4 Radiated Emission on the Bandedge

From the following plots, they show that the fundamental emissions are confined in the specified band (2400MHz and 2483.5MHz). In case of the fundamental emissions are within two standard bandwidths from the bandedge, the delta measurement technique is used for determining bandedge compliance. Standard bandwidth is the bandwidth specified by ANSI C63.4 (2003) for frequency being measured.

Emissions radiated outside of the specified frequency bands, except harmonics, are attenuated by 50 dB below the level of the fundamental or to the general radiated emission limits in FCC Part 15 Section 15.209 / Table 2 of RSS-210, whichever is the lesser attenuation, which meet the requirement of FCC Part 15 Section 15.249(d) / RSS-210 A2.9(b).

Radiated Emission on bandedge plots are attached in the Appendix and saved with filename: be.pdf

Bandedge compliance is determined by applying marker-delta method, i.e.

Resultant Field Strength = Fundamental Emissions - Delta from the plot

Resultant field strength for the lowest and/or highest channel(s), with corresponding average values are calculated as follows:

	Channel	Fundamental Emission (dB μ V/m)	Delta from the Plot (dB)	Resultant Field Strength (dB μ V/m)	Average Limit (dB μ V/m)	Margin (dB)
Base	Lowest	58.8	34.05	24.75	54	-29.25
	Highest	59.5	47.52	11.98	54	-42.02

	Channel	Fundamental Emission (dB μ V/m)	Delta from the Plot (dB)	Resultant Field Strength (dB μ V/m)	Peak Limit (dB μ V/m)	Margin (dB)
Base	Lowest	88.9	34.05	54.85	74	-19.15
	Highest	89.6	47.52	42.08	74	-31.92

The resultant field strength meets the general radiated emission limit in FCC Part 15 Section 15.209 / Table 2 of RSS-210, which does not exceed 74dB μ V/m for peak limit and also 54dB μ V/m for average limit.

INTERTEK TESTING SERVICES

4.5 AC Power Line Conducted Emission

- Not applicable – EUT is only powered by battery for operation.
- EUT connects to AC power line. Emission Data is listed in following pages.
- Base Unit connects to AC power line and has transmission. Handset connects to AC power line but has no transmission. Emission Data of Base Unit is listed in following pages.

4.5.1 AC Power Line Conducted Emission Configuration Photograph

Worst Case Line-Conducted Configuration
at

1.3290 MHz

The worst case line conducted configuration photographs are attached in the Appendix and saved with filename: config photos.pdf

4.5.2 AC Power Line Conducted Emission Data

The conducted emission test result is attached in the Appendix and saved with filename: conduct.pdf

Judgement -

Passed by 12.9 dB margin compare with average limit

INTERTEK TESTING SERVICES

4.6 Radio Frequency Exposure Compliance

The Routine RF Exposure Evaluation, Routine SAR Evaluation and Declaration of RF Exposure Compliance are saved as filename: RF exposure.pdf

INTERTEK TESTING SERVICES

5.0 Equipment List

1) Radiated Emissions Test

Equipment	Biconical Antenna	Log Periodic Antenna	Double Ridged Guide Antenna
Registration No.	EW-0954	EW-0446	EW-1015
Manufacturer	EMCO	EMCO	EMCO
Model No.	3104C	3146	3115
Calibration Date	Sep. 30, 2008	Oct. 02, 2008	Jul. 28, 2008
Calibration Due Date	Mar. 30, 2010	Apr. 02, 2010	Jan. 28, 2010

Equipment	EMI Test Receiver	Spectrum Analyzer 40GHz	Broad-Band Horn Antenna with frequency range 14G - 40GHz
Registration No.	EW-0014	EW-1792	EW-1679
Manufacturer	R&S	R&S	SCHWARZBECK
Model No.	ESVS30	FSP40	BBHA9170
Calibration Date	Jun. 01, 2009	Feb. 02, 2009	Feb. 10, 2009
Calibration Due Date	Jun. 01, 2010	Feb. 02, 2010	Feb. 10, 2010

2) Conducted Emissions Test

Equipment	EMI Test Receiver	LISN	Pulse Limiter
Registration No.	EW-0017	EW-0090	EW-0700
Manufacturer	R&S	R&S	R&S
Model No.	ESHS30	ESH3-Z5	ESH3-Z2
Calibration Date	Jun. 01, 2009	Jan. 20, 2009	Jun. 08, 2009
Calibration Due Date	Jun. 01, 2010	Jan. 20, 2010	Dec. 08, 2010

END OF TEST REPORT