

## RF Exposure Evaluation declaration

Product Name : Wi-Fi ATA  
Model No. : W200, W110  
FCC ID. : VLW-W200-110

Applicant : Soundwin Network Inc.

Address : 10F-4, No. 295, Sec. 2, Kuangfu Rd., Hsinchu  
City, Taiwan

Date of Receipt : 2007/08/08  
Date of Declaration : 2007/09/14  
Report No. : 078149R-RF-US-Exp

The declaration results relate only to the samples calculated.

The declaration shall not be reproduced except in full without the written approval of Quietek Corporation.

## 1. RF Exposure Evaluation

### 1.1. Limits

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

#### LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm <sup>2</sup> )	Average Time (Minutes)
(A) Limits for Occupational/ Control Exposures				
300-1500	--	--	F/300	6
1500-100,000	--	--	5	6
(B) Limits for General Population/ Uncontrolled Exposures				
300-1500	--	--	F/1500	6
1500-100,000	--	--	1	30

F= Frequency in MHz

Friis Formula

Friis transmission formula:  $P_d = (P_{out} * G) / (4 * \pi * r^2)$

Where

$P_d$  = power density in mW/cm<sup>2</sup>

$P_{out}$  = output power to antenna in mW

G = gain of antenna in linear scale

$\pi$  = 3.1416

R = distance between observation point and center of the radiator in cm

$P_d$  is the limit of MPE, 1 mW/cm<sup>2</sup>. If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

### 1.2. Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

The temperature and related humidity: 18°C and 78% RH.

**1.3. Test Result of RF Exposure Evaluation**

Product	Wi-Fi ATA
Test Mode	Mode 1: Transmit
Test Condition	RF Exposure Evaluation

**Antenna Gain**

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 3.13dBi or 2.056 in linear scale.

**Output Power Into Antenna & RF Exposure Evaluation Distance:**

IEEE 802.11b			
Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm <sup>2</sup> )
1	2412.00	75.1623	0.03074
6	2437.00	91.6220	0.03747
11	2462.00	123.8797	0.05067

The power density Pd (4th column) at a distance of 20 cm calculated from the Friis transmission formula is far below the limit of 1 mW/cm<sup>2</sup>.

Product	Wi-Fi ATA
Test Mode	Mode 1: Transmit
Test Condition	RF Exposure Evaluation

### Antenna Gain

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 3.13dBi or 2.056 in linear scale.

### Output Power Into Antenna & RF Exposure Evaluation Distance:

IEEE 802.11g			
Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm <sup>2</sup> )
1	2412.00	49.8884	0.02040
6	2437.00	59.9791	0.02453
11	2462.00	82.2243	0.03363

The power density Pd (4th column) at a distance of 20 cm calculated from the Friis transmission formula is far below the limit of 1 mW/cm<sup>2</sup>.