

5.1.5 Radio Frequency Exposure Compliance

RESULT: **Pass**

Test Specification

Test standard : CFR47 FCC Part 2.1091
 Limit : CFR47 FCC Part 1.1310

TABLE 1 TO § 1.1310(E)(1)—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(i) Limits for Occupational/Controlled Exposure				
0.3–3.0	614	1.63	*(100)	≤6
3.0–30	1842/f	4.89/f	*(900/f ²)	<6
30–300	61.4	0.163	1.0	<6
300–1,500			f/300	<6
1,500–100,000			5	<6
(ii) Limits for General Population/Uncontrolled Exposure				
0.3–1.34	614	1.63	*(100)	<30
1.34–30	824/f	2.19/f	*(180/f ²)	<30
30–300	27.5	0.073	0.2	<30
300–1,500			f/1500	<30
1,500–100,000			1.0	<30

f = frequency in MHz. * = Plane-wave equivalent power density.

MPE Calculation:

The power Density (mW / CM^2) is calculated as follows:

$$S = \frac{PG}{4\pi R^2}$$

S=power density (mW / CM^2)

P=power input to the antenna (mW)

G=power input to the antenna in the direction of interest relative to an isotropic radiator

R=distance to the center of radiation of the antenna (CM)

FCC MPE

Frequency (MHz)	Maximum Electric Field dBuV/m@3m	E.I.R.P. Power (mW)	Distance (CM)	Power Density (mW / CM^2)	Power Density limit (mW / CM^2)
433MHz Band	72.22	0.005	20	9.95×10^{-7}	0.289

Conclusion:

EUT is compliance with FCC's RF Exposure.