

FCC Test Report

Applicant : **Swann Communications U.S.A. Inc.**

Address : **12636 Clark Street Santa Fe Springs
California United States 90670**

Product Name : **WIRELESS NETWORK VIDEO RECORDER**

Report Date : **Feb. 02, 2024**



Shenzhen Anbotek Compliance Laboratory Limited

Shenzhen Anbotek Compliance Laboratory Limited

Address: 1/F., Building D, Sogood Science and Technology Park, Sanwei Community,
Hangcheng Street, Bao'an District, Shenzhen, Guangdong, China.
Tel: (86) 0755-26066440 Fax: (86) 0755-26014772 Email: service@anbotek.com

Code: AB-RF-05-b



Hotline

400-003-0500

www.anbotek.com.cn



Contents

1. General Information	6
1.1. Client Information	6
1.2. Description of Device (EUT)	6
1.3. Auxiliary Equipment Used During Test	7
1.4. Description of Test Configuration	7
1.5. Description Of Test Setup	8
1.6. Test Equipment List	9
1.7. Measurement Uncertainty	10
1.8. Description of Test Facility	10
1.9. Disclaimer	11
2. Summary of Test Results	12
3. Conducted Emission Test	13
3.1. Test Standard and Limit	13
3.2. Test Setup	13
3.3. Test Procedure	13
3.4. Test Data	13
4. Radiation Spurious Emission and Band Edge	16
4.1. Test Standard and Limit	16
4.2. Test Setup	16
4.3. Test Procedure	17
4.4. Test Data	18
5. Maximum Peak Output Power Test	26
5.1. Test Standard and Limit	26
5.2. Test Setup	26
5.3. Test Procedure	26
5.4. Test Data	26
6. 6dB Emission Bandwidth Test	28
6.1. Test Standard and Limit	28
6.2. Test Setup	28
6.3. Test Procedure	28
6.4. Test Data	28
7. Power Spectral Density Test	34
7.1. Test Standard and Limit	34
7.2. Test Setup	34
7.3. Test Procedure	34
7.4. Test Data	34
8. 100kHz Bandwidth of Frequency Band Edge Requirement	40



8.1. Test Standard and Limit.....	40
8.2. Test Setup.....	40
8.3. Test Procedure.....	40
8.4. Test Data.....	40
9. Antenna Requirement.....	51
9.1. Test Standard and Requirement.....	51
9.2. Antenna Connected Construction.....	51
APPENDIX I -- TEST SETUP PHOTOGRAPH.....	52
APPENDIX II -- EXTERNAL PHOTOGRAPH.....	52
APPENDIX III -- INTERNAL PHOTOGRAPH.....	52



TEST REPORT

Applicant : Swann Communications U.S.A. Inc.
Manufacturer : Zhuhai Raysharp Technology Co.,Ltd.
Product Name : WIRELESS NETWORK VIDEO RECORDER
Test Model No. : NVW-MR4K
Reference Model No. : N/A
Trade Mark : N/A
Rating(s) : Input: 12V= 2A (with DC 3.7V, 8700mAh battery inside)
Test Standard(s) : FCC Part15 Subpart, Section 15.247
Test Method(s) : ANSI C63.10: 2020, KDB 558074 D01 15.247 Meas Guidance v05r02

The device described above is tested by Shenzhen Anbotek Compliance Laboratory Limited to determine the maximum emission levels emanating from the device and the severe levels of the device can endure and its performance criterion. The measurement results are contained in this test report and Shenzhen Anbotek Compliance Laboratory Limited is assumed full of responsibility for the accuracy and completeness of these measurements. Also, this report shows that the EUT (Equipment Under Test) is technically compliant with the FCC Part 15 Subpart C requirements.

This report applies to above tested sample only and shall not be reproduced in part without written approval of Shenzhen Anbotek Compliance Laboratory Limited.

Date of receipt

Nov. 01, 2023

Date of Test

Nov. 01 ~ Dec. 08, 2023

Prepared By

Nian xiu Chen

(Nianxiu Chen)

Approved & Authorized Signer

Edward pan

(Edward Pan)



Revision History

Report Version	Description	Issued Date
R00	Original Issue.	Feb. 02, 2024



1. General Information

1.1. Client Information

Applicant	:	Swann Communications U.S.A. Inc.
Address	:	12636 Clark Street Santa Fe Springs California United States 90670
Manufacturer	:	Zhuhai Raysharp Technology Co.,Ltd.
Address	:	No.100 Technology 6th.Road,High-tech Zone, Zhuhai ,Guangdong, P.R.China
Factory	:	Zhuhai Raysharp Technology Co.,Ltd.
Address	:	No.100 Technology 6th.Road,High-tech Zone, Zhuhai ,Guangdong, P.R.China

1.2. Description of Device (EUT)

Product Name	:	WIRELESS NETWORK VIDEO RECORDER
Test Model No.	:	NVW-MR4K
Reference Model No.	:	N/A
Trade Mark	:	N/A
Test Power Supply	:	AC 120V, 60Hz for Adapter/ DC 3.7V Battery inside
Test Sample No.	:	1-2-1(Normal Sample), 1-2-2(Engineering Sample)
Adapter	:	N/A
RF Specification		
Operation Mode	:	<input checked="" type="checkbox"/> DSSS <input type="checkbox"/> FHSS
Support Bandwidth	:	<input type="checkbox"/> 125KHz <input type="checkbox"/> 250KHz <input checked="" type="checkbox"/> 500KHz
Operation Frequency	:	902~928MHz
Number of Channel	:	3 Channels
Modulation Type	:	BPSK, QPSK, 16QAM, 64QAM
Antenna Type	:	Rod Antenna
Antenna Gain(Peak)	:	2.92 dBi
Remark: 1) All of the RF specification are provided by customer. 2) For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.		



1.3. Auxiliary Equipment Used During Test

Description	Rating(s)
Adapter	MODEL: CS-1202000 INPUT: 100-240V~1.5A Max. 50/60Hz OUTPUT: 12V $\overline{=}$ 2A

1.4. Description of Test Configuration


Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	908	3	924
2	916	/	/

Note:

- The engineering test program was provided and the EUT was programmed to be in continuously transmitting mode.



1.5. Description Of Test Setup



1.6. Test Equipment List

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	L.I.S.N. Artificial Mains Network	Rohde & Schwarz	ENV216	100055	Oct. 12, 2023	1 Year
2.	Three Phase V-type Artificial Power Network	CYBERTEK	EM5040DT	E215040DT001	Jul. 05, 2023	1 Year
3.	EMI Test Receiver	Rohde & Schwarz	ESCI	100627	Oct. 12, 2023	1 Year
4.	EMI Test Receiver	Rohde & Schwarz	ESR26	101481	Oct. 12, 2023	1 Year
5.	MXA Spectrum Analysis	Agilent	N9020A	MY51170037	Oct. 12, 2023	1 Year
6.	EMI Preamplifier	SKET Electronic	LNPA-0118G -45	SKET-PA-002	Oct. 12, 2023	1 Year
7.	Double Ridged Horn Antenna	SCHWARZBECK	BBHA 9120D	02555	Oct. 16, 2022	3 Year
8.	Bilog Broadband Antenna	Schwarzbeck	VULB9163	345	Oct. 23, 2022	3 Year
9.	Loop Antenna	Schwarzbeck	FMZB1519B	00053	Oct. 12, 2023	1 Year
10.	Horn Antenna	A-INFO	LB-180400- KF	J211060628	Oct. 12, 2023	1 Year
11.	Pre-amplifier	SONOMA	310N	186860	Oct. 12, 2023	1 Year
12.	EMI Test Software EZ-EMC	SHURPLE	N/A	N/A	N/A	N/A
13.	MXA Spectrum Analysis	KEYSIGHT	N9020A	MY53280032	Oct. 12, 2023	1 Year
14.	MXG RF Vector Signal Generator	Agilent	N5182A	MY48180656	Oct. 12, 2023	1 Year
15.	Signal Generator	Agilent	E4421B	MY41000743	Oct. 12, 2023	1 Year
16.	DC Power Supply	IVYTECH	IV3605	1804D360510	Oct. 20, 2023	1 Year
17.	Constant Temperature Humidity Chamber	ZHONGJIAN	ZJ-KHWS80 B	N/A	Oct. 16, 2023	1 Year
18.	Spectrum Analyzer	Rohde & Schwarz	FSV40-N	101792	May. 26, 2023	1 Year



1.7. Measurement Uncertainty

Parameter	Uncertainty
Conducted emissions (AMN 150kHz~30MHz)	3.8dB
Occupied Bandwidth	925Hz
Conducted Output Power	0.76dB
Power Spectral Density	0.76dB
Conducted Spurious Emission	1.24dB
Radiated spurious emissions (Below 30MHz)	3.53dB
Radiated spurious emissions (30MHz~1GHz)	Horizontal: 3.92dB; Vertical: 4.52dB
Radiated spurious emissions (above 1GHz)	1G-6GHz: 4.78dB; 6G-18GHz: 4.88dB 18G-40GHz: 5.68dB
The measurement uncertainty and decision risk evaluated according to AB/WI-RF-F-032. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.	

1.8. Description of Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

FCC-Registration No.: 434132

Shenzhen Anbotek Compliance Laboratory Limited, EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration No. 434132.

ISED-Registration No.: 8058A

Shenzhen Anbotek Compliance Laboratory Limited, EMC Laboratory has been registered and fully described in a report filed with the (ISED) Innovation, Science and Economic Development Canada. The acceptance letter from the ISED is maintained in our files. Registration 8058A.

Test Location

Shenzhen Anbotek Compliance Laboratory Limited.

1/F, Building D, Sogood Science and Technology Park, Sanwei community, Hangcheng Street, Bao'an District, Shenzhen, Guangdong, China.



1.9.Disclaimer

1. The test report is invalid if not marked with the signatures of the persons responsible for preparing and approving the test report.
2. The test report is invalid if there is any evidence and/or falsification.
3. The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein.
4. This document may not be altered or revised in any way unless done so by Anbotek and all revisions are duly noted in the revisions section.
5. Content of the test report, in part or in full, cannot be used for publicity and/or promotional purposes without prior written approval from the laboratory.
6. The authenticity of the information provided by the customer is the responsibility of the customer and the laboratory is not responsible for its authenticity.

The laboratory is only responsible for the data released by the laboratory, except for the part provided by the applicant.



2. Summary of Test Results

Standard Section	Test Item	Result
15.203/15.247(c)	Antenna Requirement	PASS
15.207	Conducted Emission	PASS
15.205/15.209	Spurious Emission	PASS
15.247(b)(3)	Conducted Peak Output Power	PASS
15.247(a)(2)	6dB Emission Bandwidth	PASS
15.247(e)	Power Spectral Density	PASS
15.247(d)	Band Edge	PASS

Remark: "N/A" is an abbreviation for Not Applicable.




3. Conducted Emission Test

3.1. Test Standard and Limit

Test Standard	FCC Part15 Section 15.207		
Test Limit	Frequency	Maximum RF Line Voltage (dBuV)	
		Quasi-peak Level	Average Level
	150kHz~500kHz	66 ~ 56 *	56 ~ 46 *
	500kHz~5MHz	56	46
	5MHz~30MHz	60	50

Remark: (1) *Decreasing linearly with logarithm of the frequency.
 (2) The lower limit shall apply at the transition frequency.

3.2. Test Setup



3.3. Test Procedure

The EUT system is connected to the power mains through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm coupling impedance for the EUT system. Please refer the block diagram of the test setup and photographs. Both sides of AC line are checked to find out the maximum conducted emission. In order to find the maximum emission levels, the relative positions of equipment and all of the interface cables shall be changed according to FCC ANSI C63.10: 2020 on Conducted Emission Measurement.

The bandwidth of test receiver (ESCI) set at 9kHz.

The frequency range from 150kHz to 30MHz is checked.

3.4. Test Data

During the test, pre-scan all modes, only the worst case is recorded in the report.


AC conducted emission pre-test at both at AC 120V/60Hz and AC 240V/60Hz modes, recorded worst case AC 120V/60Hz.

Please to see the following pages.



Conducted Emission Test Data

Test Site: 1# Shielded Room
 Operating Condition: 16QAM 908MHz
 Test Specification: AC 120V, 60Hz for Adapter
 Comment: Live Line
 Temp.(°C)/Hum.(%RH): 24.8°C/61%RH




No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit (dBuV)	Over Limit (dB)	Detector	Remark
1	0.1500	18.23	19.82	38.05	55.99	-17.94	AVG	
2	0.2300	30.58	19.83	50.41	62.45	-12.04	QP	
3	0.3540	16.53	19.82	36.35	48.87	-12.52	AVG	
4	0.7140	27.51	19.87	47.38	56.00	-8.62	QP	
5	0.7140	12.60	19.87	32.47	46.00	-13.53	AVG	
6	1.1300	13.37	19.85	33.22	46.00	-12.78	AVG	
7	1.4500	28.12	19.84	47.96	56.00	-8.04	QP	
8	1.4500	12.00	19.84	31.84	46.00	-14.16	AVG	
9	1.7540	26.65	19.84	46.49	56.00	-9.51	QP	
10	1.7980	9.87	19.84	29.71	46.00	-16.29	AVG	
11	2.6340	23.75	19.84	43.59	56.00	-12.41	QP	
12	3.9020	21.32	19.85	41.17	56.00	-14.83	QP	



Conducted Emission Test Data

Test Site: 1# Shielded Room
 Operating Condition: 16QAM 908MHz
 Test Specification: AC 120V, 60Hz for Adapter
 Comment: Neutral Line
 Temp.(°C)/Hum.(%RH): 24.8°C/61%RH



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit (dBuV)	Over Limit (dB)	Detector	Remark
1	0.1500	36.16	19.82	55.98	65.99	-10.01	QP	
2	0.1500	19.22	19.82	39.04	55.99	-16.95	AVG	
3	0.2020	32.42	19.83	52.25	63.52	-11.27	QP	
4	0.4620	29.30	19.83	49.13	56.66	-7.53	QP	
5	0.4620	15.31	19.83	35.14	46.66	-11.52	AVG	
6	1.1460	28.53	19.85	48.38	56.00	-7.62	QP	
7	1.3619	13.13	19.84	32.97	46.00	-13.03	AVG	
8	1.6980	24.70	19.84	44.54	56.00	-11.46	QP	
9	1.6980	10.02	19.84	29.86	46.00	-16.14	AVG	
10	2.0780	7.71	19.83	27.54	46.00	-18.46	AVG	
11	2.6700	24.39	19.84	44.23	56.00	-11.77	QP	
12	3.1980	3.69	19.84	23.53	46.00	-22.47	AVG	



4. Radiation Spurious Emission and Band Edge

4.1. Test Standard and Limit

Test Standard	FCC Part15 C Section 15.209 and 15.205				
Test Limit	Frequency (MHz)	Field strength (microvolt/meter)	Limit (dBuV/m)	Remark	Measurement distance (m)
	0.009MHz~0.490MHz	2400/F(kHz)	-	-	300
	0.490MHz-1.705MHz	24000/F(kHz)	-	-	30
	1.705MHz-30MHz	30	-	-	30
	30MHz~88MHz	100	40.0	Quasi-peak	3
	88MHz~216MHz	150	43.5	Quasi-peak	3
	216MHz~960MHz	200	46.0	Quasi-peak	3
	960MHz~1000MHz	500	54.0	Quasi-peak	3
	Above 1000MHz	500	54.0	Average	3
-		-	74.0	Peak	3

Remark:

(1)The lower limit shall apply at the transition frequency.

(2) 15.35(b), Unless otherwise specified, the limit on peak radio frequency emissions is 20dB above the maximum permitted average emission limit applicable to the equipment under test. This peak limit applies to the total peak emission level radiated by the device.

4.2. Test Setup




Figure 1. Below 30MHz






Figure 2. 30MHz to 1GHz




Figure 3. Above 1 GHz

4.3. Test Procedure

For below 1GHz: The EUT is placed on a turntable, which is 0.8m above the ground plane.

For above 1GHz: The EUT is placed on a turntable, which is 1.5m above the ground plane.

The turn table can rotate 360 degrees to determine the position of the maximum emission level. The EUT is set 3 meters away from the receiving antenna which is mounted on a antenna tower. The antenna can be moved up and down from 1 to 4 meters to find out the maximum emission level. Rotated the EUT through three orthogonal axes to determine the maximum emissions, both horizontal and vertical polarization of the antenna are set on test. The EUT is tested in 9*6*6 Chamber. The device is evaluated in xyz orientation.



For the radiated emission test above 1GHz:

Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.

For 9kHz to 150kHz, Set the spectrum analyzer as:

RBW = 200Hz, VBW =1kHz, Detector= Quasi-Peak, Trace mode= Max hold, Sweep- auto couple.

For 150kHz to 30MHz, Set the spectrum analyzer as:

RBW = 9KHz, VBW =30kHz, Detector= Quasi-Peak, Trace mode= Max hold, Sweep- auto couple.

For 30MHz to 1000MHz, Set the spectrum analyzer as:

RBW = 100kHz, VBW =300kHz,Detector= Quasi-Peak, Trace mode= Max hold, Sweep- auto couple.

For above 1GHz,Set the spectrum analyzer as:

RBW =1MHz, VBW =1MHz, Detector= Peak, Trace mode= Max hold, Sweep- auto couple.

RBW =1MHz, VBW =10Hz, Detector= Average, Trace mode= Max hold, Sweep- auto couple.

4.4. Test Data

PASS

During the test, Pre-scan all kind of the place mode (X-axis, Y-axis, Z-axis), and found the X-axis is the worst case.

The test results of 9kHz-30MHz was attenuated more than 20dB below the permissible limits, so the results don't record in the report.

During the test, pre-scan all the modes, only the worst case is recorded in the report.



Test Results (30~1000MHz)

Test Mode: 16QAM 908MHz
 Power Source: AC 120V, 60Hz for Adapter
 Polarization: Horizontal
 Temp.(°C)/Hum.(%RH): 23.5°C/49%RH
 Fundamental



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Detector	Height (cm)	degree (deg)	Remark
1	908.0000	66.92	-6.14	60.78			peak			
2	370.7022	52.55	-16.07	36.48	46.00	-9.52	QP			
3	249.4250	51.98	-21.51	30.47	46.00	-15.53	QP			
4	150.5378	48.06	-22.91	25.15	43.50	-18.35	QP			
5	99.8777	39.87	-21.28	18.59	43.50	-24.91	QP			
6	72.3375	40.77	-22.13	18.64	40.00	-21.36	QP			
7	57.3922	37.07	-17.56	19.51	40.00	-20.49	QP			



Test Results (30~1000MHz)

Test Mode: 16QAM 908MHz
 Power Source: AC 120V, 60Hz for Adapter
 Polarization: Vertical
 Temp.(°C)/Hum.(%RH): 23.5°C/49%RH
 Fundamental



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Detector	Height (cm)	degree (deg)	Remark
1	908.0000	103.43	-6.11	97.32			peak			
2	601.4265	48.45	-10.53	37.92	46.00	-8.08	QP			
3	382.5878	51.10	-14.63	36.47	46.00	-9.53	QP			
4	170.1947	51.33	-21.12	30.21	43.50	-13.29	QP			
5	209.3129	46.77	-19.34	27.43	43.50	-16.07	QP			
6	95.4270	46.20	-17.17	29.03	43.50	-14.47	QP			
7	79.5208	45.45	-19.36	26.09	40.00	-13.91	QP			



Test Results (30~1000MHz)

Test Mode: 16QAM 908MHz
 Power Source: DC 3.7V Battery inside
 Polarization: Horizontal
 Temp.(°C)/Hum.(%RH): 23.5°C/49%RH
 Fundamental



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Detector	Height (cm)	degree (deg)	Remark
1	30.2110	41.01	-20.19	20.82	40.00	-19.18	QP			
2	46.8303	31.92	-15.41	16.51	40.00	-23.49	QP			
3	99.8777	38.87	-21.28	17.59	43.50	-25.91	QP			
4	150.5378	47.06	-22.91	24.15	43.50	-19.35	QP			
5	317.7010	56.01	-16.75	39.26	46.00	-6.74	QP			
6	370.7022	55.05	-16.07	38.98	46.00	-7.02	QP			
7	908.0000	66.92	-6.14	60.78						



Test Results (30~1000MHz)

Test Mode: 16QAM 908MHz
 Power Source: DC 3.7V Battery inside
 Polarization: Vertical
 Temp.(°C)/Hum.(%RH): 23.5°C/49%RH
 Fundamental



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Detector	Height (cm)	degree (deg)	Remark
1	46.1779	40.23	-15.22	25.01	40.00	-14.99	QP			
2	94.7601	44.55	-17.23	27.32	43.50	-16.18	QP			
3	170.1948	50.33	-21.12	29.21	43.50	-14.29	QP			
4	321.0608	46.43	-15.73	30.70	46.00	-15.30	QP			
5	382.5879	51.10	-14.63	36.47	46.00	-9.53	QP			
6	601.4265	48.45	-10.53	37.92	46.00	-8.08	QP			
7	908.0000	106.93	-6.11	100.82						



Test Results (1GHz-25GHz)

Test channel: Lowest						
Peak value:						
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	polarization
1816.00	28.42	17.67	46.09	74.00	-27.91	Vertical
2724.00	28.49	20.94	49.43	74.00	-24.57	Vertical
3632.00	29.33	22.51	51.84	74.00	-22.16	Vertical
4540.00	*			74.00		Vertical
5448.00	*			74.00		Vertical
1816.00	28.09	17.67	45.76	74.00	-28.24	Horizontal
2724.00	29.01	20.94	49.95	74.00	-24.05	Horizontal
3632.00	28.10	22.51	50.61	74.00	-23.39	Horizontal
4540.00	*			74.00		Horizontal
5448.00	*			74.00		Horizontal
Average value:						
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	polarization
1816.00	16.69	17.67	34.36	54.00	-19.64	Vertical
2724.00	17.54	20.94	38.48	54.00	-15.52	Vertical
3632.00	18.80	22.51	41.31	54.00	-12.69	Vertical
4540.00	*			54.00		Vertical
5448.00	*			54.00		Vertical
1816.00	16.42	17.67	34.09	54.00	-19.91	Horizontal
2724.00	18.04	20.94	38.98	54.00	-15.02	Horizontal
3632.00	17.61	22.51	40.12	54.00	-13.88	Horizontal
4540.00	*			54.00		Horizontal
5448.00	*			54.00		Horizontal



Test Results (1GHz-25GHz)

Test channel: Middle						
Peak value:						
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	polarization
1832.00	27.97	17.70	45.67	74.00	-28.33	Vertical
2748.00	28.46	20.97	49.43	74.00	-24.57	Vertical
3664.00	28.83	22.51	51.34	74.00	-22.66	Vertical
4580.00	*			74.00		Vertical
5496.00	*			74.00		Vertical
1832.00	27.90	17.70	45.60	74.00	-28.40	Horizontal
2748.00	28.88	20.97	49.85	74.00	-24.15	Horizontal
3664.00	27.82	22.51	50.33	74.00	-23.67	Horizontal
4580.00	*			74.00		Horizontal
5496.00	*			74.00		Horizontal
Average value:						
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	polarization
1832.00	16.78	17.70	34.48	54.00	-19.52	polarization
2748.00	17.40	20.97	38.37	54.00	-15.63	Vertical
3664.00	18.65	22.51	41.16	54.00	-12.84	Vertical
4580.00	*			54.00		Vertical
5496.00	*			54.00		Vertical
1832.00	16.53	17.70	34.23	54.00	-19.77	Vertical
2748.00	18.39	20.97	39.36	54.00	-14.64	Horizontal
3664.00	17.91	22.51	40.42	54.00	-13.58	Horizontal
4580.00	*			54.00		Horizontal
5496.00	*			54.00		Horizontal



Test Results (1GHz-25GHz)

Test channel: Highest						
Peak value:						
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	polarization
1848.00	28.10	17.74	45.84	74.00	-28.16	Vertical
2772.00	28.62	20.99	49.61	74.00	-24.39	Vertical
3696.00	29.53	22.51	52.04	74.00	-21.96	Vertical
4620.00	*			74.00		Vertical
5544.00	*			74.00		Vertical
1848.00	28.04	17.74	45.78	74.00	-28.22	Horizontal
2772.00	29.09	20.99	50.08	74.00	-23.92	Horizontal
3696.00	28.20	22.51	50.71	74.00	-23.29	Horizontal
4620.00	*			74.00		Horizontal
5544.00	*			74.00		Horizontal
Average value:						
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	polarization
1848.00	17.90	17.74	35.64	54.00	-18.36	Vertical
2772.00	18.67	20.99	39.66	54.00	-14.34	Vertical
3696.00	19.30	22.51	41.81	54.00	-12.19	Vertical
4620.00				54.00		Vertical
5544.00				54.00		Vertical
1848.00	17.71	17.74	35.45	54.00	-18.55	Horizontal
2772.00	19.19	20.99	40.18	54.00	-13.82	Horizontal
3696.00	18.06	22.51	40.57	54.00	-13.43	Horizontal
4620.00	*			54.00		Horizontal
5544.00	*			54.00		Horizontal

Remark:

- 1.Result =Reading + Factor
2. "*" means the test results were attenuated more than 20dB below the permissible limits, so the results don't record in the report.
3. During the test, pre-scan the BPSK, QPSK, 16QAM, 64QAM, and found the 16QAM is worse case, the report only record this mode.




5. Maximum Peak Output Power Test

5.1. Test Standard and Limit

Test Standard	FCC Part15 C Section 15.247 (b)(3)
Test Limit	1W (30dBm)

5.2. Test Setup



5.3. Test Procedure

This procedure shall be used when the measurement instrument has available a resolution bandwidth that is greater than the DTS bandwidth.

1. Set the RBW \geq DTS bandwidth.
2. Set the VBW $\geq 3 \times$ RBW.
3. Set the span $\geq 3 \times$ RBW.
4. Detector = peak.
5. Sweep time = auto couple.
6. Trace mode = max hold.
7. Allow trace to fully stabilize.
8. Use peak marker function to determine the peak amplitude level.

5.4. Test Data

Test Item	: Max. peak output power	Test Mode	: CH Low ~ CH High
Test Voltage	: AC 120V, 60Hz for Adapter	Temperature	: 24.1°C
Test Result	: PASS	Humidity	: 48 %

Modulation: BPSK			
Test Channel	Peak Power output (dBm)	Limit (dBm)	Results
Low	23.120	30	PASS
Middle	21.753	30	PASS
High	22.506	30	PASS



Modulation: QPSK			
Test Channel	Peak Power output (dBm)	Limit (dBm)	Results
Low	23.235	30	PASS
Middle	21.428	30	PASS
High	22.192	30	PASS

Modulation: 16QAM			
Test Channel	Peak Power output (dBm)	Limit (dBm)	Results
Low	23.791	30	PASS
Middle	21.107	30	PASS
High	21.472	30	PASS

Modulation: 64QAM			
Test Channel	Peak Power output (dBm)	Limit (dBm)	Results
Low	22.960	30	PASS
Middle	21.540	30	PASS
High	21.624	30	PASS




6. 6dB Emission Bandwidth Test

6.1. Test Standard and Limit

Test Standard	FCC Part15 C Section 15.247 (a)(2)
Test Limit	>500kHz

6.2. Test Setup



6.3. Test Procedure

1. Place the EUT on the table and set it in the transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
3. Set the spectrum analyzer as:
 RBW = 100kHz, VBW≥3*RBW
 Detector= Peak
 Trace mode= Max hold.
 Sweep- auto couple.
4. Mark the peak frequency and -6dB (upper and lower) frequency.
5. Repeat until all the rest channels are investigated.

6.4. Test Data

Test Item	: 6dB Bandwidth	Test Mode	: CH Low ~ CH High
Test Voltage	: AC 120V, 60Hz for Adapter	Temperature	: 24.1℃
Test Result	: PASS	Humidity	: 48 %

Modulation: BPSK			
Channel	Bandwidth (kHz)	Limit (kHz)	Results
Low	7391	>500	PASS
Middle	7633	>500	PASS
High	7569	>500	PASS




Modulation: QPSK			
Channel	Bandwidth (kHz)	Limit (kHz)	Results
Low	7542	>500	PASS
Middle	7650	>500	PASS
High	7513	>500	PASS

Modulation: 16QAM			
Channel	Bandwidth (kHz)	Limit (kHz)	Results
Low	7523	>500	PASS
Middle	7649	>500	PASS
High	7414	>500	PASS


Modulation: 64QAM			
Channel	Bandwidth (kHz)	Limit (kHz)	Results
Low	7581	>500	PASS
Middle	7654	>500	PASS
High	7439	>500	PASS




BPSK



Low Channel




Mid Channel




High Channel




QPSK



Low Channel




Mid Channel




High Channel




16QAM



Low Channel




Mid Channel




High Channel




64QAM



Low Channel



Mid Channel



High Channel




7. Power Spectral Density Test

7.1. Test Standard and Limit

Test Standard	FCC Part15 C Section 15.247 (e)
Test Limit	8dBm/3KHz

7.2. Test Setup



7.3. Test Procedure

1. Place the EUT on the table and set it in transmitting mode. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
2. Set the spectrum analyzer as RBW = 3kHz, VBW = 10kHz, Span = 1.5xDTS BW
3. Record the max. reading.
4. Repeat the above procedure until the measurements for all frequencies are completed.

7.4. Test Data

Test Item	: Power Spectral Density	Test Mode	: CH Low ~ CH High
Test Voltage	: AC 120V, 60Hz for Adapter	Temperature	: 24.1℃
Test Result	: PASS	Humidity	: 48 %

Modulation: BPSK			
Channel	PSD (dBm/3KHz)	Limit (dBm/3KHz)	Results
Low	-2.890	8.00	PASS
Middle	-4.185	8.00	PASS
High	-4.846	8.00	PASS

Modulation: QPSK			
Channel	PSD (dBm/3KHz)	Limit (dBm/3KHz)	Results
Low	-2.628	8.00	PASS
Middle	-4.502	8.00	PASS
High	-4.547	8.00	PASS




Modulation: 16QAM			
Channel	PSD (dBm/3KHz)	Limit (dBm/3KHz)	Results
Low	-3.426	8.00	PASS
Middle	-3.931	8.00	PASS
High	-3.192	8.00	PASS


Modulation: 64QAM			
Channel	PSD (dBm/3KHz)	Limit (dBm/3KHz)	Results
Low	-2.448	8.00	PASS
Middle	-4.197	8.00	PASS
High	-3.543	8.00	PASS




BPSK



Low Channel




Mid Channel




High Channel




QPSK



Low Channel




Mid Channel




High Channel




16QAM



Low Channel




Mid Channel




High Channel




64QAM



Low Channel



Mid Channel



High Channel




8. 100kHz Bandwidth of Frequency Band Edge Requirement

8.1. Test Standard and Limit

Test Standard	FCC Part15 C Section 15.247 (d)
Test Limit	in any 100 kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in 15.209(a).

8.2. Test Setup



8.3. Test Procedure

Using the following spectrum analyzer setting:

1. Set the RBW = 100KHz.
2. Set the VBW = 300KHz.
3. Sweep time = auto couple.
4. Detector function = peak.
5. Trace mode = max hold.
6. Allow trace to fully stabilize.

8.4. Test Data

Test Item	:	Band edge	Test Mode	:	CH Low ~ CH High
Test Voltage	:	AC 120V, 60Hz for Adapter	Temperature	:	24.1℃
Test Result	:	PASS	Humidity	:	48 %



Band edge measurements


BPSK



Lowest

Highest

QPSK



Lowest

Highest



16QAM



Lowest

Highest

64QAM




Lowest

Highest




Conducted Emission Method BPSK




CH: Low

CH: Low



CH: Low


CH: Middle



CH: Middle

CH: Middle






CH: High




CH: High



CH: High




QPSK




CH: Low

CH: Low



CH: Low

CH: Middle



CH: Middle

CH: Middle






CH: High




CH: High



CH: High




16QAM




CH: Low

CH: Low



CH: Low

CH: Middle



CH: Middle

CH: Middle






CH: High




CH: High



CH: High




64QAM



CH: Low

CH: Low



CH: Low


CH: Middle



CH: Middle

CH: Middle






CH: High



CH: High



CH: High



9. Antenna Requirement

9.1. Test Standard and Requirement

Test Standard	FCC Part15 Section 15.203 /247(c)
Requirement	<p>1) 15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.</p> <p>2) 15.247(c) (1)(i) requirement: Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi.</p>

9.2. Antenna Connected Construction

The antenna is a Rod Antenna, and the best case gain of the antenna is 2.92dBi. It complies with the standard requirement.



APPENDIX I -- TEST SETUP PHOTOGRAPH

Please refer to separated files Appendix I -- Test Setup Photograph

APPENDIX II -- EXTERNAL PHOTOGRAPH

Please refer to separated files Appendix II -- External Photograph

APPENDIX III -- INTERNAL PHOTOGRAPH

Please refer to separated files Appendix III -- Internal Photograph

----- End of Report -----

