




PLACE TOLERANCE OF THE PRINTING ± 0,3mm
TO BE PRINTED IN PRODUCTION WITH
(600DPI) THERMAL TRANSFER PRINTER

Name: _____

SN: 0720F22GW(X)

   RESET

Type: uDirect FCC ID: VMY-UDIRECT
IC ID: 2756A-UDIRECT

www.unitron.com Li-Po 4,2V

Made in Austria

Bar code 128.
height 3mm.
Module width 2 dots

Abrasion acc.
DIN 58199

Battery type

Incremental SN. (3 characters in
use for the start phase)

SAP Number (F2 for Althofen)

number of the current week

year (2007)

Bar code contents



M 1:1

Biocompatible acc. USP class 1 - ISO 10983-1
Material must be ROHS compliant

Label blanc see: AZ160-00029-□

DRAFT

Control Characteristic	ok =	Important Characteristic
.	.	.
.	.	.
.	.	.
.	.	.
0	00	.

INDEX	VERSION	DATE	CHANGE NOTE	DESCRIPTION	NAME
PROJ.	EUROPE	MATERIAL	.	TOLERANCES UNLESS OTHERWISE STATED	CUSTOMER
		TREATMENT	.		PHONAK
			.		PROJECT
			.		COMMBUTTON
SCALE	5:1	DESCRIPT.	ARTWORK LABEL TYPE UDIRECT	CODE	VERSION
		NAME	S.Piron	AZ164-00XXX_UNITRON-0	00
		DATE	13.01.2009	STAGE	SHEET 110
					SH 1 OF 1
PROPERTY OF	FLEXTRONICS			Friesacher Str. 3 A 9330 Althofen, Austria	FORMAT A4

FLEXTRONICS
Design

ALL RIGHTS RESERVED
REPRODUCTION OF THIS DOCUMENT
PARTS IN ANY FORM OR BY ANY MEANS
NOT PERMITTED WITHOUT WRITTEN
AUTHORITY FROM THE PROPRIETORS