




赣州得辉达科技有限公司
GANZHOU DEHUIDA ELECTRONICS CO.,LTD.

机型: FVA51
料号: PKG.1800000011015
品名: 贴纸
版本: 2.1



A * 单位: mm

材质要求: 如描述
表面处理: 如描述
比例: 1:1
页数: 1
绘图: 李鹏
审核: 张德军
批准: [Signature]
生效日期: 2024.02.29

版本	描述	日期
2.0	PVT试产发行 [更新AW/刀线/打码]	2024.02.27
2.1	更新Artwork	2024.02.29

来料印刷与打码



二维码格式: DATA_MATRIX, 尺寸不低于6.8*6.8mm, 扫描等级要求: ≥B级

2D bar code must be grade level of 2.0 (C). 以实现 2D bar code 达到 2.0 (C) 的最低符号质量要求。

019241005701|UY23508D010001|FVA51

customer model number(this no# should same as rating lable model no#): FVA51

分隔符: |

4位序列号: Serial number starts at 0001 till to 9999. Restart at 0001, Serial number为一直累积直到重新从0001开始, 不因订单而改变
If factory move to new location and get a new manufacturer code, must to restart at 0001.

装配线体, 采用两位数字, 从0~9中选择

生产班次: D【外发打码, 定量】

星期代码: 8【外发打码, 定量】

生产周数, 如2023年第50周=50, 53不被使用

生产年份, 如2023=23, 2024=24

制造商代码: SZ-DHD=UY

分隔符: |

TTI PN[12位数字]: 019241005701

UY23508D010001



4位序列号: Serial number starts at 0001 till to 9999. Restart at 0001, Serial number为一直累积直到重新从0001开始, 不因订单而改变
If factory move to new location and get a new manufacturer code, must to restart at 0001.

装配线体, 采用两位数字, 从0~9中选择

生产班次: D【外发打码, 定量】

星期代码: 8【外发打码, 定量】

生产周数, 如2023年第50周=50, 53不被使用

生产年份, 如2023=23, 2024=24

制造商代码: 深圳得辉达=UY

11. Date code: the weekly range is from 01-52; no 53 will be used.

sz工厂代码

UY	SHENZHEN DEHUIDA INTELLIGENT TECHNOLOGY CO.,LTD	Rm 301, Building 25, No. 121 Xikeng Road, Xikeng Community, Fucheng Street, Longhua District, Shenzhen, China 518110
----	---	--

RTI THD Walmart	North America Mexico	<p>1.(Mgf.code)YYWWCDEFFFF</p> <p>2. 2D barcode format: TTI P/N/Date code serial number (customer model number) (2D barcode on rating label is DataMatrix format)</p> <p>3. ID sticker on gift box, master carton, tray will be barcode with date code & serial number (Mgf code)YYWW(Space) FFFFFFFF barcode to be scanned same as digital shows.</p>	<p>1. YY =Year code (15 =year 2015, 16 =year 2016...) WW =Week code (01 =the 1st week, 02 =the 2nd week...) C =Day of week code: (0 =Sun, 1 =Mon, ... 6 =Sat; 8 for unspecified day) D =Work shift code D or N (D =Day shift, N =Night shift). EE =Assembly line # code with 2 digit, (2 digit could to use number from 0-9 or English letter A, B .Z, 00 for unspecified line #) FFFF = 4 digit serial number</p> <p>2.TTI P/N in 2D barcode = 12 digit console number (show 9 digit model number if BOM is no console number defined, Never to use TTI IH model no# 100XXXXXX.)</p> <p>3. ID sticker Barcode scan level must be above C class, it is 128 code format</p> <p>4.Mgf code: check it on PPS30.</p>	<p>Example for 2D barcode scan: 130189001007 XX15265D100010 R840085</p> <p>130189001007 = TTI P/N (12 digit console number)</p> <p>XX15265D100010, XX = manufacturer code 15 = year 2015 26 = week of 26th D = day shift 10 = #10 assembly line 0010 = serial number</p> <p>R840085 = customer model number(this no# should same as rating lable model no#)</p>	<p>1. Serial number starts at 0001 till to 9999. Restart at 0001. If factory move to new location and get a new manufacturer code, must to restart at 0001.</p> <p>2. The format of the gift box or carton sticker: (Mgf.code)YYWW (space) FFFFFFFF The 1st "FF" can keep "00". The next 4 "FFFF" must be consisting to the number on the rating label Between YYWW and FFFFFFFF need a space</p> <p>3. Combo kit serial no# on ID label slicked on gift box /carton just need to match only one major unit serial no# packed in. such as a combo kit include: drill/anger grinder—we need just let ID label serial no# match with drill is ok. the serial no# on ID label not need to match with angle grinder. (it means have only one gift box for the combo kit packed with 2 or more units). if with 2 or more gift box for one combo kit; then the ID label serial no# on gift box need to match the major unit in the gift box.</p>	<p>ID sticker sample</p>
-----------------------	-------------------------	--	--	---	---	--------------------------

技术要求:

- W123*H29.1mm Flexcon 21970+100#Matt PET+哑PP 单黑印刷 FCC&sn二维码rating贴纸 01924100101K-01 FVA51 环保
- 其它未标注尺寸及公差请参照图档及公差表。
- 符合REACH/RoHS/CP65/TSCA/TPCH (美国包装指令) /BPA/欧盟包装指令/MOH禁止矿物油规例 (油墨、印刷、包装纸)。

尺寸公差: +/-0.1mm