


Maximum Permissible Exposure Evaluation

Test Report No : CSTPOC12-FCC0015-1

Equipment Name : Docking System
Model No. : DS-N10A
Applicant : Inkel Corporation
Address : 3-8, CheongCheon-Dong, Bupyeong-Gu, Incheon, 403-853,
Republic of Korea

This report applies only to the product named in the title of this report manufactured at the location indicated. Test results apply only to the particular equipment and functionality described in this test report.

Prepared by : 
Young Goo, Kim / EMC Engineer

Date of Issue : August 21, 2012

Reviewed by : 
Ik Seon, Jeong / Principle Engineer

Date of Issue : August 21, 2012

CERTIFICATION SERVICE TECHNOLOGY INC.

181, Manhaero, Danwan-gu, Ansan-city, Kyeonggi-do, 425-839, Korea
Tel: +82 31 493 2001 Fax: +82 31 493 2055

<http://www.cstlab.co.kr>

1. Technical Description of EUT

Item	Specification	note
Signal-to-Noise ratio	78dB	AMPLIFIER SECTION
Dimension	320 mm x 212.2mm x 95.5mm	
RF spec	Frequency Range	2402 MHz ~ 2480 MHz
	Channel	79 Channel
	Modulation Type	GFSK (BDR), 8-DQPSK (EDR)
	Power	5.59 mW (GFSK mode), 3.31 mW (8-DQPSK mode) *Conducted power including antenna gain, declared by the applicant
	Antenna Gain	0 dBi
Weight	1.95 kg	
Power Source	AC 110V	
Power Consumption	AC 20W (DC 15W)	

NOTE:

1. This report is issued as a supplementary report of the original report.
2. The EUT, operates in the 2.4GHz frequency range, lets you connect Bluetooth devices to the network.
3. The above EUT information was declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or User's Manual.

2. General Information of Test

Certification Service Technology Inc. (CSTech)	
Test Site Location	1055, Singil-dong ,Danwon-gu ,Ansan-si, Gyeonggi-do, Korea 425-839
	TEL : +82-31-493-2001 FAX : +82-31-493-2055

3. RF Exposure Measurement

3.1 Introduction & Standard

RF Exposure Requirements	: 47 CFR §1.1307(b)
RF Radiation Exposure Limits	: 47 CFR §1.1310
RF Radiation Exposure Guidelines	: FCC OST/OET Bulletin Number 65
EUT Frequency Band	: 2402 MHz ~ 2480 MHz (Bluetooth)
Limits for General Population/Uncontrolled Exposure in the band of Power Density Limit	: 1500 MHz ~ 100000 MHz : 1 mW/cm ²

3.2 Compliance criteria

Evaluating for Power flux density

Equations are accurate in the far-field If antenna but will over-predict in the near field.

Under above describe specification of EUT and Antenna, Equivalent plane wave power density is calculated as below underlined quotation formula ;

$$S_{eq} (\text{W/m}^2) = E \times H = E^2 / \eta = \underline{\sqrt{P G(\phi) / 4 \pi r^2}}$$

Where :

- S_{eq} (W/m^2) = Equivalent plane wave power density
- E (V/m) = Electric field strength
- H (A/m) = Magnetic field strength
- η (Ω) = Free space wave impedance = $120 \pi \Omega$
- ϕ = elevation and azimuth angles
- P (W) = Power input to the antenna
- G (dBi) = Antenna gain relative to an isotropic antenna
- r (m) = distance from observation point to the antenna

1. Accordingly as a result of calculated value

- P (W) = 5.59 mW
- G (dBi) = 0 dBi (Conversion 0 dB_i to Linearity value is 1)
- r (m) = setting a distance (20cm) from the antenna to calibrated tuned receiving antenna in far field
- $\therefore S_{eq}$ (W/m^2) : $\sqrt{0.00559 \times 1 / 4 \times 3.14 \times 0.2^2} = \underline{\text{0.10548}}$

So, above calculated 0.10548 W/m² is comply with the value required standard