



Neutron Engineering Inc.

FCC RF EXPOSURE REPORT

FCC ID: VOB-P2570

Project No. : 1404C046
Equipment : Wireless Controller
Model Name : P2570
Applicant : NVIDIA Corporation
**Address : 2701 San Tomas Expressway Santa Clara,
CA95050**
Manufacturer : NVIDIA Corporation
**Address : 2701 San Tomas Expressway Santa Clara,
CA95050**
According: : FCC Guidelines for Human Exposure IEEE C92.76

Neutron Engineering Inc.

No.3, Jinshagang 1st Road, ShiXia, Dalang Town, Dong Guan, China.

TEL : (0769) 8318-3000 FAX : (0769) 8319-6000



MPE CALCULATION METHOD:

Calculation Method of RF Safety Distance:

$$S = \frac{PG}{4\pi^2} = \frac{EIRP}{4\pi^2}$$

where:

S = power density

P = power input to the antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna

Ant.	Manufacturer	Model Name	Antenna Type	Connector	Gain (dBi)
1	Yageo Corp.	ANT5320LL24 R2455A	Chip	N/A	3.51
2	Yageo Corp.	ANT5320LL24 R2455A	Chip	N/A	3.51

Note: The EUT incorporates a SISO function and only one antenna used per time

Operating Mode	1TX	2TX
TX Mode		
802.11a	V (ANT 1 or ANT 2)	-



Neutron Engineering Inc.

TEST RESULTS

EUT:	Wireless Controller	Model Name :	P2570
Temperature:	25 °C	Relative Humidity:	55 %
Pressure:	DC3.7V		
Test Mode :	Band4/TX A Mode		

Antenna Gain (dBi)	Antenna Gain (numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Power Density (S) (mW/cm ²)	Limit of Power Density (S) (mW/cm ²)	Test Result
3.15	2.0654	12.77	18.9234	0.007777948	1	Complies
3.15	2.0654	12.94	19.6789	0.00809003	1	Complies
3.15	2.0654	12.87	19.3642	0.00796068	1	Complies

Note: The calculated distance is 20cm.