

RF Exposure / SAR Statement

No. : 10622710S-A

| | | |
|--------------------------|----------|---------------------------------------|
| Applicant | : | Murata Manufacturing Co., Ltd. |
| Type of Equipment | : | Communication Module |
| Model No. | : | Type1DR |
| FCC ID | : | VPYLB1DR |

Murata Manufacturing Co., Ltd. declares that Model : Type1DR
complies with FCC radiation exposure requirement specified in the FCC Rules 2.1091.

RF Exposure Calculations:

The following information provides the minimum separation distance for the highest gain antenna provided with the “Type1DR” as calculated from FCC Part 1, §1.1310, TABLE 1 (B) Limits for General Population / Uncontrolled Exposure. This calculation is based on the highest EIRP possible from the system, considering maximum power and antenna gain, and considering a 1.0mW/cm² uncontrolled exposure limit. The Friis formula used was:

$$S = (P * G) / (4 * \pi * r^2)$$

Where

| | | |
|------------|---|-----------------|
| P = | 7.36 mW (Maximum average output power) | |
| G = | 1.23 Numerical Antenna gain; equal to | 0.91 dBi |
| r = | 20.0 cm | |

For: Type1DR

$$S = 0.00181 \text{ mW/cm}^2$$

Even taking into account the tolerance, this device can be satisfied with the limits.

UL Japan, Inc.

Shonan EMC Lab.

1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa-ken, 259-1220 JAPAN

Telephone : +81 463 50 6400

Facsimile : +81 463 50 6401