

RF Exposure / MPE Calculation

No. : 10689818H

Applicant : Murata Manufacturing Company, Ltd.
Type of Equipment : Communication Module (WLAN 5GHz band)
Model No. : LBEE5ZZ1EN
FCC ID : VPYLB1EN

Murata Manufacturing Company, Ltd. declares that Model : LBEE5ZZ1EN complies with FCC radiation exposure requirement specified in the FCC Rules 2.1091 (for mobile).

RF Exposure Calculations:

The following information provides the minimum separation distance for the highest gain antenna provided with the "LBEE5ZZ1EN" as calculated from (B) Limits for General Population / Uncontrolled Exposure of TABLE 1- LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE) of §1.1310 Radiofrequency radiation exposure limits.

This calculation is based on the highest EIRP possible from the system, considering maximum power and antenna gain, and considering a 1.0mW/cm² uncontrolled exposure limit. The Friis formula used was:

$$S = (P * G) / (4 * \pi * r^2)$$

Where

P = 25.82 mW (Maximum peak output power)
G = 3.16 Numerical Antenna gain; equal 5.00 dBi
r = 20.0 cm

For: LBEE5ZZ1EN (Antenna 1 Maximum average output power (WLAN 5GHz band Part)

$$S = 0.01625 \text{ mW/cm}^2$$

$$S = (P * G) / (4 * \pi * r^2)$$

Where

P = 4.60 mW (Maximum average output power)
G = 2.24 Numerical Antenna gain; equal 3.50 dBi
r = 20.0 cm

For: LBEE5ZZ1EN (Antenna 2 Maximum average output power (Bluetooth Low Energy Part)

$$S = 0.00205 \text{ mW/cm}^2$$

Therefore, if Antenna 1(WLAN 5GHz band) and Antenna 2 (Bluetooth Low Energy) transmit simultaneously,

$$S = 0.01625 \text{ mW/cm}^2 + 0.00205 \text{ mW/cm}^2 \\ = 0.01830 \text{ mW/cm}^2$$

Even taking into account the tolerance, this device can be satisfied with the limits.

UL Japan, Inc.

Ise EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124